

BFS and DFS

Ali Akbari

June 2025

Breadth-First Search Example

- ▶ **Problem:** Navigate maze from room A to D: $A \rightarrow B$, $A \rightarrow C$, $B \rightarrow D$, $C \rightarrow D$.
- ▶ Explore all nodes at current distance before moving farther.
- ▶ **Step-by-Step:**
 1. Start: Enqueue A.
 2. Dequeue A, visit B, C, enqueue B, C.
 3. Dequeue B, visit D, enqueue D.
 4. Dequeue C, D found.

Breadth-First Search

- ▶ Uses queue to explore nodes level by level.
- ▶ Guarantees shortest path in unweighted graphs.
- ▶ **Time Complexity:** $O(V + E)$, where V is vertices, E is edges.
- ▶ **Space Complexity:** $O(V)$.

Depth-First Search Example

- ▶ **Problem:** Same maze, explore deeply before backtracking.
- ▶ **Step-by-Step:**
 1. Start at A, visit B.
 2. From B, visit D (found).
 3. Backtrack to A, visit C, then D (visited).

Depth-First Search

- ▶ Explores as far as possible along a path, backtracks.
- ▶ Uses recursion or stack.
- ▶ **Time Complexity:** $O(V + E)$.
- ▶ **Space Complexity:** $O(V)$.