

SQL

Subqueries Returning Relations

You can also use: $s > \text{ALL } R$
 $s > \text{ANY } R$
 $\text{EXISTS } R$

Product (pname, price, category, maker)


Find products that are more expensive than all those produced
By “Gizmo-Works”

```
SELECT name
FROM   Product
WHERE  price > ALL (SELECT price
                    FROM   Purchase
                    WHERE  maker='Gizmo-Works')
```

Correlated Queries

Movie (title, year, director, length)

Find movies whose title appears more than once.



Note (1) scope of variables (2) this can still be expressed as single SFW

Complex Correlated Query

Product (pname, price, category, maker, year)

- Find products (and their manufacturers) that are more expensive than all products made by the same manufacturer before 1972

```
SELECT DISTINCT pname, maker
FROM   Product AS x
WHERE  price > ALL (SELECT price
                   FROM   Product AS y
                   WHERE  x.maker = y.maker AND y.year < 1972);
```

Very powerful ! Also much harder to optimize.

Aggregation

```
SELECT avg(price)
FROM Product
WHERE maker="Toyota"
```

```
SELECT count(*)
FROM Product
WHERE year > 1995
```

SQL supports several aggregation operations:

sum, count, min, max, avg

Except count, all aggregations apply to a single attribute

Aggregation: Count

COUNT applies to duplicates, unless otherwise stated:

```
SELECT Count(category)
FROM   Product
WHERE  year > 1995
```

same as Count(*)

We probably want:

```
SELECT Count(DISTINCT category)
FROM   Product
WHERE  year > 1995
```

More Examples

Purchase(product, date, price, quantity)

```
SELECT Sum(price * quantity)
FROM   Purchase
```


```
SELECT Sum(price * quantity)
FROM   Purchase
WHERE  product = 'bagel'
```

What do
they mean ?

Purchase Simple Aggregations

Product	Date	Price	Quantity
Bagel	10/21	1	20
Banana	10/3	0.5	10
Banana	10/10	1	10
Bagel	10/25	1.50	20

```
SELECT Sum(price * quantity)
FROM Purchase
WHERE product = 'bagel'
```



50 (= 20+30)

Grouping and Aggregation

Purchase(product, date, price, quantity)

Find total sales after 10/1/2005 per product.

```
SELECT    product, Sum(price*quantity) AS TotalSales
FROM      Purchase
WHERE     date > '10/1/2005'
GROUP BY  product
```

Let's see what this means...

Grouping and Aggregation


1. Compute the **FROM** and **WHERE** clauses.
2. Group by the attributes in the **GROUPBY**
3. Compute the **SELECT** clause: grouped attributes and aggregates.

1&2. FROM-WHERE-GROUPBY

Product	Date	Price	Quantity
Bagel	10/21	1	20
Bagel	10/25	1.50	20
Banana	10/3	0.5	10
Banana	10/10	1	10

3. SELECT

Product	Date	Price	Quantity
Bagel	10/21	1	20
Bagel	10/25	1.50	20
Banana	10/3	0.5	10
Banana	10/10	1	10



Product	TotalSales
Bagel	50
Banana	15

```
SELECT    product, Sum(price*quantity) AS TotalSales
FROM      Purchase
WHERE     date > '10/1/2005'
GROUP BY product
```

GROUP BY v.s. Nested Quereis

```
SELECT    product, Sum(price*quantity) AS TotalSales
FROM      Purchase
WHERE     date > '10/1/2005'
GROUP BY  product
```

```
SELECT DISTINCT x.product, (SELECT Sum(y.price*y.quantity)
                             FROM   Purchase y
                             WHERE  x.product = y.product
                             AND y.date > '10/1/2005')
                             AS TotalSales
FROM      Purchase x
WHERE     x.date > '10/1/2005'
```

Another Example

What does
it mean ?

```
SELECT    product,  
          sum(price * quantity) AS SumSales  
          max(quantity) AS MaxQuantity  
FROM      Purchase  
GROUP BY product
```