



ON THE DENOISING OF CROSS-SPECTRAL MATRICES FOR (AERO)ACOUSTIC APPLICATIONS

Alice Dinsenmeyer¹, Jérôme Antoni¹, Quentin Leclère¹ and Antonio Pereira²

¹ Laboratoire Vibrations Acoustique

Univ Lyon, INSA-Lyon, LVA EA677, F-69621 Villeurbanne, France

² Laboratoire de Mécanique des Fluides et d'Acoustique

Univ Lyon, École Centrale de Lyon, F-69134, Écully, France

Abstract

Array systems and multichannel pressure measurements are widely used for source localization and quantification. Measurement noise such as calibration, electronic or ambient noise affects the performance of acoustic imaging algorithms. In aeroacoustic applications, acoustic pressure measurements can be highly disturbed by the presence of flow-induced noise [?]. However, signals are supposed to be stationary and performing averaging of cross-spectral quantities over several time snapshots will concentrate uncorrelated noise along the diagonal of the cross-spectral matrix (CSM). A common practice is thus to set the diagonal of the CSM to zero, which is known to improve the dynamic range of the source localization maps, yet this also leads to underestimated source levels [?]. More advanced techniques have been recently developed to avoid such problems by preserving or reconstructing source information that lies in the CSM diagonal [? ?].

Several existing approaches for CSM denoising are investigated in this paper and some new ones are proposed as well. We consider an unknown number of uncorrelated sources and no reference background noise. New methods are proposed based on the decomposition of the CSM into a low-rank part and a residual diagonal part attached to the unwanted noise; the corresponding inference problem is set up within a probabilistic framework which is ideally suited to take the non-deterministic nature of the estimated CSM into account. This is then solved by computing the maximum a posteriori estimates of the decomposition by using an expectation-maximization algorithm or by estimating the full a posteriori probability distribution by running a Markov chain Monte Carlo. For each method, reconstruction errors and convergence are compared in the frame of various numerical experiments, for different acoustic signals and noise structures.

1 Numerical experiments

1.1 Simulation of CSM

Source spectra are generated randomly :

$$\mathbf{c} \sim \mathcal{N}(0, \frac{c_{rms}}{\sqrt{2}}) \quad (1)$$

where c_{rms} stands for the root mean squared value of the spectra chosen equal to one for all the monopoles.

The propagator \mathbf{H} is the Green functions for free field monopoles :

$$\mathbf{H} = \frac{e^{jk\mathbf{r}}}{4\pi\mathbf{r}} \quad (2)$$

k being the wavenumber and \mathbf{r} distances between sources and receivers.

The acoustic signal is obtained from source propagation :

$$\mathbf{a} = \mathbf{H}\mathbf{c} \quad (3)$$

and a Gaussian noise is added :

$$\mathbf{p} = \mathbf{a} + \mathbf{n} \quad (4)$$

with

$$\mathbf{n} \sim \mathcal{N}(0, \frac{n_{rms}}{\sqrt{2}}) \quad (5)$$

where $n_{rms} = \langle \mathbf{a} \rangle_M \times 10^{-SNR/20}$ and $\langle \bullet \rangle$ is the average value over the M receivers.

Finally, cross-spectra are calculated :

$$\mathbf{S}_{aa} = \frac{1}{N_s} \mathbf{a}\mathbf{a}' \quad \text{used as the refence signal for denoising,} \quad (6)$$

$$\mathbf{S}_{pp} = \frac{1}{N_s} \mathbf{p}\mathbf{p}' \quad \text{which is the measurement spectrum to be denoised.} \quad (7)$$

1.2 Configuration of the simulated acoustical propagation

The acoustical field produced by a line of K uncorrelated monopoles is measured by $M = 93$ receivers distributed as a spiral. Default values for each parameter are given by the table ??.

Parameter	Notation	Default value
Frequency	f	15 kHz
Number of monopoles	K	20
Number of receivers	M	93
SNR	SNR	10 dB
Number of snapshots	N_s	10^4

Table 1: Default values for the numerical simulations.




Figure 1: Receiver and source positions used for acoustic field simulation (source line is tilted of 1 degree from the vertical to break antenna symmetry).

2 Diagonal reconstruction

In this section, three methods for diagonal reconstruction are presented. The idea of these method is to reduce as much as possible the self-induced noise concentrated on the diagonal elements of the CSM. The diagonale is minimized as long as the denoised CSM stay positive semidefinite. This problem can be written as :

$$\text{maximize } \sum_i D_{ii} \text{ subject to } \mathbf{S}_{pp} - \mathbf{D} \geq 0 \quad (8)$$

\mathbf{D} being a diagonal matrix.

2.1 Convex optimization

Hald use sconvex programming with the CVX toolbox [? ?] to solve this problem [?].

2.2 Linear optimization

Dougherty express this problem as a linear programming problem :

$$\text{maximize } \sum_i D_{ii} \text{ subject to } \mathbf{V}^{i-1} (\mathbf{S}_{pp} - \mathbf{D}^i) \mathbf{V}^{i-1} \geq 0 \quad (9)$$

where \mathbf{V}^{i-1} are the eigenvectors of $\mathbf{S}_{pp} - \mathbf{D}^{i-1}$.

2.3 Alternating projections

Alternating projections method can also be used. The solution is the intersection between two sets : the first set is the positive semi-definite matrices and the second is the set of diagonal matrices for the noise matrix :

$$\begin{aligned} \bar{\mathbf{S}}_{pp}^0 &= \mathbf{S}_{pp} - \text{diagonal}(\mathbf{S}_{pp}) \\ \text{for } i & \\ \mathbf{s}^i &= \text{eigenvalues}(\mathbf{S}_{pp}^i) \\ \mathbf{V}^i &= \text{eigenvectors}(\mathbf{S}_{pp}^i) \\ \mathbf{s}^i(s \leq 0) &= 0 \\ \bar{\mathbf{S}}_{pp}^{i+1} &= \bar{\mathbf{S}}_{pp}^0 + \mathbf{V}^{i'} \mathbf{s}^i \mathbf{V}^i \\ \text{endfor} \end{aligned} \quad (10)$$

This algorithm stops when all the eigenvalues of the denoised CSM are nonnegative.

2.4 Comparison of diagonal reconstruction methods

For each of these methods, we study the relative error of the estimated signal spectra $\hat{\mathbf{S}}_{aa}$ defined as :

$$\text{err} = \frac{\|\text{diag}(\mathbf{S}_{aa}) - \text{diag}(\hat{\mathbf{S}}_{aa})\|_2}{\|\text{diag}(\mathbf{S}_{aa})\|_2} \quad (11)$$

$\|\bullet\|$ being the L_2 norm. For each method, three parameters are successively changed :

- rank of signal matrix \mathbf{S}_{aa} by increasing the number of monopoles from 1 to M ,
- SNR from -10 to 10 dB,
- number of snapshots N_s .

When one parameter is changed, the others are constant, given by the table ??.




Figure 2: Error on the reconstructed diagonal, for different simulation parameters. On the right, error is plotted for 20, 80 and 93 sources.

Rank of S_{aa}

References

- [1] R. Dougherty. “Cross spectral matrix diagonal optimization.” In *6th Berlin Beamforming Conference*. 2016.
- [2] R. P. Dougherty. “Beamforming in Acoustic Testing.” In *Aeroacoustic Measurements* (edited by T. J. Mueller), chapter 2, pages 62–97. Springer-Verlag Berlin Heidelberg New York, 2002. ISBN 3-540-41757-5.
- [3] B. A. Fenech. *Accurate aeroacoustic measurements in closed-section hard-walled wind tunnels*. Ph.D. thesis, University of Southampton, School of Engineering Sciences, 2009. URL <http://eprints.soton.ac.uk/71636/>.
- [4] M. Grant and S. Boyd. “Graph implementations for nonsmooth convex programs.” In *Recent Advances in Learning and Control* (edited by V. Blondel, S. Boyd, and H. Kimura), Lecture Notes in Control and Information Sciences, pages 95–110. Springer-Verlag Limited, 2008. http://stanford.edu/~boyd/graph_dcp.html.
- [5] M. Grant and S. Boyd. “CVX: Matlab software for disciplined convex programming, version 2.1.” <http://cvxr.com/cvx>, 2014.
- [6] J. Hald. “Removal of incoherent noise from an averaged cross-spectral matrix.” *The Journal of the Acoustical Society of America*, 142(2), 846–854, 2017.