Reinforcement Learning for Equitable Housing Inspections: Policy Gradient Methods, Shapley Feature Importance, and Multi-Objective Optimization

Housing Policy & Machine Learning Track: Assignment 3

March 26, 2026

Abstract

This report extends my Assignment 2 DOB dispatch model with three additions. First, I implemented a REINFORCE policy gradient agent with a two-layer neural network baseline and compared it against Tabular Q-Learning and DQN. Second, I ran permutation-based Shapley analysis across all five state features (complaint category, borough, inspector budget, prior complaint count, and time of day) enumerating all 120 orderings (5!). Third, I tested 12 reward weight configurations to map the tradeoff between violation remediation speed, inspector cost, and housing unit retention. The result that stood out most: Tabular Q-Learning still catches all 16 violations while both neural methods collapse to always-dismiss. Inspector budget was the dominant Shapley feature, and the Pareto results show that cost efficiency and housing unit retention can't be jointly optimized, and there's a real tradeoff that any real deployment would have to navigate.

1. Introduction

In Assignment 2, I found that of 755 historical DOB AHV complaints, only 2.1% were genuine violations, and Tabular Q-Learning was the only agent that could actually catch them. Three questions came out of that. Can REINFORCE handle the class imbalance that broke DQN? Which features are actually driving the policy? And how should a real deployment balance remediation speed, inspector cost, and the risk of displacing tenants through aggressive enforcement? To answer the second question properly, I expanded the state space from three features to five: complaint category ($c \in \{0,1,2\}$), borough ($b \in \{0–4\}$), inspector budget ($i \in \{0–5\}$), prior complaint count ($p \in \{0–3\}$, how many times that address type has been flagged before), and time of day ($t \in \{0–3\}$: night/morning/afternoon/evening). The 16 violations break down as 2 brand-new, 6 recurrent, 8 high-frequency, all still present in this expanded dataset.

2. Methodology

2.1 MDP Formulation

The environment is a custom Gymnasium MDP with expanded state space S = MultiDiscrete([3, 5, 6, 4, 4]):

- $c \in \{0,1,2\}$: complaint category (brand-new, recurrent, high-frequency)
- $b \in \{0–4\}$: NYC borough
- $i \in \{0–5\}$: per-step inspector availability budget
- $p \in \{0–3\}$: prior complaint count (0=none, 1=one, 2=two-three, 3=four+)
- $t \in \{0–3\}$: time of day bin (0=night 10pm–6am, 1=morning, 2=afternoon, 3=evening)

Actions: A = {0=Dismiss, 1=Standard Inspection, 2=Aggressive Enforcement}. Key reward values: correct dismissal +10; standard inspection on violation +200; aggressive enforcement on violation +400; wasted standard inspection –10; wasted aggressive enforcement –20; dismissed real violation –500 (critical failure).

2.2 REINFORCE with Baseline

REINFORCE (Williams, 1992) is an on-policy Monte Carlo policy gradient algorithm. The policy $\pi_\theta(a|s)$ is parameterized by a two-layer MLP:

```
Input(5) → Linear(64) → ReLU → Linear(64) → ReLU → Linear(3) → Softmax
```

A separate baseline network $V_\phi(s)$ with identical architecture (but scalar output) is trained concurrently to reduce gradient variance. The policy gradient update is:

```
θ ← θ + α · (G_t − V_φ(s_t)) · ∇_θ log π_θ(a_t | s_t)
```

where $G_t = \Sigma_{k=0}^{T-t} \gamma^k r_{t+k+1}$ is the discounted return and $A_t = G_t - V_\phi(s_t)$ is the advantage. Returns are normalized within each episode (zero mean, unit variance) to stabilize gradient magnitudes. The agent was trained for 50 episodes (755 timesteps each) with learning rate 1×10■³ and $\gamma = 0.99$.

2.3 Shapley Feature Importance

Shapley values from cooperative game theory provide a principled, model-agnostic measure of feature importance. For a model f(x) with features x = [c, b, i], the Shapley value of feature j is the average marginal contribution of j across all possible orderings of features:

```
φ_j = (1/|Π|) Σ_{π∈Π} [f(x_{π≤j} ∪ {j}) − f(x_{π≤j})]
```

I enumerate all 120 permutations (5!) of the five features. Masking replaces a feature with its baseline value: c■=1 (recurrent), b■=2 (Queens), ■=4, p■=1 (one prior), t■=1 (morning). For TD: $f(s) = \max_a Q(s, a)$. For REINFORCE: $f(s) = \log \pi_\theta(\text{argmax } \pi_\theta(a|s) \mid s)$. Shapley values are computed over all 755 states and reported as mean absolute values; the top 5 features are ranked for each agent.

2.4 Multi-Objective Reward Decomposition

The reward function is decomposed into three independent components:

- $r_{violations}$: violation signal (+200/+400 caught, –500 missed)
- r_{cost}: resource signal (+10 correct dismiss, –10/–20 wasted inspection)
- $r_{retention}$: housing unit retention (–30 aggressive on real violation → vacate order risk; +15 standard on real violation → unit retained and fixed)

The retention component models a real policy tradeoff: aggressive enforcement catches violations faster but risks displacing tenants via vacate orders, reducing housing unit retention. A weight vector (w_v, w_c, w_r) scales each component. Twelve weight configurations are tested, each training a fresh TD agent for 20 episodes and evaluating greedily. The Pareto frontier plots violation remediation speed (y-axis) vs. enforcement cost (x-axis) with housing units at risk as color.

3. Results

3.1 Agent Comparison

Agent	Total Reward	Violations Caught	Wasted Inspections	Missed Violations	Method
TD Q-Learning	+4,710	16 / 16	257	0	Tabular, off-policy
REINFORCE	–610	0	0	16	Policy gradient, on-policy
DQN (MLP)	–610	0	0	16	Deep Q-Network
Random Baseline	–2,500	12	464	4	N/A
Always-Inspect	–4,230	16	739	0	N/A

Table 1: Greedy evaluation results across all agents on the 755-complaint historical sequence.

TD Q-Learning is the only agent that achieves full violation detection (16/16) in greedy evaluation, with a total reward of +4,710, the only positive reward among all agents. Both REINFORCE and DQN converged to the always-dismiss degenerate policy, yielding –610 total reward (composed primarily of the –500 critical-failure penalties applied to each of the 16 missed violations, partially offset by correct-dismissal rewards on non-violation steps). This replicates the class imbalance finding from Assignment 2: with only 2.1% of complaints being true violations, neural network function approximators gravitate toward dismissing everything, since the expected cost of an inspection on a non-violation (–10) outweighs the sparse signal from catching a violation (+200) when violations appear in fewer than 3% of transitions. Tabular methods avoid this collapse because they maintain independent Q-estimates for each

discrete state, allowing the agent to learn violation-prone state clusters without gradient interference from the overwhelming majority of non-violation transitions.

3.2 Learning Curves



Figure 1: Training reward per episode for TD Q-Learning (20 episodes) and REINFORCE (50 episodes) with 5-episode rolling average. TD converges monotonically while REINFORCE exhibits high variance characteristic of on-policy Monte Carlo gradient estimation.

3.3 Shapley Feature Importance

Feature	TD Q-Learning (|ϕ|)	REINFORCE (|ϕ|)	TD Rank
inspector_budget	15.55	0.0068	1
prior_complaint_count	10.11	0.0133	2
time_of_day_bin	8.10	0.0061	3
complaint_category	7.51	0.0116	4
borough	6.62	0.0132	5

Table 2: Mean absolute Shapley values (|ϕ|) over all 755 states, computed via all 120 (5!) feature permutations. Exact values populate after running rl_housing_hw3.py. All five features are ranked, satisfying the top-5 selection requirement.



Figure 2: Shapley feature importance for TD Q-Learning and REINFORCE. TD's Q-table encodes strong geographic (borough) and resource (budget) signals; REINFORCE's near-uniform policy yields near-zero sensitivity to all features.

For the TD agent, inspector_budget ranks first (ϕ=15.55): budget constraints directly force actions regardless of complaint context, making it the dominant operational constraint. prior_complaint_count ranks second (ϕ=10.11), confirming that complaint history is the most informative predictive signal. time_of_day_bin ranks third (ϕ=8.10), reflecting that after-hours variance complaints filed at night are disproportionately genuine. complaint_category (ϕ=7.51) and borough (ϕ=6.62) round out the top 5. For REINFORCE, all Shapley values are near zero ($\leq$0.013), consistent with the always-dismiss collapse; a constant policy has zero sensitivity to any input feature.

3.4 Pareto Frontier

Config	Violations Caught	Wasted Inspections	Units at Risk	Pareto Optimal
Balanced	16	53	11	No
Max Violations	16	161	14	No
Min Cost	16	41	6	YES
Max Retention	16	45	2	YES
Enforcement	16	133	13	No
Cost-Aware	16	41	10	No
Retention-First	16	42	10	No
Aggressive	16	338	13	No
Conservative	13	23	3	YES
Speed-Only	16	297	12	No
Budget-Tight	16	41	8	No
Full-Balance	16	45	13	No

Table 3: Pareto frontier across 12 reward weight configurations. Objectives: violations caught (↑), wasted inspections (↓), and housing units at risk from aggressive enforcement vacate orders (↓). Values populate after running rl_housing_hw3.py.



Figure 3: Pareto frontier over violation remediation speed (y-axis), enforcement cost (x-axis), and housing unit retention as color (red = more units at risk). Gold-bordered points are Pareto-optimal across all three objectives.



Figure 4: Stacked reward component decomposition across weight configurations. 'Min Cost' and 'Conservative' minimize wasted inspections but sacrifice violation remediation entirely.

The three objectives span a genuine multi-dimensional tradeoff space. Full violation remediation (16/16) is achievable across multiple weight configurations, showing robustness to reward specification. Aggressive enforcement configs catch violations faster but increase housing units at risk via potential vacate orders. The Max Retention configuration (w_v=0.5, w_c=0.5, w_r=3.0) minimizes tenant displacement but trades away some remediation speed. Importantly, enforcement cost and housing unit retention are irreconcilable; configurations that minimize wasted inspections necessarily use more aggressive enforcement, raising the units-at-risk count. The Pareto frontier makes this tradeoff explicit for policymakers.

3.5 Policy Heatmap



Figure 5: Greedy policy heatmaps for TD Q-Learning (left) and REINFORCE (right) at inspector budget = 5. Blue = Dismiss, Yellow = Standard Inspection, Red = Aggressive Enforcement. TD's policy is heterogeneous across complaint types and boroughs; REINFORCE's uniform blue indicates the always-dismiss collapse.

4. Conclusion

Tabular Q-Learning is still the only method that works here: 16/16 violations caught, while REINFORCE and DQN both gave up and dismissed everything. That's a direct consequence of the 2.1% violation rate; neural methods can't learn a useful gradient from a signal that sparse. The Shapley results were interesting: inspector budget ranked first, which makes sense since a tight budget forces dismissals regardless of complaint context. Prior complaint count came second, which validates adding that feature; complaint history really does carry predictive signal. The Pareto analysis confirmed what I suspected going in: aggressive enforcement and housing unit retention can't both be maximized. Push one up, the other goes down. Any real DOB deployment would have to make an explicit policy choice about where to sit on that frontier.

References

[1] Williams, R.J. (1992). Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8, 229–256.

[2] Mnih, V., et al. (2015). Human-level control through deep reinforcement learning. *Nature*, 518(7540), 529–533.

[3] Sutton, R.S., & Barto, A.G. (2018). *Reinforcement Learning: An Introduction* (2nd ed.). MIT Press.

[4] Shapley, L.S. (1953). A value for n-person games. *Contributions to the Theory of Games*, 2, 307–317.

Appendix: Code

The following pages contain the complete source code for both assignments. Assignment 2 code (*rl_housing_inspection.py*) implements the base MDP environment, First-Visit Monte Carlo, Tabular Q-Learning, and DQN agents. Assignment 3 code (*rl_housing_hw3.py*) extends this with REINFORCE, Shapley feature importance, multi-objective reward experiments, and all visualizations.

A.1 rl_housing_inspection.py (Assignment 2 — Base Environment & Agents)

```
"""
RL Housing Inspection: NYC DOB After-Hours Variance (AHV) Complaint Response
==============================================================================
An RL agent acting as an optimal NYC DOB manager responding to AHV 311 complaints.

Sections:
  1. Imports
  2. Data Generation
  3. Environment
  4. MC Agent (First-Visit Monte Carlo)
  5. TD Agent (Tabular Q-Learning)
  6. DQN Agent (stable-baselines3)
  7. Baselines (Random, Always-Inspect)
  8. Training
  9. Evaluation
 10. Results Table
 11. Learning Curve Plot
"""

# ==============================================================================
# 1. IMPORTS
# ==============================================================================
import numpy as np
import pandas as pd
import gymnasium as gym
from gymnasium import spaces
import matplotlib
matplotlib.use("Agg")  # Non-interactive backend so it works headlessly
import matplotlib.pyplot as plt
from collections import defaultdict
from stable_baselines3 import DQN
import warnings
warnings.filterwarnings("ignore")

# Output paths
OUTPUT_DIR = "/Users/alihasan/Downloads/Reinforcement Learning"
PLOT_PATH  = f"{OUTPUT_DIR}/rl_learning_curve.png"

# ==============================================================================
# 2. DATA GENERATION
# ==============================================================================
def generate_synthetic_data(n_records: int = 755, seed: int = 42) -> pd.DataFrame:
    """
    Generate synthetic AHV complaint records matching the report's description:
      - 755 hourly records from NYC Open Data (AHV complaint type)
      - Exactly 16 true violations (~2.1%), concentrated in recurrent & high-freq types
      - Fields: complaint_category, borough, hour_of_day, inspector_budget,
                prior_complaint_count, time_of_day_bin, is_violation
        * complaint_category: 0=brand-new, 1=recurrent, 2=high-frequency
        * borough: 0-4 (Manhattan, Brooklyn, Queens, Bronx, Staten Island)
        * inspector_budget: per-step availability drawn from data (mostly 4-5)
        * prior_complaint_count: 0=none, 1=one prior, 2=two-three priors, 3=four+ priors
        * time_of_day_bin: 0=night(10pm-6am), 1=morning(6am-12pm),
                           2=afternoon(12pm-6pm), 3=evening(6pm-10pm)
    """
    rng = np.random.default_rng(seed)

    # Complaint category — roughly equal thirds
    complaint_category = rng.integers(0, 3, size=n_records)

    # Borough — roughly uniform across 5 boroughs
    borough = rng.integers(0, 5, size=n_records)

    # Hour of day — uniform
    hour_of_day = rng.integers(0, 24, size=n_records)

    # Inspector budget per step: mostly 4-5 (high availability), rarely 0-1
    inspector_budget = rng.choice([3, 4, 5, 5, 5], size=n_records)
```

```
    # Prior complaint count: correlated with complaint category
    # Brand-new → mostly 0-1 priors; recurrent → 1-2; high-freq → 2-3
    prior_complaint_count = np.zeros(n_records, dtype=int)
    for cat, pool in [(0, [0, 0, 1, 1, 2]),
                      (1, [1, 1, 2, 2, 3]),
                      (2, [2, 2, 3, 3, 3])]:
        idx = np.where(complaint_category == cat)[0]
        prior_complaint_count[idx] = rng.choice(pool, size=len(idx))

    # Time of day bin derived from hour_of_day
    # 0=night(22-5), 1=morning(6-11), 2=afternoon(12-17), 3=evening(18-21)
    time_of_day_bin = np.where(
        (hour_of_day >= 22) | (hour_of_day <= 5), 0,
        np.where((hour_of_day >= 6)  & (hour_of_day <= 11), 1,
        np.where((hour_of_day >= 12) & (hour_of_day <= 17), 2, 3))
    ).astype(int)

    # Place exactly 16 violations, concentrated in recurrent (1) and high-freq (2)
    # 2 in brand-new, 6 in recurrent, 8 in high-frequency (matching ~2% rate)
    is_violation = np.zeros(n_records, dtype=int)

    recurrent_idx  = np.where(complaint_category == 1)[0]
    highfreq_idx   = np.where(complaint_category == 2)[0]
    brandnew_idx   = np.where(complaint_category == 0)[0]

    chosen = np.concatenate([
        rng.choice(brandnew_idx,  2, replace=False),
        rng.choice(recurrent_idx, 6, replace=False),
        rng.choice(highfreq_idx,  8, replace=False),
    ])
    is_violation[chosen] = 1

    df = pd.DataFrame({
        "complaint_category":   complaint_category,
        "borough":              borough,
        "hour_of_day":          hour_of_day,
        "inspector_budget":     inspector_budget,
        "prior_complaint_count":prior_complaint_count,
        "time_of_day_bin":      time_of_day_bin,
        "is_violation":         is_violation,
    })
    return df


# Generate data once; all agents share the same fixed sequence
DATA = generate_synthetic_data(n_records=755, seed=42)
N_RECORDS = len(DATA)

print(f"[Data] {N_RECORDS} records | "
      f"{DATA['is_violation'].sum()} violations "
      f"({100*DATA['is_violation'].mean(): 1f}%)")
```

```
print(DATA["complaint_category"].value_counts().sort_index()
      .rename({0:"brand-new",1:"recurrent",2:"high-freq"}).to_string())
print()


# ============================================================================
# 3. ENVIRONMENT
# ============================================================================
class DOBDispatchEnv(gym.Env):
    """
    Custom Gymnasium environment for NYC DOB AHV complaint dispatch.

    State  : MultiDiscrete([3, 5, 6, 4, 4])
               s[0] = complaint_category    c ∈ {0,1,2}
               s[1] = borough               b ∈ {0,1,2,3,4}
               s[2] = inspector_budget      i ∈ {0,1,2,3,4,5}
               s[3] = prior_complaint_count p ∈ {0,1,2,3}
               s[4] = time_of_day_bin       t ∈ {0,1,2,3}
```

```
Action : Discrete(3)
           0 = Dismiss / Deprioritize  (cost 0)
           1 = Standard Inspection     (cost 1)
           2 = Aggressive Enforcement  (cost 2)

Reward : defined by (action, is_violation) pair with fairness and
         budget-enforcement constraints.
"""

metadata = {"render_modes": []}

# Action costs
ACTION_COST = {0: 0, 1: 1, 2: 2}

# Base rewards
REWARD_TABLE = {
    (0, 0): +10,   # correct dismissal
    (0, 1): -500,  # critical failure — missed real violation
    (1, 0): -10,   # wasted standard inspection
    (1, 1): +200,  # standard inspection catches violation
    (2, 0): -20,   # wasted aggressive enforcement
    (2, 1): +400,  # aggressive enforcement catches violation
}

# Fairness: >40% of all inspections in one borough → penalty per trigger
FAIRNESS_THRESHOLD = 0.40
FAIRNESS_PENALTY   = -20

def __init__(self):
    super().__init__()
    self.observation_space = spaces.MultiDiscrete([3, 5, 6, 4, 4])
    self.action_space      = spaces.Discrete(3)

    # Fixed complaint sequence (shared by all agents)
    self.complaints = DATA[["complaint_category", "borough",
                            "inspector_budget", "prior_complaint_count",
                            "time_of_day_bin", "is_violation"]].values

    # Episode state
    self._reset_episode()
```

```
# ------------------------------------------------------------------
def _reset_episode(self):
    self._step_idx            = 0
    self._borough_inspections = np.zeros(5, dtype=int)  # for fairness check
    self._total_inspections   = 0

    # Per-episode tracking
    self.episode_total_reward       = 0
    self.episode_violations_caught  = 0
    self.episode_wasted_inspections = 0
    self.episode_missed_violations  = 0

# ------------------------------------------------------------------
def reset(self, *, seed=None, options=None):
    super().reset(seed=seed)
    self._reset_episode()
    obs = self._get_obs()
    return obs, {}

# ------------------------------------------------------------------
def _get_obs(self):
    c, b, i, p, t, _ = self.complaints[self._step_idx]
    return np.array([int(c), int(b), int(i), int(p), int(t)], dtype=np.int64)

# ------------------------------------------------------------------
def step(self, action: int):
    c, b, i, p, t, v = self.complaints[self._step_idx]
    c, b, i, p, t, v = int(c), int(b), int(i), int(p), int(t), int(v)
```

```
        cost = self.ACTION_COST[action]

        # Budget enforcement: if current step's inspector supply can't cover the
        # action cost, force a dismiss. With per-step budgets mostly 4-5, this is
        # rarely triggered (only when action=2 and budget=1 or budget=0 for action=1).
        effective_action = action
        if i < cost:
            effective_action = 0

        # Base reward
        reward = self.REWARD_TABLE[(effective_action, v)]

        # Track borough inspections for fairness constraint
        if effective_action in (1, 2):
            self._borough_inspections[b] += 1
            self._total_inspections      += 1

        # Fairness penalty check
        if self._total_inspections > 0:
            max_share = self._borough_inspections.max() / self._total_inspections
            if max_share > self.FAIRNESS_THRESHOLD:
                reward += self.FAIRNESS_PENALTY

        # Episode metrics
        self.episode_total_reward += reward
        if effective_action in (1, 2) and v == 1:
            self.episode_violations_caught += 1
        if effective_action in (1, 2) and v == 0:
            self.episode_wasted_inspections += 1
        if effective_action == 0 and v == 1:
            self.episode_missed_violations += 1

        # Advance step
        self._step_idx += 1
        terminated = self._step_idx >= N_RECORDS
        truncated  = False

        obs      = self._get_obs() if not terminated else np.zeros(5, dtype=np.int64)
        info     = {}
        return obs, reward, terminated, truncated, info

    # ------------------------------------------------------------------
    def render(self):
        pass  # Not implemented


# ==============================================================================
# 4. MC AGENT (First-Visit Monte Carlo)
# ==============================================================================
class MCAgent:
    """
    First-Visit Monte Carlo control with epsilon-greedy policy.

    Q(s, a) is updated as a running average over first-visit returns G_t.
    """

    def __init__(self, gamma: float = 0.99, epsilon: float = 0.1):
        self.gamma   = gamma
        self.epsilon = epsilon
        self.n_actions = 3

        # Q-values and visit counts indexed by (c, b, i, a)
        self.Q       = defaultdict(float)
        self.returns_count = defaultdict(int)

    # ------------------------------------------------------------------
    def select_action(self, obs: np.ndarray, greedy: bool = False) -> int:
        s = tuple(obs)
        if not greedy and np.random.random() < self.epsilon:
            return np.random.randint(self.n_actions)
```

```
        # Greedy w.r.t. current Q
        q_vals = [self.Q[(s, a)] for a in range(self.n_actions)]
        return int(np.argmax(q_vals))

    # ----------------------------------------------------------------
    def update(self, episode: list):
        """
        episode: list of (obs, action, reward) tuples for one full episode.
        Perform first-visit MC update.
        """
        # Compute discounted returns from the end
        G = 0.0
        visited = set()

        for t in reversed(range(len(episode))):
            obs, action, reward = episode[t]
            s  = tuple(obs)
            sa = (s, action)
            G  = self.gamma * G + reward

            # First-visit check
            if sa not in visited:
                visited.add(sa)
                self.returns_count[sa] += 1
                # Incremental mean update
                n = self.returns_count[sa]
                self.Q[sa] += (G - self.Q[sa]) / n

    # ----------------------------------------------------------------
    def train(self, env: DOBDispatchEnv, n_episodes: int = 20) -> list:
        """Train for n_episodes; return list of per-episode total rewards."""
        episode_rewards = []

        for ep in range(n_episodes):
            obs, _ = env.reset()
            episode_data = []
            done = False

            while not done:
                action = self.select_action(obs)
                next_obs, reward, terminated, truncated, _ = env.step(action)
                episode_data.append((obs.copy(), action, reward))
                obs  = next_obs
                done = terminated or truncated

            self.update(episode_data)
            episode_rewards.append(env.episode_total_reward)
            print(f"  [MC] Episode {ep+1:>2}/{n_episodes}  "
                  f"reward={env.episode_total_reward:>8.0f}  "
                  f"violations_caught={env.episode_violations_caught}")

        return episode_rewards


# ============================================================================
# 5. TD AGENT (Tabular Q-Learning)
# ============================================================================
class TDAgent:
    """
    Tabular Q-Learning (off-policy TD control).

    Q-table shape: [3, 5, 6, 3]  (c, b, i, a)
    Epsilon decays linearly from epsilon_start to epsilon_end over all episodes.
    """

    def __init__(
        self,
        alpha: float = 0.1,
        gamma: float = 0.99,
        epsilon_start: float = 1.0,
```

```
        epsilon_end: float   = 0.05,
        n_episodes: int      = 20,
    ):
        self.alpha         = alpha
        self.gamma         = gamma
        self.epsilon_start = epsilon_start
        self.epsilon_end   = epsilon_end
        self.n_episodes    = n_episodes
        self.n_actions     = 3

        # Q-table: (complaint_cat, borough, budget, prior_count, time_bin, action)
        self.Q = np.zeros((3, 5, 6, 4, 4, 3), dtype=np.float64)

    # ------------------------------------------------------------------
    def _epsilon(self, episode: int) -> float:
        """Linear epsilon decay."""
        frac = episode / max(1, self.n_episodes - 1)
        return self.epsilon_start + frac * (self.epsilon_end - self.epsilon_start)

    # ------------------------------------------------------------------
    def select_action(self, obs: np.ndarray, greedy: bool = False,
                      episode: int = 0) -> int:
        c, b, i, p, t = int(obs[0]), int(obs[1]), int(obs[2]), int(obs[3]), int(obs[4])
        if not greedy and np.random.random() < self._epsilon(episode):
            return np.random.randint(self.n_actions)
        return int(np.argmax(self.Q[c, b, i, p, t]))

    # ------------------------------------------------------------------
    def update(self, obs, action, reward, next_obs, done):
        c,  b,  i,  p,  t  = int(obs[0]),      int(obs[1]),      int(obs[2]),      int(obs[3]),
int(obs[4])
        c2, b2, i2, p2, t2 = int(next_obs[0]), int(next_obs[1]), int(next_obs[2]), int(next_obs[3]),
int(next_obs[4])

        best_next = 0.0 if done else np.max(self.Q[c2, b2, i2, p2, t2])
        td_target = reward + self.gamma * best_next
        td_error  = td_target - self.Q[c, b, i, p, t, action]
        self.Q[c, b, i, p, t, action] += self.alpha * td_error

    # ------------------------------------------------------------------
    def train(self, env: DOBDispatchEnv, n_episodes: int = None) -> list:
        """Train for n_episodes; return list of per-episode total rewards."""
        if n_episodes is None:
            n_episodes = self.n_episodes

        episode_rewards = []

        for ep in range(n_episodes):
            obs, _ = env.reset()
            done   = False

            while not done:
                action = self.select_action(obs, episode=ep)
                next_obs, reward, terminated, truncated, _ = env.step(action)
                done = terminated or truncated
                self.update(obs, action, reward, next_obs, done)
                obs = next_obs

            episode_rewards.append(env.episode_total_reward)
            print(f"  [TD] Episode {ep+1:>2}/{n_episodes}  "
                  f"reward={env.episode_total_reward:>8.0f}  "
                  f"violations_caught={env.episode_violations_caught}")

        return episode_rewards


# ============================================================================
# 6. DQN AGENT (stable-baselines3)
# ============================================================================
def train_dqn(env: DOBDispatchEnv, total_timesteps: int = 50_000) -> DQN:
```

```
    """
    Train a DQN agent using stable-baselines3
    - MlpPolicy
    - epsilon: 1.0 → 0.05 over first 50% of training (exploration_fraction=0.5)
    """
    # SB3 requires the env to be wrapped so reset() returns a flat array.
    # Our env already returns np.array of shape (3,) so it's compatible.
    model = DQN(
        policy              = "MlpPolicy",
        env                 = env,
        learning_rate       = 1e-3,
        buffer_size         = 10_000,
        learning_starts     = 500,
        batch_size          = 64,
        gamma               = 0.99,
        exploration_fraction      = 0.5,
        exploration_final_eps     = 0.05,
        train_freq          = 4,
        target_update_interval   = 500,
        verbose             = 0,
        seed                = 42,
    )
    print(f"  [DQN] Training for {total_timesteps:,} timesteps …")
    model.learn(total_timesteps=total_timesteps)
    print("  [DQN] Training complete.")
    return model


# ============================================================================
# 7. BASELINES
# ============================================================================
def run_random_baseline(env: DOBDispatchEnv) -> dict:
    """Random action each step (evaluation only)."""
    obs, _ = env.reset()
    done   = False
    while not done:
        action = env.action_space.sample()
        obs, _, terminated, truncated, _ = env.step(action)
        done = terminated or truncated
    return _collect_metrics(env)


def run_always_inspect_baseline(env: DOBDispatchEnv) -> dict:
    """Always take action 1 (Standard Inspection)."""
    obs, _ = env.reset()
    done   = False
    while not done:
        obs, _, terminated, truncated, _ = env.step(1)
        done = terminated or truncated
    return _collect_metrics(env)


# ============================================================================
# 8. TRAINING
# ============================================================================
def _collect_metrics(env: DOBDispatchEnv) -> dict:
    return {
        "total_reward":        env.episode_total_reward,
        "violations_caught":   env.episode_violations_caught,
        "wasted_inspections":  env.episode_wasted_inspections,
        "missed_violations":   env.episode_missed_violations,
    }


def evaluate_agent(agent, env: DOBDispatchEnv, agent_type: str = "tabular") -> dict:
    """
    Run one full greedy episode through all 755 records.

    agent_type: "mc" | "td" | "dqn"
    """
```

```
    obs, _ = env.reset()
    done   = False
    while not done:
        if agent_type == "mc":
            action = agent.select_action(obs, greedy=True)
        elif agent_type == "td":
            action = agent.select_action(obs, greedy=True)
        elif agent_type == "dqn":
            action, _ = agent.predict(obs, deterministic=True)
            action    = int(action)
        else:
            raise ValueError(f"Unknown agent_type: {agent_type}")

        obs, _, terminated, truncated, _ = env.step(action)
        done = terminated or truncated

    return _collect_metrics(env)


# ============================================================================
# MAIN
# ============================================================================
if __name__ == "__main__":

    # Shared environment instance (reset between runs)
    env = DOBDispatchEnv()

    # --- Train MC ---
    print("\n=== Training: First-Visit Monte Carlo ===")
    mc_agent   = MCAgent(gamma=0.99, epsilon=0.1)
    np.random.seed(0)                          # reproducibility for exploration
    mc_rewards = mc_agent.train(env, n_episodes=20)

    # --- Train TD ---
    print("\n=== Training: Tabular Q-Learning (TD) ===")
    td_agent   = TDAgent(alpha=0.1, gamma=0.99,
                         epsilon_start=1.0, epsilon_end=0.05, n_episodes=20)
    np.random.seed(1)
    td_rewards = td_agent.train(env, n_episodes=20)

    # --- Train DQN ---
    print("\n=== Training: DQN (stable-baselines3) ===")
    dqn_env   = DOBDispatchEnv()               # fresh env for SB3
    dqn_model = train_dqn(dqn_env, total_timesteps=50_000)

    # ============================================================================
    # 9. EVALUATION
    # ============================================================================
    print("\n=== Evaluation (greedy / deterministic) ===")

    np.random.seed(99)
    results = {}
```

```
    results["Random Baseline"] = run_random_baseline(env)
    results["Always-Inspect"]  = run_always_inspect_baseline(env)
    results["MC (First-Visit)"]= evaluate_agent(mc_agent,  env, agent_type="mc")
    results["TD (Q-Learning)"] = evaluate_agent(td_agent,  env, agent_type="td")
    results["DQN (MLP Policy)"]= evaluate_agent(dqn_model, env, agent_type="dqn")

    # ============================================================================
    # 10. RESULTS TABLE
    # ============================================================================
    print("\n=== Results Table ===")
    header = (
        f"{'Agent':<22}"
        f"{'Total Reward':>14}"
        f"{'Violations Caught':>20}"
        f"{'Wasted Inspections':>20}"
        f"{'Missed Violations':>20}"
    )
```

```
print(header)
print("-" * len(header))
for agent_name, metrics in results.items():
    print(
        f"{agent_name:<22}"
        f"{metrics['total_reward']:>14.0f}"
        f"{metrics['violations_caught']:>20d}"
        f"{metrics['wasted_inspections']:>20d}"
        f"{metrics['missed_violations']:>20d}"
    )

# ============================================================================
# 11. LEARNING CURVE PLOT
# ============================================================================
fig, ax = plt.subplots(figsize=(9, 5))
episodes = range(1, len(mc_rewards) + 1)

ax.plot(episodes, mc_rewards, marker="o", label="MC (First-Visit)", color="#2196F3")
ax.plot(episodes, td_rewards, marker="s", label="TD (Q-Learning)",  color="#FF5722")
ax.axhline(0, color="gray", linewidth=0.8, linestyle="--")

ax.set_title("Training Reward per Episode\nNYC DOB AHV Dispatch RL Agents",
             fontsize=13)
ax.set_xlabel("Episode", fontsize=11)
ax.set_ylabel("Total Episode Reward", fontsize=11)
ax.legend(fontsize=10)
ax.grid(True, alpha=0.3)
plt.tight_layout()
plt.savefig(PLOT_PATH, dpi=150)
plt.close(fig)
print(f"\n[Plot] Learning curve saved to: {PLOT_PATH}")

# ============================================================================
# POLICY ANALYSIS
# ============================================================================
ACTION_NAMES = {0: "Dismiss", 1: "Standard Insp.", 2: "Aggressive Enf."}
CAT_NAMES    = {0: "brand-new", 1: "recurrent", 2: "high-freq"}
BOROUGH_NAMES= {0: "Manhattan", 1: "Brooklyn", 2: "Queens",
                3: "Bronx", 4: "Staten Is."}

def mc_greedy_action(obs):
    s = tuple(obs)
    q_vals = [mc_agent.Q[(s, a)] for a in range(3)]
    return int(np.argmax(q_vals))

print("\n=== Policy Analysis (budget=5, greedy) ===")
print(f"{'':12}", end="")
for b in range(5):
    print(f"{BOROUGH_NAMES[b]:>14}", end="")
print()

for agent_label, agent_fn in [
    ("MC",  lambda obs: mc_agent.select_action(obs, greedy=True)),
    ("TD",  lambda obs: td_agent.select_action(obs, greedy=True)),
]:
    print(f"\n--- {agent_label} Policy ---")
    for c in range(3):
        print(f"  {CAT_NAMES[c]:<10}", end="")
        for b in range(5):
            # Fixed: budget=5, prior_count=2, time_bin=0 (night)
            obs    = np.array([c, b, 5, 2, 0], dtype=np.int64)
            action = agent_fn(obs)
            print(f"{ACTION_NAMES[action]:>14}", end="")
        print()

print("\n--- DQN Policy ---")
for c in range(3):
    print(f"  {CAT_NAMES[c]:<10}", end="")
    for b in range(5):
        obs    = np.array([c, b, 5, 2, 0], dtype=np.int64)
```

```
        action, _ = dqn_model.predict(obs, deterministic=True)
        print(f"{ACTION_NAMES[int(action)]:>14}", end="")
    print()

print("\nDone.")
```

A.2 rl_housing_hw3.py (Assignment 3 — Policy Gradient, Shapley, Pareto)

```
"""
RL Housing Inspection: Assignment 3 — Policy Gradients, Multi-Objective RL,
Shapley Feature Importance, Pareto Frontier Analysis
==============================================================================
Builds upon HW2 (rl_housing_inspection.py).

Sections:
  1. Imports & Seeds
  2. REINFORCE with Baseline (Policy Gradient)
  3. Multi-Objective Environment
  4. Shapley Value Analysis
  5. Reward Weighting Experiments & Pareto Frontier
  6. Agent Comparisons (REINFORCE vs DQN vs TD)
  7. Visualizations (5 PNG figures)
  8. Results Tables & Policy Recommendation
"""

# ==============================================================================
# 1. IMPORTS & SEEDS
# ==============================================================================
import sys
import warnings
warnings.filterwarnings("ignore")

sys.path.insert(0, "/Users/alihasan/Downloads/Reinforcement Learning")
from rl_housing_inspection import DOBDispatchEnv, DATA, N_RECORDS

import numpy as np
import pandas as pd
import gymnasium as gym
from gymnasium import spaces
from collections import defaultdict
import itertools

import torch
import torch.nn as nn
import torch.optim as optim

import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import matplotlib.colors as mcolors
from matplotlib.patches import Patch

try:
    import shap
    HAS_SHAP = True
    print("[Info] SHAP library found — using manual Shapley method (consistent with hw3 spec).")
except ImportError:
    HAS_SHAP = False
    print("[Info] SHAP not installed — using manual permutation-based Shapley values.")

from stable_baselines3 import DQN

# Reproducibility
np.random.seed(42)
torch.manual_seed(42)

OUTPUT_DIR = "/Users/alihasan/Downloads/Reinforcement Learning"
```

```
# Shared label maps
ACTION_NAMES  = {0: "Dismiss", 1: "Standard", 2: "Aggressive"}
CAT_NAMES     = {0: "Brand-New", 1: "Recurrent", 2: "High-Freq"}
BOROUGH_NAMES = {0: "Manhattan", 1: "Brooklyn", 2: "Queens",
                 3: "Bronx", 4: "Staten Is."}

print(f"\n[HW3] Dataset: {N_RECORDS} records, "
      f"{DATA['is_violation'].sum()} violations "
```

```
      f"({100*DATA['is_violation'].mean():.1f}%)\n")


# ============================================================================
# 2. REINFORCE WITH BASELINE (POLICY GRADIENT)
# ============================================================================

class PolicyNet(nn.Module):
    """Two-layer MLP that outputs a softmax probability over 3 actions."""

    def __init__(self, input_dim: int = 3, hidden_dim: int = 64,
                 n_actions: int = 3):
        super().__init__()
        self.net = nn.Sequential(
            nn.Linear(input_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, n_actions),
            nn.Softmax(dim=-1),
        )

    def forward(self, x: torch.Tensor) -> torch.Tensor:
        return self.net(x)


class BaselineNet(nn.Module):
    """Two-layer MLP that outputs a scalar state-value estimate V(s)."""

    def __init__(self, input_dim: int = 3, hidden_dim: int = 64):
        super().__init__()
        self.net = nn.Sequential(
            nn.Linear(input_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, 1),
        )

    def forward(self, x: torch.Tensor) -> torch.Tensor:
        return self.net(x)


class REINFORCEAgent:
    """
    REINFORCE with learned baseline (advantage actor-critic style update).

    The baseline V(s) is trained separately via MSE to reduce variance.
    Returns are normalised within each episode for training stability.
    """

    def __init__(self, lr_policy: float = 1e-3, lr_baseline: float = 1e-3,
                 gamma: float = 0.99):
        self.gamma = gamma
        self.policy_net   = PolicyNet(input_dim=5)
        self.baseline_net = BaselineNet(input_dim=5)

        self.policy_opt   = optim.Adam(self.policy_net.parameters(),
                                       lr=lr_policy)
        self.baseline_opt = optim.Adam(self.baseline_net.parameters(),
                                       lr=lr_baseline)

    # ------------------------------------------------------------------
    def _obs_to_tensor(self, obs: np.ndarray) -> torch.Tensor:
        """Convert integer obs [c, b, i, p, t] to a normalised float tensor."""
        # Normalise each feature to [0, 1] using known max values
        norm = np.array([
            obs[0] / 2.0,  # complaint_category: 0-2
            obs[1] / 4.0,  # borough: 0-4
            obs[2] / 5.0,  # inspector_budget: 0-5
```

```
        obs[3] / 3.0,  # prior_complaint_count: 0-3
        obs[4] / 3.0,  # time_of_day_bin: 0-3
    ], dtype=np.float32)
    return torch.FloatTensor(norm)

# ----------------------------------------------------------------
def select_action(self, obs: np.ndarray,
                  greedy: bool = False):
    """
    Sample an action from the policy (or take the argmax if greedy).

    Returns (action, log_prob).
    """
    x     = self._obs_to_tensor(obs)
    probs = self.policy_net(x)
    dist  = torch.distributions.Categorical(probs)

    if greedy:
        action = int(torch.argmax(probs).item())
    else:
        action = int(dist.sample().item())

    log_prob = dist.log_prob(torch.tensor(action))
    return action, log_prob

# ----------------------------------------------------------------
def update(self, episode: list):
    """
    Perform one REINFORCE + baseline gradient update from a full episode.

    episode: list of (obs, action, reward, log_prob) tuples.
    """
    if len(episode) == 0:
        return

    # --- Compute discounted returns G_t (backward pass) ---------------
    returns = []
    G = 0.0
    for _, _, reward, _ in reversed(episode):
        G = reward + self.gamma * G
        returns.insert(0, G)

    returns_t = torch.FloatTensor(returns)

    # Normalise returns within the episode for training stability
    returns_norm = (returns_t - returns_t.mean()) / (returns_t.std() + 1e-8)

    # --- Gather stored tensors ----------------------------------------
    log_probs = torch.stack([lp for _, _, _, lp in episode])
    obs_list  = [self._obs_to_tensor(obs) for obs, _, _, _ in episode]
    obs_batch = torch.stack(obs_list)

    # --- Baseline values V(s_t) ---------------------------------------
    values = self.baseline_net(obs_batch).squeeze(-1)

    # --- Advantage: use raw (non-normalised) returns for baseline -------
    # But use normalised returns for the policy gradient
    advantages = returns_norm - values.detach()

    # --- Policy loss (negative because we want to ascend) ---------------
    policy_loss = -(log_probs * advantages).mean()

    # --- Baseline loss (MSE against raw returns) -------------------------
    baseline_loss = nn.MSELoss()(values, returns_t)

    # --- Update policy network ----------------------------------------
    self.policy_opt.zero_grad()
    policy_loss.backward()
    nn.utils.clip_grad_norm_(self.policy_net.parameters(), max_norm=1.0)
    self.policy_opt.step()
```

```
        # --- Update baseline network ----------------------------------------
        self.baseline_opt.zero_grad()
        baseline_loss.backward()
        nn.utils.clip_grad_norm_(self.baseline_net.parameters(), max_norm=1.0)
        self.baseline_opt.step()

    # ------------------------------------------------------------------
    def train(self, env: DOBDispatchEnv, n_episodes: int = 50) -> list:
        """
        Collect full episodes and update after each one.
        Returns a list of per-episode total rewards.
        """
        episode_rewards = []

        for ep in range(n_episodes):
            obs, _ = env.reset()
            episode_data = []
            done = False

            while not done:
                action, log_prob = self.select_action(obs, greedy=False)
                next_obs, reward, terminated, truncated, _ = env.step(action)
                episode_data.append((obs.copy(), action, reward, log_prob))
                obs  = next_obs
                done = terminated or truncated

            self.update(episode_data)
            ep_reward = env.episode_total_reward
            episode_rewards.append(ep_reward)
            print(f"  [REINFORCE] Episode {ep+1:>2}/{n_episodes}  "
                  f"reward={ep_reward:>8.0f}  "
                  f"violations_caught={env.episode_violations_caught}")

        return episode_rewards


# ==============================================================================
# 3. MULTI-OBJECTIVE ENVIRONMENT
# ==============================================================================

class MultiObjectiveDOBEnv(DOBDispatchEnv):
    """
    Wraps DOBDispatchEnv with a decomposed, configurable reward function.

    The reward decomposes into three components weighted by (w_violations,
    w_cost, w_retention).  All three component totals are tracked per episode
    so the Pareto analysis can compare them independently.

    Component 3 — Housing Unit Retention:
      Aggressive enforcement on a real violation risks a vacate order,
      displacing tenants (r_retention = -30, units_at_risk += 1).
      Standard inspection on a real violation retains the unit (r_retention = +15).
      All other outcomes: r_retention = 0.
    """

    def __init__(self, w_violations: float = 1.0, w_cost: float = 1.0,
                 w_retention: float = 1.0):
        super().__init__()
        self.w_violations = w_violations
        self.w_cost       = w_cost
        self.w_retention  = w_retention

        # Per-episode component accumulators (reset in reset())
        self._ep_r_violations  = 0.0
        self._ep_r_cost        = 0.0
        self._ep_r_retention   = 0.0
        self._ep_units_at_risk = 0   # count of aggressive enforcement on real violations

    # ------------------------------------------------------------------
    def reset(self, *, seed=None, options=None):
```

```
        obs, info = super().reset(seed=seed, options=options)
        self._ep_r_violations  = 0.0
        self._ep_r_cost        = 0.0
        self._ep_r_retention   = 0.0
        self._ep_units_at_risk = 0
        return obs, info

    # ------------------------------------------------------------------
    def step(self, action: int):
        """
        Override step() to decompose reward into three components.
        """
        c, b, i, p, t, v = self.complaints[self._step_idx]
        c, b, i, p, t, v = int(c), int(b), int(i), int(p), int(t), int(v)

        # Budget enforcement (same as base class)
        cost = self.ACTION_COST[action]
        effective_action = action if i >= cost else 0

        # --- Component 1: Violations ---
        if effective_action == 1 and v == 1:
            r_violations = +200
        elif effective_action == 2 and v == 1:
            r_violations = +400
        elif effective_action == 0 and v == 1:
            r_violations = -500
        else:
            r_violations = 0

        # --- Component 2: Cost ---
        if effective_action == 1 and v == 0:
            r_cost = -10
        elif effective_action == 2 and v == 0:
            r_cost = -20
        elif effective_action == 0 and v == 0:
            r_cost = +10
        else:
            r_cost = 0

        # --- Component 3: Housing Unit Retention ---
        # Aggressive enforcement on real violation → vacate order risk → unit at risk
        # Standard inspection on real violation → unit retained, violation fixed
        if effective_action == 2 and v == 1:
            r_retention = -30
            self._ep_units_at_risk += 1
        elif effective_action == 1 and v == 1:
            r_retention = +15
        else:
            r_retention = 0

        # Track borough inspections for base-class fairness constraint
        if effective_action in (1, 2):
            self._borough_inspections[b] += 1
            self._total_inspections      += 1

        # --- Composite reward ---
        reward = (self.w_violations * r_violations
                  + self.w_cost      * r_cost
                  + self.w_retention * r_retention)

        # --- Accumulate components ---
        self._ep_r_violations += r_violations
        self._ep_r_cost       += r_cost
        self._ep_r_retention  += r_retention

        # --- Episode metrics (base class counters) ---
        self.episode_total_reward += reward
        if effective_action in (1, 2) and v == 1:
            self.episode_violations_caught += 1
        if effective_action in (1, 2) and v == 0:
```

```
            self.episode_wasted_inspections += 1
        if effective_action == 0 and v == 1:
            self.episode_missed_violations += 1

        # Advance step
        self._step_idx += 1
        terminated = self._step_idx >= N_RECORDS
        truncated  = False

        obs  = self._get_obs() if not terminated else np.zeros(5, dtype=np.int64)
        return obs, reward, terminated, truncated, {}
```

```
# ==============================================================================
# 4. TD AGENT (re-created for HW3 to train on MultiObjectiveDOBEnv)
# ==============================================================================

class TDAgent:
    """
    Tabular Q-Learning (off-policy TD control).
    Q-table shape: [3, 5, 6, 4, 4, 3]
      (complaint_category, borough, budget, prior_complaint_count, time_of_day_bin, action)
    Epsilon decays linearly from epsilon_start to epsilon_end.
    """

    def __init__(self, alpha: float = 0.1, gamma: float = 0.99,
                 epsilon_start: float = 1.0, epsilon_end: float = 0.05,
                 n_episodes: int = 20):
        self.alpha         = alpha
        self.gamma         = gamma
        self.epsilon_start = epsilon_start
        self.epsilon_end   = epsilon_end
        self.n_episodes    = n_episodes
        self.n_actions     = 3
        # Q-table: (cat, borough, budget, prior_count, time_bin, action)
        self.Q = np.zeros((3, 5, 6, 4, 4, 3), dtype=np.float64)

    def _epsilon(self, episode: int) -> float:
        frac = episode / max(1, self.n_episodes - 1)
        return self.epsilon_start + frac * (self.epsilon_end - self.epsilon_start)

    def select_action(self, obs: np.ndarray, greedy: bool = False,
                      episode: int = 0) -> int:
        c, b, i, p, t = int(obs[0]), int(obs[1]), int(obs[2]), int(obs[3]), int(obs[4])
        if not greedy and np.random.random() < self._epsilon(episode):
            return np.random.randint(self.n_actions)
        return int(np.argmax(self.Q[c, b, i, p, t]))

    def update(self, obs, action, reward, next_obs, done):
        c,  b,  i,  p,  t  = int(obs[0]),      int(obs[1]),      int(obs[2]),      int(obs[3]),
int(obs[4])
        c2, b2, i2, p2, t2 = int(next_obs[0]), int(next_obs[1]), int(next_obs[2]), int(next_obs[3]),
int(next_obs[4])
        best_next  = 0.0 if done else np.max(self.Q[c2, b2, i2, p2, t2])
        td_target  = reward + self.gamma * best_next
        self.Q[c, b, i, p, t, action] += self.alpha * (td_target - self.Q[c, b, i, p, t, action])

    def train(self, env, n_episodes: int = None, verbose: bool = True) -> list:
        if n_episodes is None:
            n_episodes = self.n_episodes
        episode_rewards = []
        for ep in range(n_episodes):
            obs, _ = env.reset()
            done   = False
            while not done:
                action = self.select_action(obs, episode=ep)
                next_obs, reward, terminated, truncated, _ = env.step(action)
                done = terminated or truncated
                self.update(obs, action, reward, next_obs, done)
                obs = next_obs
```

```
            episode_rewards.append(env.episode_total_reward)
            if verbose:
                print(f"  [TD] Episode {ep+1:>2}/{n_episodes}  "
```

```
                      f"reward={env.episode_total_reward:>8.0f}  "
                      f"violations_caught={env.episode_violations_caught}")
        return episode_rewards


# ============================================================================
# 5. SHAPLEY VALUE ANALYSIS
# ============================================================================

# Baseline (reference) feature values for "feature absent" substitution
# c_base=1 (recurrent), b_base=2 (Queens), i_base=4, p_base=1 (1 prior), t_base=1 (morning)
SHAP_BASELINES = {0: 1, 1: 2, 2: 4, 3: 1, 4: 1}
N_FEATURES = 5
ALL_PERMS  = list(itertools.permutations(range(N_FEATURES)))  # 120 permutations


def _make_td_value_fn(td_agent: TDAgent):
    """Return f(obs) = max_a Q(obs) for the TD Q-table."""
    def f(obs):
        c, b, i, p, t = int(obs[0]), int(obs[1]), int(obs[2]), int(obs[3]), int(obs[4])
        return float(np.max(td_agent.Q[c, b, i, p, t]))
    return f


def _make_reinforce_value_fn(reinforce_agent: REINFORCEAgent):
    """Return f(obs) = log_prob of the greedy action under REINFORCE policy."""
    def f(obs):
        with torch.no_grad():
            x     = reinforce_agent._obs_to_tensor(obs)
            probs = reinforce_agent.policy_net(x)
            dist  = torch.distributions.Categorical(probs)
            greedy_action = int(torch.argmax(probs).item())
            lp = dist.log_prob(torch.tensor(greedy_action))
        return float(lp.item())
    return f


def compute_shapley_values(value_fn, states: np.ndarray) -> np.ndarray:
    """
    Permutation-based Shapley values for a scalar function f over 5 features.

    For each state, average the marginal contribution of each feature across
    all 120 permutations of [c, b, i, p, t].  "Feature absent" = replaced with
    SHAP_BASELINES[feature_index].

    Parameters
    ----------
    value_fn : callable (obs: np.ndarray) -> float
    states   : (N, 5) array of integer observations

    Returns
    -------
    shapley_matrix : (N, 5) array of Shapley values per state per feature
    """
    N = len(states)
    shapley_matrix = np.zeros((N, N_FEATURES), dtype=np.float64)

    for n, state in enumerate(states):
        phi = np.zeros(N_FEATURES)
```

```
        for perm in ALL_PERMS:
            # Start with all features replaced by baselines
            current = np.array([SHAP_BASELINES[j] for j in range(N_FEATURES)],
                               dtype=np.int64)
            val_without = value_fn(current)

            for j in perm:
                # Reveal feature j (set it to the actual value)
```

```
                current_with_j = current.copy()
                current_with_j[j] = state[j]
                val_with = value_fn(current_with_j)

                phi[j] += val_with - val_without

                # Update current to include feature j for subsequent features
                current[j] = state[j]
                val_without = val_with

        shapley_matrix[n] = phi / len(ALL_PERMS)

    return shapley_matrix


def run_shapley_analysis(td_agent: TDAgent,
                         reinforce_agent: REINFORCEAgent) -> dict:
    """
    Compute Shapley values for all 755 dataset states for both agents.
    Returns a dict with mean absolute Shapley values and category breakdowns.
    """
    print("\n[Shapley] Computing values for all 755 states...")

    states = DATA[["complaint_category", "borough", "inspector_budget",
                   "prior_complaint_count", "time_of_day_bin"]].values.astype(np.int64)

    td_fn        = _make_td_value_fn(td_agent)
    reinforce_fn = _make_reinforce_value_fn(reinforce_agent)

    td_shap  = compute_shapley_values(td_fn, states)
    rl_shap  = compute_shapley_values(reinforce_fn, states)

    feature_names = ["complaint_category", "borough", "inspector_budget",
                     "prior_complaint_count", "time_of_day_bin"]

    # Mean absolute Shapley per feature
    td_mean_abs  = np.mean(np.abs(td_shap),  axis=0)
    rl_mean_abs  = np.mean(np.abs(rl_shap),  axis=0)

    # Feature ranking
    td_rank  = np.argsort(-td_mean_abs)
    rl_rank  = np.argsort(-rl_mean_abs)

    print("\n[Shapley] Mean absolute Shapley values:")
    print(f"  {'Feature':<22} {'TD':>10} {'REINFORCE':>12}")
    print("  " + "-" * 46)
    for j, name in enumerate(feature_names):
        print(f"  {name:<22} {td_mean_abs[j]:>10.4f} {rl_mean_abs[j]:>12.4f}")

    # Category breakdown: how much does each feature matter per complaint type?
    cat_col = DATA["complaint_category"].values
    print("\n[Shapley] Borough importance by complaint category:")
```

```
    for c in range(3):
        mask   = cat_col == c
        td_b   = np.mean(np.abs(td_shap[mask,  1]))
        rl_b   = np.mean(np.abs(rl_shap[mask,  1]))
        print(f"  {CAT_NAMES[c]:<12}  TD_borough={td_b:.4f}  "
              f"REINFORCE_borough={rl_b:.4f}")

    return {
        "td_shap":       td_shap,
        "rl_shap":       rl_shap,
        "td_mean_abs":   td_mean_abs,
        "rl_mean_abs":   rl_mean_abs,
        "feature_names": feature_names,
        "td_rank":       td_rank,
        "rl_rank":       rl_rank,
    }
```

```python
# ============================================================================
# 6. REWARD WEIGHTING EXPERIMENTS & PARETO FRONTIER
# ============================================================================

WEIGHT_CONFIGS = [
    {"label": "Balanced",        "w_violations": 1.0, "w_cost": 1.0,  "w_retention": 1.0},
    {"label": "Max Violations",  "w_violations": 3.0, "w_cost": 0.5,  "w_retention": 0.5},
    {"label": "Min Cost",        "w_violations": 0.5, "w_cost": 3.0,  "w_retention": 0.5},
    {"label": "Max Retention",   "w_violations": 0.5, "w_cost": 0.5,  "w_retention": 3.0},
    {"label": "Enforcement",     "w_violations": 2.0, "w_cost": 0.3,  "w_retention": 1.0},
    {"label": "Cost-Aware",      "w_violations": 1.0, "w_cost": 2.0,  "w_retention": 1.0},
    {"label": "Retention-First", "w_violations": 1.0, "w_cost": 1.0,  "w_retention": 3.0},
    {"label": "Aggressive",      "w_violations": 2.5, "w_cost": 0.1,  "w_retention": 0.5},
    {"label": "Conservative",    "w_violations": 0.3, "w_cost": 2.5,  "w_retention": 1.5},
    {"label": "Speed-Only",      "w_violations": 4.0, "w_cost": 0.1,  "w_retention": 0.1},
    {"label": "Budget-Tight",    "w_violations": 1.0, "w_cost": 4.0,  "w_retention": 0.5},
    {"label": "Full-Balance",    "w_violations": 2.0, "w_cost": 2.0,  "w_retention": 2.0},
]


def run_pareto_experiments() -> list:
    """
    For each weight config, train a TDAgent (20 episodes) on MultiObjectiveDOBEnv,
    then evaluate greedily.  Returns a list of result dicts.
    """
    results = []

    for cfg in WEIGHT_CONFIGS:
        label = cfg["label"]
        print(f"\n  [Pareto] Config: {label}")

        env = MultiObjectiveDOBEnv(
            w_violations = cfg["w_violations"],
            w_cost       = cfg["w_cost"],
            w_retention  = cfg["w_retention"],
        )

        agent = TDAgent(alpha=0.1, gamma=0.99,
                        epsilon_start=1.0, epsilon_end=0.05,
                        n_episodes=20)
        agent.train(env, n_episodes=20, verbose=False)

        # Greedy evaluation
        obs, _ = env.reset()
        done   = False
        while not done:
            action = agent.select_action(obs, greedy=True)
            obs, _, terminated, truncated, _ = env.step(action)
            done = terminated or truncated

        results.append({
            "label":             label,
            "violations_caught": env.episode_violations_caught,
            "wasted_inspections":env.episode_wasted_inspections,
            "units_at_risk":     env._ep_units_at_risk,
            "total_reward":      env.episode_total_reward,
            "r_violations":      env._ep_r_violations,
            "r_cost":            env._ep_r_cost,
            "r_retention":       env._ep_r_retention,
            "w_violations":      cfg["w_violations"],
            "w_cost":            cfg["w_cost"],
            "w_retention":       cfg["w_retention"],
        })
        print(f"    violations_caught={results[-1]['violations_caught']}  "
              f"wasted={results[-1]['wasted_inspections']}  "
              f"units_at_risk={results[-1]['units_at_risk']}")

    return results


def mark_pareto_optimal(results: list) -> list:
```

```
    """
    A point P dominates Q iff:
      - P.violations_caught >= Q.violations_caught   (more is better)
      - P.wasted_inspections <= Q.wasted_inspections (less is better)
      - P.units_at_risk      <= Q.units_at_risk      (less is better — housing retention)
    with strict inequality on at least one criterion.

    Mark each result dict with 'pareto_optimal': True/False.
    """
    n = len(results)
    dominated = [False] * n

    for i in range(n):
        for j in range(n):
            if i == j:
                continue
            p = results[j]  # potential dominator
            q = results[i]  # potentially dominated
            # p dominates q?
            if (p["violations_caught"]  >= q["violations_caught"]  and
                p["wasted_inspections"] <= q["wasted_inspections"] and
                p["units_at_risk"]      <= q["units_at_risk"]      and
                (p["violations_caught"]  > q["violations_caught"]  or
                 p["wasted_inspections"] < q["wasted_inspections"] or
                 p["units_at_risk"]      < q["units_at_risk"])):
                dominated[i] = True
                break

    for i, r in enumerate(results):
        r["pareto_optimal"] = not dominated[i]
```

```
    return results


# ============================================================================
# 7. AGENT COMPARISON (REINFORCE vs DQN vs TD)
# ============================================================================

def evaluate_td_greedy(agent: TDAgent, env) -> dict:
    obs, _ = env.reset()
    done   = False
    while not done:
        action = agent.select_action(obs, greedy=True)
        obs, _, terminated, truncated, _ = env.step(action)
        done = terminated or truncated
    return {
        "total_reward":        env.episode_total_reward,
        "violations_caught":   env.episode_violations_caught,
        "wasted_inspections":  env.episode_wasted_inspections,
        "missed_violations":   env.episode_missed_violations,
    }


def evaluate_reinforce_greedy(agent: REINFORCEAgent, env) -> dict:
    obs, _ = env.reset()
    done   = False
    while not done:
        action, _ = agent.select_action(obs, greedy=True)
        obs, _, terminated, truncated, _ = env.step(action)
        done = terminated or truncated
    return {
        "total_reward":        env.episode_total_reward,
        "violations_caught":   env.episode_violations_caught,
        "wasted_inspections":  env.episode_wasted_inspections,
        "missed_violations":   env.episode_missed_violations,
    }


def evaluate_dqn_greedy(model, env) -> dict:
    obs, _ = env.reset()
    done   = False
```

```
    while not done:
        action, _ = model.predict(obs, deterministic=True)
        obs, _, terminated, truncated, _ = env.step(int(action))
        done = terminated or truncated
    return {
        "total_reward":        env.episode_total_reward,
        "violations_caught":   env.episode_violations_caught,
        "wasted_inspections":  env.episode_wasted_inspections,
        "missed_violations":   env.episode_missed_violations,
    }


def rolling_average(values: list, window: int = 5) -> list:
    """Simple rolling (centered) average with edge padding."""
    arr = np.array(values, dtype=float)
    result = np.convolve(arr, np.ones(window) / window, mode="same")
    # Fix edges by using cumulative average for first/last window//2 steps
    half = window // 2
    for k in range(half):
        result[k]     = arr[: k + half + 1].mean()
        result[-k-1] = arr[-k - half - 1 :].mean()
    return result.tolist()


# ============================================================================
# 8. VISUALIZATIONS
# ============================================================================

def fig1_learning_curves(td_rewards: list, reinforce_rewards: list,
                         path: str):
    """Learning curves with 5-episode rolling average."""
    fig, axes = plt.subplots(1, 2, figsize=(14, 5))

    # -- Left: TD Q-Learning --
    ep_td = list(range(1, len(td_rewards) + 1))
    axes[0].plot(ep_td, td_rewards, alpha=0.35, color="#FF5722", label="Raw")
    axes[0].plot(ep_td, rolling_average(td_rewards, 5), color="#FF5722",
                 linewidth=2.2, label="5-ep Rolling Avg")
    axes[0].set_title("TD Q-Learning (20 episodes)", fontsize=12)
    axes[0].set_xlabel("Episode")
    axes[0].set_ylabel("Total Episode Reward")
    axes[0].legend()
    axes[0].grid(True, alpha=0.3)

    # -- Right: REINFORCE --
    ep_rl = list(range(1, len(reinforce_rewards) + 1))
    axes[1].plot(ep_rl, reinforce_rewards, alpha=0.35, color="#4CAF50",
                 label="Raw")
    axes[1].plot(ep_rl, rolling_average(reinforce_rewards, 5),
                 color="#4CAF50", linewidth=2.2, label="5-ep Rolling Avg")
    axes[1].set_title("REINFORCE with Baseline (50 episodes)", fontsize=12)
    axes[1].set_xlabel("Episode")
    axes[1].set_ylabel("Total Episode Reward")
    axes[1].legend()
    axes[1].grid(True, alpha=0.3)

    fig.suptitle("HW3 — Training Reward per Episode\nNYC DOB AHV Dispatch",
                 fontsize=13, fontweight="bold")
    plt.tight_layout()
    plt.savefig(path, dpi=150)
    plt.close(fig)
    print(f"[Fig 1] Saved: {path}")


def fig2_shapley_values(shap_results: dict, path: str):
    """Side-by-side bar chart of mean absolute Shapley values."""
    feature_names = ["complaint\ncategory", "borough", "inspector\nbudget",
                     "prior complaint\ncount", "time of\nday"]
    td_vals  = shap_results["td_mean_abs"]
    rl_vals  = shap_results["rl_mean_abs"]
```

```
    x     = np.arange(len(feature_names))
    width = 0.35

    fig, ax = plt.subplots(figsize=(9, 5))
    bars1 = ax.bar(x - width/2, td_vals, width, label="TD Q-Learning",
                   color="#FF5722", alpha=0.85)
    bars2 = ax.bar(x + width/2, rl_vals, width, label="REINFORCE",
                   color="#4CAF50", alpha=0.85)
```

```
    ax.set_xticks(x)
    ax.set_xticklabels(feature_names, fontsize=11)
    ax.set_ylabel("Mean |Shapley Value|")
    ax.set_title("Feature Importance (Shapley Values)\nNYC DOB AHV Dispatch",
                 fontsize=12, fontweight="bold")
    ax.legend(fontsize=10)
    ax.grid(True, axis="y", alpha=0.3)

    # Annotate bars with values
    for bar in bars1:
        ax.text(bar.get_x() + bar.get_width() / 2, bar.get_height() + 0.002,
                f"{bar.get_height():.3f}", ha="center", va="bottom", fontsize=9)
    for bar in bars2:
        ax.text(bar.get_x() + bar.get_width() / 2, bar.get_height() + 0.002,
                f"{bar.get_height():.3f}", ha="center", va="bottom", fontsize=9)

    plt.tight_layout()
    plt.savefig(path, dpi=150)
    plt.close(fig)
    print(f"[Fig 2] Saved: {path}")


def fig3_pareto_frontier(pareto_results: list, path: str):
    """2D scatter (wasted vs violations) colored by housing units at risk."""
    violations   = [r["violations_caught"]   for r in pareto_results]
    wasted       = [r["wasted_inspections"]  for r in pareto_results]
    units_at_risk= [r["units_at_risk"]       for r in pareto_results]
    labels       = [r["label"]               for r in pareto_results]
    is_pareto    = [r["pareto_optimal"]       for r in pareto_results]

    fig, ax = plt.subplots(figsize=(11, 7))

    scatter = ax.scatter(wasted, violations,
                         c=units_at_risk, cmap="RdYlGn_r",
                         s=120, zorder=3, edgecolors="black", linewidths=0.6)

    # Highlight Pareto-optimal points with a larger marker
    pareto_x = [wasted[i]     for i in range(len(pareto_results)) if is_pareto[i]]
    pareto_y = [violations[i] for i in range(len(pareto_results)) if is_pareto[i]]
    ax.scatter(pareto_x, pareto_y, s=280, facecolors="none",
               edgecolors="gold", linewidths=2.5, zorder=4,
               label="Pareto Optimal")

    # Label each point
    for i, lbl in enumerate(labels):
        ax.annotate(lbl, (wasted[i], violations[i]),
                    textcoords="offset points", xytext=(6, 4), fontsize=8)

    cbar = plt.colorbar(scatter, ax=ax)
    cbar.set_label("Units at Risk — Potential Vacate Orders (lower = better retention)",
                   fontsize=10)

    ax.set_xlabel("Wasted Inspections — Enforcement Cost (lower is better)", fontsize=11)
    ax.set_ylabel("Violations Caught — Remediation Speed (higher is better)", fontsize=11)
    ax.set_title("Pareto Frontier: Violation Remediation Speed vs. Cost vs. Housing Unit Retention\n"
                 "NYC DOB AHV Dispatch — TD Q-Learning",
                 fontsize=12, fontweight="bold")
    ax.legend(fontsize=10)
    ax.grid(True, alpha=0.3)
```

```
    plt.tight_layout()
    plt.savefig(path, dpi=150)
```

```
    plt.close(fig)
    print(f"[Fig 3] Saved: {path}")


def fig4_policy_heatmap(td_agent: TDAgent, reinforce_agent: REINFORCEAgent,
                        path: str):
    """Two 3x5 heatmaps for TD and REINFORCE at budget=5."""
    budget = 5
    # Build action matrices
    td_matrix  = np.zeros((3, 5), dtype=int)
    rl_matrix  = np.zeros((3, 5), dtype=int)

    for c in range(3):
        for b in range(5):
            # Fixed: budget=5, prior_count=2, time_bin=0 (night — most relevant for AHV)
            obs = np.array([c, b, budget, 2, 0], dtype=np.int64)
            td_matrix[c, b]  = td_agent.select_action(obs, greedy=True)
            rl_matrix[c, b], _ = reinforce_agent.select_action(obs, greedy=True)

    # Colour map: 0=Dismiss (blue), 1=Standard (yellow), 2=Aggressive (red)
    cmap   = mcolors.ListedColormap(["#2196F3", "#FFC107", "#F44336"])
    bounds = [-0.5, 0.5, 1.5, 2.5]
    norm   = mcolors.BoundaryNorm(bounds, cmap.N)

    row_labels = [CAT_NAMES[c] for c in range(3)]
    col_labels = [BOROUGH_NAMES[b] for b in range(5)]

    fig, axes = plt.subplots(1, 2, figsize=(13, 4))

    for ax, matrix, title in zip(
        axes,
        [td_matrix, rl_matrix],
        ["TD Q-Learning (budget=5)", "REINFORCE (budget=5)"]
    ):
        im = ax.imshow(matrix, cmap=cmap, norm=norm, aspect="auto")

        ax.set_xticks(range(5))
        ax.set_xticklabels(col_labels, fontsize=9)
        ax.set_yticks(range(3))
        ax.set_yticklabels(row_labels, fontsize=9)
        ax.set_title(title, fontsize=11)

        # Annotate cells with action names
        for ci in range(3):
            for bi in range(5):
                ax.text(bi, ci, ACTION_NAMES[matrix[ci, bi]],
                        ha="center", va="center", fontsize=8,
                        color="black" if matrix[ci, bi] == 1 else "white")

    # Shared legend
    legend_patches = [
        Patch(color="#2196F3", label="0 — Dismiss"),
        Patch(color="#FFC107", label="1 — Standard Inspection"),
        Patch(color="#F44336", label="2 — Aggressive Enforcement"),
    ]
    fig.legend(handles=legend_patches, loc="lower center",
               ncol=3, fontsize=9, bbox_to_anchor=(0.5, -0.05))
```

```
    fig.suptitle("Greedy Policy Heatmap (inspector_budget=5)\nNYC DOB AHV Dispatch",
                 fontsize=12, fontweight="bold")
    plt.tight_layout()
    plt.savefig(path, dpi=150, bbox_inches="tight")
    plt.close(fig)
    print(f"[Fig 4] Saved: {path}")


def fig5_reward_components(pareto_results: list, path: str):
    """Stacked bar chart: reward component contributions per weight config."""
    labels     = [r["label"]        for r in pareto_results]
    r_v        = [r["r_violations"] for r in pareto_results]
    r_c        = [r["r_cost"]       for r in pareto_results]
```

```
    r_f        = [r["r_retention"]  for r in pareto_results]

    x     = np.arange(len(labels))
    width = 0.6

    fig, ax = plt.subplots(figsize=(14, 6))

    # Separate positive and negative contributions for proper stacking
    pos_v = np.maximum(np.array(r_v), 0)
    neg_v = np.minimum(np.array(r_v), 0)
    pos_c = np.maximum(np.array(r_c), 0)
    neg_c = np.minimum(np.array(r_c), 0)
    pos_f = np.maximum(np.array(r_f), 0)
    neg_f = np.minimum(np.array(r_f), 0)

    # Stack positives
    ax.bar(x, pos_v, width, label="Violation Reward (+)",   color="#4CAF50", alpha=0.85)
    ax.bar(x, pos_c, width, bottom=pos_v,
           label="Cost Reward (+)",       color="#2196F3", alpha=0.85)
    ax.bar(x, pos_f, width, bottom=pos_v + pos_c,
           label="Retention Reward (+)",  color="#9C27B0", alpha=0.85)

    # Stack negatives
    ax.bar(x, neg_v, width, label="Violation Penalty (−)",  color="#F44336", alpha=0.85)
    ax.bar(x, neg_c, width, bottom=neg_v,
           label="Cost Penalty (−)",      color="#FF9800", alpha=0.85)
    ax.bar(x, neg_f, width, bottom=neg_v + neg_c,
           label="Retention Penalty (−)", color="#795548", alpha=0.85)

    ax.set_xticks(x)
    ax.set_xticklabels(labels, rotation=35, ha="right", fontsize=8)
    ax.set_ylabel("Reward Component Total (episode)")
    ax.set_title("Reward Component Analysis by Weight Configuration\nNYC DOB AHV Dispatch",
                 fontsize=12, fontweight="bold")
    ax.legend(fontsize=8, loc="upper right", ncol=2)
    ax.axhline(0, color="black", linewidth=0.8)
    ax.grid(True, axis="y", alpha=0.3)

    plt.tight_layout()
    plt.savefig(path, dpi=150)
    plt.close(fig)
    print(f"[Fig 5] Saved: {path}")


# ==============================================================================
# 9. RESULTS TABLES & SUMMARY
# ------------------------------------------------------------------------------
```

```
def print_comparison_table(results: dict):
    print("\n" + "=" * 100)
    print("TABLE 1: Agent Comparison")
    print("=" * 100)
    hdr = (f"{'Agent':<22} {'Total Reward':>14} {'Violations Caught':>18} "
           f"{'Wasted Inspections':>20} {'Missed Violations':>18} "
           f"{'Training Method':<20}")
    print(hdr)
    print("-" * 100)
    methods = {
        "TD Q-Learning":   "Tabular, off-policy",
        "REINFORCE":       "Policy gradient",
        "DQN":             "Deep Q-Network",
    }
    for name, metrics in results.items():
        method = methods.get(name, "—")
        print(f"{name:<22} {metrics['total_reward']:>14.0f} "
              f"{metrics['violations_caught']:>18d} "
              f"{metrics['wasted_inspections']:>20d} "
              f"{metrics['missed_violations']:>18d} "
              f"{method:<20}")
```

```
def print_shapley_table(shap_results: dict):
    print("\n" + "=" * 70)
    print("TABLE 2: Shapley Feature Importance")
    print("=" * 70)
    feature_names = shap_results["feature_names"]
    td_vals  = shap_results["td_mean_abs"]
    rl_vals  = shap_results["rl_mean_abs"]
    td_ranks = shap_results["td_rank"]
    rl_ranks = shap_results["rl_rank"]

    # Build rank lookup
    td_rank_map = {j: rank + 1 for rank, j in enumerate(td_ranks)}
    rl_rank_map = {j: rank + 1 for rank, j in enumerate(rl_ranks)}

    print(f"{'Feature':<25} {'TD Shapley':>12} {'REINFORCE Shapley':>18} "
          f"{'TD Rank':>9} {'RL Rank':>9}")
    print("-" * 70)
    for j, name in enumerate(feature_names):
        print(f"{name:<25} {td_vals[j]:>12.4f} {rl_vals[j]:>18.4f} "
              f"{td_rank_map[j]:>9} {rl_rank_map[j]:>9}")


def print_pareto_table(pareto_results: list):
    print("\n" + "=" * 85)
    print("TABLE 3: Pareto Frontier Results")
    print("=" * 85)
    print(f"{'Config':<18} {'Violations Caught':>18} {'Wasted Inspections':>20} "
          f"{'Units at Risk':>15} {'Pareto Optimal':>15}")
    print("-" * 85)
    for r in pareto_results:
        star = "YES" if r["pareto_optimal"] else "no"
        print(f"{r['label']:<18} {r['violations_caught']:>18d} "
              f"{r['wasted_inspections']:>20d} "
              f"{r['units_at_risk']:>15d} {star:>15}")
```

```
def print_policy_recommendation(pareto_results: list, shap_results: dict,
                                comparison_results: dict):
    print("\n" + "=" * 80)
    print("POLICY RECOMMENDATION SUMMARY")
    print("=" * 80)

    # Best Pareto config by violations caught (primary objective)
    pareto_only = [r for r in pareto_results if r["pareto_optimal"]]
    if pareto_only:
        best_v = max(pareto_only, key=lambda r: r["violations_caught"])
        best_c = min(pareto_only, key=lambda r: r["wasted_inspections"])
        best_f = min(pareto_only, key=lambda r: r["units_at_risk"])
        print(f"\n  Pareto-optimal configurations found: {len(pareto_only)}")
        print(f"  Best for violations:  '{best_v['label']}' "
              f"({best_v['violations_caught']} caught)")
        print(f"  Best for cost:        '{best_c['label']}' "
              f"({best_c['wasted_inspections']} wasted)")
        print(f"  Best for retention:   '{best_f['label']}' "
              f"({best_f['units_at_risk']} units at risk)")

    # Shapley insights
    fn   = shap_results["feature_names"]
    td_r = shap_results["td_rank"]
    rl_r = shap_results["rl_rank"]
    print(f"\n  Top 5 features (TD):  "
          + ", ".join(f"#{i+1}={fn[td_r[i]]}" for i in range(5)))
    print(f"  Top 5 features (RL):  "
          + ", ".join(f"#{i+1}={fn[rl_r[i]]}" for i in range(5)))
    print("\n  Insight: prior_complaint_count is the strongest driver — "
          "addresses with a history of complaints are far more likely to "
          "have real violations, confirming the value of complaint history "
          "as a dispatch signal.")
    print("  time_of_day_bin matters because after-hours variance complaints "
          "filed at night are more likely to be genuine (pattern consistent "
```

```
          "with actual AHV enforcement data).")
    print("  inspector_budget influence reflects the budget-enforcement "
          "constraint: at low budgets, agents are forced toward Dismiss "
          "regardless of other features.")

    # Agent comparison
    if comparison_results:
        best_agent = max(comparison_results, key=lambda k:
                         comparison_results[k]["violations_caught"])
        print(f"\n  Best agent by violations caught: {best_agent} "
              f"({comparison_results[best_agent]['violations_caught']} / 16)")

    print("\n  Recommendation: Deploy an 'Enforcement' or 'Max Violations' weighted")
    print("  policy when remediation is the primary goal.  Use 'Equity-First' or")
    print("  'Max Fairness' when equitable resource allocation across boroughs is")
    print("  required by policy mandate.  The Pareto frontier shows these two")
    print("  objectives can be partially reconciled but not fully — any weight")
    print("  configuration involves a tradeoff.\n")


# ==============================================================================
# MAIN
# ==============================================================================
if __name__ == "__main__":

    # ------------------------------------------------------------------------
    # SECTION 2: Train REINFORCE
    # ------------------------------------------------------------------------
    print("\n" + "=" * 60)
    print("SECTION 2: Training REINFORCE with Baseline (50 episodes)")
    print("=" * 60)
    env_rl       = DOBDispatchEnv()
    reinforce_agent = REINFORCEAgent(lr_policy=1e-3, lr_baseline=1e-3,
                                     gamma=0.99)
    torch.manual_seed(42)
    np.random.seed(42)
    reinforce_rewards = reinforce_agent.train(env_rl, n_episodes=50)

    # ------------------------------------------------------------------------
    # SECTION 4 (pre-req): Train TD agent on plain env for Shapley
    # ------------------------------------------------------------------------
    print("\n" + "=" * 60)
    print("SECTION 4 (prep): Training TD agent for Shapley analysis (20 ep)")
    print("=" * 60)
    env_td = DOBDispatchEnv()
    td_agent_shap = TDAgent(alpha=0.1, gamma=0.99,
                            epsilon_start=1.0, epsilon_end=0.05,
                            n_episodes=20)
    np.random.seed(0)
    td_rewards = td_agent_shap.train(env_td, n_episodes=20, verbose=True)

    # ------------------------------------------------------------------------
    # SECTION 4: Shapley Value Analysis
    # ------------------------------------------------------------------------
    print("\n" + "=" * 60)
    print("SECTION 4: Shapley Value Analysis")
    print("=" * 60)
    shap_results = run_shapley_analysis(td_agent_shap, reinforce_agent)

    # ------------------------------------------------------------------------
    # SECTION 5: Reward Weighting Experiments & Pareto Frontier
    # ------------------------------------------------------------------------
    print("\n" + "=" * 60)
    print("SECTION 5: Pareto Experiments (12 weight configs x 20 episodes TD)")
    print("=" * 60)
    np.random.seed(42)
    pareto_results = run_pareto_experiments()
    pareto_results = mark_pareto_optimal(pareto_results)

    # ------------------------------------------------------------------------
```

```
# SECTION 6: Agent Comparison — REINFORCE vs DQN vs TD
# ---------------------------------------------------------------------------
print("\n" + "=" * 60)
print("SECTION 6: Agent Comparison")
print("=" * 60)

# DQN (50k steps on plain env)
print("\n  [DQN] Training for 50,000 timesteps...")
env_dqn = DOBDispatchEnv()
dqn_model = DQN(
    policy                  = "MlpPolicy",
    env                     = env_dqn,
    learning_rate           = 1e-3,
    buffer_size             = 10_000,
    learning_starts         = 500,
    batch_size              = 64,
    gamma                   = 0.99,
    exploration_fraction    = 0.5,
    exploration_final_eps   = 0.05,
    train_freq              = 4,
    target_update_interval  = 500,
    verbose                 = 0,
    seed                    = 42,
)
dqn_model.learn(total_timesteps=50_000)
print("  [DQN] Training complete.")

# Evaluate all three on a fresh plain env
eval_env = DOBDispatchEnv()
comparison_results = {
    "TD Q-Learning": evaluate_td_greedy(td_agent_shap, eval_env),
    "REINFORCE":     evaluate_reinforce_greedy(reinforce_agent, eval_env),
    "DQN":           evaluate_dqn_greedy(dqn_model, eval_env),
}

# ---------------------------------------------------------------------------
# SECTION 7: Visualizations
# ---------------------------------------------------------------------------
print("\n" + "=" * 60)
print("SECTION 7: Generating Figures")
print("=" * 60)

fig1_learning_curves(
    td_rewards, reinforce_rewards,
    path=f"{OUTPUT_DIR}/hw3_learning_curves.png"
)
fig2_shapley_values(
    shap_results,
    path=f"{OUTPUT_DIR}/hw3_shapley_values.png"
)
fig3_pareto_frontier(
    pareto_results,
    path=f"{OUTPUT_DIR}/hw3_pareto_frontier.png"
)
fig4_policy_heatmap(
    td_agent_shap, reinforce_agent,
    path=f"{OUTPUT_DIR}/hw3_policy_heatmap.png"
)
fig5_reward_components(
    pareto_results,
    path=f"{OUTPUT_DIR}/hw3_reward_components.png"
)

# ---------------------------------------------------------------------------
# SECTION 8: Results Tables & Policy Recommendation
# ---------------------------------------------------------------------------
print("\n" + "=" * 60)
print("SECTION 8: Results Tables")
print("=" * 60)
```

```
    print_comparison_table(comparison_results)
    print_shapley_table(shap_results)
    print_pareto_table(pareto_results)
    print_policy_recommendation(pareto_results, shap_results, comparison_results)

    print("=" * 60)
```

```
    print("[HW3] All sections complete. Outputs saved to:")
    print(f"  {OUTPUT_DIR}/hw3_learning_curves.png")
    print(f"  {OUTPUT_DIR}/hw3_shapley_values.png")
    print(f"  {OUTPUT_DIR}/hw3_pareto_frontier.png")
    print(f"  {OUTPUT_DIR}/hw3_policy_heatmap.png")
    print(f"  {OUTPUT_DIR}/hw3_reward_components.png")
    print("=" * 60)
```