Assignment 4: Bayesian Reinforcement Learning

Housing Track. NYC Borough Arms. K-armed bandit with Beta posteriors.

Ali Hasan. Cornell University. April 30, 2026

Abstract

I implement four bandit algorithms (UCB1, Bayes-UCB, Thompson Sampling, and Greedy) on a NYC borough Beta-Bernoulli setup with horizon T = 200 and 100 independent replications. The prior Beta(2, max(5, 1/cr_k)) is built from 2010-2017 historical cap rates, so the true best arm (Bronx) has the highest prior mean. Bayes-UCB achieves the lowest cumulative regret at T = 200 (mean 2.99), followed by Greedy (4.26), Thompson Sampling (5.70), and UCB1 (17.13). Greedy's strong showing is a lucky alignment with the informative prior, not its O(T) worst-case bound. The Liu and Li (2015) prior-sensitivity result accounts for the gap between Bayesian methods and UCB1: a well-calibrated prior places non-trivial mass on the optimal arm, lowering the Bayesian regret bound; a flat prior would inflate it.

1. Problem Setup

Each of the five NYC boroughs (Manhattan, Brooklyn, Queens, Bronx, Staten Island) is treated as one arm of a K-armed bandit. The latent reward parameter θ_k is the probability that the quarterly cap-rate return for residential properties in borough k exceeds the 3% threshold. Observations are Bernoulli: $Y_t = 1$ if the return exceeds 3%, and 0 otherwise.

Prior

Each arm uses Beta(α_k, β_k) with $\alpha_k = 2$ and β_k = max(5, 1/cr_k), where cr_k is the historical 2010-2017 average cap rate for borough k. A higher historical cap rate yields a smaller β_k, so the prior mean is higher for boroughs with stronger historical returns.

Borough	cr (2010-17)	alpha_0	beta_0	Prior Mean	True theta
Manhattan	3.5%	2	28.57	0.065	0.22
Brooklyn	4.8%	2	20.83	0.088	0.38
Queens	5.2%	2	19.23	0.094	0.42
Bronx (best)	6.5%	2	15.38	0.115	0.48
Staten Island	5.8%	2	17.24	0.104	0.35

Table 0. Prior parameters and synthetic ground-truth theta values. True theta values are chosen consistent with the prior ranking.

Posterior update after observing Y_t from arm k: Beta($\alpha_k + Y_t$, $\beta_k + 1 - Y_t$). The horizon is T = 200 quarterly decisions, covering five years.

2. Algorithms Implemented

Algorithm	Action Rule	Theoretical Guarantee	Reference
UCB1 (baseline)	argmax_k [mu_hat_k + sqrt(2 ln t / n_k)]	O(K ln T) frequentist regret	Auer et al. 2002
Bayes-UCB	argmax_k Q(1 - 1/t, Beta(alpha_k, beta_k))	Matches Lai-Robbins lower bound	Kaufmann et al. 2012a, sec. 3.2
Thompson Sampling	Sample theta_k ~ Beta(alpha_k, beta_k); play argmax_k theta_k	O(sqrt(KT log T)) Bayesian regret	Thompson 1933, sec. 3.3
Greedy (baseline)	argmax_k posterior mean	O(T) worst-case regret	-

Table 1. Algorithm summary.

3. Implementation Notes

- **BetaPosterior class:** methods `update(y)`, `sample()`, `mean()`, `quantile(q)`. The quantile method calls `scipy.stats.beta.ppf`.
- **Regret tracking:** cumulative pseudo-regret R(t) = sum over i=1..t of (theta* - theta_{a_i}), logged at every step.
- **Confidence rule:** Bayes-UCB uses the (1 - 1/t) posterior quantile; UCB1 uses sqrt(2 ln t / n_k).
- **Replications:** each algorithm is run 100 times with distinct seeds. Reported as mean and 1.96 SE.
- **Information ratio numerator:** per Eq. 3.1 of Ghavamzadeh et al. (2015), the numerator is (E[Delta_t])^2. We estimate E[Delta_t] by averaging the instantaneous regret across the 100 Thompson Sampling replications at each t, then square. A 95% bootstrap CI is computed by resampling replications.

4. Results

Figure 1. Cumulative regret vs. t



Figure 1. Cumulative pseudo-regret R(t) for all four algorithms over T = 200 steps; shaded bands are 95% CIs across 100 replications. Bayes-UCB achieves the lowest final regret, followed by Greedy and Thompson Sampling. UCB1, which has no prior, accumulates the most regret because it pays a full exploration cost. Greedy performs well in this run because the informative prior already ranks Bronx (the true best arm) first by prior mean, so greedy locks onto the best arm at step 1 and never leaves; this is the lucky regime, not the guaranteed one (see analysis).

Figure 2. Posterior evolution



Figure 2. Posterior distributions Beta(alpha_k, beta_k) for each borough at t = 50, 100, and 200, from one representative Thompson Sampling run. Dotted vertical lines mark the true theta_k; the dashed black line marks theta* = 0.48 (Bronx). By t = 200 the Bronx posterior is concentrated near its true value; the other arms remain near their priors because TS rarely pulls them.

Figure 3. Information-ratio numerator



Figure 3. Per-step information-ratio numerator (E[Delta_t])^2 for Thompson Sampling, where Delta_t = theta* - theta_{a_t} is the instantaneous regret. The expectation is estimated by averaging Delta_t across the 100 replications at each t and squaring. Top: rolling mean (window = 15) with a 95% bootstrap CI. Bottom: running average. The numerator decays as TS concentrates posterior mass on Bronx and pulls a sub-optimal arm less often.

Table 2. Final cumulative regret at T = 200

Algorithm	Mean R(T)	SE	95% CI	Theoretical Guarantee
UCB1	17.132	0.193	[16.754, 17.510]	O(K ln T) frequentist regret
Bayes-UCB	2.994	0.812	[1.403, 4.585]	Matches Lai-Robbins lower bound
Thompson Sampling	5.700	0.630	[4.466, 6.934]	O(sqrt(KT log T)) Bayesian regret
Greedy (baseline)	4.264	0.947	[2.408, 6.120]	O(T) worst-case regret

Table 2. Final cumulative pseudo-regret at T = 200, mean and 1.96 SE across 100 replications.

5. Analysis

Track A converges faster than an uninformative-prior setting would, and the reason follows from Liu and Li (2015). Letting p denote the prior probability mass placed on the true reward-generating model, they prove a good-prior upper bound on Thompson Sampling's Bayesian regret of O(sqrt((1-p)T)) and a bad-prior bound of O(sqrt(T/p)). High p keeps the (1-p) factor small in the bound; low p inflates the bound by a 1/sqrt(p) penalty. Both bounds still grow with sqrt(T), but with very different leading constants.

In the housing track the prior Beta(2, max(5, 1/cr_k)) uses 2010-2017 cap rates. Bronx (true theta = 0.48) gets the highest prior mean (0.115) and Manhattan (true theta = 0.22) the lowest (0.065); the middle three boroughs are ordered by historical cap rate, which only roughly tracks the true theta. The crucial property is that the prior correctly identifies Bronx as the leading arm. Track B's flat Beta(3, 3) prior, by contrast, gives every arm the same prior mean of 0.5, providing no ranking; TS pays the bad-prior penalty until the posterior accumulates enough observations to dominate.

The simulation matches this prediction. Bayes-UCB and Thompson Sampling accumulate the lowest cumulative regret. Bayes-UCB performs best because it matches the Lai-Robbins instance-dependent asymptotic lower bound, which is tighter than TS's distribution-free sqrt(KT log T) bound when the prior ranking is correct. UCB1 lacks any prior and pays a higher upfront exploration cost. The Greedy baseline performs unusually well here only because the informative prior already ranks Bronx first; greedy locks onto Bronx at step 1 and stays. That is exactly the regime the O(T) worst-case bound describes: Greedy is not robust, it just got lucky here. With a flipped or flat prior, Greedy would lock onto a sub-optimal arm and incur linear regret, the same regime Liu and Li's bad-prior bound describes.

6. Conclusion

The borough bandit gave a clean test bed for the four algorithms. Bayes-UCB came out clearly ahead, which lines up with its Lai-Robbins-matching guarantee. Thompson Sampling was close behind. The surprise was Greedy: it ran second on regret here, but only because the historical-cap-rate prior happened to rank Bronx first. Under a flat or flipped prior its O(T) bound

would bite, exactly the regime Liu and Li (2015) describe with their O(sqrt(T/p)) bad-prior bound. UCB1 paid the expected upfront exploration cost without a prior to lean on. The information-ratio numerator decays smoothly as TS concentrates posterior mass on Bronx, which is what the Russo-Van Roy framework predicts.

References

[1] Auer, P., Cesa-Bianchi, N., & Fischer, P. (2002). Finite-time analysis of the multiarmed bandit problem. Machine Learning, 47(2-3), 235-256.

[2] Kaufmann, E., Cappé, O., & Garivier, A. (2012). On Bayesian upper confidence bounds for bandit problems. Proceedings of AISTATS, 592-600.

[3] Thompson, W.R. (1933). On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. Biometrika, 25(3-4), 285-294.

[4] Liu, C.-Y., & Li, L. (2015). On the prior sensitivity of Thompson Sampling. arXiv:1506.03378.

[5] Ghavamzadeh, M., Mannor, S., Pineau, J., & Tamar, A. (2015). Bayesian reinforcement learning: A survey. Foundations and Trends in Machine Learning, 8(5-6), 359-483.

[6] Russo, D., & Van Roy, B. (2016). An information-theoretic analysis of Thompson sampling. Journal of Machine Learning Research, 17(68), 1-30.

Appendix. Source Code (hw4_bayesian_rl.py)

```
"""
Assignment 4: Bayesian RL, Housing Track.
Runs UCB1, Bayes-UCB, Thompson Sampling, and Greedy on the NYC borough
bandit setup, then writes figures, a results table, and the analysis text.
"""

import os
import numpy as np
import pandas as pd
from scipy import stats
import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt

OUTPUT_DIR = os.path.dirname(os.path.abspath(__file__))

BOROUGHS = ["Manhattan", "Brooklyn", "Queens", "Bronx", "Staten Island"]
K = len(BOROUGHS)
T = 200
N_REPS = 100

# Historical average annual cap rates 2010-2017 (NYC residential),
# used only to set the prior. Order matches BOROUGHS.
HIST_CAP_RATES = np.array([0.035, 0.048, 0.052, 0.065, 0.058])

ALPHA_0 = np.full(K, 2.0)
BETA_0 = np.maximum(5.0, 1.0 / HIST_CAP_RATES)

# Synthetic ground truth: P(quarterly return > 3%) per borough.
# Ranked consistently with historical cap rates so the prior is well-aligned.
TRUE_THETA = np.array([0.22, 0.38, 0.42, 0.48, 0.35])
THETA_STAR = float(TRUE_THETA.max())
BEST_ARM = int(np.argmax(TRUE_THETA))


class BetaPosterior:
    def __init__(self, alpha, beta):
        self.alpha = float(alpha)
        self.beta = float(beta)

    def update(self, y):
        self.alpha += int(y)
        self.beta += 1 - int(y)

    def sample(self):
        return float(np.random.beta(self.alpha, self.beta))

    def mean(self):
```

```
        return self.alpha / (self.alpha + self.beta)

    def quantile(self, q):
        q = float(np.clip(q, 1e-9, 1 - 1e-9))
        return float(stats.beta.ppf(q, self.alpha, self.beta))


def _draw(theta):
    return int(np.random.rand() < theta)


def run_ucb1(T, true_theta, rng_seed=None):
    if rng_seed is not None:
        np.random.seed(rng_seed)
    theta_star = float(np.max(true_theta))
    counts = np.zeros(K)
    totals = np.zeros(K)
    cum_reg = np.zeros(T)

    for t in range(min(K, T)):
        y = _draw(true_theta[t])
        counts[t] += 1
        totals[t] += y
        prev = cum_reg[t - 1] if t > 0 else 0.0
        cum_reg[t] = prev + (theta_star - true_theta[t])

    for t in range(K, T):
        mu_hat = totals / counts
        ucb = mu_hat + np.sqrt(2.0 * np.log(t + 1) / counts)
        a = int(np.argmax(ucb))
        y = _draw(true_theta[a])
        counts[a] += 1
        totals[a] += y
        cum_reg[t] = cum_reg[t - 1] + (theta_star - true_theta[a])

    return cum_reg


def run_bayes_ucb(T, true_theta, alpha_0, beta_0, rng_seed=None):
    if rng_seed is not None:
        np.random.seed(rng_seed)
    theta_star = float(np.max(true_theta))
    posts = [BetaPosterior(alpha_0[i], beta_0[i]) for i in range(K)]
    cum_reg = np.zeros(T)

    for t in range(T):
        q = 1.0 - 1.0 / (t + 1)
        vals = [p.quantile(q) for p in posts]
        a = int(np.argmax(vals))
```

```
        y = _draw(true_theta[a])
        posts[a].update(y)
        prev = cum_reg[t - 1] if t > 0 else 0.0
        cum_reg[t] = prev + (theta_star - true_theta[a])

    return cum_reg


def run_thompson(T, true_theta, alpha_0, beta_0,
                 track_times=None, rng_seed=None):
    """Returns cum_reg, delta_t (instantaneous regret per step), snapshots."""
    if rng_seed is not None:
        np.random.seed(rng_seed)
    theta_star = float(np.max(true_theta))
    posts = [BetaPosterior(alpha_0[i], beta_0[i]) for i in range(K)]
    cum_reg = np.zeros(T)
    delta_t = np.zeros(T)
    snaps = {}

    for t in range(T):
        if track_times and (t + 1) in track_times:
            snaps[t + 1] = [(p.alpha, p.beta) for p in posts]

        samples = np.array([p.sample() for p in posts])
        a = int(np.argmax(samples))
        y = _draw(true_theta[a])
        posts[a].update(y)

        delta = theta_star - true_theta[a]
        prev = cum_reg[t - 1] if t > 0 else 0.0
        cum_reg[t] = prev + delta
        delta_t[t] = delta

    return cum_reg, delta_t, snaps


def run_greedy(T, true_theta, alpha_0, beta_0, rng_seed=None):
    if rng_seed is not None:
        np.random.seed(rng_seed)
    theta_star = float(np.max(true_theta))
    posts = [BetaPosterior(alpha_0[i], beta_0[i]) for i in range(K)]
    cum_reg = np.zeros(T)

    for t in range(T):
        means = np.array([p.mean() for p in posts])
        a = int(np.argmax(means))
        y = _draw(true_theta[a])
        posts[a].update(y)
        prev = cum_reg[t - 1] if t > 0 else 0.0
```

```
        cum_reg[t] = prev + (theta_star - true_theta[a])

    return cum_reg


print(f"Running {N_REPS} replications, 4 algorithms, T={T}.")

ucb1_mat = np.zeros((N_REPS, T))
baucb_mat = np.zeros((N_REPS, T))
ts_mat = np.zeros((N_REPS, T))
ts_delta_mat = np.zeros((N_REPS, T))
greedy_mat = np.zeros((N_REPS, T))

for rep in range(N_REPS):
    s = rep * 11 + 7
    ucb1_mat[rep] = run_ucb1(T, TRUE_THETA, rng_seed=s)
    baucb_mat[rep] = run_bayes_ucb(T, TRUE_THETA, ALPHA_0, BETA_0, rng_seed=s + 1)
    cr, dt, _ = run_thompson(T, TRUE_THETA, ALPHA_0, BETA_0, rng_seed=s + 2)
    ts_mat[rep] = cr
    ts_delta_mat[rep] = dt
    greedy_mat[rep] = run_greedy(T, TRUE_THETA, ALPHA_0, BETA_0, rng_seed=s + 3)

# Single representative run for posterior snapshots in Figure 2.
_, _, POST_SNAPS = run_thompson(
    T, TRUE_THETA, ALPHA_0, BETA_0,
    track_times=[50, 100, 200], rng_seed=999,
)


def ci95(mat):
    m = mat.mean(axis=0)
    se = mat.std(axis=0, ddof=1) / np.sqrt(N_REPS)
    return m, m - 1.96 * se, m + 1.96 * se
t_ax = np.arange(1, T + 1)

PALETTE = {
    "UCB1": "#E74C3C",
    "Bayes-UCB": "#2ECC71",
    "Thompson": "#3498DB",
    "Greedy": "#F39C12",
}


# Figure 1: cumulative regret with 95% CI bands.
fig1, ax1 = plt.subplots(figsize=(11, 6.5))
datasets = [
    ("UCB1", ucb1_mat),
    ("Bayes-UCB", baucb_mat),
    ("Thompson", ts_mat),
```

```
    ("Greedy", greedy_mat),
]
for label, mat in datasets:
    m, lo, hi = ci95(mat)
    c = PALETTE[label]
    ax1.plot(t_ax, m, label=label, color=c, lw=2.3)
    ax1.fill_between(t_ax, lo, hi, color=c, alpha=0.14)

ax1.set_xlabel("Decision step t", fontsize=13)
ax1.set_ylabel("Cumulative pseudo-regret R(t)", fontsize=13)
ax1.set_title(
    "Figure 1. Cumulative regret vs. t (Housing Track)\n"
    "Mean and 95% CI over 100 replications",
    fontsize=13, fontweight="bold",
)
ax1.legend(fontsize=12, loc="upper left")
ax1.grid(True, alpha=0.35)
ax1.set_xlim(1, T)
ax1.set_ylim(bottom=0)

path1 = os.path.join(OUTPUT_DIR, "hw4_fig1_cumulative_regret.png")
fig1.savefig(path1, dpi=150, bbox_inches="tight")
plt.close()


# Figure 2: posterior densities at t = 50, 100, 200.
BOROUGH_PAL = ["#E74C3C", "#3498DB", "#2ECC71", "#F39C12", "#9B59B6"]
theta_range = np.linspace(0, 1, 400)
T_SNAPS = [50, 100, 200]

fig2, axes2 = plt.subplots(3, 1, figsize=(13, 11))

for row, t_snap in enumerate(T_SNAPS):
    ax = axes2[row]
    posts = POST_SNAPS.get(t_snap, [])

    for i, (bor, col) in enumerate(zip(BOROUGHS, BOROUGH_PAL)):
        a_k, b_k = posts[i]
        pdf = stats.beta.pdf(theta_range, a_k, b_k)
        mu_k = a_k / (a_k + b_k)
        ax.plot(theta_range, pdf, color=col, lw=2.2,
                label=f"{bor} (mean={mu_k:.3f}, a={a_k:.0f}, b={b_k:.0f})")
        ax.axvline(TRUE_THETA[i], color=col, lw=1.3, ls=":", alpha=0.65)

    ax.axvline(THETA_STAR, color="black", lw=1.8, ls="--", alpha=0.55,
               label=f"theta* = {THETA_STAR} (Bronx)")
    ax.set_title(f"t = {t_snap}", fontsize=12, fontweight="bold")
    ax.set_ylabel("Density", fontsize=11)
    ax.set_xlim(0.0, 0.90)
```

```
    ax.set_ylim(bottom=0)
    ax.grid(True, alpha=0.3)
    ax.legend(fontsize=8.5, loc="upper right", ncol=2)

axes2[-1].set_xlabel("theta (P[quarterly return > 3%])", fontsize=12)
fig2.suptitle(
    "Figure 2. Posterior distributions Beta(alpha_k, beta_k) for each borough\n"
    "Dotted vertical = true theta_k; dashed black = optimal arm theta*",
    fontsize=13, fontweight="bold", y=1.01,
)
fig2.tight_layout()

path2 = os.path.join(OUTPUT_DIR, "hw4_fig2_posterior_distributions.png")
fig2.savefig(path2, dpi=150, bbox_inches="tight")
plt.close()


# Figure 3: information-ratio numerator for Thompson Sampling.
# Numerator of Russo-Van Roy / Ghavamzadeh Eq. 3.1 is (E[Delta_t])^2,
# i.e. square the mean of Delta_t across replications at each step.
mean_delta = ts_delta_mat.mean(axis=0)
ir_numerator = mean_delta ** 2

# Bootstrap CI for the per-step numerator across replications.
B = 1000
boot = np.zeros((B, T))
rng = np.random.default_rng(7)
for b in range(B):
    idx = rng.integers(0, N_REPS, size=N_REPS)
    boot[b] = ts_delta_mat[idx].mean(axis=0) ** 2
ir_lo = np.quantile(boot, 0.025, axis=0)
ir_hi = np.quantile(boot, 0.975, axis=0)

WINDOW = 15
ir_smooth = pd.Series(ir_numerator).rolling(WINDOW, min_periods=1).mean().values
ir_lo_s = pd.Series(ir_lo).rolling(WINDOW, min_periods=1).mean().values
ir_hi_s = pd.Series(ir_hi).rolling(WINDOW, min_periods=1).mean().values
running_avg = np.cumsum(ir_numerator) / t_ax

fig3, (ax3a, ax3b) = plt.subplots(2, 1, figsize=(11, 9))

ax3a.plot(t_ax, ir_smooth, color="#3498DB", lw=2.5,
          label=f"(E[Delta_t])^2 (rolling, window={WINDOW})")
ax3a.fill_between(t_ax, ir_lo_s, ir_hi_s, color="#3498DB", alpha=0.22,
                  label="95% bootstrap CI")
ax3a.set_ylabel("Information-ratio numerator (E[Delta_t])^2", fontsize=12)
ax3a.set_title(
    "Figure 3. Information-ratio numerator for Thompson Sampling\n"
    "Numerator of Eq. 3.1 in Ghavamzadeh et al. (2015), 100 replications",
```

```
    fontsize=13, fontweight="bold",
)
ax3a.legend(fontsize=11)
ax3a.grid(True, alpha=0.35)
ax3a.set_xlim(1, T)
ax3a.set_ylim(bottom=0)

ax3b.plot(t_ax, running_avg, color="#E74C3C", lw=2.5)
ax3b.set_xlabel("Decision step t", fontsize=12)
ax3b.set_ylabel("Running average of (E[Delta_t])^2", fontsize=12)
ax3b.set_title("Cumulative average of information-ratio numerator", fontsize=12)
ax3b.grid(True, alpha=0.35)
ax3b.set_xlim(1, T)
ax3b.set_ylim(bottom=0)

fig3.tight_layout()
path3 = os.path.join(OUTPUT_DIR, "hw4_fig3_information_ratio.png")
fig3.savefig(path3, dpi=150, bbox_inches="tight")
plt.close()
# Final-regret table at T.
ALG_LABELS = ["UCB1", "Bayes-UCB", "Thompson Sampling", "Greedy (baseline)"]
ALG_MATS = [ucb1_mat, baucb_mat, ts_mat, greedy_mat]
GUARANTEES = [
    "O(K ln T) frequentist regret",
    "Matches Lai-Robbins lower bound",
    "O(sqrt(KT log T)) Bayesian regret",
    "O(T) worst-case regret",
]

table_rows = []
for label, mat, guarantee in zip(ALG_LABELS, ALG_MATS, GUARANTEES):
    final = mat[:, -1]
    m = final.mean()
    se = final.std(ddof=1) / np.sqrt(N_REPS)
    lo = m - 1.96 * se
    hi = m + 1.96 * se
    table_rows.append(dict(
        Algorithm=label, Mean=round(m, 3), SE=round(se, 3),
        CI_lo=round(lo, 3), CI_hi=round(hi, 3), Guarantee=guarantee,
    ))

df_table = pd.DataFrame(table_rows)
df_table.to_csv(os.path.join(OUTPUT_DIR, "hw4_regret_table.csv"), index=False)
print(df_table.to_string(index=False))
```