Small Models, Big Problems: Jailbreaking Attacks on Lightweight LLMs

Ali Hashish
Computer Engineering
Cairo University
Cairo, Egypt
ali.hashish001@gmail.com

Hla Hany
Computer Engineering
Cairo University
Cairo, Egypt
hla.ahmed00@eng-st.cu.edu.eg

Mostafa Osama
Computer Engineering
Cairo University
Cairo, Egypt
mostafa.mahmoud00@eng-st.cu.edu.eg

Omar Amin
Computer Engineering
Cairo University
Cairo, Egypt
oamin.omar@gmail.com

Disclaimer: This paper contains harmful and offensive model responses.

***Abstract*—In a world where Large Language Models (LLMs) are becoming more prominent and widely used, jailbreaking attacks remain a serious challenge to their safety. In this study, we evaluated three template-based attacks: TemplateJailbreak, Parameters, and DeepInception on popular lightweight models: Phi-2-2.7B, Llama-3.2-1B, DeepSeek-R1-1.5B and Qwen3-0.6B. We use HarmBench for evaluation and a fine-tuned RoBERTa model to classify jailbreak success. Our results show that template-based attacks are still very effective, with TemplateJailbreak attack achieving a 100% success rate altough it required a large number of queries. The Parameters attack was more efficient but did not work with all models. The DeepInception attack was the least effective overall. These findings highlight that even state-of-the-art lightweight LLMs remain highly vulnerable to prompt-based jailbreak attacks.**

***Index Terms*—Large Language Model, Machine Learning, Jailbreaking, Cyber Security**

I. Introduction

With the rapid advancements in the field of machine learning, and at the early stage where Large Language Models (LLMs) became more powerful and widely integrated into everyday applications, threat actors and cybercriminal groups began exploiting LLMs for various illegal activities. These include generating phishing campaigns, creating malicious payloads, disclosing sensitive information, and spreading misinformation. Their exploitation is not limited to textual models, threat actors are also leveraging multimodal LLMs to produce highly realistic fake content, such as images and videos. A prominent example of this is **Deepfake** (Westerlund, 2019). One of the well-known incidents demonstrating the potential risks of LLMs occurred when sensitive source code was leaked at **Samsung** (Ray, n.d.). Similarly, other companies, such as **Amazon**, reported incidents where responses generated by ChatGPT contained internal company information.

Moreover, the **Open Worldwide Application Security Project (OWASP)**, a nonprofit organization focused on software security, has published the **OWASP Top 10 for Large Language Model Applications** (Fasha et al., 2024). This community-driven initiative aims to identify and raise awareness about security issues in artificial intelligence (AI) applications. The OWASP Top 10 highlights the most critical vulnerabilities affecting LLM-based systems. At the top of the list is the **Prompt Injection** attack, where a threat actor crafts a malicious prompt and feeds it to the LLM. This type of attack can lead to several serious consequences, including—but not limited to—sensitive information disclosure, remote code execution (RCE), and the generation of harmful content.

The research community is actively exploring this fertile attack surface to uncover blind spots and weaknesses in modern LLMs, especially alongside the ongoing race among companies to release increasingly sophisticated models. Studies such as Xu, Liu, Deng, Li, and Picek (2024a) have introduced standardized evaluation frameworks to identify and mitigate potential risks in LLMs. Mazeika et al. (2024) extended this effort by incorporating defense mechanisms into the models and evaluating both attack and defense techniques against various types of jailbreaking methods.

Our research aims to shed light on the gaps in defensive mechanisms of modern LLMs, by attempting to penetrate and jailbreak them through various attack approaches. For the scope of our paper, we try three template-based techniques, namely TemplateJailbreak (Liu et al., 2024), Parameters (Huang, Gupta, Xia, Li, & Chen, 2023), and Deep Inception (Li et al., 2024). We thoroughly test these approaches against modern LLMs such as Deepseek (Hugging Face, 2025a) and Qwen (Hugging Face, 2025b), models that were released so recently. The insights we gain from this project would further improve the defensive capabilities of LLMs, bolstering them against malicious intentions.

Running our different attack models on a dataset of 60 harmful prompts collected by Xu et al. (2024a) following OpenAI's guidelines, we find that the most effective attack method is the TemplateJailbreak. It shows a consistent attack success rate (ASR) of 100% across all models. It also shows the highest efficiency compared to Deep Inception and Parameters. Furthermore, Qwen3-0.6B proved the hardest model to jailbreak, despite its simplicity. It boasts an impressive ASR of 71.67% for Parameters, compared to the 90+% of other models. It even has an efficiency of only around 13% for Parameters. This great performance is further augmented by Deep Inception only scoring 10% ASR and efficiency against it.

To conclude, our contributions lie primarily in evaluating

new LLMs that were released in the past 1.5 years. This reveals the improvement in the defensive capabilities of LLMs, while also highlighting the gaps that need to be filled.

The paper outline is as follows: Firstly, Section II discusses the literature surrounding LLMs, jailbreaking approaches, and evaluation benchmarks. Secondly, Section III thoroughly explains the chosen attack approaches and LLM models. It also states our machine specifications. Followed by that, Section IV contains the results and insights regarding them. Finally, Section V concisely concludes the paper, highlighting future work.

II. Literature Review

Jailbreaking large language models (LLMs) has become an increasingly active topic in research, with various attack methods being actively explored. In the context of jailbreaking attack techniques, two main categories exist: **dynamic** and **static** attacks. This categorization is based on the way the prompt is created. Dynamic techniques, such as **Generative** methods like **TAP** (Mehrotra et al., 2024) and **LoFT** (Shah et al., 2023), rely on dynamically updating the jailbreak prompt based on feedback from the target LLM. In contrast, static techniques, such as **Template-Based** methods like **DeepInception** (Li et al., 2024), **Generation Exploitation Attack (Parameters Attack)** (Huang et al., 2023), and **the prompt engineering technique** using 78 predefined templates proposed by Liu et al. (2024), use fixed values to build the prompt or tune the model response generation parameters, with no live updates during the attack.

This growing interest highlights the need for standardized evaluation frameworks to assess LLMs' robustness against harmful or malicious prompts. In response, benchmarks such as **PromptRobust** (Zhu et al., 2023), **DecodingTrust** (Wang et al., 2024), **Jailbreakbench** (Chao et al., 2024), **TrustLLM** (Huang et al., 2024), **EasyJailbreak** (Zhou et al., 2024), **HarmBench** (Mazeika et al., 2024), and Liu et al. (2024) have been developed to provide benchmarks to evaluate how effectively LLMs handle adversarial or unsafe inputs.

A. Jailbreaking Attack Techniques

We conduct our study on several target LLMs by building upon the work of Xu, Liu, Deng, Li, and Picek (2024b), who performed a comprehensive analysis of various attack and defense techniques on **GPT-3.5 Turbo**, **Vicuna-v1.5**, and **Llama-2** (Touvron et al., 2023). In our study, we specifically focus on **Template-Based** approaches, which shows more effectiveness than generative methods in Xu et al. (2024b). Among the template-based techniques examined in their study, we concentrate on the **Generation Exploitation Attack (Parameters Attack)** (Huang et al., 2023), **DeepInception** (Li et al., 2024), and **Template-Jailbreaking** (Liu et al., 2024) methods. We evaluate these techniques against a set of newer lightweight LLMs, including **Llama 3.2** (Grattafiori et al., 2024), **Phi-2** (Hugging Face, 2023), **DeepSeek-R1-Distill** (DeepSeek-AI et al., 2025) and **Qwen3-0.6B** (Hugging Face, 2025b).

In their study Liu et al. (2024) used a collection of 78 verified templates for their prompts and categorized them into 3 types; Pretending, privilege escalation and attention shifting they executed 31,200 total queries to analyze jailbreak effectiveness and model robustness they Found that 86.3% of the tested scenarios could be successfully jailbroken using the collected prompts.

The **Generation Exploitation Attack** (Huang et al., 2023), also referred to as the **Parameters Attack** in Xu et al. (2024b), is a black-box technique that targets open-source LLMs by simply modifying sampling parameters like *Top-p*, *Top-k*, and *Temperature*. Their study found that tuning these sampling parameters could lead to misaligned outputs, with at least 50% of them containing harmful content.

DeepInception Li et al. (2024) is a template-based approach that is inspired by the **Milgram shock experiment** Milgram (1974), which shows that individuals are likely to follow harmful instructions when directed by an authority figure. This method leverages nested prompts (inceptions) to simulate authority scenarios, enabling the LLM to override its safety guardrails without the need of any fine tuning.

B. Evaluation Benchmarks

Zhu et al. (2023) introduced **PromptRobust**, a Python library used to evaluate LLMs and its ability to handle different types of types harmful prompts, but it does not mainly focus on jailbreaking LLMs.

Added to that, both **DecodingTrust** (Wang et al., 2024) and **TrustLLM** (Huang et al., 2024) evaluate LLMs performance against jailbreaking attacks, but only deal with static template attack techniques.

HarmBench (Mazeika et al., 2024) benchmark, a standardized evaluation framework designed to assess both dynamic and static jailbreaking techniques. This benchmark includes 510 harmful behaviors, consisting of 400 textual and 110 multimodal examples.

We adopted the framework proposed by Liu et al. (2024), as it aligns with the **OpenAI** compliance categories (*OpenAI Platform*, 2023). Our dataset consists of 60 malicious prompts, evenly distributed across the following categories:

1) Adult content
2) Privacy violations
3) Illegal content
4) Harmful content
5) Fraudulent content
6) Unlawful content

This wide range of categories enables a comprehensive evaluation of an LLM's robustness against diverse forms of harmful input.

III. Study Design

A. Jailbreak Attack Techniques

*1) **TemplateJailbreak Attack**:* It is a template-based attack method used to bypass the built-in safety measures of large language models (LLMs) and produce unintended outputs

through carefully crafted prompts. Here are the key points about this technique:

- **Predefined Templates:** The attack relies on carefully constructed prompt templates that exploit model vulnerabilities.
- **High Success Rate:** By running multiple templates against the same input question, the attack increases the chances of a successful jailbreak.
- **Iterative Attempts:** The same question is tested across many iterations to maximize the attack success rate.
- **Heavy Computational Cost:** It requires many queries for each question, making it resource intensive.
- **Simplicity:** The technique is easy to understand and implement.

In our study, we conducted experiments against 78 templates, running five iterations for each prompt question. We utilized the dataset introduced by Liu et al. (2024), which represents the first comprehensive collection of jailbreak prompts targeting ChatGPT. The dataset consists of 78 prompts sourced from the Jailbreak Chat website[1], known for hosting one of the largest collections of ChatGPT jailbreaks available online.

*2) **Parameters Attack**:* It is a black-box attack technique that exploits the decoding parameters of open-source LLMs to induce misaligned outputs. The attack targets parameters such as *Top-p*, *Top-k*, and *Temperature*, which control the generation process of the model. Below are the key points of this technique:

- **Sampling Parameters:** The attack relies on manipulating the model's decoding settings, such as *Top-p*, *Top-k*, and *Temperature*, to alter the output generation.
- **High Misalignment Rate:** By adjusting these parameters, the attack has been shown to lead to a significant misalignment in the model's outputs.
- **Simplicity and Efficiency:** The technique is relatively simple to implement and does not require fine-tuning of the model, making it efficient for real-world use.

In our study, we tested this attack by changing the following sampling parameters following the work of Huang et al. (2023):

- **Temperature:** We tested values within the range [0.05, 1], where lower values (closer to 0) make the model's output more deterministic, and higher values (closer to 1) make the output more random.
- **Top-p:** We tested values within the range [0, 1], where Top-p controls the cumulative probability distribution of the model's output, with higher values allowing more diversity in the output.
- **Presence Penalty:** We tested values within the range [-2, 2], which adjusts the model's tendency to repeat the same words. Positive values discourage repetition, while negative values encourage it.
- **Frequency Penalty:** We tested values within the range [-2, 2], which adjusts how much the model penalizes frequent words. Negative values encourage frequent words, while positive values reduce their occurrence.
- **Top-k:** We tested values (1, 2, 5, 10, 20, 50, 100, 200, 500), where Top-k limits the number of possible next tokens considered during generation, making the output more focused or more diverse depending on the value.

This wide range of parameters allows us to study the effectiveness of the Generation Exploitation Attack across different settings, which shows how different configurations impact the possibility of generating harmful content.

*3) **DeepInception Attack**:* This is yet another template-based attack. As the name suggests, it relies on deeply nested layers of scenarios, where each scenario represents a request or prompt. The scenarios are initially harmless, but progressively become unsafe. The acting of nesting these scenarios to illicit the required output is called Deep Inception (Li et al., 2024).

Deep Inception attack's approach is based on the Milgram experiment (Milgram, 1974). The experiment aimed to prove that normal people are capable of committing atrocious acts under the guise of obedience to an authoritative figure. An instructor would order people to commit heinous acts, and they would surprisingly follow through, with the excuse of following orders. Similarly, Deep Inception aims to replicate that notion of subservience, by progressively guiding the model towards more harmful actions.

The key points of this technique are highlighted in:

- **Multi-layered:** The nested instructions let the LLM create a virtual, multi-layer scene with multiple characters to jailbreak with a specific objective, as shown in fig 1.
- **High Complexity:** Due its nested nature, the attack requires high GPU usage, so only light models can be tested given our GPU limitations.
- **Responsibility Delegation:** As a result of nesting so many scenarios, the LLM loses its sense of accountability. Making it more prone to jailbreaking.



Fig. 1. Nested Instructions of DeepInception

We tested various DeepInception scenarios provided by Li et al. (2024) in their paper. The scenarios varied over many fields, to ensure the malicious prompt would seem like a natural extension to at least one scenario, increasing the chances of jailbreaking.

B. Tested LLMs

- **Phi-2-2.7B** (Hugging Face, 2023) is a transformer developed by Microsoft. It has 2.7 billion parameters, yet does not require intensive GPU resources when running.

[1] https://www.jailbreakchat.com/

- **Llama-3.2-1B** (Hugging Face, 2024) has 1 billion parameters. It is an open-source model developed by Meta.
- **DeepSeek-R1-Distill-Qwen-1.5B** (Hugging Face, 2025a) has 1.5 billion parameters. We chose this distilled smaller version so that it is easier to run locally.
- **Qwen3-0.6B** (Hugging Face, 2025b) has 0.6 billion parameters. It was developed by Alibaba Cloud as a mixture-of-experts (MoE) model.

C. Testing Setup

We test the project on Google Colab, due to the intensive GPU requirements of the models. Furthermore, we split the data into three equal parts to facilitate the testing process.

Colab's machine has the following specifications:

TABLE I
THE SPECIFICATIONS OF GOOGLE COLAB'S MACHINE

System Ram	12.7 GB
GPU RAM	15 GB
GPU	T4 GPU
Disk	112.6 GB

IV. RESULTS AND EVALUATION

To determine whether a model was jailbroken or not, we initially experimented with a few approaches. Manual evaluation quickly proved infeasible, due to the great number of prompts involved, as well as the inevitability of human bias. Setting fixed rules and searching for certain keywords to determine whether or not a jailbreak took place seemed like a promising idea. However, after further investigation, we noticed that different models respond differently to jailbreaking attempts, making it impossible to create a set of rules to label the responses with high accuracy and validity.

It was evident that we need to utilize a model trained specifically for this task. Xu et al. (2024a) fine-tuned a RoBERTa model to classify LLM responses, facilitating the evaluation process. Their model achieves an accuracy of 92% on our dataset, surpassing many other models, including GPT-4 which showed an accuracy of 87.4%, as reported by Xu et al. (2024a).

A. Evaluation Metrics

To assess the effectiveness of jailbreaking techniques, we employ two core evaluation metrics:

- **Attack Success Rate (ASR):** This metric quantifies how effective an attack is by calculating the ratio of successfully compromised questions c to the total number of questions n.

$$\text{ASR} = \frac{c}{n}$$

- **Efficiency:** Efficiency evaluates the effectiveness of the attack attempts themselves. It is calculated as the ratio of successful attack queries q to the total number of query attempts o. Each query corresponds to a single prompt or experimental trial, allowing us to assess how resource-intensive an attack is.

$$\text{Efficiency} = \frac{q}{o}$$

B. Attack Performance

All attacks were conducted over a fixed set of 60 questions, categorized into six types of harmful content: *harmful*, *adult*, *privacy-violating*, *unlawful*, *fraudulent-deceptive*, and *illegal* prompts, as shown in fig IV-B. These categories ensure a comprehensive evaluation across diverse and critical safety violations. We evaluated each attack technique on four different models:

- Phi-2-2.7B (Hugging Face, 2023)
- Llama-3.2-1B (Hugging Face, 2024)
- DeepSeek-R1-Distill-Qwen-1.5B (Hugging Face, 2025a)
- Qwen3-0.6B (Hugging Face, 2025b)



Fig. 2. Distribution of prompt categories in dataset

*1) **TemplateJailbreak Attack:*** The TemplateJailbreak method demonstrated **complete success** against both models, achieving a 100% ASR:

TABLE II
TEMPLATE JAILBREAK RESULTS

Model	ASR	Efficiency
Phi-2	60/60	5288/13860
Llama 3.2	60/60	4595/13860
DeepSeek-R1-Distill	60/60	4235/13860
Qwen3-0.6B	60/60	4235/13860

Despite achieving a perfect attack success rate, the number of queries required highlights the cost of such an attack. We run each question on 78 templates, with 3 iterations per template, resulting in a high computational cost that demands high GPU resources to execute. However, it is the simplest algorithm and can be easily understood.

*2) **Parameters Attack:*** This technique performed strongly but did not reach perfect success rates:

This shows that `Phi-2` was more susceptible to Parameters attack both in terms of success rate and efficiency. `Llama 3.2` required fewer total attempts but yielded fewer successful queries proportionally.

TABLE III
PARAMETERS RESULTS

Model	ASR	Efficiency
Phi-2	55/60	2088/5400
Llama 3.2	54/60	1258/5400
DeepSeek-R1-Distill	55/60	1561/5400
Qwen3-0.6B	43/60	721/5400

*3) **DeepInception Attack:*** This approach was less effective, succeeding on fewer than half the questions:

TABLE IV
DEEPINCEPTION RESULTS

Model	ASR	Efficiency
Phi-2	22/60	110/300
Qwen3-0.6B	6/60	18/180

This attack yielded lower results in both ASR and efficiency, suggesting it may not scale well. We were able to run DeepInception attack on only Phi-2 and Qwen3-0.6B because they are the lightest models. The attack is highly GPU-intensive, making it difficult to run on larger models.

C. Summary

As shown in table V, **TemplateJailbreak** emerges as the most reliable technique across models, although with a moderate efficiency. **Parameters** strikes a stronger balance between success rate and efficiency on `Phi-2`, while **DeepInception** proved less effective overall. Figure IV-C shows the ASR for the TemplateJailbreak and Parameters techniques across the evaluated models.



Fig. 3. Attack Success Rate (ASR) for TemplateJailbreak and Parameters techniques across models

V. CONCLUSIONS AND FUTURE WORK

In this study, we evaluated three jailbreak attack techniques: TemplateJailbreak, Parameters, and DeepInception, on four lightweight language models: Phi-2, DeepSeek-R1-Distill, Qwen3-0.6B, and Llama 3.2. Our findings demonstrate that the TemplateJailbreak technique achieved the highest attack success rate across all models, despite requiring a large number of queries. The Parameters attack presented a more balanced performance, offering reasonable efficiency with moderate success rates. On the other hand, the DeepInception attack was the least effective and could not be executed on all models due to its high computational requirements.

For future work, we plan to extend our evaluation to include larger-scale language models. Additionally, we aim to explore a wider range of jailbreak techniques, i.e. generative approaches, that may offer greater generality, adaptability and dynamic behaviour, coupled with less human intervention. However, such additions will require significant computational resources, particularly GPU access, which posed a limitation in our current work.

TABLE V
ASR AND EFFICIENCY PER MODEL AND ATTACK TYPE

Model	Parameters		TemplateJailbreak		DeepInception	
	ASR	***Efficiency***	***ASR***	***Efficiency***	***ASR***	***Efficiency***
Phi-2	91.67%	38.67%	100%	38.15%	36.67%	36.67%
Llama 3.2	90%	23.3%	100%	33.15%	–	–
DeepSeek-R1-Distill	91.67%	28.91%	100%	30.56%	–	–
Qwen3-0.6B	71.67%	13.35%	100%	34.48%	10%	10%

REFERENCES

Chao, P., Debenedetti, E., Robey, A., Andriushchenko, M., Croce, F., Sehwag, V., … Wong, E. (2024, October). *JailbreakBench: An Open Robustness Benchmark for Jailbreaking Large Language Models.* arXiv. Retrieved from http://arxiv.org/abs/2404.01318 (arXiv:2404.01318) doi: 10.48550/arXiv.2404.01318

DeepSeek-AI, Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., … Zhang, Z. (2025, January). *DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2501.12948 (arXiv:2501.12948) doi: 10.48550/arXiv.2501.12948

Fasha, M., Rub, F. A., Matar, N., Sowan, B., Al Khaldy, M., & Barham, H. (2024, February). Mitigating the OWASP Top 10 For Large Language Models Applications using Intelligent Agents. In *2024 2nd International Conference on Cyber Resilience (ICCR)* (pp. 1–9). Dubai, United Arab Emirates: IEEE. Retrieved 2025-05-20, from https://ieeexplore.ieee.org/document/10532874/ doi: 10.1109/ICCR61006.2024.10532874

Grattafiori, A., Dubey, A., Jauhri, A., Pandey, A., Kadian, A., Al-Dahle, A., … Ma, Z. (2024, November). *The Llama 3 Herd of Models.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2407.21783 (arXiv:2407.21783) doi: 10.48550/arXiv.2407.21783

Huang, Y., Gupta, S., Xia, M., Li, K., & Chen, D. (2023, October). *Catastrophic Jailbreak of Open-source LLMs via Exploiting Generation.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2310.06987 (arXiv:2310.06987) doi: 10.48550/arXiv.2310.06987

Huang, Y., Sun, L., Wang, H., Wu, S., Zhang, Q., Li, Y., … Zhao, Y. (2024, September). *TrustLLM: Trustworthiness in Large Language Models.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2401.05561 (arXiv:2401.05561) doi: 10.48550/arXiv.2401.05561

Hugging Face. (2023). *microsoft/phi-2 · Hugging Face.* Retrieved 2025-05-19, from https://huggingface.co/microsoft/phi-2

Hugging Face. (2024, December). *Meta-llama/llama-3. 2-3b · hugging face.* Retrieved 2025-05-20, from https://huggingface.co/meta-llama/Llama-3.2-3B

Hugging Face. (2025a, January). *Deepseek-ai/deepseek-r1-distill-qwen-1. 5b · hugging face.* Retrieved 2025-05-20, from https://huggingface.co/deepseek-ai/DeepSeek-R1-Distill-Qwen-1.5B

Hugging Face. (2025b, May). *Qwen/Qwen3-0.6B · Hugging Face.* Retrieved 2025-05-19, from https://huggingface.co/Qwen/Qwen3-0.6B

Li, X., Zhou, Z., Zhu, J., Yao, J., Liu, T., & Han, B. (2024, November). *DeepInception: Hypnotize Large Language Model to Be Jailbreaker.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2311.03191 (arXiv:2311.03191) doi: 10.48550/arXiv.2311.03191

Liu, Y., Deng, G., Xu, Z., Li, Y., Zheng, Y., Zhang, Y., … Liu, Y. (2024, March). *Jailbreaking ChatGPT via Prompt Engineering: An Empirical Study.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2305.13860 (arXiv:2305.13860) doi: 10.48550/arXiv.2305.13860

Mazeika, M., Phan, L., Yin, X., Zou, A., Wang, Z., Mu, N., … Hendrycks, D. (2024, February). *HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal.* arXiv. Retrieved from http://arxiv.org/abs/2402.04249 (arXiv:2402.04249) doi: 10.48550/arXiv.2402.04249

Mehrotra, A., Zampetakis, M., Kassianik, P., Nelson, B., Anderson, H., Singer, Y., & Karbasi, A. (2024, October). *Tree of Attacks: Jailbreaking Black-Box LLMs Automatically.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2312.02119 (arXiv:2312.02119) doi: 10.48550/arXiv.2312.02119

Milgram, S. (1974). *Obedience to authority: an experimental view* (1st ed. ed.). New York: Harper & Row.

OpenAI Platform. (2023). Retrieved 2025-05-20, from https://platform.openai.com

Ray, S. (n.d.). *Samsung Bans ChatGPT Among Employees After Sensitive Code Leak.* Retrieved 2025-05-20, from https://www.forbes.com/sites/siladityaray/2023/05/02/samsung-bans-chatgpt-and-other-chatbots-for-employees-after-sensitive-code-leak/

Shah, M. A., Sharma, R., Dhamyal, H., Olivier, R., Shah, A., Konan, J., … Singh, R. (2023). *LoFT: Local Proxy Fine-tuning For Improving Transferability Of Adversarial Attacks Against Large Language Model.* arXiv. Retrieved 2025-05-19, from https://arxiv.org/abs/2310.04445 doi: 10.48550/ARXIV

.2310.04445

Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., … Scialom, T. (2023). *Llama 2: Open Foundation and Fine-Tuned Chat Models.* arXiv. Retrieved 2025-05-19, from https://arxiv.org/abs/2307.09288 doi: 10.48550/ARXIV.2307.09288

Wang, B., Chen, W., Pei, H., Xie, C., Kang, M., Zhang, C., … Li, B. (2024, February). *DecodingTrust: A Comprehensive Assessment of Trustworthiness in GPT Models.* arXiv. Retrieved 2025-05-19, from http://arxiv.org/abs/2306.11698 (arXiv:2306.11698) doi: 10.48550/arXiv.2306.11698

Westerlund, M. (2019, 11/2019). The emergence of deepfake technology: A review. *Technology Innovation Management Review*, *9*, 40-53. Retrieved from timreview.ca/article/1282 doi: http://doi.org/10.22215/timreview/1282

Xu, Z., Liu, Y., Deng, G., Li, Y., & Picek, S. (2024a). A Comprehensive Study of Jailbreak Attack versus Defense for Large Language Models. In *Findings of the Association for Computational Linguistics ACL 2024* (pp. 7432–7449). Bangkok, Thailand and virtual meeting: Association for Computational Linguistics. Retrieved 2025-05-19, from https://aclanthology.org/2024.findings-acl.443 doi: 10.18653/v1/2024.findings-acl.443

Xu, Z., Liu, Y., Deng, G., Li, Y., & Picek, S. (2024b). A Comprehensive Study of Jailbreak Attack versus Defense for Large Language Models. In *Findings of the Association for Computational Linguistics ACL 2024* (pp. 7432–7449). Bangkok, Thailand and virtual meeting: Association for Computational Linguistics. Retrieved 2025-05-19, from https://aclanthology.org/2024.findings-acl.443 doi: 10.18653/v1/2024.findings-acl.443

Zhou, W., Wang, X., Xiong, L., Xia, H., Gu, Y., Chai, M., … Huang, X. (2024, March). *EasyJailbreak: A Unified Framework for Jailbreaking Large Language Models.* arXiv. Retrieved 2025-05-20, from http://arxiv.org/abs/2403.12171 (arXiv:2403.12171) doi: 10.48550/arXiv.2403.12171

Zhu, K., Wang, J., Zhou, J., Wang, Z., Chen, H., Wang, Y., … Xie, X. (2023, June). PromptRobust: Towards Evaluating the Robustness of Large Language Models on Adversarial Prompts. *arXiv e-prints*, arXiv:2306.04528. Retrieved 2025-05-19, from https://ui.adsabs.harvard.edu/abs/2023arXiv230604528Z/abstract doi: 10.48550/arXiv.2306.04528

APPENDIX



Fig. 4. Example of a jailbroken response generated by LLaMA 3.2 using the TemplateJailBreak attack technique.



Fig. 5. Example of a jailbroken response generated by Phi-2 (temperature=0.75) using the Parameters attack technique.



Fig. 6. Example of a jailbroken response generated by Phi-2 using the DeepInception attack technique.