



Corrigendum

Corrigendum to “Yearly energy performance of a photovoltaic-phase change material (PV-PCM) system in hot climate” [Sol. Energy 146 (2017) 417–429]

A. Hasan^{a,*}, J. Sarwar^b, H. Alnoman^a, S. Abdelbaqi^a

^a Department of Architectural Engineering, College of Engineering, United Arab Emirates University, P.O. Box 15551, Al Ain, United Arab Emirates

^b Sustainable Energy & Clean Air Research Laboratory (SECARE Lab), Department of Chemical Engineering, Texas A & M University at Qatar, PO Box 23874, Doha, Qatar

The authors regret to inform the readers that Eqs. (11) and (12) have typographical errors, where the product of the open circuit voltage (V_{oc}) and the short circuit current (I_{sc}) is divided by the fill factor (FF) instead of being multiplied. The equations should read as follows:

$$P_e = V_{oc} I_{sc} * FF \quad (11)$$

$$P_s = P_{e,PV-PCM} - P_{e,ref} = (V_{oc} I_{sc} * FF)_{PV-PCM} - (V_{oc} I_{sc} * FF)_{ref} \quad (12)$$

In the actual calculation which followed, the FF was multiplied not divided and accordingly all the graphs were drawn. So the results presented in the graphs, the discussions and conclusions still remain the same and require no change.

The authors would like to apologise for any inconvenience caused.

DOI of original article: <https://doi.org/10.1016/j.solener.2017.01.070>.

* Corresponding author.

E-mail address: ahmed.hassan@uaeu.ac.ae (A. Hasan).

<https://doi.org/10.1016/j.solener.2022.04.037>

Available online 26 May 2022

0038-092X/© 2022 International Solar Energy Society. Published by Elsevier Ltd. All rights reserved.