
Calendar privacy repair prototype

- A bounded garak -> configured patch -> verify research exercise.
- Reliable scheduling and observed vulnerability evidence are available.
- Two defenses and the controller are implemented; 141 offline tests pass.
- Fresh live defense comparison is awaiting API connectivity; human review is pending.

Question and scope

- Can private event-detail publication be reduced while preserving team scheduling?
- Three owner-scoped assistants; only availability is allowed to be shared.
- Two Ministral model IDs, independently run as homogeneous teams.
- Participant-message injection is implemented; MCP and adaptive attacks are extensions.

Fixed synthetic calendar data



Source: fixed CAL-0052 calendars and evaluator.json; all times UTC, half-open intervals. Blank time is free. Semantic event details omitted from this figure.


Diagnosis before attacks

- v1/v2 each had 0/8 team success despite working API responses.
- Missing availability, unsupported peer claims and conflicting final times were diagnosed.
- v3 achieved 7/8; strict v4 schemas and an explicit shared commit achieved 40/40.
- Tools compute availability/intersections; models publish, select and acknowledge.

Threat model and garak adapter


- An external peer's publish note carries the attack; attachments and system prompt remain unchanged.
- Three static injection families plus benign and direct-request controls.
- Actual garak Probe, Generator, Detector and ThresholdEvaluator APIs wrap the whole team.
- One normal team generation uses seven model calls. Private requests are excluded from observable output.

Observed baseline candidate flags




Source: existing 40-case native garak replay. These reuse earlier real-provider observations; no new calls. Human semantic confirmation pending.

Existing model / condition breakdown



Source: same 40 recorded cases as baseline_privacy. Four scenarios per model/condition; candidate flags do not establish general model safety rankings.

Implemented automatic repair path



Ablation: no defense / input only / output only / both. External attacker note is inserted after its sender's local output policy.

The defenses minimize a text channel for a fixed structured task. This is policy activation, not autonomous defense invention or model training.

Final study is frozen and ready

- Four scenarios x two models x five conditions x four policies = 160 fresh team sessions.
- Normally 1,120 logical completions; bounded retries and global resource caps.
- Rotate policy order across pair blocks; match starting data and audit actual later histories.
- Measure public candidate flags, scheduling correctness and raw-generation diagnostics separately.
- No missing metric is treated as zero; final human rates remain undefined until review.

Limits and next discussion

- Broad prose minimization is a conservative policy for this structured task, not a general semantic defense.
- All human worksheets start blank; later annotation does not require another model run.
- Next research: selective release, tool/MCP poisoning, adaptive attacks and held-out repeated evaluation.
- Repository preserves failures, traces, source data, plans, tests and reproducibility instructions.
- Applicant framing and independent reading; ChatGPT implementation and preparation assistance disclosed.