

```
# Imports math library
import numpy as np
# Imports plotting library
import matplotlib.pyplot as plt
```

```
# Define the Rectified Linear Unit (ReLU) function - Points: 10
def ReLU(preactivation):
    # TODO write code to implement the ReLU and compute the activation at the
    # hidden unit from the preactivation
    # Replace the given code with your code
    # To understand the input format, look at the code cell below this one
    return np.maximum(preactivation, 0)
```

```
# Make an array of inputs
z = np.arange(-5,5,0.1)
ReLU_z = ReLU(z)

# Plot the ReLU function
fig, ax = plt.subplots()
ax.plot(z, ReLU_z, 'r-')
ax.set_xlim([-5,5]); ax.set_ylim([-5,5])
ax.set_xlabel('z'); ax.set_ylabel('ReLU[z]')
ax.set_aspect('equal')
plt.show()
```

```
# Define a shallow neural network with, one input, one output, and three hidden
units - Points: 12
def shallow_1_1_3(x, activation_fn, phi_0, phi_1, phi_2, phi_3, theta_10, theta_11,
theta_20, theta_21, theta_30, theta_31):
    # TODO Replace the code below to compute the three initial lines
    # from the theta parameters (i.e. implement equations given at bottom of figure
a-c below this Code Cell). These are the preactivations
    pre_1 = theta_10 + theta_11*x
    pre_2 = theta_20 + theta_21*x
    pre_3 = theta_30 + theta_31*x

    # Pass these through the ReLU function to compute the activations as in figure
d-f given below. No need to replace anything here
    act_1 = activation_fn(pre_1)
```

```

act_2 = activation_fn(pre_2)
act_3 = activation_fn(pre_3)

# TODO Replace the code below to weight the activations using phi1, phi2 and
phi3 to create the equivalent of figure g-i
w_act_1 = phi_1*act_1
w_act_2 = phi_2*act_2
w_act_3 = phi_3*act_3

# TODO Replace the code below to combining the weighted activations and add
phi_0 to create the output as in figure j
y = phi_0 + w_act_1 + w_act_2 + w_act_3

# Return everything we have calculated
return y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3

```

```

# Plot the shallow neural network. We'll assume input in is range [0,1] and
output [-1,1]
# If the plot_all flag is set to true, then we'll plot all the intermediate
stages as in figure given below.
def plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=False, x_data=None, y_data=None):

    # Plot intermediate plots if flag set
    if plot_all:
        fig, ax = plt.subplots(3,3)
        fig.set_size_inches(8.5, 8.5)
        fig.tight_layout(pad=3.0)
        ax[0,0].plot(x,pre_1,'r-'); ax[0,0].set_ylabel('Preactivation')
        ax[0,1].plot(x,pre_2,'b-'); ax[0,1].set_ylabel('Preactivation')
        ax[0,2].plot(x,pre_3,'g-'); ax[0,2].set_ylabel('Preactivation')
        ax[1,0].plot(x,act_1,'r-'); ax[1,0].set_ylabel('Activation')
        ax[1,1].plot(x,act_2,'b-'); ax[1,1].set_ylabel('Activation')
        ax[1,2].plot(x,act_3,'g-'); ax[1,2].set_ylabel('Activation')
        ax[2,0].plot(x,w_act_1,'r-'); ax[2,0].set_ylabel('Weighted Act')
        ax[2,1].plot(x,w_act_2,'b-'); ax[2,1].set_ylabel('Weighted Act')
        ax[2,2].plot(x,w_act_3,'g-'); ax[2,2].set_ylabel('Weighted Act')

        for plot_y in range(3):
            for plot_x in range(3):

```

```

        ax[plot_y,plot_x].set_xlim([0,1]);ax[plot_x,plot_y].set_ylim([-1,1])
        ax[plot_y,plot_x].set_aspect(0.5)
        ax[2,plot_y].set_xlabel('Input, $x$');
        plt.show()

fig, ax = plt.subplots()
ax.plot(x,y)
ax.set_xlabel('Input, $x$'); ax.set_ylabel('Output, $y$')
ax.set_xlim([0,1]);ax.set_ylim([-1,1])
ax.set_aspect(0.5)
if x_data is not None:
    ax.plot(x_data, y_data, 'mo')
    for i in range(len(x_data)):
        ax.plot(x_data[i], y_data[i],)
plt.show()

```

```

# Now lets define some parameters and run the neural network
theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = -0.3; phi_1 = 2.0; phi_2 = -1.0; phi_3 = 7.0

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, ReLU, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11, theta_20,
theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```

```

# TODO - Points: 20 (2.5 for each part. Answer this question in the cell space
given below this cell)
# 1. Predict what effect changing phi_0 will have on the network.

# 2. Predict what effect multiplying phi_1, phi_2, phi_3 by 0.5 would
have. Check if you are correct

```

```

# 3. Predict what effect multiplying phi_1 by -1 will have. Check if you are
correct.

# 4. Predict what effect setting theta_20 to -1.2 will have. Check if you are
correct.

# 5. Change the parameters so that there are only two "joints" (including outside
the range of the plot)
# There are actually three ways to do this. See if you can figure them all out

# 6. With the original parameters, the second line segment is flat (i.e. has
slope zero)
# How could you change theta_10 so that all of the segments have non-zero slopes

# 7. What do you predict would happen if you multiply theta_20 and theta_21 by
0.5, and phi_2 by 2.0?
# Check if you are correct.

# 8. What do you predict would happen if you multiply theta_20 and theta_21 by -
0.5, and phi_2 by -2.0?
# Check if you are correct.

theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = -0.3; phi_1 = 2.0; phi_2 = -1.0; phi_3 = 7.0

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, ReLU, phi_0, phi_1, phi_2, phi_3, theta_10, theta_11, theta_20,
theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```

```

# Least squares function - Points: 10
def least_squares_loss(y_train, y_predict):
    # TODO Replace the line below to compute the sum of squared

```

```

    # differences between the real values of y and the predicted values from the
    model f[x_i,phi] (figure given above)
    # you will need to use the function np.sum
    # Loop is not allowed
    loss = np.sum((y_train - y_predict)**2)
    return loss

```

```

# Now lets define some parameters, run the neural network, and compute the loss
theta_10 = 0.0 ; theta_11 = 0.5
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = -0.1; phi_1 = 2.0; phi_2 = -1.0; phi_3 = 7.0

# Define a range of input values
x = np.arange(0,1,0.01)

x_train =
np.array([0.09291784,0.46809093,0.93089486,0.67612654,0.73441752,0.86847339,\
          0.49873225,0.51083168,0.18343972,0.99380898,0.27840809,0.38028
817,\
          0.12055708,0.56715537,0.92005746,0.77072270,0.85278176,0.05315
950,\
          0.87168699,0.58858043])
y_train = np.array([-
0.15934537,0.18195445,0.451270150,0.13921448,0.09366691,0.30567674,\
          0.372291170,0.40716968,-
0.08131792,0.41187806,0.36943738,0.3994327,\
          0.019062570,0.35820410,0.452564960,-0.0183121,0.02957665,-
0.24354444, \
          0.148038840,0.26824970])

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, ReLU, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11, theta_20,
theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True, x_data = x_train, y_data = y_train)

# Run the neural network on the training data
y_predict, *_ = shallow_1_1_3(x_train, ReLU, phi_0,phi_1,phi_2,phi_3, theta_10,
theta_11, theta_20, theta_21, theta_30, theta_31)

```

```

# Compute the least squares loss and print it out
loss = least_squares_loss(y_train,y_predict)
print('Your Loss = %3.3f, True value = 9.385'%(loss))

# TODO. Manipulate the parameters (by hand!) to make the function - Points: 8
# fit the data better and try to reduce the loss to as small a number
# as possible. The best that I could do was 0.181
# Tip... start by manipulating phi_0.
# It's not that easy, so don't spend too much time on this!

```

```

import plotly.graph_objects as go

# Code to draw 2D function -- read it so you know what is going on, but you don't
have to change it
def draw_2D_function(ax, x1_mesh, x2_mesh, y):
    pos = ax.contourf(x1_mesh, x2_mesh, y, levels=256 ,cmap = 'hot', vmin=-
10,vmax=10.0)
    ax.set_xlabel('x1');ax.set_ylabel('x2')
    levels = np.arange(-10,10,1.0)
    ax.contour(x1_mesh, x2_mesh, y, levels, cmap='winter')

# Plot the shallow neural network. We'll assume input in is range [0,10],[0,10]
and output [-10,10]
def plot_neural_2_inputs(x1,x2, y, pre_1, pre_2, pre_3, act_1, act_2, act_3,
w_act_1, w_act_2, w_act_3):

    fig, ax = plt.subplots(3,3)
    fig.set_size_inches(8.5, 8.5)
    fig.tight_layout(pad=3.0)
    draw_2D_function(ax[0,0], x1,x2,pre_1); ax[0,0].set_title('Preactivation')
    draw_2D_function(ax[0,1], x1,x2,pre_2); ax[0,1].set_title('Preactivation')
    draw_2D_function(ax[0,2], x1,x2,pre_3); ax[0,2].set_title('Preactivation')

    draw_2D_function(ax[1,0], x1,x2,act_1); ax[1,0].set_title('Activation')
    draw_2D_function(ax[1,1], x1,x2,act_2); ax[1,1].set_title('Activation')
    draw_2D_function(ax[1,2], x1,x2,act_3); ax[1,2].set_title('Activation')
    draw_2D_function(ax[2,0], x1,x2,w_act_1); ax[2,0].set_title('Weighted Act')
    draw_2D_function(ax[2,1], x1,x2,w_act_2); ax[2,1].set_title('Weighted Act')
    draw_2D_function(ax[2,2], x1,x2,w_act_3); ax[2,2].set_title('Weighted Act')
    plt.show()

fig, ax = plt.subplots()

```

```

draw_2D_function(ax,x1,x2,y)
ax.set_title('Network output, $y$')
ax.set_aspect(1.0)
plt.show()

```

```

# Define a shallow neural network with, two input, one output, and three hidden
units - Points: 12
def shallow_2_1_3(x1,x2, activation_fn, phi_0,phi_1,phi_2,phi_3, theta_10,
theta_11,\
                    theta_12, theta_20, theta_21, theta_22, theta_30, theta_31,
theta_32):
    # TODO Replace the lines below to compute the three initial linear functions
    # (figure a-c) from the theta parameters. These are the preactivations
    pre_1 = theta_10 + theta_11*x1 + theta_12*x2
    pre_2 = theta_20 + theta_21*x1 + theta_22*x2
    pre_3 = theta_30 + theta_31*x1 + theta_32*x2

    # Pass these through the ReLU function to compute the activations as in figure
d-f
    act_1 = activation_fn(pre_1)
    act_2 = activation_fn(pre_2)
    act_3 = activation_fn(pre_3)

    # TODO Replace the code below to weight the activations using phi1, phi2 and
phi3
    # To create the equivalent of figure g-i
    w_act_1 = phi_1*act_1
    w_act_2 = phi_2*act_2
    w_act_3 = phi_3*act_3

    # TODO Replace the code below to combining the weighted activations and add
    # phi_0 to create the output as in j
    y = phi_0 + w_act_1 + w_act_2 + w_act_3

    # Return everything we have calculated
    return y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3

```

```

# Now lets define some parameters and run the neural network
theta_10 = -4.0 ; theta_11 = 0.9; theta_12 = 0.0

```

```

theta_20 = 5.0 ; theta_21 = -0.9 ; theta_22 = -0.5
theta_30 = -7 ; theta_31 = 0.5; theta_32 = 0.9
phi_0 = 0.0; phi_1 = -2.0; phi_2 = 2.0; phi_3 = 1.5

x1 = np.arange(0.0, 10.0, 0.1)
x2 = np.arange(0.0, 10.0, 0.1)
x1,x2 = np.meshgrid(x1 ,x2)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_2_1_3(x1,x2, ReLU, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11,
theta_12, theta_20, theta_21, theta_22, theta_30, theta_31, theta_32)
# And then plot it

plot_neural_2_inputs(x1,x2, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1,
w_act_2, w_act_3)

```

```

def plot_neural_2_inputs_2_outputs(x1,x2, y1, y2, pre_1, pre_2, pre_3, act_1,
act_2, act_3, w_act_11, w_act_12, w_act_13, w_act_21, w_act_22, w_act_23):

    # Plot intermediate plots if flag set
    fig, ax = plt.subplots(4,3)
    fig.set_size_inches(8.5, 8.5)
    fig.tight_layout(pad=3.0)
    draw_2D_function(ax[0,0], x1,x2,pre_1); ax[0,0].set_title('Preactivation')
    draw_2D_function(ax[0,1], x1,x2,pre_2); ax[0,1].set_title('Preactivation')
    draw_2D_function(ax[0,2], x1,x2,pre_3); ax[0,2].set_title('Preactivation')
    draw_2D_function(ax[1,0], x1,x2,act_1); ax[1,0].set_title('Activation')
    draw_2D_function(ax[1,1], x1,x2,act_2); ax[1,1].set_title('Activation')
    draw_2D_function(ax[1,2], x1,x2,act_3); ax[1,2].set_title('Activation')
    draw_2D_function(ax[2,0], x1,x2,w_act_11); ax[2,0].set_title('Weighted Act 1')
    draw_2D_function(ax[2,1], x1,x2,w_act_12); ax[2,1].set_title('Weighted Act 1')
    draw_2D_function(ax[2,2], x1,x2,w_act_13); ax[2,2].set_title('Weighted Act 1')
    draw_2D_function(ax[3,0], x1,x2,w_act_21); ax[3,0].set_title('Weighted Act 2')
    draw_2D_function(ax[3,1], x1,x2,w_act_22); ax[3,1].set_title('Weighted Act 2')
    draw_2D_function(ax[3,2], x1,x2,w_act_23); ax[3,2].set_title('Weighted Act 2')
    plt.show()

    fig, ax = plt.subplots()
    draw_2D_function(ax,x1,x2,y1)
    ax.set_title('Network output, $y_1$')
    ax.set_aspect(1.0)

```



```
plt.show()

fig, ax = plt.subplots()
draw_2D_function(ax,x1,x2,y2)
ax.set_title('Network output, $y_2$')
ax.set_aspect(1.0)
plt.show()
```

```
# Define a shallow neural network with, two inputs, two outputs, and three hidden
units - Points: 14
def shallow_2_2_3(x1,x2, activation_fn, phi_10,phi_11,phi_12,phi_13,
phi_20,phi_21,phi_22,phi_23, theta_10, theta_11,\
                theta_12, theta_20, theta_21, theta_22, theta_30, theta_31,
theta_32):

    # TODO -- write this function -- replace the dummy code below
    pre_1 = theta_10 + theta_11*x1 + theta_12*x2
    pre_2 = theta_20 + theta_21*x1 + theta_22*x2
    pre_3 = theta_30 + theta_31*x1 + theta_32*x2
    act_1 = activation_fn(pre_1)
    act_2 = activation_fn(pre_2)
    act_3 = activation_fn(pre_3)
    w_act_11 = phi_11*act_1
    w_act_12 = phi_12*act_2
    w_act_13 = phi_13*act_3
    w_act_21 = phi_21*act_1
    w_act_22 = phi_22*act_2
    w_act_23 = phi_23*act_3
    y1 = phi_10 + w_act_11 + w_act_12 + w_act_13
    y2 = phi_20 + w_act_21 + w_act_22 + w_act_23

    # Return everything we have calculated
    return y1,y2, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_11, w_act_12,
w_act_13, w_act_21, w_act_22, w_act_23
```

```
# Now lets define some parameters and run the neural network
theta_10 = -4.0 ; theta_11 = 0.9; theta_12 = 0.0
theta_20 = 5.0 ; theta_21 = -0.9 ; theta_22 = -0.5
```

```

theta_30 = -7 ; theta_31 = 0.5; theta_32 = 0.9
phi_10 = 0.0; phi_11 = -2.0; phi_12 = 2.0; phi_13 = 1.5
phi_20 = -2.0; phi_21 = -1.0; phi_22 = -2.0; phi_23 = 0.8

x1 = np.arange(0.0, 10.0, 0.1)
x2 = np.arange(0.0, 10.0, 0.1)
x1,x2 = np.meshgrid(x1,x2)

# We run the neural network for each of these input values
y1, y2, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_11, w_act_12, w_act_13,
w_act_21, w_act_22, w_act_23 = \
    shallow_2_2_3(x1,x2, ReLU, phi_10,phi_11,phi_12,phi_13,
phi_20,phi_21,phi_22,phi_23, theta_10, theta_11, theta_12, theta_20, theta_21,
theta_22, theta_30, theta_31, theta_32)
# And then plot it
plot_neural_2_inputs_2_outputs(x1,x2, y1, y2, pre_1, pre_2, pre_3, act_1, act_2,
act_3, w_act_11, w_act_12, w_act_13, w_act_21, w_act_22, w_act_23)

```

```

# Plot the shallow neural network. We'll assume input is in range [0,1] and
output [-1,1]
# If the plot_all flag is set to true, then we'll plot all the intermediate
stages as in activity 2 (also given in image above).
def plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=False, x_data=None, y_data=None):

    # Plot intermediate plots if flag set
    if plot_all:
        fig, ax = plt.subplots(3,3)
        fig.set_size_inches(8.5, 8.5)
        fig.tight_layout(pad=3.0)
        ax[0,0].plot(x,pre_1,'r-'); ax[0,0].set_ylabel('Preactivation')
        ax[0,1].plot(x,pre_2,'b-'); ax[0,1].set_ylabel('Preactivation')
        ax[0,2].plot(x,pre_3,'g-'); ax[0,2].set_ylabel('Preactivation')
        ax[1,0].plot(x,act_1,'r-'); ax[1,0].set_ylabel('Activation')
        ax[1,1].plot(x,act_2,'b-'); ax[1,1].set_ylabel('Activation')
        ax[1,2].plot(x,act_3,'g-'); ax[1,2].set_ylabel('Activation')
        ax[2,0].plot(x,w_act_1,'r-'); ax[2,0].set_ylabel('Weighted Act')
        ax[2,1].plot(x,w_act_2,'b-'); ax[2,1].set_ylabel('Weighted Act')
        ax[2,2].plot(x,w_act_3,'g-'); ax[2,2].set_ylabel('Weighted Act')

    for plot_y in range(3):

```

```

    for plot_x in range(3):
        ax[plot_y,plot_x].set_xlim([0,1]);ax[plot_x,plot_y].set_ylim([-1,1])
        ax[plot_y,plot_x].set_aspect(0.5)
        ax[2,plot_y].set_xlabel('Input, $x$');
    plt.show()

fig, ax = plt.subplots()
ax.plot(x,y)
ax.set_xlabel('Input, $x$'); ax.set_ylabel('Output, $y$')
ax.set_xlim([0,1]);ax.set_ylim([-1,1])
ax.set_aspect(0.5)
if x_data is not None:
    ax.plot(x_data, y_data, 'mo')
    for i in range(len(x_data)):
        ax.plot(x_data[i], y_data[i],)
plt.show()

```

```

# Now lets define some parameters and run the neural network
theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = -0.3; phi_1 = 2.0; phi_2 = -1.0; phi_3 = 7.0

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, ReLU, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11, theta_20,
theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```

```

# Define the sigmoid function - Points: 10
def sigmoid(activation):
    # TODO write code to implement the sigmoid function and compute the activation
    at the
    # hidden unit from the preactivation. Use the np.exp() function.
    return 1/(1+np.exp(-10*activation))

```

```

# Make an array of inputs
z = np.arange(-1,1,0.01)
sig_z = sigmoid(z)

# Plot the sigmoid function
fig, ax = plt.subplots()
ax.plot(z,sig_z,'r-')
ax.set_xlim([-1,1]);ax.set_ylim([0,1])
ax.set_xlabel('z'); ax.set_ylabel('sig[z]')
plt.show()

```

```

theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = 0.3; phi_1 = 0.5; phi_2 = -1.0; phi_3 = 0.9

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, sigmoid, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11,
theta_20, theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```

```

# Define the heaviside function - Points: 10
def heaviside(preactivation):
    # TODO write code to implement the heaviside function and compute the
    activation at the
    # hidden unit from the preactivation.
    return np.where(preactivation>=0,1,0)

```

```

# Make an array of inputs
z = np.arange(-1,1,0.01)
heav_z = heaviside(z)

```

```

# Plot the heaviside function
fig, ax = plt.subplots()
ax.plot(z, heav_z, 'r-')
ax.set_xlim([-1,1]); ax.set_ylim([-2,2])
ax.set_xlabel('z'); ax.set_ylabel('heaviside[z]')
plt.show()

```

```

theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = 0.3; phi_1 = 0.5; phi_2 = -1.0; phi_3 = 0.9

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, heaviside, phi_0, phi_1, phi_2, phi_3, theta_10, theta_11,
theta_20, theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```

```

# Define the linear activation function
def lin(preactivation):
    a = 0.5
    b = -.4
    # Compute linear function
    activation = a+b * preactivation
    # Return
    return activation

```

```

# TODO - Points: 2
# 1. The linear activation function above just returns the input:  $(0+1*z) = z$ 

```

```

# Before running the code Make a prediction about what the ten panels of the
drawing will look like
# Now run the code below to see if you were right. What family of functions can
this represent?

# Answer: Since the z remains unchanged after activation, the activation function
essentially has no effect on the model

# 2. What happens if you change the parameters (a,b) to different values?
# Try a=0.5, b=-0.4 Don't forget to run the cell again to update the function

# Answer: When the values of a and b are change the preactivation and activation
lines are essentially completely different lines

theta_10 = 0.3 ; theta_11 = -1.0
theta_20 = -1.0 ; theta_21 = 2.0
theta_30 = -0.5 ; theta_31 = 0.65
phi_0 = 0.3; phi_1 = 0.5; phi_2 = -1.0; phi_3 = 0.9

# Define a range of input values
x = np.arange(0,1,0.01)

# We run the neural network for each of these input values
y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2, w_act_3 = \
    shallow_1_1_3(x, lin, phi_0,phi_1,phi_2,phi_3, theta_10, theta_11, theta_20,
theta_21, theta_30, theta_31)
# And then plot it
plot_neural(x, y, pre_1, pre_2, pre_3, act_1, act_2, act_3, w_act_1, w_act_2,
w_act_3, plot_all=True)

```