

Operating System (OS)

CS232

Memory Virtualization

Dr. Muhammad Mobeen Movania

Outlines

- Memory Abstraction using Address Spaces
- Historical Perspectives
 - Early systems
 - Multiprogramming and Time Sharing
- Address Space
- Memory Abstraction Goals
- Summary

Memory Abstraction using Address Space

- Key Idea
 - Provide memory to a process through an abstraction of address space
- Why
 - It makes access to memory easier
 - A diverse range of memory hardware may be easily supported

Early Systems

- OS was a bunch of libraries
- Only a single user program ran
- Not much abstraction needed because of the simple architecture




Figure 13.1: **Operating Systems: The Early Days**

Multiprogramming and Time Sharing

- Machines were expensive.
- Efficient use demanded sharing
 - b/w processes
 - b/w users
- With many users interactivity became important
- With time sharing, it is important to provide memory protection
 - ensures that a process cannot in anyway access some other process's memory




Figure 13.2: Three Processes: Sharing Memory

Address Space

- It's an abstraction
 - a running program's view of memory
- The program thinks it's loaded at address 0
- Example of process A (Fig. 13.2), it's loaded at address 320KB




Figure 13.3: An Example Address Space

Memory Abstraction Goals



Transparency



Protection



Efficiency

Pointers store virtual addresses

- All addresses in a program are virtual addresses

```
#include <stdio.h>
#include <stdlib.h>

int g_i=10;

int main(int argc, char** argv)
{
    printf("Location of code segment: %p\n", (void*)main);
    printf("Location of data segment: %p\n", (void*)&g_i);
    printf("Location of          heap: %p\n", (void*)malloc(1));
    int x = 3;
    printf("Location of          stack: %p\n", (void*)&x);

    return 0;
}
```


Pointers store virtual addresses

- Program output on my laptop

```
Location of code segment: 0x7f5130b7e189  
Location of data segment: 0x7f5130b81010  
Location of      heap: 0x7fffd4f12b0  
Location of      stack: 0x7fffe704fa34
```

} All of these are virtual addresses

Summary

- We introduced what memory abstraction means
- We talked about how OS uses the concept of address space
- We detailed the goals of memory virtualization which include
 - Transparency
 - Efficiency
 - Isolation
- All address in a user program are virtual addresses