

Computer Networks

CS3001

(Section BDS-7A)


Lecture 10 (ONLINE)

Instructor: Dr. Syed Mohammad Irteza

Assistant Professor, Department of Computer Science

22 September, 2023 (Rescheduled, Friday)

DNS: a distributed, hierarchical database




Client wants IP address for www.amazon.com; 1st approximation:

- client queries root server to find .com DNS server
- client queries .com DNS server to get amazon.com DNS server
- client queries amazon.com DNS server to get IP address for www.amazon.com

DNS: root name servers


- official, contact-of-last-resort by name servers that can not resolve name



DNS: root name servers

- official, contact-of-last-resort by name servers that can not resolve name
- *incredibly important* Internet function
 - Internet couldn't function without it!
 - DNSSEC – provides security (authentication, message integrity)
- ICANN (Internet Corporation for Assigned Names and Numbers) manages root DNS domain


13 logical root name “servers”
worldwide each “server” replicated
many times (~200 servers in US)



Top-Level Domain, and authoritative servers

Top-Level Domain (TLD) servers:

- responsible for .com, .org, .net, .edu, .aero, .jobs, .museums, and all top-level country domains, e.g.: .cn, .uk, .fr, .ca, .jp
- Network Solutions: authoritative registry for .com, .net TLD
- Educause: .edu TLD



authoritative DNS servers:

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider

Local DNS name servers


- when host makes DNS query, it is sent to its *local* DNS server
 - Local DNS server returns reply, answering:
 - from its local cache of recent name-to-address translation pairs (possibly out of date!)
 - forwarding request into DNS hierarchy for resolution
 - each ISP has local DNS name server; to find yours:
 - MacOS: `% scutil --dns`
 - Windows: `>ipconfig /all`
- local DNS server doesn't strictly belong to hierarchy

DNS name resolution: iterated query

Example: host at `engineering.nyu.edu`
wants IP address for `gaia.cs.umass.edu`

Iterated query:

- contacted server replies with name of server to contact
- “I don’t know this name, but ask this server”




DNS name resolution: recursive query

Example: host at `engineering.nyu.edu`
wants IP address for `gaia.cs.umass.edu`

Recursive query:

- puts burden of name resolution on contacted name server
- heavy load at upper levels of hierarchy?



Caching DNS Information

- once (any) name server learns mapping, it *caches* mapping, and *immediately* returns a cached mapping in response to a query
 - caching improves response time
 - cache entries timeout (disappear) after some time (TTL)
 - TLD servers typically cached in local name servers
- cached entries may be *out-of-date*
 - if named host changes IP address, may not be known Internet-wide until all TTLs expire!
 - *best-effort name-to-address translation!*

DNS records

DNS: distributed database storing resource records (RR)

RR format: (name, value, type, ttl)

type=A

- name is hostname
- value is IP address

type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME

- name is alias name for some “canonical” (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

type=MX


- value is name of SMTP mail server associated with name

DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:

message header:

- **identification**: 16 bit # for query, reply to query uses same #
- **flags**:
 - query or reply
 - recursion desired
 - recursion available
 - reply is authoritative



DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:

← 2 bytes → ← 2 bytes →

identification	flags
# questions	# answer RRs
# authority RRs	# additional RRs
questions (variable # of questions)	
answers (variable # of RRs)	
authority (variable # of RRs)	
additional info (variable # of RRs)	

name, type fields for a query

RRs in response to query

records for authoritative servers

additional “helpful” info that may
be used

Getting your info into the DNS

example: new startup “Network Utopia”

- register name networkutopia.com at *DNS registrar* (e.g., Network Solutions)
 - provide names, IP addresses of authoritative name server (primary and secondary)
 - registrar inserts NS, A RRs into .com TLD server:
`(networkutopia.com, dns1.networkutopia.com, NS)`
`(dns1.networkutopia.com, 212.212.212.1, A)`
- create authoritative server locally with IP address `212.212.212.1`
 - type A record for `www.networkutopia.com`
 - type MX record for `networkutopia.com`

DNS security

DDoS attacks

- bombard root servers with traffic
 - not successful to date
 - traffic filtering
 - local DNS servers cache IPs of TLD servers, allowing root server bypass
- bombard TLD servers
 - potentially more dangerous

Spoofing attacks

- intercept DNS queries, returning bogus replies
 - DNS cache poisoning
 - RFC 4033: DNSSEC authentication services