

Logistic Regression

Classification

Classification

Email: Spam / Not Spam?


Online Transactions: Fraudulent (Yes / No)?

Tumor: Malignant / Benign ?

$$y \in \{0, 1\}$$

0: “Negative Class” (e.g., benign tumor)

1: “Positive Class” (e.g., malignant tumor)



Threshold classifier output $h_{\theta}(x)$ at 0.5:

If $h_{\theta}(x) \geq 0.5$, predict "y = 1"

If $h_{\theta}(x) < 0.5$, predict "y = 0"

Classification: $y = 0$ or 1

$h_{\theta}(x)$ can be > 1 or < 0

Logistic Regression: $0 \leq h_{\theta}(x) \leq 1$

Logistic Regression

Hypothesis Representation


(How the function will look like?)

Logistic Regression Model

Want $0 \leq h_{\theta}(x) \leq 1$

$$h_{\theta}(x) = \theta^T x$$

Sigmoid function
Logistic function



Interpretation of Hypothesis Output

$h_{\theta}(x)$ = estimated probability that $y = 1$ on input x

Example: If $x = \begin{bmatrix} x_0 \\ x_1 \end{bmatrix} = \begin{bmatrix} 1 \\ \text{tumorSize} \end{bmatrix}$

$$h_{\theta}(x) = 0.7$$

Tell patient that 70% chance of tumor being malignant

“probability that $y = 1$, given x ,
parameterized by θ ”

$$P(y = 0|x; \theta) + P(y = 1|x; \theta) = 1$$

$$P(y = 0|x; \theta) = 1 - P(y = 1|x; \theta)$$

Logistic Regression


Decision Boundary

(Talking about the decision boundary will give us a better sense of what the logistic regression hypothesis function is computing.)

Logistic regression

$$h_{\theta}(x) = g(\theta^T x)$$

$$g(z) = \frac{1}{1+e^{-z}}$$




Suppose predict “ $y = 1$ ” if $h_{\theta}(x) \geq 0.5$

predict “ $y = 0$ ” if $h_{\theta}(x) < 0.5$

Let's use this to better understand how the hypothesis of logistic regression makes those predictions.


Decision Boundary



$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2)$$


Predict “ $y = 1$ ” if $-3 + x_1 + x_2 \geq 0$

Non-linear decision boundaries



$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1^2 + \theta_4 x_2^2)$$

Predict “ $y = 1$ ” if $-1 + x_1^2 + x_2^2 \geq 0$



$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1^2 + \theta_4 x_1^2 x_2 + \theta_5 x_1^2 x_2^2 + \theta_6 x_1^3 x_2 + \dots)$$

So with these visualizations, I hope that gives you a what's the range of hypothesis functions we can represent using the representation that we have

Now that we know what $h(x)$ can represent.

Next: see how to automatically choose the parameters θ .

So that given a training set we can automatically fit the parameters to our data.

Logistic Regression

Cost Function

Training set: $\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})\}$

m examples $x \in \begin{bmatrix} x_0 \\ x_1 \\ \dots \\ x_n \end{bmatrix} \quad x_0 = 1, y \in \{0, 1\}$



$$h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$

How to choose parameters θ ?

Cost function


Linear regression: $J(\theta) = \frac{1}{m} \sum_{i=1}^m \frac{1}{2} (h_{\theta}(x^{(i)}) - y^{(i)})^2$

$$\text{Cost}(h_{\theta}(x^{(i)}), y^{(i)}) = \frac{1}{2} (h_{\theta}(x^{(i)}) - y^{(i)})^2$$



Logistic regression cost function

$$\text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$



Cost = 0 if $y = 1, h_{\theta}(x) = 1$

But as $h_{\theta}(x) \rightarrow 0$


$\text{Cost} \rightarrow \infty$

Captures intuition that if $h_{\theta}(x) = 0$,
(predict $P(y = 1|x; \theta) = 0$), but $y = 1$,
we'll penalize learning algorithm by a very
large cost.

Logistic regression cost function

$$\text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$

If $y = 0$



Logistic Regression

Cost Function and Gradient Descent

Logistic regression cost function

$$J(\theta) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(h_{\theta}(x^{(i)}), y^{(i)})$$

$$\text{Cost}(h_{\theta}(x), y) = \begin{cases} -\log(h_{\theta}(x)) & \text{if } y = 1 \\ -\log(1 - h_{\theta}(x)) & \text{if } y = 0 \end{cases}$$

Note: $y = 0$ or 1 always

Logistic regression cost function

$$J(\theta) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(h_{\theta}(x^{(i)}), y^{(i)})$$


To fit parameters θ :

$$\min_{\theta} J(\theta)$$

To make a prediction given new x :

$$\text{Output } h_{\theta}(x) = \frac{1}{1 + e^{-\theta^T x}}$$

Gradient Descent

Want $\min_{\theta} J(\theta)$:

Repeat {

$$\theta_j := \theta_j - \alpha \frac{\partial}{\partial \theta_j} J(\theta)$$

}

(simultaneously update all θ_j)

Gradient Descent

Want $\min_{\theta} J(\theta)$:

Repeat {

$$\theta_j := \theta_j - \alpha \frac{1}{m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) x_j^{(i)}$$

} (simultaneously update all θ_j)

Algorithm looks identical to linear regression!

Logistic Regression

Multi-class Classification

One-vs-All


Multiclass classification

Email foldering/tagging: Work, Friends, Family, Hobby


Medical diagrams: Not ill, Cold, Flu

Weather: Sunny, Cloudy, Rain, Snow


Binary classification:





Multi-class classification:



One-vs-all (one-vs-rest):






Class 1: 

Class 2: 

Class 3: 

$$h_{\theta}^{(i)}(x) = P(y = i|x; \theta) \quad (i = 1, 2, 3)$$



One-vs-all

Train a logistic regression classifier $h_{\theta}^{(i)}(x)$ for each class i to predict the probability that $y = i$.

On a new input x , to make a prediction, pick the class i that maximizes

$$\max_i h_{\theta}^{(i)}(x)$$