

Introduction to Programming

Lecture 11:

struct & typedef & enum



What We Will Learn

- Introduction
- **struct** definition
- Using **struct**
 - **struct** & Array
 - **struct** & Pointers
 - **struct** & Functions
- **enum**



What We Will Learn

- Introduction
- `struct` definition
- Using `struct`
 - `struct` & Array
 - `struct` & Pointers
 - `struct` & Functions
- `enum`



Introduction

- Our variables until now

- Single variable

- ```
int i, char c, float f
```

- Set of **same type** elements: Array

- ```
int a[10], char c[20]
```

- If data are not same type, but related? Example:
Information about students

- Student Name
 - Student Family Name
 - Student Number
 - Student Grade



Introduction

➤ How to save the student information?

➤ 1- Use separated variables

➤ `char st_name[20];`

➤ `char st_fam_name[20];`

➤ `int id;`

➤ `int grade;`

➤ 2- Put them altogether, they are related

➤ Use **struct**



What We Will Learn

- Introduction
- **struct** definition
- Using struct
 - struct & Array
 - struct & Pointers
 - struct & Functions
- enum



struct: version 1

- Set of related variables
 - Each variable in **struct** has its own type
- **struct** in C (version 1)

```
struct {  
    <variable declaration>  
} <identifier list>;
```



struct (version 1): Example

```
struct{  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
} st1;
```

- We declare a variable `st1`
- Type of `st1` is `struct`
- `id` is a **member** of the struct
- `grade` is a **member** of the struct



struct (version 1): Example

```
struct{  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
} st1, st2, st3;
```

- We declare three variables: `st1`, `st2`, `st3`
- Type of `st1`, `st2`, `st3` is the struct
- In this model, we cannot reuse the struct definition in other location (e.g., input of function)



struct: Version 2

➤ struct in C (version 2)

```
struct <tag> {  
    <variable declaration>  
};
```

```
struct <tag> <identifiers>;
```



struct (version 2): Example

```
struct std_info{  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
};
```

```
struct std_info st1, st2, st3;
```

- We define a struct with tag `std_info`
 - We don't allocate memory, it is just definition
- We declare variables `st1, st2, st3` from `std_info`



typedef

- We can assign a new name for each type
 - Assign name “integer” to “int”
 - Assign name “int_array” to “int[100]”
 - Assign name “int_pointer” to “int *”
- New names are assigned by **typedef**
- After we assigned the new name, we can use it in identifier declaration



typedef: Examples

```
/* Assign new name integer to type int */  
typedef int integer;
```

```
/* Use the new name */  
integer i, j, k;
```

```
/* Assign new name alephba to type char */  
typedef char alephba;
```

```
/* Use the new name */  
alephba c1, c2;
```



typedef: Examples

```
/* Assign new name intptr to type int * */
```

```
typedef int * intptr;
```

```
/* Use the new name */
```

```
intptr pi, pj, pk;
```

```
typedef int int_arr1[10], int_arr2[20];
```

```
int_arr1 array1;
```

```
int_arr2 array2;
```



struct: Version 3.1

- struct in C (version 3.1)
- Using the typedef

```
struct <tag>{  
    <variables>  
};
```

```
typedef struct <tag> <new_name>;
```

```
<new_name> <variables>;
```



struct (Version 3.1): Examples

```
struct std_info{  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
};
```

```
typedef struct std_info information;  
  
information st1, st2;
```



struct: Version 3.2

- struct in C (version 3.2)
- Using the typedef

```
typedef struct {  
    <variables>  
} <new_name>;
```

```
<new_name> <variables>;
```



struct (Version 3.2): Examples

```
typedef struct {  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
}  
information;  
  
information st1, st2;
```



Structures as New Data Type

- When we define a new **struct**, in fact we are define a new data type
 - Then we use the new data type and define variables
- So, we need to learn how to work it
 - Access to members
 - Operators for **struct**
 - Array of **struct**
 - **struct** in functions
 - Pointer to **struct**



What We Will Learn

- Introduction
- `struct` definition
- Using **`struct`**
 - **`struct`** & Array
 - **`struct`** & Pointers
 - **`struct`** & Functions
- `enum`



Size of struct

- The size of a struct = sum of the size of members

```
struct std_info{  
    char st_name[20];  
    char st_fam_name[20];  
    int id;  
    int grade;  
};  
  
struct std_info st1, st2, st3;  
  
sizeof(struct std_info) → 48  
sizeof(st1) → 48
```



Using struct

- We should declare variables from struct type
 - Versions 1, 2, 3.1, 3.2
- How to access to the members of struct
 - `<struct variable>.<element name>`
 - `st1.st_name` is a array of char in struct st1
 - `st2.grade` is a int variable in struct st2



struct initialization

- Similar to array initialization

```
information st1 = {"Ali", "Karimi", 9222, 10};
```

- “Ali” is assigned to st_name
- “Karimi” is assigned to st_fam_name
- 9222 is assigned to id
- 10 is assigned to grade
- Order of values should be exactly the order of the members
- The number of values must be \leq the number of members
- Initial values cannot be assigned in struct definition



```
#include <stdio.h>
```

```
typedef struct{
```

```
    char name[20];
```

```
    char fam_name[20];
```

```
    int id;
```

```
    int grade;
```

```
} information;
```

```
void main(void) {
```

```
    information st2, st1 = {"Ali", "Hassani",  
    90131, 20};
```

```
    printf("After init: \n");
```

مثالی ساده برای نحوه
استفاده از struct


```
printf("Name = %s, \nFam. Name = %s, \nid =  
%d, \ngrade = %d\n", st1.name, st1.fam_name,  
st1.id, st1.grade);
```

```
scanf("%s", st2.name);
```

```
scanf("%s", st2.fam_name);
```

```
scanf("%d", &st2.id);
```

```
scanf("%d", &st2.grade);
```

```
printf("Your Input is: \n");
```

```
printf("Name = %s, \nFam. Name = %s, \nid =  
%d, \ngrade = %d\n",
```

```
st2.name, st2.fam_name, st2.id, st2.grade);
```

```
}
```

Nested struct

```
struct date_type{
    int rooz, mah, sal;
};

typedef struct{
    char name[20];
    char fam_name[20];
    int id;
    int grade;
    struct date_type date;
} information;
```



Nested struct

```
information st1 = {"A", "B", 1, 10, {2, 3, 1368}};
```

```
information st2;
```

```
st2.name = "C";
```

```
st2.fam_name = "D";
```

```
st2.id = 2;
```

```
st2.grade = 15;
```

```
st2.date.rooz = 10;
```

```
st2.date.mah = 5;
```

```
st2.date.sal = 1390;
```



struct: Copy and Assignment

```
struct date_type{
    int rooz, mah, sal;
};

struct date_type d1, d2 = {2, 1, 1360};

d1 = d2;

/* d1.rooz = d2.rooz;
   d1.mah = d2.mah;
   d1.sal = d2.sal;
*/
```



struct: Copy and Assignment

```
struct test_type{  
    char name[10];  
    int id[10];  
};
```

```
struct test_type d1, d2 = {"ABC", {1, 2,  
3}};
```

```
d1 = d2;
```

```
/* d1.name = "ABC";  
   d1.id   = {1, 2, 3};  
*/
```



struct: Comparing

➤ We **cannot** compare **struct** variables

➤ `==`, `<=`, `<`, `>`, `>=` cannot be used for struct

```
information st1, st2;
```

```
if(st1 <= st2) {    // Compile Error
```

```
    . . .
```

```
}
```

➤ Why?

➤ What does this mean? `st1 <= st2`



struct: Comparing

- We can compare members of structs

```
if((st1.id == st2.id) && (strcmp(st1.name,st2.name) ==  
    0) &&  
    (strcmp(st2.fam_name,st2.fam_name) == 0)) {  
    /* st1 == st2 */  
}
```

- We can **define** <, <=, >, >= for struct

```
if((st1.id > st2.id) && (strcmp(st1.name,st2.name) == 0)  
    &&  
    (strcmp(st2.fam_name,st2.fam_name) == 0)) {  
    /* st1 > st2 */  
}
```



What We Will Learn

- Introduction
- `struct` definition
- Using `struct`
 - **`struct` & Array**
 - `struct` & Pointers
 - `struct` & Functions
- `enum`



Array of struct: Definition

➤ struct is a type → We can define array of struct

```
struct std1{  
    int id;  
    int grad;  
};  
struct std1 std_arr[20];
```

```
typedef struct{  
    int id;  
    int grad;  
} std2;  
std2 std_arr[20];
```



```
#include <stdio.h>
```

```
int main(void) {
```

```
    struct std{
```

```
        int id;
```

```
        int grade;
```

```
    };
```

```
    const int num = 25;
```

```
    double sum, average;
```

```
    int i;
```

```
    struct std std_arr[num];
```

```
    for(i = 0; i < num; i++){
```

```
        printf("Enter ID and grade\n");
```

```
        scanf("%d", &(std_arr[i].id));
```

```
        scanf("%d", &(std_arr[i].grade));
```

```
    }
```

برنامه‌ای که شماره و نمره دانشجویان را بگیرد و لیست دانشجویانی که نمره آنها بیشتر از میانگین است را تولید کند.

```
sum = 0;
for(i = 0; i < num; i++)
    sum += std_arr[i].grade;

average = sum / num;

for(i = 0; i < num; i++)
    if(std_arr[i].grade >= average)
        printf("Student %d passed \n",
               std_arr[i].id);

return 0;
}
```

```
#include <stdio.h>
```

```
int main(void) {
```

```
    struct std{
```

```
        char name[20];
```

```
        int id;
```

```
        int grade;
```

```
    };
```

```
    const int num = 25;
```

```
    struct std std_arr[num];
```

```
    int sid, i;
```

```
    for(i = 0; i < num; i++){
```

```
        printf("Enter Name, ID and grade\n");
```

```
        scanf("%s", std_arr[i].name);
```

```
        scanf("%d", &(std_arr[i].id));
```

```
        scanf("%d", &(std_arr[i].grade));
```

```
    }
```

برنامه‌ای که یک لیست از دانشجویان را بگیرد.
سپس یک شماره دانشجویی بگیرد و اگر دانشجو
در لیست است اطلاعات وی را نشان دهد.

```
printf("Enter Search ID: ");
```

```
scanf("%d", &sid);
```

```
for(i = 0; i < num; i++)
```

```
    if(std_arr[i].id == sid) {
```

```
        printf("Found:\n");
```

```
        printf("Name = %s\n", std_arr[i].name);
```

```
        printf("ID = %d\n", std_arr[i].id);
```

```
        printf("Grade = %s\n", std_arr[i].grade);
```

```
    }
```

```
return 0;
```

```
}
```

What We Will Learn

- Introduction
- `struct` definition
- Using `struct`
 - `struct` & Array
 - **`struct` & Pointers**
 - `struct` & Functions
- `enum`



Pointer to struct: Definition

- A variable of struct type is a **variable**
- It has **address**, we can have **pointer** to it

```
struct std{  
    int id;  
    int grade;  
};  
  
struct std st1;  
struct std *ps;  
  
ps = &st1;
```



Pointer to `struct`: Usage (Version 1)

- We can use `*pointer` method
- `*ps` means the content of the address that `ps` refers to there → it is struct
- `(*ps) . id` is the member of struct that `ps` refers to it
- `(*ps) . grade` is the member of struct that `ps` refers to it



Pointer to struct: Usage (Version 2)

➤ We can use “->” method

```
struct std{  
    int id;  
    int grade;  
};
```

```
struct std st1, *ps;  
ps = &st1  
int y = ps->id;      // (*ps).id  
int z = ps->grade;   // (*ps).grade
```



What We Will Learn

- Introduction
- `struct` definition
- Using `struct`
 - `struct` & Array
 - `struct` & Pointers
 - **`struct` & Functions**
- `enum`



struct & Functions

- **struct** is a type → It can be used
 - In **input** parameter list of functions
 - Call by **value**
 - Call by **reference**
 - In **return type** of functions

`void f(struct std s1);` // call by value input

`void g(struct std *s2);` // call by reference

`struct std h(void);` // return type



struct & Functions: Example

➤ struct as call by value input parameter

```
void print_st_info(information st) {  
    printf("Name = %s\n", st.name);  
    printf("Fam = %s\n", st.fam_name);  
    printf("id = %d\n", st.id);  
    printf("grade = %d\n", st.grade);  
}  
  
//----- Calling the function -----  
information st1;  
print_st_info(st1);
```



struct & Functions: Example

- struct as call by reference input parameter

```
void read_st_info(information *pst) {  
    scanf("%s", pst->name);  
    scanf("%s", pst->fam_name);  
    scanf("%d", &(pst->id));  
    scanf("%d", &(pst->grade));  
}  
  
//----- Calling the function -----  
  
information st1;  
read_st_info(&st1);
```



struct & Functions: Example

➤ struct as output of function

```
information create_st_info(void) {  
    information tmp;  
    scanf("%s", tmp.name);  
    scanf("%s", tmp.fam_name);  
    scanf("%d", &tmp.id);  
    scanf("%d", &tmp.grade);  
    return tmp;  
}  
  
//----- Calling the function -----  
information st1;  
st1 = create_st_info();
```



Scope of struct definition

- A struct can be used only
 - In the defined scope
 - After definition
- → if struct is defined in a function
 - It can be used only in the function
 - No other function knows about it
- → If struct is defined as a global
 - It can be used in all function after the definition



Scope of struct variables

- The scope of struct **variables** are the same other variables
- If struct variable is global
 - Initialized to zero and visible to the functions after its declaration
- If struct variable is automatic local
 - There is not any initial value, destroyed when the block finishes
- If struct variable is static
 - Kept in memory until program finishes




```
struct guia{  
    int sorat, makhraj;  
};
```

تابعی که دو عدد گویا را می‌گیرد و حاصل
جمع و تفریق آنها را تولید می‌کند.

```
void f(struct guia a, struct guia b, struct guia *  
    tafrigh, struct guia * jaam){  
    int mokhraj_moshtarak = a.makhraj * b.makhraj;  
  
    int min = a.sorat * b.makhraj - b.sorat * a.makhraj;  
    int sum = a.sorat * b.makhraj + b.sorat * a.makhraj;  
  
    tafrigh->sorat = min;  
    tafrigh->makhraj = mokhraj_moshtarak;  
  
    jaam->sorat = sum;  
    jaam->makhraj = mokhraj_moshtarak;  
}
```

```
#include <stdio.h>
```

```
struct time{
```

```
    int hour;
```

```
    int min;
```

```
    int sec;
```

```
};
```

```
/*  1:  t1 > t2, 0:  t1 = t2, -1: t1 < t2  */
```

```
int time_cmp(struct time t1, struct time t2){
```

```
    if(t1.hour > t2.hour)
```

```
        return 1;
```

```
    else if(t2.hour > t1.hour)
```

```
        return -1;
```

```
    else if(t1.min > t2.min)
```

```
        return 1;
```

```
    else if(t2.min > t1.min)
```

```
        return -1;
```

```
    else if(t1.sec > t2.sec)
```

```
        return 1;
```

```
    else if(t2.sec > t1.sec)
```

```
        return -1;
```

```
    else
```

```
        return 0;
```

```
}
```

برنامه‌ای یک مجموعه از زمان‌ها را بگیرد و آنها را مرتب کند. هر زمان شامل ساعت، دقیقه و ثانیه است.

```
void time_swap(struct time *t1, struct time *t2){
    struct time tmp;
    tmp = *t1;
    *t1 = *t2;
    *t2 = tmp;
}

/* Find index of max element */
int rec_max(struct time time_arr[], int start, int end){
    int tmp, res;
    if(start == end)
        res = start;
    else{
        tmp = rec_max(time_arr, start + 1, end);
        if(time_cmp(time_arr[start], time_arr[tmp]) >= 0)
            res = start;
        else
            res = tmp;
    }
    return res;
}
```

```

/* Recursively sort array from start to end */
void rec_sort(struct time time_arr[], int start, int end){
    int max;
    if(start == end)
        return;

    max = rec_max(time_arr, start, end);
    time_swap(&(time_arr[start]), &(time_arr[max]));
    rec_sort(time_arr, start + 1, end);
}

/* Print Array elements from start to end */
void print_array(struct time time_arr[], int start, int end){

    for(int i = start; i <= end; i++)
        printf("%d:%d:%d, ", time_arr[i].hour, time_arr[i].min,
            time_arr[i].sec);

    printf("\n");
}

```

```
int main(void){  
    struct time ta[5] = {{4, 0, 1},  
        {6, 1, 0}, {2, 2, 1},  
        {6, 4, 7}, {8, 5, 4}};  
  
    print_array(ta, 0, 4);  
    rec_sort(ta, 0, 4);  
    print_array(ta, 0, 4);  
  
    return 0;  
}
```

More Dynamic Data Structures

➤ In Arrays

- We know the size of array when you **develop code (coding time)**

➤ In Dynamic Memory Allocation

- We know the size of array when **program runs**

➤ What can we do, if we **don't know data size** even in run time?

- We use dynamic memory allocation & resize
 - Resizing array has cost & overhead

➤ What can we do, if we want to add/remove an element to/from middle of the array?

- We use dynamic memory allocation & resize
 - Resizing array has cost & overhead



Dynamic Data Structures: Linked List

- **linked list** data structure can be used to implement the dynamic structures
- linked list: Nodes that linked together
 - info: Save the information
 - next: Pointer to next node



linked list in C

- linked list is implemented by **struct** and **pointer to struct**
- Struct has a member to save the info
- Struct has a pointer to point the next node

```
struct node{  
    int info;  
    struct node *next;  
};
```



Create nodes

- We need a function to create each node in list. The function do
 - 1- Allocate the memory
 - 2- Set the info member
 - 3- Set the next member
 - 4- Return the pointer to new node



Create Node

```
struct node{
    int info;
    struct node *next;
};

struct node * create_node(int i) {
    struct node * nn;
    nn = (struct node *)
    malloc(sizeof(struct node));
    nn->info = i;
    nn->next = NULL;
    return nn;
}
```



Example: 3 Nodes List

```
struct node * list = NULL;  
  
list = create_node(10);  
  
list->next = create_node(20);  
  
list->next->next =  
    create_node(30);
```



Operation on linked list

- Print the list: `print_list`
- Add new node to end of list: `add_end`
- Add new node to front of list: `add_front`
- Insert new node after some node:
`insert_next_node`
- Delete the first node in list: `delete_first`
- Delete the end node in list: `delete_end`
- Delete a node from the middle of list: `delete_next`



add_end: Add new node to end of list

```
void add_end(struct node *list,
             struct node * new_node) {
    struct node *current;
    for(current = list; current->
next != NULL; current = current-
>next) ;
    current->next = new_node;
    new_node->next = NULL;
}
```



add_front: Add new node in start of list

```
void add_front(struct node **plist, struct
node *new_node) {

    new_node->next = *plist;

    *plist = new_node;

}

main() {

    struct node * list;

    ...

    add_front(&list, new_node1);
```



delete_end (if more than 2 nodes)

```
void delete_end(struct node *  
    list) {  
    struct node * current = list;  
    while (current->next->next !=  
        NULL)  
        current = current->next;  
    free(current->next) ;  
    current->next = NULL;  
}
```



```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node{  
    int value;  
    struct node *next;  
};
```

```
int in_list(struct node *list, int i){  
    struct node *current = list;  
    while(current != NULL){  
        if(current->value == i)  
            return 1;  
        current = current->next;  
    }  
    return 0;  
}
```

برنامه‌ای یک آرایه را بگیرد و با حذف
عضوهای تکراری آن، یک لیست پیوند
ایجاد کند.


```
void add_front(struct node *new_node, struct node **list){
    new_node->next = *list;
    *list = new_node;
}
```

```
void add_end(struct node *new_node, struct node *list){
    struct node *current;
    for(current = list; current-> next != NULL; current =
current->next);
    current->next = new_node;
    new_node->next = NULL;
}
```

```
void print_list(struct node *list){
    struct node * current = list;
    while(current != NULL){
        printf("%d ", current->value);
        current = current->next;
    }
}
```

```

struct node *create_set(int arr[], int size){
    int i;
    struct node *list = NULL;
    for(i = 0; i < size; i++){
        if(in_list(list, arr[i]) == 0){
            struct node *new_node = (struct node
*)malloc(sizeof(struct node));
            if(new_node == NULL){
                printf("Cannot create node\n");
                exit(-1);
            }
            new_node->value = arr[i]; new_node->next=NULL;
            if(list == NULL)
                add_front(new_node, &(list));
            else
                add_end(new_node, list);
        }
    }
    return list;
}

```

```
int main(void) {  
    int myarr[]={1,2,1,3,1,7,8,2,3,4,11,4,9,9,9,10};  
    struct node * mylist = create_set(myarr, sizeof(myarr) /  
sizeof(myarr[0]));  
    print_list(mylist);  
  
    getchar();  
    return 0;  
}
```

What We Will Learn

- Introduction
- `struct` definition
- Using `struct`
 - `struct` & Array
 - `struct` & Pointers
 - `struct` & Functions
- **enum**



Introduction

- Some data are naturally ordered
 - Days of week
 - Months of year
- We want to use the order, e.g.
 - The number of visitors per day
 - The salary per month
- We need an array
 - visitors[0] → The number of visitors in **Saturday**
 - visitors[1] → The number of visitors in **Sunday**



Introduction

- Enumeration is a mechanism to assign a name for each number
- We can use numbers instead of numbers
 - More readable code
- E.g.

visitors[saturday], visitors[friday]

salary[april], salary[june]



enum

- **enum** is used to define a set of names and their corresponding numbers

enum tag {name_1, name_2, ..., name_N}

- **tag** is the enumeration type

- We use it to define variables

- **name_1 = 0**

- **name_2 = 1**

- **name_i = (Name_(i-1)) + 1**
-



enum

```
enum week {sat, sun, mon, tue,  
           wed, thu, fri};
```

➤ **sat = 0, sun = 1, mon = 2, ..., fri = 6**

```
enum year {feb, jan, mar, apr,  
           may, jun, jul, aug, sep, oct,  
           nov, des};
```

➤ **feb = 0, jan = 1, ..., nov = 10, des = 11**



enum

- We can assign the numbers

```
enum week {sat = 1, sun, mon, tue,  
           wed, thu, fri};
```

- sat = 1, sun = 2, mon = 3, ..., fri = 7

```
enum condition {False = 0, True,  
               No = 0, Yes, Ghalat = 0, Dorost};
```

- False = No = Ghalat = 0

- True = Yes = Dorost = 1



enum

- After definition of an enumeration
- We can use the tag to declare variables
- We can use the names to assign values to the variables

```
enum week {sat, sun, mon, tue,  
           wed, thu, fri};
```

```
enum week day = sat;
```

```
for(day = sat; day <= fri; day++)
```



Example: Read the number of visitors

```
enum week {sat, sun, mon, tue,  
           wed, thu, fri};  
  
int visitors[7];  
  
enum week day;  
  
for(day = sat; day <= fri; day++)  
    scanf("%d", &visitors[day]);
```



Caution

- C compiler does **not** check the value is assigned to the **enum variables**

```
enum test1 {t1, t2, t3};
```

```
enum test2 {t4, t5, t6};
```

```
enum test1 t1v = t1;
```

```
enum test2 t2v = t4;
```

```
if(t1v == t2v) → true
```

```
t1v = t5;
```

```
t2v = 100;
```



Common Bugs

- The last “NULL” in Liked-list is very important
 - Always keep it
- Operation of linked-list has many exceptions
 - When list is empty
 - When we want to add to the first of list
 - ...
- Enumerations are just integer, they can be casted without, be careful



Reference

- **Reading Assignment:** Chapter 10 and Sections 12.1-12.4 of “C How to Program”



Homework

➤ homework

