deeplearning.ai

Neural Style Transfer

Style cost function

Meaning of the "style" of an image



Say you are using layer l's activation to measure "style."
Define style as correlation between activations across channels.



How correlated are the activations across different channels?

[Gatys et al., 2015. A neural algorithm of artistic style]

Intuition about style of an image

Style image



Correlated?

Uncorrelated



Generated Image



[Gatys et al., 2015. A neural algorithm of artistic style]

Style matrix

Let $a^{[l]}_{i,j,k}$ = activation at (i, j, k). $G^{[l]}$ is $n_c^{[l]} \times n_c^{[l]}$

H W C

n_c

$G^{[l]}_{kk'}$

$k = 1, \ldots, n_c$

$$G^{[l](S)}_{kk'} = \sum_{i=1}^{n_H^{[l]}} \sum_{j=1}^{n_W^{[l]}} a^{[l](S)}_{ijk} \, a^{[l](S)}_{ijk'}$$

$$G^{[l](G)}_{kk'} = \sum_{i=1}^{n_H^{[l]}} \sum_{j=1}^{n_W^{[l]}} a^{[l](G)}_{ijk} \, a^{[l](G)}_{ijk}$$

"Gram matrix"

$$J^{[l]}_{style}(S, G) = \frac{1}{(\ldots)} \left\| G^{[l](S)} - G^{[l](G)} \right\|_F^2$$

$$= \frac{1}{(2 n_H^{[l]} n_W^{[l]} n_c^{[l]})^2} \sum_k \sum_{k'} \left(G^{[l](S)}_{kk'} - G^{[l](G)}_{kk'} \right)^2$$

β

[Gatys et al., 2015. A neural algorithm of artistic style]

Style cost function

$$\left\| G^{[l](S)} - G^{[l](G)} \right\|_F^2$$

$$J_{style}^{[l]}(S,G) = \frac{1}{\left(2n_H^{[l]} n_W^{[l]} n_C^{[l]}\right)^2} \sum_k \sum_{k'} \left(G_{kk'}^{[l](S)} - G_{kk'}^{[l](G)}\right)$$

$$J_{style}(S,G) = \sum_l \lambda^{[l]} J_{style}^{[l]}(S,G)$$

$$J(G) = \alpha J_{content}(C,G) + \beta J_{style}(S,G)$$

G

[Gatys et al., 2015. A neural algorithm of artistic style]