

A. Guess a number!

time limit per test: 1 second
memory limit per test: 256 megabytes
input: standard input
output: standard output

A TV show called "Guess a number!" is gathering popularity. The whole Berland, the old and the young, are watching the show.

The rules are simple. The host thinks of an integer y and the participants guess it by asking questions to the host. There are four types of acceptable questions:

- Is it true that y is strictly larger than number x ?
- Is it true that y is strictly smaller than number x ?
- Is it true that y is larger than or equal to number x ?
- Is it true that y is smaller than or equal to number x ?

On each question the host answers truthfully, "yes" or "no".

Given the sequence of questions and answers, find any integer value of y that meets the criteria of all answers. If there isn't such value, print "Impossible".

Input

The first line of the input contains a single integer n ($1 \leq n \leq 10000$) — the number of questions (and answers). Next n lines each contain one question and one answer to it. The format of each line is like that: "*sign x answer*", where the *sign* n is:

- ">" (for the first type queries),
- "<" (for the second type queries),
- ">=" (for the third type queries),
- "<=" (for the fourth type queries).

All values of x are integer and meet the inequation $-10^9 \leq x \leq 10^9$. The *answer* is an English letter "Y" (for "yes") or "N" (for "no").

Consecutive elements in lines are separated by a single space.

Output

Print any of such integers y , that the answers to all the queries are correct. The printed number y must meet the inequation $-2 \cdot 10^9 \leq y \leq 2 \cdot 10^9$. If there are many answers, print any of them. If such value doesn't exist, print word "Impossible" (without the quotes).

Examples

input
4 >= 1 Y < 3 N <= -3 N > 55 N
output
17

input

2
> 100 Y
< -100 Y

output

Impossible