

A. Party

time limit per test: 3 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

A company has n employees numbered from 1 to n . Each employee either has no immediate manager or exactly one immediate manager, who is another employee with a different number. An employee A is said to be the superior of another employee B if at least one of the following is true:

- Employee A is the immediate manager of employee B
- Employee B has an immediate manager employee C such that employee A is the superior of employee C .

The company will not have a managerial cycle. That is, there will not exist an employee who is the superior of his/her own immediate manager.

Today the company is going to arrange a party. This involves dividing all n employees into several groups: every employee must belong to exactly one group. Furthermore, within any single group, there must not be two employees A and B such that A is the superior of B .

What is the minimum number of groups that must be formed?

Input

The first line contains integer n ($1 \leq n \leq 2000$) — the number of employees.

The next n lines contain the integers p_i ($1 \leq p_i \leq n$ or $p_i = -1$). Every p_i denotes the immediate manager for the i -th employee. If p_i is -1, that means that the i -th employee does not have an immediate manager.

It is guaranteed, that no employee will be the immediate manager of him/herself ($p_i \neq i$). Also, there will be no managerial cycles.

Output

Print a single integer denoting the minimum number of groups that will be formed in the party.

Examples

input
5 -1 1 2 1 -1
output
3

Note

For the first example, three groups are sufficient, for example:

- Employee 1
- Employees 2 and 4
- Employees 3 and 5