

C. Substitutes in Number

time limit per test: 1 second

memory limit per test: 256 megabytes

input: standard input

output: standard output

Andrew and Eugene are playing a game. Initially, Andrew has string s , consisting of digits. Eugene sends Andrew multiple queries of type " $d_i \rightarrow t_i$ ", that means "replace all digits d_i in string s with substrings equal to t_i ". For example, if $s = 123123$, then query " $2 \rightarrow 00$ " transforms s to 10031003 , and query " $3 \rightarrow$ " ("replace 3 by an empty string") transforms it to $s = 1212$. After all the queries Eugene asks Andrew to find the remainder after division of number with decimal representation equal to s by 1000000007 ($10^9 + 7$). When you represent s as a decimal number, please ignore the leading zeroes; also if s is an empty string, then it's assumed that the number equals to zero.

Andrew got tired of processing Eugene's requests manually and he asked you to write a program for that. Help him!

Input

The first line contains string s ($1 \leq |s| \leq 10^5$), consisting of digits — the string before processing all the requests.

The second line contains a single integer n ($0 \leq n \leq 10^5$) — the number of queries.

The next n lines contain the descriptions of the queries. The i -th query is described by string " $d_i \rightarrow t_i$ ", where d_i is exactly one digit (from 0 to 9), t_i is a string consisting of digits (t_i can be an empty string). The sum of lengths of t_i for all queries doesn't exceed 10^5 . The queries are written in the order in which they need to be performed.

Output

Print a single integer — remainder of division of the resulting number by 1000000007 ($10^9 + 7$).

Examples

input
123123 1 2->00
output
10031003

input
123123 1 3->
output
1212

input
222 2 2->0 0->7
output
777

input

10000000008 0
output
1

Note

Note that the leading zeroes are not removed from string s after the replacement (you can see it in the third sample).