

E. Blood Cousins Return

time limit per test: 3 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Polycarpus got hold of a family tree. The found tree describes the family relations of n people, numbered from 1 to n . Every person in this tree has at most one direct ancestor. Also, each person in the tree has a name, the names are not necessarily unique.

We call the man with a number a a 1-ancestor of the man with a number b , if the man with a number a is a direct ancestor of the man with a number b .

We call the man with a number a a k -ancestor ($k > 1$) of the man with a number b , if the man with a number b has a 1-ancestor, and the man with a number a is a $(k - 1)$ -ancestor of the 1-ancestor of the man with a number b .

In the tree the family ties do not form cycles. In other words there isn't a person who is his own direct or indirect ancestor (that is, who is an x -ancestor of himself, for some x , $x > 0$).

We call a man with a number a the k -son of the man with a number b , if the man with a number b is a k -ancestor of the man with a number a .

Polycarpus is very much interested in how many sons and which sons each person has. He took a piece of paper and wrote m pairs of numbers v_i, k_i . Help him to learn for each pair v_i, k_i the number of distinct names among all names of the k_i -sons of the man with number v_i .

Input

The first line of the input contains a single integer n ($1 \leq n \leq 10^5$) — the number of people in the tree. Next n lines contain the description of people in the tree. The i -th line contains space-separated string s_i and integer r_i ($0 \leq r_i \leq n$), where s_i is the name of the man with a number i , and r_i is either the number of the direct ancestor of the man with a number i or 0, if the man with a number i has no direct ancestor.

The next line contains a single integer m ($1 \leq m \leq 10^5$) — the number of Polycarpus's records. Next m lines contain space-separated pairs of integers. The i -th line contains integers v_i, k_i ($1 \leq v_i, k_i \leq n$).

It is guaranteed that the family relationships do not form cycles. The names of all people are non-empty strings, consisting of no more than 20 lowercase English letters.

Output

Print m whitespace-separated integers — the answers to Polycarpus's records. Print the answers to the records in the order, in which the records occur in the input.

Examples

input

```
6
pasha 0
gerald 1
gerald 1
valera 2
igor 3
olesya 1
5
1 1
1 2
1 3
3 1
6 1
```

output

2
2
0
1
0

input

6
valera 0
valera 1
valera 1
gerald 0
valera 4
kolya 4
7
1 1
1 2
2 1
2 2
4 1
5 1
6 1

output

1
0
0
0
2
0
0