# A. Misha and Forest

time limit per test: 1 second memory limit per test: 256 megabytes

input: standard input output: standard output

Let's define a forest as a non-directed acyclic graph (also without loops and parallel edges). One day Misha played with the forest consisting of n vertices. For each vertex v from 0 to n - 1 he wrote down two integers,  $degree_v$  and  $s_v$ , were the first integer is the number of vertices adjacent to vertex v, and the second integer is the XOR sum of the numbers of vertices adjacent to v (if there were no adjacent vertices, he wrote down 0).

Next day Misha couldn't remember what graph he initially had. Misha has values  $degree_{v}$  and  $s_{v}$  left, though. Help him find the number of edges and the edges of the initial graph. It is guaranteed that there exists a forest that corresponds to the numbers written by Misha.

## Input

The first line contains integer n ( $1 \le n \le 2^{16}$ ), the number of vertices in the graph.

The *i*-th of the next lines contains numbers  $degree_i$  and  $s_i$  ( $0 \le degree_i \le n - 1$ ,  $0 \le s_i \le 2^{16}$ ), separated by a space.

## **Output**

In the first line print number m, the number of edges of the graph.

Next print m lines, each containing two distinct numbers, a and b ( $0 \le a \le n - 1$ ,  $0 \le b \le n - 1$ ), corresponding to edge (a, b).

Edges can be printed in any order; vertices of the edge can also be printed in any order.

### **Examples**

```
input

3
2 3
1 0
1 0
0 0

output

2
1 0
2 0
```

```
input

2
1 1
1 0

output

1
0 1
```

#### Note

The XOR sum of numbers is the result of bitwise adding numbers modulo 2. This operation exists in many modern programming languages. For example, in languages C++, Java and Python it is represented as " $^$ ", and in Pascal — as "xor".