B. Roma and Changing Signs

time limit per test: 2 seconds memory limit per test: 256 megabytes input: standard input

output: standard output

Roma works in a company that sells TVs. Now he has to prepare a report for the last year.

Roma has got a list of the company's incomes. The list is a sequence that consists of n integers. The total income of the company is the sum of all integers in sequence. Roma decided to perform exactly k changes of signs of several numbers in the sequence. He can also change the sign of a number one, two or more times.

The operation of changing a number's sign is the operation of multiplying this number by -1.

Help Roma perform the changes so as to make the total income of the company (the sum of numbers in the resulting sequence) maximum. Note that Roma should perform **exactly** k changes.

Input

The first line contains two integers n and k ($1 \le n, k \le 10^5$), showing, how many numbers are in the sequence and how many swaps are to be made.

The second line contains a **non-decreasing** sequence, consisting of *n* integers a_i ($|a_i| \le 10^4$).

The numbers in the lines are separated by single spaces. Please note that the given sequence is sorted in non-decreasing order.

Output

In the single line print the answer to the problem — the maximum total income that we can obtain after exactly k changes.

Examples

```
input
3 2
-1 -1 1
output
3
```

```
input
3 1
-1 -1 1
output
1
```

Note

In the first sample we can get sequence [1, 1, 1], thus the total income equals 3.

In the second test, the optimal strategy is to get sequence [-1, 1, 1], thus the total income equals 1.