

# G. Puzzling Language

time limit per test: 1 second  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

In this problem you will write a simple code generator for a 2D programming language derived from [Brainfuck](#).

The code in this language is a rectangular grid of characters '.' and 'X'. The code is converted to a Brainfuck program as follows: the characters are read in the usual order (top to bottom, left to right), and each 'X' character is converted a Brainfuck instruction to be executed. The instruction is defined by the left, top and right neighbors of the 'X' character using the following conversion table:

You are given a string. Output a program in the described language which prints this string.

You can download the language interpreter used for judging here: <https://assets.codeforces.com/rounds/952/puzzling-interpreter.cpp> (use C++11 to compile the code). Note several implementation details:

- The first step of the language interpretation is conversion to a Brainfuck program, which is then executed.
- The code must be rectangular, with all lines of the same length. It can have at most 10,000 lines and 10,000 columns, and can have at most 500,000 'X' characters.
- The code has toroidal topology, i.e. the 'X' on the first line will have top neighbor in the last line.
- Brainfuck interpreter has 30000 memory cells which store integers from 0 to 255 with increment/decrement done modulo 256.
- Console input (, command) is allowed in Brainfuck code but has no effect when executed.

## Input

The input consists of a single string of characters with ASCII codes between 33 ('!') and 122 ('z'), inclusive. The length of the string is between 1 and 10 characters, inclusive.

## Output

Output a program in the described language which, when executed, will print the given message.

## Example

input
\$\$\$
output
<pre>.....X..... .....XXX..... .....XXXXX..... ....XXXXXXXX.... ...XXXXXXXXXX... ..XXXXXXXXXXXXX. . XXXXXXXXXXXXX. . XXXXXXXXXXXXX. ..... X.....X X..... X..... X.....</pre>

## Note

The example corresponds to the following Brainfuck program:

```
-
>+<
>+++<
```

```
>+++++<
>+++++++<
>+++++++<
>+++++++<
```

```
<      >
.
.
.
```

The triangular block decrements the first memory cell and sets the value of the second memory cell to 36 - the ASCII code of '\$' character. The next line after the triangular block moves the memory pointer to the second memory cell, and the next three lines print the '\$' character three times.