



PARTNER INTEGRATION

External API Integration Guide

Live group-ticketing and Umrah-package inventory
through one secure, unified booking workflow.

API version 1.0

Production integration document · September 2026

Abid Air International (Pvt.) Ltd.

Integration overview

The Partner API gives approved server-side integrations access to Abid Air's live public inventory. Inventory remains shared with the Abid Air portal; availability and fares can change between requests.

1. Fetch inventory



2. Select inventoryId



3. Create booking



4. Save reference

One booking endpoint. Submit a group-ticketing or Umrah-package ID as `inventoryId`. The API identifies its type, calculates the authoritative price, reserves the correct inventory, and returns the new booking's `_id`.

Base URL

```
https://abidairtravels.com/api/external/v1
```

Authentication

Send the issued API key with every request. Keys must only be stored and used on your server.

```
Authorization: Bearer aa_live_REPLACE_WITH_YOUR_KEY
Accept: application/json
```

Alternatively, send `X-API-Key: aa_live_....`. Available scopes are `inventory:read`, `bookings:read`, and `bookings:write`.

Security: Never place an API key in browser JavaScript, mobile-app source, public repositories, screenshots, or client-visible logs.

Operational defaults

Setting	Value	Notes
Format	JSON	Use <code>Content-Type: application/json</code> for POST requests.
Rate limit	120/minute	Per API client; inspect response rate-limit headers.
Pagination	25 default	<code>limit</code> accepts 1–100.
Dates	ISO 8601	Send calendar dates as <code>YYYY-MM-DD</code> .

Endpoint directory

Method	Path	Scope	Purpose
GET	/group-ticketing	inventory:read	List available public ticket groups.
GET	/group-ticketing/{id}	inventory:read	Fetch one available group.
GET	/umrah-packages	inventory:read	List available public Umrah packages.
GET	/umrah-packages/{id}	inventory:read	Fetch one available package.
POST	/availability	inventory:read	Check requested availability and obtain a token.
POST	/bookings	bookings:write	Create either booking type using an availability token.
GET	/bookings	bookings:read	List this API client's bookings.
GET	/bookings/{bookingId}	bookings:read	Fetch this API client's booking.
POST	/bookings/{bookingId}/cancel	bookings:write	Cancel an on-hold booking.

Group-ticketing inventory

```
GET /group-ticketing?page=1&limit=25&groupType=Umrah%20Groups&airline=PIA
```

Only groups with `internalStatus = Public` and positive seat availability are returned. The response exposes selling fares and PNR; internal buying prices, payment data, and supplier accounts are excluded.

```
{
  "success": true,
  "data": [{
    "id": "6a9174db6190d2c2cfff3f950",
    "groupCode": "GRP-1787917531522-K50T7I",
    "name": "PK-MUX-JED-MUX",
    "type": "Umrah Groups",
    "sector": "MUX-JED-MUX",
    "airline": "PAKISTAN INTERNATIONAL AIRLINE",
    "pnr": "9EPUMT",
    "availableSeats": 16,
    "currency": "PKR",
    "fares": { "adult": 148000, "child": 130000, "infant": 30000 },
    "flights": []
  }],
  "meta": { "page": 1, "limit": 25, "total": 1, "pages": 1 }
}
```

Umrah-package inventory

```
GET /umrah-packages?page=1&limit=25&source=local-db
```

Only public packages with positive availableRooms are returned. The optional source filter accepts local-db or travel-network.

```
{
  "success": true,
  "data": [{
    "id": "65fd12ab34cd56ef7890abcd",
    "name": "21 Day Umrah Package",
    "source": "local-db",
    "days": 21,
    "availableRooms": 12,
    "packageTotals": {
      "double": 285000, "triple": 255000, "quad": 235000,
      "shared": 220000, "childWithBed": 195000,
      "childWithoutBed": 125000, "infant": 45000
    },
    "flights": [], "hotels": [], "transports": [], "visa": null
  }],
  "meta": { "page": 1, "limit": 25, "total": 1, "pages": 1 }
}
```

Freshness: Fetch the selected inventory item immediately before creating a booking. A successful inventory response is not a reservation.

Get one inventory item

```
GET /group-ticketing/6a9174db6190d2c2cff3f950
GET /umrah-packages/65fd12ab34cd56ef7890abcd
```

A private, sold-out, exhausted, or unknown item returns 404. An invalid MongoDB identifier returns 400.

Create a unified booking

POST /bookings

First call POST /availability with inventoryId and the Adult, Child, and Infant counts. If available, use the returned five-minute token with the exact same inventory and passenger counts. Each successful booking request reserves inventory.

```
{ "inventoryId": "65fd12ab34cd56ef7890abcd", "adults": 1, "children": 1, "infants": 0 }
```

```
Authorization: Bearer aa_live_REPLACE_WITH_YOUR_KEY
Content-Type: application/json
X-Availability-Token: REPLACE_WITH_AVAILABILITY_TOKEN
```

Common request fields

Field	Required	Rules
inventoryId	Yes	ID returned by either inventory endpoint.
contactPersonName	Yes	Non-empty string.
roomType	Umrah only	sharing, quad, triple, or double.
passengers	Yes	At least one Adult or Child; array must not be empty.

Passenger fields

Field	Rules
type	Exactly Adult, Child, or Infant.
title	Examples: MR, MRS, MS, CHD, INF.
givenName, surName	Required.
passport, nationality	Required.
dateOfBirth, passportExpiry	Required for Umrah; valid ISO dates when supplied.
passportIssue	Optional valid ISO date.
childType	For Umrah Child pricing: withBed or withoutBed.

Booking request example

```
curl -X POST "https://abidairtravels.com/api/external/v1/bookings" \
-H "Authorization: Bearer aa_live_REPLACE_WITH_YOUR_KEY" \
-H "Content-Type: application/json" \
-H "X-Availability-Token: REPLACE_WITH_AVAILABILITY_TOKEN" \
-d '{
  "inventoryId": "65fd12ab34cd56ef7890abcd",
  "contactPersonName": "Muhammad Ali",
  "roomType": "double",
  "passengers": [{
    "type": "Adult",
    "title": "MR",
    "givenName": "Muhammad",
    "surName": "Ali",
    "passport": "AB1234567",
    "dateOfBirth": "1990-05-15",
    "passportIssue": "2022-06-01",
    "passportExpiry": "2032-05-31",
    "nationality": "Pakistan"
  }]
}'
```

Group-ticketing response

```
{
  "success": true,
  "data": {
    "_id": "6aa3e6b9a88c2c844c958b54",
    "status": "on hold",
    "expiresAt": "2026-09-11T14:30:00.000Z",
    "passengerCounts": { "adults": 1, "children": 0, "infants": 0, "total": 1 },
    "pricing": { "adultPrice": 148000, "grandTotal": 148000 }
  }
}
```

Umrah-package response

```
{
  "success": true,
  "data": {
    "_id": "6aa3e76ca88c2c844c958b61",
    "status": "On Hold",
    "packageId": "65fd12ab34cd56ef7890abcd",
    "packageName": "21 Day Umrah Package",
    "roomType": "double",
    "pricing": { "pricePerPerson": 285000, "totalPrice": 285000, "currency": "PKR" }
  }
}
```

Successful creation returns HTTP 201.

Fetch and cancel bookings

List your bookings

```
GET /bookings?page=1&limit=25
```

Returns only bookings created by the authenticated API client. Group-ticketing and Umrah-package bookings are combined, sorted newest first, and paginated.

Fetch

```
GET /bookings/6aa3e6b9a88c2c844c958b54
```

The API searches the correct booking collection using the booking `_id`. A client may retrieve only bookings created using its own API key.

Cancel

```
POST /bookings/6aa3e6b9a88c2c844c958b54/cancel
```

Only on-hold bookings may be cancelled through the API. Successful cancellation releases the previously reserved seats or package availability. Repeating a completed cancellation returns the already-cancelled booking.

Errors and recovery

```
{
  "success": false,
  "error": {
    "code": "INSUFFICIENT_INVENTORY",
    "message": "The inventory does not have enough availability."
  }
}
```

Status	Meaning	Recommended action
400	Malformed identifier/request	Correct the request before retrying.
401	Missing, invalid, or revoked key	Check authentication; do not repeatedly retry.
403	Missing scope or inactive owner	Contact Abid Air integration support.
404	Inventory/booking unavailable	Refresh inventory or verify the reference.
409	Availability/state conflict	Refresh state; offer another option.
422	Validation failed	Display field details and correct the payload.
429	Rate limit exceeded	Honor Retry-After; use exponential backoff.
500	Unexpected server error	Check the booking list before deciding whether to retry.

Production checklist

Area	Requirement
Credentials	Store the key in a server-side secret manager or protected environment variable.
Booking IDs	Persist the exact booking <code>_id</code> returned by the creation response.
Pricing	Display API-returned selling prices; never submit or calculate authoritative prices locally.
Availability	Refresh the selected item immediately before booking and handle HTTP 409.
Logging	Log request IDs, status codes, and references—never API keys or full passport records.
Retries	Back off on 429/5xx responses and verify the booking list before retrying creation.
Privacy	Encrypt passenger data in transit and at rest; restrict access and retention.

Source of truth: The machine-readable OpenAPI contract is distributed alongside this guide as `openapi.yaml`. Contact Abid Air before relying on undocumented fields.

Support handoff information

When reporting an integration issue, include the timestamp and timezone, endpoint, HTTP status, error code, and returned booking ID. Redact API keys and sensitive passenger data.