

API / Integration Documentation

Document: E-Numerak REST API & PEPPOL Integration Reference **Service Provider:** AL MERAK TAX CONSULTANT L.L.C **Base URL:** `https://api.e-numerak.com` **API version prefix:** `/api/v1/` **Date:** 2026-06-20

1. Overview

E-Numerak exposes a versioned REST API (Django REST Framework). All business endpoints are mounted under `/api/v1/`. Authentication is **JWT (bearer token)**, except the public health probes and the machine-to-machine PEPPOL AS4 receiving endpoint.

Concern	Value
Auth	Authorization: Bearer <code><access_token></code> (JWT)
Content type	<code>application/json</code> (except AS4: SOAP/MTOM)
Versioning	URL prefix <code>/api/v1/</code>
IDs	UUID v4
Transport	HTTPS / TLS only

Health probes (no auth)

Method	Path	Purpose
GET	<code>/health/</code>	Liveness
GET	<code>/ready/</code>	Readiness (DB/cache)

2. Authentication — [/api/v1/auth/](#)

Method	Path	Description
POST	check-email/	Check if an email is registered
POST	register/	Register a new account
POST	login/	Obtain JWT access + refresh tokens
POST	logout/	Invalidate refresh token
POST	token/refresh/	Refresh access token
GET/PATCH	me/	Current user profile
POST	change-password/	Change password
POST	verify-email/ , resend-verification/	Email verification
POST	forgot-password/ , reset-password/	Password reset
POST	mfa/setup/ , mfa/enable/ , mfa/disable/ , GET mfa/status/	MFA (TOTP) management
POST	mfa/verify-login/ , mfa/setup-login/ , mfa/enable-login/	MFA at login

Login example:

```
POST /api/v1/auth/login/
Content-Type: application/json
```

```
{ "email": "user@example.com", "password": "....." }
```

```
{ "access": "<jwt>", "refresh": "<jwt>", "user": { "...": "..." } }
```

3. Companies — [/api/v1/companies/](#)

Method	Path	Description
GET/POST	/	List / create companies
GET/PATCH/DELETE	{company_id}/	Company detail
GET/POST	{company_id}/members/	List / add members
GET/PATCH/DELETE	{company_id}/members/{member_id}/	Member detail

Related: [/api/v1/customers/](#) , [/api/v1/taxes/](#) , [/api/v1/onboarding/](#) .

4. Invoices — /api/v1/invoices/

Core outbound (PEPPOL sending) surface.

Method	Path	Description
GET/POST	``	List / create invoices
GET/PATCH/DELETE	{invoice_id}/	Invoice detail
POST	{invoice_id}/validate/	Pre-submit PINT-AE validation (XSD + Schematron)
POST	{invoice_id}/submit/	Generate UBL, validate, send via PEPPOL AS4
POST	{invoice_id}/cancel/	Cancel
POST	{invoice_id}/deactivate/	Deactivate
POST	{invoice_id}/credit-note/	Issue a credit note
GET	{invoice_id}/download-xml/	Download the PINT-AE UBL XML
GET	{invoice_id}/download-pdf/	Download the PDF rendering
GET	{invoice_id}/vat-summary/	VAT breakdown
GET/POST	{invoice_id}/items/ , {invoice_id}/items/{item_id}/	Line items
POST	{invoice_id}/report-fta/	Manual FTA (TDD) re-report
GET	{invoice_id}/payments/	Supplier payment view
GET	dashboard/ , export/ , gap-report/	Reporting helpers
GET/POST	products/ , products/{pk}/	Product catalog

Submit flow (what /submit/ does internally): 1. Build PINT-AE UBL (services/xml_generator). 2. Validate (services/peppol/pint_ae) — reject if invalid. 3. SMP discovery of receiver (services/smp_client). 4. Validate recipient cert (services/as4/cert_validation). 5. Sign + encrypt + send AS4 (services/as4/*). 6. Generate + submit AE TDD to C5 (services/peppol/tdd).

5. Inbound (PEPPOL receiving, C3) — `/api/v1/inbound/`

Method	Path	Auth	Description
POST	<code>as4/</code>	None (m2m)	PEPPOL AS4 receiving endpoint (Corner 3)
POST	<code>submit/</code>	JWT	Supplier-facing submission
GET	<code>''</code>	JWT	List received invoices
GET	<code>stats/</code>	JWT	Inbound statistics
GET	<code>{pk}/</code>	JWT	Received invoice detail
POST	<code>{pk}/approve/ , {pk}/reject/</code>	JWT	Approve / reject
POST	<code>{pk}/resend-observation/</code>	JWT	Resend MLS observation
GET/POST	<code>suppliers/ , suppliers/activate/</code>	JWT	Supplier management
GET/POST	<code>portal/ , portal/submit/</code>	JWT (inbound_supplier role)	Supplier portal

AS4 receiving endpoint (the address registered in our SMP):

```
POST https://api.e-numerak.com/api/v1/inbound/as4/  
Content-Type: multipart/related; ... (SOAP 1.2 + MTOM)
```

On receipt the AP verifies signature + signer trust, decrypts, validates the PINT-AE document, stores it, and returns an **MLS ApplicationResponse** (AB=accepted / RE=rejected).

6. Other modules

Prefix	Module
<code>/api/v1/reports/</code>	Reporting
<code>/api/v1/ocr/</code>	AI OCR (invoice scanning)
<code>/api/v1/fraud/</code>	Fraud detection
<code>/api/v1/chat/</code>	Assistant chat
<code>/api/v1/buyers/ , /api/v1/buyer/</code>	Buyer portal (invite + portal)
<code>/api/v1/admin/</code>	Admin panel
<code>/admin/</code>	Django admin

7. PEPPOL identifiers (integration constants)

Item	Value
Participant ID	0235:104132266800003 (scheme 0235 = UAE)
AS4 transport profile	peppol-transport-as4-v2_0
PINT-AE Billing CustomizationID	urn:peppol:pint:billing-1@ae-1
PINT-AE Self-Billing CustomizationID	urn:peppol:pint:selfbilling-1@ae-1
AE TDD CustomizationID	urn:peppol:taxdata:ae-1
Process (billing)	urn:peppol:bis:billing
Process (tax reporting)	urn:peppol:taxreporting

8. Error model

Standard HTTP status codes; error bodies are JSON:

```
{ "detail": "human-readable message", "code": "optional_error_code" }
```

- 400 validation error · 401 unauthenticated · 403 forbidden · 404 not found · 409 conflict (state) · 422 document validation failed · 500 server error.