

Final Exam Python

Ali ZAINOUL
ali.zainoul.az@gmail.com

August 2, 2024

Class Diagram

You were tasked to implement an Online Shopping System in Python, given the following class diagram:




Figure 1: Class diagram for the Online Shopping System

Analysis of the Class Diagram

The class diagram represents an Online Shopping System with three classes: Product, ShoppingCart, and Customer. Let's analyze each class:

Product

- **Attributes:**
 - id: int (private)
 - name: string (private)
 - price: float (private)
- **Methods:**
 - Product(id: int, name: string, price: float) (public constructor)
 - getId(): int (public method)
 - getName(): string (public method)
 - getPrice(): float (public method)

ShoppingCart

- **Attributes:**
 - products: List<Product> (private)
- **Methods:**
 - ShoppingCart() (public constructor)
 - addProduct(product: Product) (public method)
 - removeProduct(product: Product) (public method)
 - getTotalPrice(): float (public method)
 - displayCart() (public method)

Customer

- **Attributes:**
 - name: string (private)
 - cart: ShoppingCart (private)
- **Methods:**
 - Customer(name: string) (public constructor)
 - addToCart(product: Product) (public method)
 - removeFromCart(product: Product) (public method)
 - checkout() (public method)

The class diagram shows the relationships between the classes:

- The Customer class has a composition relationship with the ShoppingCart class (1:1). A Customer has one ShoppingCart, and the ShoppingCart is owned by the Customer.
- The ShoppingCart class has an aggregation relationship with the Product class (1 to *). A ShoppingCart can contain multiple Products, but the Products exist independently of the ShoppingCart.

In summary, the class diagram illustrates the structure of an Online Shopping System, where Customers can have their own ShoppingCart and interact with Products through operations such as adding, removing, and checking out items.

Class Product Implementation

```
# File: Product.py
class Product:
    def __init__(self, id: int, name: str, price: float):
        """
        Constructor for the Product class.

        Parameters:
            id (int): The product ID.
            name (str): The product name.
            price (float): The product price.
        """
        self.__id = id # Private attribute to store the product ID
        self.__name = name # Private attribute to store the product name
        self.__price = price # Private attribute to store the product price

    def get_id(self) -> int:
        """
        Get the product ID.

        Returns:
            int: The product ID.
        """
        return self.__id

    def get_name(self) -> str:
        """
        Get the product name.

        Returns:
            str: The product name.
        """
        return self.__name

    def get_price(self) -> float:
        """
        Get the product price.

        Returns:
            float: The product price.
        """
        return self.__price
```

In this code, we use double underscores (__) to declare **private attributes** (__id, __name, and __price). The constructor **__init__** takes the arguments id, name, and price and initializes the private attributes. The methods get_id, get_name, and get_price are **public methods** that allow **accessing the private attributes** by returning their values.

Good luck! ♥