


ø19.25±0.05 9) Ø15.8 -0.05


Blowhead tube

Scale 2:1


Material-Steel


Ø8






Material-Steel






1. H14,h14,±IT14/2. 2. Mark: XXI–KPM–26–2–700–17–ExtraNew Mark: 5015 Mark ordinal number (h=8) & PSI logo. Depth of marking-0.2...0.3 mm.





XXI-KPM-26-2-700-17-ExtraNew


					l	Контакт: info@ps
		MATERIAL/	CAST IRON (GS900)	MACHINE/	EMHART GLASS-BB-DG 5 1/2"-8	JOB TITLE/HAЗВАНИЕ РАБОТЫ:
		МАТЕРИАЛ:	CAST IKUN (US900)	машина:	EMUAKI OLASS-DD-DO S 1/2 -0	
		welding/	Cupface (UDC 25 /0)	DESIGNER/		///I-I/I I I - 20 - 2 - 700 - 17 - LXII
		НАПЛАВКА:	Surface (HRC 3540)	ДИЗАЙНЕР:		DRAWING NUMBER/HOMEP YEPTEЖA:
, ,		QUANTITY/		DATE/	24.04.20	5015-BH-1
DATE/ДАТА	REVISIONS/ИЗМЕНЕНИЯ	КОЛИЧЕСТВО:		ДАТА:	Z4.U4.ZU	ו-ווט-נוטנ

SCALE/ MACШТАБ: 1:1











SCALE/ MACIIITAB:

6.3





A (4:1)

6.3

- 1. H14, h14, ±1T14/2.
- 2. Keep sharp edge B. 3. Mark: XXI-KPM-26-2-700-17-ExtraNew Mark: PSI/5015
- after marking is done Remove all burrs and wire-edges Mark ordinal number. Depth of marking – 0.2–0.3 mm.





Адрес: 199034, Россия, Санкт-Петербура, В.О., 14 линия, д. 7. Тел.: +7(812)3202959


Контакт: info@psiglass.ru


JOB TITLE/HA3BAHME PA5OTS DRAWING NUMBER/HOMEP HEPTEXA XXI-KPM-26-2-700-


5015-FGP-1

24.04.20

OTFXA:	: 17-ExtraNew	
- <u>-</u> -	SCALE/ MACШTA5:	













8+0.1











- 1. Both halves of mould (A & B) must be marked with same ordinal number and used together.
- 2. Gap in mould joint must be not more than 0.05 mm.
- 3. Positional tolerance of forming cavity axis T 0.1 mm. Base joint plane
- 4. Allowed deviation of forming cavity dimensions is not more than ± 0.05 mm.
- except for dimensions that are specially shown.
- 5. Keep sharp edges P.
- 6.*Reference only dimensions 7 H14 h14 +IT14/2

- 8. Hardness after welding HRC335..40.
- 9. Mark: XXI-KPM-26-2-700-17-ExtraNew Mark: 5015
- Mark ordinal number (h=8) & PSI logo. Depth of marking-0.2...0.3 mm.
- 10. Cap holes with screws M8x8 and punch.

р. 9	
36.5	
22	

	/. Π14, Π14, ≛11 14/2.						
		ASSEMBLY NUMBER/ НОМЕР СБОРКИ:	53	MATERIAL/ MATEРИАЛ:	CAST IRON (GS900)	MACHINE/ MAШИНА:	EMHART GLASS-BB-DG 5 1/2"-8
24.04.20	(2)	INVERT CENTRE/	105	WELDING/	Dass and odass (UDC DE 10)	DESIGNER/	
24.04.20	\bigcirc	инверт:	רטו	НАПЛАВКА:	Base and edges (HRC 3540)	ДИЗАЙНЕР:	
21.01.20		'H' DIMENSION/	57 15	QUANTITY/		DATE/	24.04.20
DATE/ДАТА	REVISIONS/ИЗМЕНЕНИЯ	PA3MEP 'H': (PACCTOSHUE OT	ОСИ ФОРМЫ ДО ВЕРХНЕЙ ГУБКИ)	количество:		ДАТА:	24.04.20



1:1

XXI-KPM-26-2-700-17-ExtraNew DRAWING NUMBER/HOMEP YEPTEXA: 5015-MLD3-3

