

'L' RATIO				
CAP. TO S	ETTLE LINE		ml	
S.L.HT. FRO	M NR LINE		mm	
INVERT		90	mm	
"H" DIM.		117.5	mm	
HOLDER SIZE		#23		
BLOW MOULD				
COLD CLAS	GHT SS FACTOR	380 x0.4	g	
CAP. TO	O'FLOW	152 +520	ml ml	
SHRINKAGI	E (1.5%)	672 X1.01	ml	
DISPL. OF FIN. ABOVE	SEATED E MOULD	678.8 -16.8	ml ml	
MLD + B		662		
INVERT		90	mm	
"H" DIM.		57.15	mm	
HOLDER SIZE		#53		
XI-B-30-45-500-14				
VEIGHT	380±10g			
BRIMFUL CAPACITY	520±10ml			

500±10ml

Emhart DG  $5\frac{1}{2}$ "

CHECKED APPROVED

FILL POINT CAPACITY

1:1

DRAW 10/10/2019

FINISH TYPE:

SCALE MACHINE TYPE:

BLANK MOULD

380 x0.41

+68.6

-14

155.8 ml

210.4 ml

ml

WEIGHT HOT GLASS FACTOR

GOB CAPACITY

OVERCAP 44%

NR NOL - PL VOL

CALC. BLK+BA DISPL

FINISH:			
BLOW NECK	ø26.2		
BLANK NECK	ø25.8		
RING NECK	ø26		
TONG NECK			
BLOW NECK RAD	R1		
BLOW HEAD DEPTH	28.2		