

Homework Assignment 1

Perceptron and Logistic Regression

Lecturer: Kyunghyun Cho

January 30, 2017

1. When defining a perceptron, we have augmented an input vector \mathbf{x} with an extra 1:

$$M(\mathbf{x}) = \text{sign}(\mathbf{w}^\top \tilde{\mathbf{x}}),$$

where $\tilde{\mathbf{x}} = [\mathbf{x}; 1]$. Why is this necessary? Provide an example in which this extra 1 is necessary.

2. We used the following distance function for perceptron in the lecture:

$$D(M^*(\mathbf{x}), M, \mathbf{x}) = -(M^*(\mathbf{x}) - M(\mathbf{x})) (\mathbf{w}^\top \tilde{\mathbf{x}}).$$

This distance function has a problem of a trivial solution. What is the trivial solution? Propose a solution to this.

3. The distance function of logistic regression was defined as

$$D(y^*, \mathbf{w}, \mathbf{x}) = -(y^* \log M(\mathbf{x}) + (1 - y^*) \log(1 - M(\mathbf{x}))).$$

Derive its gradient with respect to the weight vector \mathbf{w} step-by-step.

4. (Programming Assignment) Complete the implementation of perceptron and logistic regression using Python and scikit-learn. The completed notebooks must be submitted together with the answers to the questions above.

Perceptron https://github.com/nyu-dl/Intro_to_ML_Lecture_Note/blob/master/notebook/Perceptron1.ipynb

Logistic Regression https://github.com/nyu-dl/Intro_to_ML_Lecture_Note/blob/master/notebook/Logistic%20Regression%201.ipynb