

Logistic Knowledge Tracing: A Constrained Framework for Learner Modeling

Philip I. Pavlik, Jr. , Luke G. Eglington, and Leigh M. Harrell-Williams

Abstract—Adaptive learning technology solutions often use a learner model to trace learning and make pedagogical decisions. The present research introduces a formalized methodology for specifying learner models, logistic knowledge tracing (LKT), that consolidates many extant learner modeling methods. The strength of LKT is the specification of a symbolic notation system for alternative logistic regression models that is powerful enough to specify many extant models in the literature and many new models. To demonstrate the generality of LKT, we fit 12 models, some variants of well-known models and some newly devised, to six learning technology datasets. The results indicated that no single learner model was best in all cases, further justifying a broad approach that considers multiple learner model features and the learning context. We introduce features to stand in for student-level intercepts and argue that to be maximally applicable, a learner model needs to adapt to student differences. The results of our comparisons show the general importance of modeling recent learning for all datasets, with special importance for terms that model memory in datasets involving fact learning.

Index Terms—Computer-aided instruction, educational technology, knowledge tracing, learning management systems, model comparison, models of learning.

I. CREATING AND USING LOGISTIC REGRESSION LEARNER MODELS TO INFORM LEARNING TECHNOLOGY PEDAGOGY

THERE is growing research interest to understand student learning in adaptive, personalized educational software. Adaptive personalization typically requires a model of student learning that captures the complexities of learning, but it can be unclear which of the many candidate models, including off-the-shelf approaches such as the additive factors model (AFM), instructional factors analysis (IFA), performance factors analysis

(PFA), PFA-decay, or recent-PFA (R-PFA) [1]–[7], is ideal in a particular context. This article introduces a theoretically motivated framework for systematic specification and evaluation of student models for adaptive instructional environments, logistic knowledge tracing (LKT), built on logistic regression methodology. The LKT framework, which subsumes other methods, also facilitates comparing the relative strengths and weaknesses of different learner models, enabling more productive research. The LKT framework promotes a better understanding of the possible models that could be specified given the factors at play in any learning system. Further, by delineating the possibilities for predictive features in a logistic regression model, the framework makes it easier for modelers to create and test new features.

The necessity of a flexible model development approach became clear over our work on the LearnSphere/DataShop project. The LearnSphere/DataShop project aims to facilitate sharing educational data and analyses (as of January 2021, Carnegie Mellon University DataShop contained more than 3400 datasets comprising 1 million hours of student learning data in which they learn a variety of content) [8]–[10]. Via LearnSphere, researchers develop and share components that allow others to run various models of learning that track student performance across time. The variety of datasets and educational contexts in the DataShop datasets made it clear that a great variety of logistic regression learner models can be specified for different contexts. However, until now, there has no principled framework for learner model development. Because logistic regression modeling is quite flexible, it leads to the question: What do these models have in common? By identifying the common elements of these logistic regression models (described below), it becomes possible to provide a unified system (an LKT component) in the LearnSphere for creating logistic regression learning models. The LearnSphere LKT component implements the LKT framework, a unified system that permits easier creation and comparison of logistic regression models of correctness. We have also released LKT as an easy-to-use R package.

A. Utility of the Approach

The primary utility of a model of student learning is to make inferences about learning that guide pedagogical decisions, i.e., decisions about what and when to teach. Such pedagogical decision making is the basis for any automated instructional system [11], [12]. Using the sequence of prior performances for each student practicing items (e.g., a specific

Manuscript received August 13, 2019; revised January 8, 2021 and September 6, 2021; accepted November 14, 2021. Date of publication November 16, 2021; date of current version January 17, 2022. This work was supported in part by the National Science Foundation through the LearnSphere under Grant 1443068 and the Learner Data Institute under Grant 1934745, and in part by the Institute of Education Sciences under Grant ED#R305A190448. (Corresponding author: Philip I. Pavlik, Jr.)

Philip I. Pavlik, Jr. is with the Institute of Intelligent Systems, Department of Psychology, University of Memphis, Memphis, TN 38152 USA (e-mail: ppavlik@memphis.edu).

Luke G. Eglington is with the School of Interactive Computing, Georgia Institute of Technology, Atlanta, GA 30332 USA (e-mail: leglington3@gatech.edu).

Leigh M. Harrell-Williams is with the Department of Counseling, Educational Psychology, and Research, University of Memphis, Memphis, TN 38152 USA, and also with the Institute of Intelligent Systems, University of Memphis, Memphis, TN 38152 USA (e-mail: lmwillm14@memphis.edu).

Digital Object Identifier 10.1109/TLT.2021.3128569

1939-1382 © 2021 IEEE. Personal use is permitted, but republication/redistribution requires IEEE permission. See <https://www.ieee.org/publications/rights/index.html> for more information.

test question), the model estimates the probability each subsequent item may be correctly answered.

Typically, this probability prediction guides pedagogical decision making by the system, student, or teacher. For example, a low probability prediction implies that instruction is needed and that the item might be challenging for the student. In contrast, a high probability may indicate that instruction is less critical. In fact, a high probability prediction by the model implies that the item could be marked as learned since the probability is intended to be tracking learning. This method of using the probability is known as mastery learning, the pedagogical principle that skills should be practiced until learning reaches a pre-specified criterion (e.g., 95% correct prediction [13]). Another possible use is shown by research that has suggested that selecting items for practice causes maximal learning at some fixed correctness probability (e.g., practice whichever item is closest to 80% correctness probability) [14], [15]. This conclusion about the presence of an optimal difficulty level has been supported by other methodological approaches based on an exhaustive search for an optimal schedule [14], [16]. The optimal difficulty will depend on features of the to-be-learned content (e.g., [17]). Another use of this article is in creating open student [18], in which the student can view the predictions the model has made about them. This feedback allows students to metacognitively monitor their performance more accurately, leading to more efficient learning if students address the deficiencies predicted by the model.

B. History

To better understand the goal of producing an accurate model using logistic regression for learner modeling, it is useful to survey the history of such an approach. The model within the LKT framework can be traced from the development of item response theory (IRT) [19], [20]. IRT models are generalized linear models predicting the probability of student success on an individual item given item characteristics, such as item difficulty and discrimination, and student's latent trait estimate. Whereas items typically refer to a specific test or quiz items, but we extend the concept of an item to any single step of a task that is learned, including any immediate review following the task. Thus, the concept of an item is generalized to include practice items with or without subsequent feedback or review.

The linear logistic test model (LLTM) introduced the idea that multiple discrete "cognitive operations" may combine to determine an item's difficulty [21]. Whereas parameters in traditional IRT models do not map onto mental constructs, the LLTM describes how latent traits combine to produce an item's difficulty. This work maps closely "rule spaces" or what have come to be known as Q-matrices, which are a means to specify the skills, concepts, knowledge, or cognitive operations needed to correctly answer a practice or test item [22], [23]. Many researchers use the term knowledge component (or KC) to refer generically to any of these learned proficiencies, knowledge of how to apply the least common denominator to do fraction addition, needed to respond correctly to practice items (e.g., [24]).

On a path toward modeling learning, Scheiblechner [25] used the LLTM model, but also examined changes in difficulty

as people repeated KCs. This article is well-reviewed by Spada and McGaw [26], who unpacked the history of these sorts of models have come to be known more recently as the AFM [7] within the artificial intelligence in education (AIED) and educational data mining (EDM) communities. AFM proposes that we add a term to these IRT-type models that capture each KC's prior quantity of practice as a linear effect. These skill tracking models have been combined with the Q-matrix KC models. A variant of this LLTM/AFM model is built into the DataShop repository at Carnegie Mellon University and is currently being used to do an automated search for better Q-matrices to represent the skills in different educational systems [9].

PFA further improved the AFM model by fitting separate parameters for prior successes and failures to predict future performance and made logistic regression about as accurate as Bayesian knowledge tracing (BKT), a Markov model frequently used to fit similar data [6], [13], [27]. The PFA model assumes that there are two fundamental categories of practice, success, and failure. As the psychological literature suggests, successes (in contrast to review after failing) may lead to more production-based learning and/or less forgetting [28]–[30] and may lead to automaticity [31]–[34]. In contrast, failure reveals a need for declarative learning of problem structure and verbal rules for production compilation [35]. We might expect learning after failure to depend most notably on the feedback that occurs after the task is complete. PFA methodology of categorizing event types within a KC was generalized into IFA, which explains that all event types may be tracked individually [36].

The previously mentioned models assume linear terms, but we also might consider terms that are nonlinear. The simplest examples are terms that use the natural log function of the prior trials [36], [37]. The idea of nonlinear features opens a realm of complex possibilities, as shown in recent research. The earliest example of a nonlinear feature in the EDM/AIED literature appears to be the introduction of the PFA-decay model [4], which elaborates on PFA by proposing that the counts of success and failures be exponentially weighted as a function of their recency in the stream of observations of performance for a KC. In terms of PFA, this means that if a student transitions from failure to success across a sequence of trials, the model can adjust its predictions quickly since past failures may have minimal effect relative to a history of recent successes. This weighting creates a greater sensitivity to recent changes in learning.

R-PFA is a variant of PFA-decay, which introduced another nonlinear component, a recency-weighted proportion of prior correct responses for a KC [3]. Like PFA-decay, the attempts used to compute the proportion decay exponentially, so this feature is highly sensitive to performance changes. In later sections, we used a modified recency weighted proportion that had one ghost success and one ghost failure. These initial settings allow the model performance to trend downwards as well as upwards. We also apply the decaying proportion feature more generally because we found that it also works well to trace overall performance as a substitute for a student intercept parameter. In support of our goal for models that generalize to

new data, the results of this article document alternatives to using fixed or random student intercepts.

Concurrently with learner model development in psychometrics, EDM, and AIED communities, other fields are working on similar goals using logistic regression modeling. Memory researchers from psychological backgrounds have found strong evidence that memory follows consistent patterns of decay over time [38]–[42] and have researched how this decay may be reduced (e.g., [30], [41]). However, few learner models incorporate decay in their predictions. One recent example is the predictive performance equation (PPE) [38], [43], which bridges the gap between learner models and cognitive models by more explicitly basing its structure on memory principles, including forgetting, spacing effects, and practice effects. PPE uses many features of the adaptive character of thought-rational (ACT-R) memory model [41]. While the PPE model has developed in the psychology cognitive modeling tradition, since it uses logistic regression (unlike ACT-R), it may be applicable for easy transfer to the psychometric, EDM, and AIED communities, if only it could be combined with other aspects of learner modeling, such as adaptivity and KC specific parameters. In this article, we show how LKT allows the easy creation of such models.

We present two additional models that account for forgetting, base2 and base4, which are also based on the ACT-R model. This suggests that there may be a family of ACT-R derivatives, and in this article, we compare the three versions: 1) PPE; 2) base2; and 3) base4. While the PPE equation uses all the ages since past practices to estimate forgetting, the base2 and base4 equations only use the first trial's age to estimate forgetting. In contrast, base2 is much simpler, with one parameter scaling difference in interference and one parameter capturing forgetting. While base2 is not sensitive to spacing effect learning benefits in the data, both base4 and PPE use two parameters to scale the effects of practice according to the distribution (i.e., spacing) of that practice.

One may wonder why this article does not include comparisons of other methods, such as BKT or deep knowledge tracing (DKT). The main reason for this was to intentionally limit our scope to fully introduce the LKT methodology. This article aims not to show which model is best or which modeling method is best, which others have done, most recently [44], but rather to open the world of logistic regression possibilities by providing a tool for researchers. This tool will enable richer comparisons with BKT or DKT if that is what the user wants. However, perhaps more meaningfully, the tool allows the user to tailor a model to the data characteristics in ways that are not currently possible with other methods. As we discuss, it is practical to create nonlinear features in addition to linear features by nesting the solution of these nonlinear features within a logistic model. This capability allows LKT models to use various parameterized nonlinear features that capture cognitive effects such as memory recency, the benefit of distributed practice, forgetting, and diminishing marginal returns for overlearning.

Further, using the logit from the logistic regression, it is possible to transform the logistic regression model predictions

to predict future actions' latency. In addition to this flexibility, also argued for by others [3], one point we emphasize is the ease of use of the subsequent model in a running adaptive learning system as demonstrated in several ways, most recently including testing a system with an adaptive model of practice for learning Anatomy and Physiology textbook knowledge [15]–[17], [45], [46]. Unlike BKT, LKT does not typically require the full sequence of prior practices and is highly configurable for complex features. Unlike DKT, LKT does not require iterative pretraining and is highly interpretable [47]. These advantages make LKT a good choice for an adaptive learning system user model. While some might argue the BKT is more popular than other methods, this may be a simple artifact of the high publication rates related to earlier development and research on the Carnegie Learning, Inc. systems [13], [48]. It is difficult to find other companies that use BKT, and other large companies use other methods and regression variants (e.g., Duolingo, Inc.) [49].

C. Goals of the Paper

At the heart of this project is the specification of a symbolic notation system for alternative logistic regression models that is powerful enough to specify many models in recent literature. The notation system reveals a pallet of features that can be combined in a linear equation to specify novel models. The system allows more precise communication about the differences between two models since the differences can be precisely specified using the models' symbolic notation.

The notation system involves specifying the number of terms in the model, each describing a feature of the data for some factor (we call these components). Components are split into levels, each describing a subset of data for which a feature applies (e.g., student or KC). The most straightforward feature is the intercept, which results in a constant coefficient for each factor's level. Another broad type of feature is the linear feature, where the effect is a linear function of some prior count of an event type within each level of the factor, similar to the AFM and PFA models [6], [7]. The most complex feature type is a nonlinear feature, where a nonlinear function is applied to data in contrast to a linear function. Some nonlinear functions also require nonlinear parameters. Equation (1) shows an example of this notation for each term, where p is probability and the feature is listed in regular font with the component noted in subscript, such as $\text{feature}_{\text{component}}$

$$\ln \frac{p(\text{success})}{1 - p(\text{success})} = \text{propdec}_{\text{Student}} + \text{intercept}_{\text{Item}} + \text{logsucc}_{\text{KC}} + \text{logfail}_{\text{KC}} + \text{propdec}_{\text{Student}} + \text{recency}_{\text{Item}} \quad (1)$$

This article's primary goal is to demonstrate the utility of LKT by expressing several previously developed and popular models (e.g., AFM, PFA, R-PFA) and new models (e.g., base4) as special cases of the general model using several datasets, further validating the method's generality. The models also illustrate why no specific model is likely to be "best" for all circumstances by showing differences by dataset even

though some features appear to be generally useful to include. We focus on models that are easily implementable in an adaptive learning system by avoiding models (in the main comparison) with fixed or random intercepts for individual students. While a pretest could be used to estimate student-level model intercept values, we do not address this possibility here. Instead, the models here attempt to avoid student parameters as a partial solution to the cold start problem that occurs when models are transferred between different populations of students.

In addition to our goal of introducing the LKT system for building adaptive learning models, we illustrate the framework's extensibility by comparing some models that use novel features included in LKT. These other new features might apply to KC or item-level components. For example, we introduce four new memory-based features, inspired by or directly transferred from the psychology literature [38]–[42]. The LKT framework contains several other features that are not tested here due to the limits of space. These examples are intended to demonstrate the extensibility of the framework.

II. LKT FRAMEWORK

To use LKT, one needs to have the following.

- 1) Terms of the model, each including a feature that describes change across repetitions of categories at a component level.
- 2) A sequence of learner event data with the subject and correctness columns (at minimum). Usually, this takes the form of a tab-delimited file with columns for student and correctness. See details below in Section II-E.

A. Component Level

The component specifies the subsets of the data for which the feature applies. We might think of the most fundamental component as the subject itself. There are other components as well, such as the items and KCs. In the model, each feature's effects for each component sum together to compute the additive effect of multiple features. It is assumed that, except for constant intercepts, a feature is applied for all component levels individually within the data for each subject.

1) *Items*: An item is a specific practice performance opportunity, such as providing the English meaning of the Spanish word "gato" or providing the next step in the problem $5x+6=0$. Typically, items are split so that each item is assigned a single target KC (see below) since if a single performance maps to many skills, it becomes hard to assign blame for failure results. The item-level component captures the fact that idiosyncratic differences exist for any specific instantiated problem for a topic or concept. Therefore, an item-level component intercept is isomorphic with the difficulty parameter in item-response theory. Such difficulties may come from any source, including the context of the problem, numbers used in the item (e.g., for a math problem), vocabulary used in the item (e.g., for a story problem or essay response item), and any other factors that result in the item being difficult for the average student. While we may consider the existence of item by person interactions (e.g., item A is

easy for Sally, but not for John), they are rarely possible to identify ahead of time and so are not used in the models here.

Item components may also be traced using learning or performance tracing feature. Items are most simply defined as problems with a constant response to a constant stimulus, and people tend to learn constant responses to exact stimulus repetitions very quickly [24]. Often, item-level learning tracing is not used because adaptive systems are built never to repeat items and focus on KC component-level learning and performance tracing. Item-level components in LKT allow researchers to compare with KC-level models, which may help identify possible model weaknesses and lead to model respecification.

2) *Knowledge Components*: Any common learnable factor in a cluster of items that controls that cluster's performance may be described as a KC. KCs are intended to capture transfer between related tasks so that practicing the component in one item is assumed to benefit other items that also share the component. It is conceivable that performance for an item may depend on one or more KCs. In the case where multiple KCs are present, it is possible to use probability rules to model situations where knowledge of multiple components is necessary for a student to answer a specific item correctly. However, in the work here, we take the standard compensatory approach, in which the sum of the influence of the KCs is used to estimate the performance for the item if multiple KCs influence that performance. This compensatory approach is similar to the LLTM model that sums factors to estimate performance.

3) *Overall Individual*: The student-level component is used to make a feature be a function of the student's prior performance from all prior data. In the case of a student intercept, the entire student's data are used in estimating a constant value. Unlike the intercept, it should be noted that most features are dynamic in this method, depending on prior data. This article's only constant features are intercepts representing subjects (initial models) and intercepts representing items (main comparison models). A "dynamic" feature means that its effect in the model potentially changes with each trial for a subject. Most dynamic features start at a value of 0 and change as a function of the student's changing history as time passes in some learning system.

4) *Other Components*: The flexibility of LKT means that users are not limited to the standard components above. For example, if students were grouped into four clusters, a column of the data could be used for component levels to fit each cluster using a different intercept.

B. Features

These are the functions for computing the effect of the components' histories for each student (except for the fixed feature, the constant intercept). Some features have a single term such as exponential decay (expdecaf, described in Section II-C.6), a transform using the sequence of prior trials, and a decay parameter. Other features are inherently interactive, such as base2, which scales the logarithmic effect of practice by multiplying by a memory decay effect term. Other terms like base4 and PPE involve the interaction of at least three

TABLE I
SELECTED FEATURES CURRENTLY SUPPORTED BY LKT

Feature	Pars	Adaptive	Dynamic	Input data needed for component level (e.g., KCs) for each learner
intercept	0	no	no	Intercepts are an exception since they are fit without regard to subject history
lineafm	0	no	yes	Total practice counts
logafm	0	no	yes	Total practice counts
powafm	1	no	yes	Total practice counts
recency	1	no	yes	Age of most recent trial
expdecaf	1	no	yes	Total practice counts
base	1	no	yes	Total practice counts and age of oldest trial
base2	2	no	yes	Total practice counts, age of oldest trial, and intrasession total time
base4	4	no	yes	Total practice counts, age of oldest trial, and intrasession total time
ppe	4	no	yes	Total practice counts and ages of all trials
logsuc	0	yes	yes	Success counts
linesuc	0	yes	yes	Success counts
logfail	0	yes	yes	Failure counts
linefail	0	yes	yes	Failure counts
expdecsuc	1	yes	yes	Success history
expdecfail	1	yes	yes	Failure history
basesuc	1	yes	yes	Success count and age of oldest trial
basefail	1	yes	yes	Failure count and age of oldest trial
base2fail	2	yes	yes	Failure count, age of oldest trial, and intrasession total time
base2suc	2	yes	yes	Success count, age of oldest trial, and intrasession total time
linecomp	0	yes	yes	Success and failure counts
prop	0	yes	yes	Success and failure counts
propdec	1	yes	yes	Success and failure histories
logit	0	yes	yes	Success and failure counts
logitdec	1	yes	yes	Success and failure histories

inputs. Table I summarizes 25 features currently supported in the LearnSphere and the R package, indicating if the feature is adaptive and/or dynamic, as well as explaining the input data required from the KCs. Adaptive features change as a function of the prior practices' outcome (typically correct or incorrect). In contrast, dynamic features change independent of prior practice quality (these features are functions of when or how much prior practice occurs, NOT the quality of those performances). These features are individually described in the next section.

In the parameters column, 0 indicates a linear feature, and 1 or more indicates how many additional nonlinear parameters the feature requires for estimation.

C. Feature Descriptions

1) *Constant (Intercept)*: This feature is a simple generalized linear model intercept, computed for a categorical factor (i.e., whatever categories are specified by the component factor).

2) *Total Count (Lineafm)*: This feature, from the AFM model [7], predicts performance as a linear function of prior experiences with the KC.




Fig. 1. Graph of logit effect as trials increases with different features.




Fig. 2. Graph of age^{-d} effect as age increases with different decay rates.

3) *Log Total Count (Logafm)*: This predictor, used in prior work (e.g., [36]), implies logarithmically decreasing marginal returns for practice as total prior opportunities increase. We add 1 to the prior trial count to avoid taking the $\log(0)$.

4) *Power-Decay for the Count (Powafm)*: This feature, a component of the predictive performance equation (PPE) model [38], models a power-law decrease in the effect of successive opportunities. The model describes smaller or greater diminishing marginal returns by raising the count to a positive power (nonlinear parameter) between 0 and 1. For applications not needing forgetting, it may provide a simple, flexible alternative to logafm. Fig. 1 shows how for a power value $d = 0.45$, the unscaled logit contribution is similar to the natural log for the first 10 trials before increasing faster. The curve for the power value $d = 0.60$ is steeper than either the natural log or the power value $d = 0.45$ across all trials. The unscaled logit contribution refers to the feature's effect before considering the effect of the logistic regression coefficient, which is fit either overall (i.e., one coefficient for all levels of a component factor) or individually (i.e., using the $\$$ operator to fit a coefficient for each level of the component factor, see Section II-D).

5) *Recency (Recency)*: This feature, inspired by the strong effect of the time interval since the previous encounter with a component (typically an item or KC), was created for this article. The recency effect, well-known in psychology, is captured with a power-law decay function to simulate performance improvement when the prior practice was recent. This feature only considers the just prior observation; older trials are not considered. Fig. 2 shows the basic form of the power-law decay function as a function of time. This function assumes

time is greater than 1, as this makes the learning equivalent at the start of the function.

6) *Exponential Decay (Expdecaf)*: This predictor considers the effect of the component as a decaying quantity according to an exponential function. It behaves similarly to logafm or powafm, as shown in Fig. 1, and is similar to the mechanisms used in the PFA-decay model [4].

7) *Power-Law Decay (Base, Base2)*: This predictor multiplies logafm by the age since the first practice (trace creation) to the power of a decay rate (negative power), as shown in Fig. 2. This predictor characterizes situations where forgetting is expected to occur in the context of accumulating practice effects. Because this factor does not consider the time between individual trials, it implicitly assumes even spacing between repetitions and does not capture recency effects. The base2 version shrinks the time between sessions by some factor, for example, 0.5, making time between sessions count only 50% towards estimating age. This mechanism in base2 to scale forgetting when interference is less was first introduced in cognitive modeling research [40].

8) *Power-Law Decay With Spacing (Base4)*: This predictor involves the same configuration as base2, multiplied by the mean spacing to a fractional power. The fractional power scales the effect of spacing such that if the power is 0 or close to 0, then spacing the scaling factor is 1. If the fractional power is between 0 and 1, there are diminishing marginal returns for increasing average spacing between trials. This feature was introduced for this article as a comparison to the PPE feature.

9) *Performance Prediction Equation*: This predictor, introduced over the last several years, shows excellent efficacy in fitting spacing effect data [38], [43]. It is novel because it simultaneously scales practice such as the powafm mechanism, captures power-law decay forgetting, spacing effects, and has an interesting mechanism that weights trials according to their recency.

10) *Log Performance Measures (Logsuc and Logfail)*: This expression is simply the log-transformed performance factor (total successes or failures), corresponding to the hypothesis that there are declining marginal returns according to a natural log function [8; 26].

11) *Linear PFA (Linesuc and Linefail)*: These terms are equivalent to the terms in PFA [6], [27], [50], [51].

12) *Exponential Decay (Expdecsuc and Expdecfail)*: This expression, first tested by Gong et al. [4], uses the decayed count of right or wrong. Also part of R-PFA, it is used for tracking failures only, whereas R-PFA uses propdec to track correctness [3]. The function is generally the same as for expdecaf. However, when used with a performance factor, the exponential decay weights on the events seen recently, so a history of recent successes or failures might quickly change predictions since only the recent events count for much, especially if the decay rate is relatively fast.

13) *Linear Sum Performance (Linecomp)*: This term, created for this article, uses the successes minus failures to provide a simple summary of overall performance. This feature is parsimonious and less likely to lead to model overfitting or multicollinearity.

14) *Proportion (Prop)*: This expression, created for this article, uses the prior probability correct. It is seeded at .5 for the first attempt.

15) *Exponential Decay of Proportion (Propdec and Propdec2)*: This expression, introduced as part of the R-PFA model [3], [52], [53], uses the prior probability correct. This function requires an additional nonlinear parameter to characterize the exponential rate of decay. For propdec, we set the number of ghost successes at 1 and ghost failures at 1. This modification of Galyardt and Goldin [3] produces an initial value that can either decrease or increase, unlike the Galyardt and Goldin version (propdec2), which can only increase due to the use of three ghost failures and no ghost successes. Our initial comparisons in Table IV show that the modified version works to track subject-level variance during learning. Galyardt and Goldin [3] illustrate an extensive number of examples of propdec2's behavior across patterns of successful and unsuccessful trials at various parameter values. The new propdec behaves analogously, except it starts at a value of 0.5 to represent the different ratio of ghost success to failure at the beginning of practice. As a point of fact, the number of ghost attempts of each type are additional parameters, and we have implemented two settings: 1) one ghost success and one ghost failure (propdec); or 2) three ghost failures (propdec2).

16) *Logit (Logit)*: This expression, created for this article, uses the logit (natural log of the success divided by failures). This function requires an additional nonlinear parameter to characterize the initial number of successes or failures.

17) *Exponential Decay of Logit (Logitdec)*: This expression, created for this article, uses the logit (natural log of the success divided by failures) with the decayed counts like R-PFA, assuming exponential decay and 1 ghost success and 1 ghost failure.

D. Feature Types

The standard feature type (except for intercept, which is always fit with a coefficient for each level) is fit with the same coefficient for all levels of the component factor. Features may also be fit for each level of the component feature with the \$ operator, which causes LKT to use the R model formula operator ":" to fit a coefficient for each level of the component factor (which indicates a regression interaction without main effects in R notation). The most straightforward example of this interaction is for KCs. As shown in Table II, all the models use \$ to indicate they fit a different coefficient for each KC. For example, in AFM variants, each KC gets a coefficient to characterize how fast it is learned across opportunities. If a \$ operator is not present, a single coefficient would be fit for the feature. Not using the \$ operator is particularly relevant when finding a student-level predictor. The \$ operator would produce a unique coefficient for each student, indicating the different effects of the feature depending on the student. In this article, we are specifically focused on models that generalize to a new set of students, so we wish to avoid models that require such individual student parameters. For this reason, we do not use the \$ operator to compute the interaction by the

TABLE II
MAIN COMPARISON MODELS FOR THE DATASETS

#	Model Features	Variant of
1	propdec _{Student} + intercept _{KC} + lineafm _{KC}	AFM
2	propdec _{Student} + intercept _{KC} + logafm _{KC}	AFM
3	propdec _{Student} + intercept _{KC} + linesuc _{KC} + linefail _{KC}	PFA
4	propdec _{Student} + intercept _{KC} + logsuc _{KC} + logfail _{KC}	PFA
5	propdec _{Student} + intercept _{KC} + logsuc _{KC} + logfail _{KC} + recency _{KC}	PFA
6	propdec _{Student} + intercept _{KC} + expdec _{suc} _{KC} + expdec _{fail} _{KC}	PFA-Decay
7	propdec _{Student} + intercept _{KC} + propdec _{KC}	R-PFA
8	propdec _{Student} + intercept _{KC} + propdec _{KC} + logfail _{KC}	R-PFA
9	propdec _{Student} + intercept _{KC} + propdec _{KC} + expdec _{fail} _{KC}	R-PFA
10	propdec _{Student} + intercept _{KC} + propdec _{KC} + ppe _{KC}	PPE
11	propdec _{Student} + intercept _{KC} + propdec _{KC} + base2 _{KC}	new
12	propdec _{Student} + intercept _{KC} + propdec _{KC} + base4 _{KC}	new

TABLE III
STUDENT VARIANCE ONLY MODELS USED IN INITIAL COMPARISON FOR THE DATASETS

#	Model Feature(s)
1	intercept@ _{Student}
2	intercept _{Student}
3	propdec _{Student}
4	propdec2 _{Student}
5	logitdec _{Student}
6	intercept _{Student} + propdec _{Student}

student (as shown in Table II). Intercept features can be modified with the @ operator, which produces random intercepts using the lmer package instead of the default fixed intercepts. This feature was included primarily to show the initial comparisons of features for modeling student individual differences in Table III.

E. Learner Data Requirements

The LKT model relies on data being in the DataShop format, but only some columns are needed for the models. The data must consist of practice events for each student, which minimally includes outcome (i.e., correct or incorrect) and optionally includes column(s) identifying times of each practice event, the item id, and any groupings of items into KCs. Additional columns can be used as categorical or quantitative covariates.

The six datasets used in this article were chosen to be representative of variability in real learning: two datasets concerned fact-learning (MH, statistics cloze), some were more procedural (tonal learning), and others were a mixture of learning and application of facts and procedures (Assistments, KDD, Andes). This distinction is important because learning and memory theories make distinct predictions for learning and remembering facts versus procedural information depending on the learning context. The MH dataset has not been publicly released, but the other datasets are available on DataShops, with Memphis DataShop [54] housing the cloze data and the other four datasets residing in the CMU DataShop [55].

TABLE IV
MCFADDEN'S R^2 VALUES FOR STUDENT INDIVIDUAL DIFFERENCE MODELS FOR THE DATASETS

#	Model Feature(s)	Cloze	Tone	Assis	KDD	Andes	MH
1	intercept@ _{Stu.}	0.055	0.054	0.044	0.035	0.054	0.057
2	intercept _{Stu.}	0.077	0.068	0.060	0.038	0.057	0.080
3	propdec _{Stu.}	0.070	0.066	0.062	0.057	0.076	0.060
4	propdec2 _{Stu.}	0.077	0.054	0.066	0.054	0.074	0.066
5	logitdec _{Stu.}	0.071	0.066	0.061	0.057	0.070	0.060
6	intercept@ _{Stu.} + propdec _{Stu.}	0.088	0.080	0.076	0.061	0.092	0.082
7	AFM model	0.293	0.100	0.130	0.130	0.113	0.194
8	PFA model	0.300	0.104	0.132	0.139	0.122	0.204
9	1 param IRT	0.177	0.096	0.122	0.123	0.104	0.095

F. Making a Model From Scratch

Starting with a dataset and making a model from scratch in the current system requires the user to choose from the available list of features. Beyond the 12 models shown in this article, thousands of other models may be created that are effective and reasonable in different contexts. Because of this broad generalizability, we conclude with a brief discussion of how to compose a model using LKT.

Most models begin with some representation of student ability. If the model is meant to generalize to unseen students, this will likely begin with the propdec or logitdec features. Either of these features will quickly capture student variability given a reasonably long sequence of practice data. If the model is meant to have a more post hoc, explanatory function, the average student ability can be captured by student intercepts.

Some representation of the initial difficulty of KCs or items will typically be important since few domains contain skills of equal difficulty. Variable initial difficulty can be accounted for with fixed or random effect intercepts. Fixed effects may be adequate unless the items are truly sampled from some distribution or if the data are sparse. Fixed effects are typically fit for the data's KC level, but fixed effects may also be fit for the items. Since items are frequently nested within KCs, it is possible to create redundant KC models given the item parameters. Fitting more item-level difficulty parameters makes a model more complex but may be acceptable if there is enough data to estimate item difficulties accurately.

After having accounted for differences prior to practice, differences from practice can be considered. Most importantly, there is the effect of learning, and most models include some term that causes an upward slope to performance as practice accumulates. Lineafm is the most basic of these features. The more complex learning features capturing learning may additionally capture forgetting, decreasing marginal return to practice, or spacing effects.

Finally, another useful contribution of LKT is that it enables modelers to evaluate and compare candidate learner models more efficiently. For instance, after the modeler has developed an initial model that cross validates well with dynamic change features, additional adaptive components can be added. It is often useful to think about "splitting" the dynamic features that work well. After fitting a model with lineafm, the modeler could split the feature and instead use linesuc and linefail. Of course, it is possible that simply splitting will not capture the

possible richness of alternative models. For example, the fit statistics of these initial models and the modeler's expertise may lead them to hypothesize that the basefail feature may improve fit due to students forgetting the feedback they receive after incorrect responding. The modeler may ultimately conclude that the most robust parsimonious dynamic change model was a combination of linesuc and basefail. In summary, LKT enables easier navigation through the space of possible learner models, with appropriate tools such as cross-validation and model visualizations being used to confirm that the found models are generalizable.

III. MODELS

We choose the models for our main comparison to show various existing and new logistic models across multiple datasets. The multiplicity of new features we use contrasts past work, which typically only shares one new feature per paper. As discussed in Section I-C, we specifically choose to create models that did not include student parameters, except for models 7–9 provided for reference in Tables III and IV. For this reason, the models we present are particularly applicable for actual use in adaptive learning systems, rather than as analytic tools to understand the properties of the domain or for other purposes. In Table II, the 12 main models are shown. All 12 models use the propdec feature to adapt to students. Models 1 and 2 are versions of the AFM model [7], differing from each other only due to the nonlinear (log) practice function for KCs in model 2. Models 3 and 4 parallel models 1 and 2 in that they are propdec student adaptive versions of the PFA model [6], differing only due to the nonlinear (log) practice function for KCs. Model 5 takes the typically better log versions of PFA and adds a new recency term that gives a boost as a function of when the KC was seen last. Model 6 is the PFA Decay model [4], only differing from the original version because it uses propdec rather than a student intercept. Model 7 uses a simplified R-PFA [3] with only the adaptive KC term, while model 8 uses the standard R-PFA terms (but see above regarding propdec vs. propdec2) with the same adaptive student term. Model 9 attempts to improve on R-PFA by making the count of failures sensitive to recency. Models 10–12 use the knowledge tracing term from R-PFA (like model 7), but instead of adding failure tracking, memory tracking is added. Model 10 does that with the ppe feature [38], while models 11 and 12 use features new to this article to track forgetting (model 11) and spacing effects and forgetting (model 12). In short, the new features are motivated by two insights about feature design. The first insight is that for any particular learning effect, such as recency or forgetting, there may be multiple ways to represent it in a model, and some ways will work better to predict learning. The second insight is that we can design new features by turning to cognitive psychology to provide hypotheses about important learning effects that may be captured by new dynamic or adaptive features. Indeed, the original PFA model was based on insight from a long tradition in cognitive psychology, and the new memory and spacing based features are similarly inspired.

These new and recombined models are made possible by how easy it is to add a new feature to the LKT architecture. Features can be combined with other features to create complex hybrid models. We felt it important that the system allowed many options for replication so that prior ideas can be compared with new options. Table II shows the 12 models we compared for each dataset.

There were 100 runs for each model, and we provide the average test values for McFadden's R^2 and AUC overall. We also provide the mean test RMSE at the subject level (the same values are used to compute the t-test comparison). Each model was tested using student stratification 100 times using a split-half holdout validation procedure with bootstrapped t-tests. This procedure was designed to allow statistical inference (paired t-tests) where the assumptions of the statistic are fully supported. The 100 runs allowed us to estimate a stable mean t-score difference between each of the models. To do this, we took the data for the held-out fold and computed the error for each held out subject for each model. Using the error for each subject with each model, we could compute the differences in error for the same group of held-out subjects for each pairwise model comparison. Since these data are independent, the data are appropriate for a valid paired t-test to see if the difference is greater than 0. We averaged the t-values across the 100 runs to get a more accurate estimate of the test statistic, but this had no influence on power. We include these significance tests after describing the fit of each model.

Since all 12 models use the propdec feature at the student level to dynamically capture student variability (as an alternative to random effects or fixed constants), a first analysis focused on nine initial models to facilitate a comparison of the propdec, propdec2, random and fixed intercepts, and another possible feature to represent students, logitdec (see Table III). Since these models had student intercept parameters, they were not appropriate to cross-validate using our student stratification methods because they cannot be generalized to new students. These comparisons have many fewer parameters than the more complicated main comparison in Table II (which cross-validate without issues, as we can see below), so they can be expected to be stable and were not crossvalidated. We also provide AFM, PFA, and IRT model fits for comparison to the main models.

We applied the same filtering procedure to all six datasets. Students within each dataset were omitted unless they had at least 25 observations. KCs within each dataset were omitted unless they had at least 600 observations. If a student only experienced an example of a KC once, that observation was excluded. Extreme trial duration outliers (>95th percentile) were winsorized to equal the 95th percentile trial duration values. Missing trial duration values were imputed with the overall median trial duration. We applied this procedure to all datasets to maintain consistency and interpretability of results while also ensuring reliable parameter estimates. For some datasets, students were provided hints and additional attempts after making errors (Assistments, KDD, Chinese tones, Andes). We chose only to analyze the correctness of students' initial attempts at the first steps of problems. For example, if a student encountered a problem and was initially incorrect but was eventually correct




Fig. 3. Statistics cloze p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with the average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < .05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

after being provided additional hints, only that initial attempt was included. If the student reencountered the same problem later, again, only the initial attempt would be included. There are practical and theoretical reasons for this focus. For example, if a student answers a multiple-choice problem and is initially incorrect (and told that they are), accuracy will necessarily increase for subsequent attempts immediately following that feedback purely due to the process of elimination (assuming that the student would not pick the same incorrect answer). Second, in many cases, the hints are progressively stronger, eventually providing the correct answer. Finally, our focus is to fit models that track performance and learning over time and across attempts, not the cognitive processes associated with learning from feedback (or following prompts) immediately after the student provides an incorrect answer. Modeling such cognitive processes is a valuable research area but is beyond the scope of this work.

IV. RESULTS

A. Initial Student Feature Comparison for Datasets

Table IV below shows McFadden's R^2 results for some models of student individual differences. This analysis aimed to evaluate how the adaptive methods compared to fixed and random intercepts as approaches to capture individual differences. This analysis shows the similarity of fits for the two intercept-based measures and the three adaptive measures. The sixth model shows how little additional benefit is provided by combining the intercept and the propdec features, suggesting that the propdec feature is highly colinear with the intercept.

All of the models were computed with fixed-effect coefficients (except for #1 shown for comparison purposes).

B. Statistics Content Cloze Items

The statistics cloze dataset included 58 316 observations from 478 participants who learned statistical concepts by reading sentences and filling in missing words. Participants were adults recruited from Amazon Mechanical Turk. There were 144 KCs in the dataset, derived from 36 sentences, each with

TABLE V
STATISTICS CLOZE DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	$\text{RMSE}_{\text{test}}$	AUC_{test}
1	lineafm _{KC}	0.265	0.415	0.818
2	logafm _{KC}	0.286	0.408	0.829
3	linesuc _{KC} + linefail _{KC}	0.279	0.413	0.822
4	logsuc _{KC} + logfail _{KC}	0.294	0.408	0.83
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.342	0.392	0.855
6	expdec _{suc_{KC}} + expdec _{fail_{KC}}	0.314	0.4	0.842
7	propdec _{KC}	0.207	0.434	0.782
8	propdec _{KC} + logfail _{KC}	0.303	0.405	0.835
9	propdec _{KC} + expdec _{fail_{KC}}	0.314	0.4	0.842
10	propdec _{KC} + ppc _{KC}	0.346	0.39	0.857
11	propdec _{KC} + base2 _{KC}	0.339	0.393	0.853
12	propdec _{KC} + base4 _{KC}	0.342	0.392	0.854

one of four different possible words missing (cloze items). The number of times specific cloze items were presented was manipulated, as well as the temporal spacing between presentations (narrow, medium, or wide). The post-practice test (filling in missing words) could be after 2 min, one day, or three days (manipulated between students). The stimuli type, manipulation of spacing, repetition of KCs and items, and multiple-day delays made this dataset appropriate for evaluating model fit to well-known patterns in human learning data (e.g., substantial forgetting across delays, benefits of spacing).

The results are displayed in Fig. 3 and Table V. Models with features based on theories of declarative memory (models 10–12) significantly improved fit beyond those that were insensitive to memory decay. These memory models' success was consistent with the learning task (participants being asked to recall missing words) and the spacing intervals between practice attempts. However, not all learning may be as vulnerable to decay [57], as suggested by the next dataset.

C. Chinese Tone Learning

The Chinese tone learning dataset included 48 443 observations from 97 adult participants enrolled in their first Chinese language course in a US university. Data were collected via an automated tutoring system that provided access to hints after errors (hint requests were treated as incorrect in the following analyses). Only first attempts on the first steps of problems were included for analysis, ultimately retaining 47% of the original dataset. There were five KCs, each representing a different tone. These tones differed in their acoustic pitch contours (e.g., rising versus falling pitch). Participants listened to a recording of a tone and then identified the type of tone by pressing one of five buttons. Depending on which of the three conditions a participant was assigned, the label associated with each button included either of the following:

- 1) a number label (1–5) along with the pinyin (an alphabetic system to aid reading Chinese);
- 2) a visual depiction of the auditory contour of that tone as well as the pinyin;
- 3) the visual depiction by itself.

Only first attempts at classifying the tone were included in the present analysis. Missing values for the trial duration were imputed with the overall median trial duration.




Fig. 4. Chinese tone p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with the average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < 0.05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

TABLE VI
CHINESE TONE LEARNING DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	$\text{RMSE}_{\text{test}}$	AUC_{test}
1	lineafm _{KC}	0.0984	0.385	0.698
2	logafm _{KC}	0.0982	0.385	0.709
3	linesuc _{KC} + linefail _{KC}	0.106	0.383	0.704
4	logsuc _{KC} + logfail _{KC}	0.111	0.381	0.722
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.113	0.381	0.724
6	expdec _{suc} _{KC} + expdec _{fail} _{KC}	0.113	0.381	0.725
7	propdec _{KC}	0.108	0.383	0.722
8	propdec _{KC} + logfail _{KC}	0.111	0.382	0.723
9	propdec _{KC} + expdec _{fail} _{KC}	0.112	0.381	0.725
10	propdec _{KC} + ppe _{KC}	0.112	0.382	0.724
11	propdec _{KC} + base2 _{KC}	0.111	0.382	0.724
12	propdec _{KC} + base4 _{KC}	0.11	0.383	0.722

The results are displayed in Fig. 4 and Table VI. In contrast with the cloze dataset, tone learning was not predicted best by the models with memory features. Instead, simpler models that were insensitive to memory decay over time, e.g., Model 8, were sufficient. Differentiating and classifying the perceptual qualities of sounds may not be expected to decay to the same extent as declarative concepts [57]. The distinct differences between the best fitting models for the cloze and tone datasets highlight the need for an overarching framework that allows various knowledge-tracing features to be compared.

D. Assistments

The Assistments dataset included 580 785 observations from 912 middle school students learning mathematics, collected across 2004/2005. The Assistments tutoring system assists students when they answer questions incorrectly by breaking down the original problem into multiple simpler problems (for a detailed explanation, see [58]). Only first attempts on the first steps of problems were included for analysis, ultimately retaining 23% of the original dataset.

The results are displayed in Fig. 5 and Table VII. With the Assistments dataset, R-PFA (model 9) and models with memory features (models 10–12) were not significantly different in fit from each other. However, they were generally better than the other models. This pattern suggests that weighting performance




Fig. 5. Assistments p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < 0.05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

TABLE VII
ASSISTMENTS DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	$\text{RMSE}_{\text{test}}$	AUC_{test}
1	lineafm _{KC}	0.114	0.455	0.715
2	logafm _{KC}	0.118	0.454	0.721
3	linesuc _{KC} + linefail _{KC}	0.117	0.455	0.717
4	logsuc _{KC} + logfail _{KC}	0.12	0.453	0.721
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.125	0.452	0.726
6	expdec _{suc} _{KC} + expdec _{fail} _{KC}	0.124	0.452	0.725
7	propdec _{KC}	0.111	0.456	0.714
8	propdec _{KC} + logfail _{KC}	0.123	0.452	0.724
9	propdec _{KC} + expdec _{fail} _{KC}	0.124	0.452	0.725
10	propdec _{KC} + ppe _{KC}	0.126	0.451	0.726
11	propdec _{KC} + base2 _{KC}	0.125	0.452	0.725
12	propdec _{KC} + base4 _{KC}	0.125	0.452	0.725

according to recency (which all of the better performing models could achieve) was important.

E. KDD Cup

Random subsets of the KDD cup 2005/2006 dataset (809, 694 observations) were used in the present analyses. For each of the 100 runs, we randomly choose 120 students of the total 574 students in the file. In the original study, students learned algebra using the Cognitive tutor system and were given feedback on their responses as well as solution hints (see [59]). Only first attempts on the first steps of problems were included for analysis, which included 87% of observations. There were typically 39 KCs in a run.

The results are displayed in Fig. 6 and Table VIII. In the KDD cup dataset, models 1–3 tended to provide worse fits than more complex models. As was found with the Assistments dataset, superior models included features that could weight performance according to recency, but explicitly accounting for memory decay was not as relevant.

F. Andes

In the Andes dataset, 66 students learned physics using the Andes tutoring system, generating 345 536 observations. Because participants were given feedback and solution hints on their responses and were asked qualitative “reflective”




Fig. 6. KDD cup p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with the average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < 0.05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

TABLE VIII
KDD DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	$\text{RMSE}_{\text{test}}$	AUC_{test}
1	lineafm _{KC}	0.128	0.379	0.731
2	logafm _{KC}	0.129	0.378	0.733
3	linesuc _{KC} + linefail _{KC}	0.139	0.376	0.74
4	logsuc _{KC} + logfail _{KC}	0.147	0.374	0.749
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.161	0.372	0.761
6	expdec _{KC} + expdecfail _{KC}	0.152	0.373	0.754
7	propdec _{KC}	0.149	0.374	0.753
8	propdec _{KC} + logfail _{KC}	0.152	0.373	0.754
9	propdec _{KC} + expdecfail _{KC}	0.152	0.373	0.753
10	propdec _{KC} + ppe _{KC}	0.169	0.37	0.768
11	propdec _{KC} + base2 _{KC}	0.154	0.373	0.755
12	propdec _{KC} + base4 _{KC}	0.155	0.373	0.756




Fig. 7. Andes p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < 0.05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

questions after feedback [60], only first attempts on the first steps of problems were included for analysis, which included 36% of the original dataset. There were 45 KCs.

The results are displayed in Fig. 7 and Table IX. For Andes, several different models provided notable benefits over the simpler models. The PPE model (#10) was again the best fitting model. Models 11–12 (that have some similarities to PPE) also fit well. Interestingly, model 5 was the second-best fitting model. Inspecting the differences in performance between models 5 and

TABLE IX
ANDES DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	$\text{RMSE}_{\text{test}}$	AUC_{test}
1	lineafm _{KC}	0.131	0.394	0.732
2	logafm _{KC}	0.131	0.394	0.733
3	linesuc _{KC} + linefail _{KC}	0.143	0.391	0.741
4	logsuc _{KC} + logfail _{KC}	0.146	0.39	0.743
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.155	0.388	0.753
6	expdec _{KC} + expdecfail _{KC}	0.148	0.389	0.746
7	propdec _{KC}	0.143	0.39	0.743
8	propdec _{KC} + logfail _{KC}	0.149	0.389	0.746
9	propdec _{KC} + expdecfail _{KC}	0.148	0.389	0.746
10	propdec _{KC} + ppe _{KC}	0.165	0.386	0.762
11	propdec _{KC} + base2 _{KC}	0.149	0.389	0.746
12	propdec _{KC} + base4 _{KC}	0.151	0.389	0.748




Fig. 8. McGraw Hill p-values, sorted by mean model p-value, for pairwise model comparisons for heldout-subjects. Figure rows and columns are sorted with average lowest p-values on top for the y-axis and the right for the x-axis. * indicates uncorrected $p < 0.05$ for the two-sided test. ** indicates significance after adjusting p-values to control false discovery rate [56].

4 indicates that the recency feature may have been beneficial (the only difference between those two models).

G. McGraw Hill

The McGraw Hill dataset contained 124 387 observations from 1047 adult participants. Participants were college students taking coursework on fitness and nutrition that incorporated an intelligent tutoring system. The questions had multiple-choice or multiple-answer formats. Corrective feedback was provided immediately regardless of their correctness. Broadly, the task required recalling information more so than applying skills (in contrast to the Assistments and KDD datasets). There were 111 KCs.

The results are displayed in Fig. 8 and Table X. There were large differences in fit between the best model (model 10) and the worst fitting model (model 1), similar to the cloze dataset. In both cases, students needed to learn and recall factual information, which is more prone to decay over time. Consequently, models that explicitly attempted to track such decay did better (models 10–12). Models that indirectly tracked these changes over time also performed better, such as those using propdec without memory features (models 7–9), exponential decay (model 6), and recency (model 5). Although features like propdec may not have been explicitly developed with memory decay in mind, they

TABLE X
MCGRAW HILL DATA FIT STATISTICS FOR THE 12 MODELS

#	Model Abbreviation	R^2_{test}	RMSE _{test}	AUC _{test}
1	lineafm _{KC}	0.102	0.458	0.717
2	logafm _{KC}	0.158	0.433	0.768
3	linesuc _{KC} + linefail _{KC}	0.109	0.457	0.718
4	logsuc _{KC} + logfail _{KC}	0.167	0.431	0.766
5	logsuc _{KC} + logfail _{KC} + recency _{KC}	0.271	0.389	0.82
6	expdec _{KC} + expdecfail _{KC}	0.268	0.391	0.819
7	propdec _{KC}	0.165	0.423	0.769
8	propdec _{KC} + logfail _{KC}	0.217	0.408	0.795
9	propdec _{KC} + expdecfail _{KC}	0.269	0.39	0.821
10	propdec _{KC} + ppe _{KC}	0.275	0.388	0.823
11	propdec _{KC} + base2 _{KC}	0.223	0.408	0.795
12	propdec _{KC} + base4 _{KC}	0.22	0.408	0.794

can indirectly account for some of the variance tracked by memory-based models.

V. GENERAL DISCUSSION

The results demonstrate the generality of the LKT framework across multiple models and datasets. This article's analyses demonstrated how LKT could combine various old, modified, and new features to replicate older models and provide examples of new models. The new models outperformed the standard models (e.g., AFM, PFA), demonstrating the utility of LKT. LKT is powerful because these methods are general to a library of features, can be applied broadly to experimental and naturalistic learning data, and allow easy specification of hierarchal models with multiple terms.

LKT shows how logistic regression can serve as an extensible system for learner performance modeling, because it is open-source and written in the widely used R statistical programming language. Individual features can be added as part of the LearnSphere project or submitted to our GitHub R repository for inclusion in the main code [61]. Often adding new features requires adding only a few lines of code, after which the new feature can be freely combined to form complex models.

The heart of LKT is the specification system that opens a new realm of possible models by making explicit the many choices that occur in the process. We hope users of the system will arrive at better models through greater awareness of the palette of choices a modeler of learning must make to arrive at a model suitable for their purpose. LKT is intended to make the model-building process more systematic by providing this menu of choices and understanding that ordering off the menu is possible (i.e., adding a new feature to the LKT system).

A. Specific Comparisons

Other than the general utility of the LKT method, there were also some specific results revealed by the comparisons. One interesting result was a contrast in the general model structure for some of the models we tested. Specifically, models 10–12 (the models with memory terms combined with the propdec feature) performed at least as well as the most accurate PFA version, R-PFA. In datasets where students learned more facts instead of procedural skills, models that included memory features tended to outperform those that did not. This advantage

has two parts. The first part is that the memory terms in models 10–12 are capturing new variance that was not captured by the expdecfail term in model 9. The second aspect is in the model structure since models 10–12 conveniently separate performance gain into two terms, one term captures the memory benefit that occurs regardless of the success or failure (which assumes feedback is provided in the task), and the other term captures any adjustment to those gains based on tracking the average performance. This model structure may solve one of the key failings of the PFA model methods, which is that they inherently obscure the difference between model adjustments as a function of prior performance and model adjustments as a function of learning. In PFA type models, one term represents the combined learning and performance resulting from prior success, and the other term represents the combined learning and performance resulting from prior failures. This difference may be significant in considerations about which item to choose in an adaptive system since the modeler may wish to select items based on what causes the largest jump in learning rather than the largest jump in performance.

The importance of prior practice's recency as a feature is highlighted by the strength of the R-PFA, PPE, and log PFA with the recency term model (model 5). These three models allow recency effects to dominate the model to the extent they are important for prediction. In R-PFA, proportion correct and count of errors exhibit exponential decay, which makes effects highly dependent on the most recent observations. In PPE, the prior ages of trials can be weighted to recent vs. older, which affects how recency and general forgetting are balanced in the data. In the log PFA model with the simple recency feature, we have further evidence that the recency of similar practices by itself is a highly useful predictor.

The importance of forgetting was highlighted by the PPE, base2, and base4 features in the statistics cloze data results. All three of these models did significantly better than all the recency only models, but only for this dataset. This result was also interesting because this dataset coded the KC at the item level. Hence, repetitions in this model were verbatim repetitions where declarative memory might be expected to be a crucial factor in response accuracy (similar to [41]). In contrast, for the other datasets, base2 and base4 did not provide important advantages. This result suggests that memory features may be useful when a model is used to trace learning for verbatim repetitions of an item.

Other contrasts were similarly interesting and perhaps useful. For example, in all the datasets, the logafm and log PFA models provide large gains relative to the linear models. The consistent advantage of a log transformation indicates that the effect of trials typically shows diminishing marginal returns, a characteristic of the natural log function. These diminishing marginal returns hint at the unexplored possibility that features based on a power function for practice might provide substantial improvement and be more precise in targeting the learning function's curvature. In fact, in addition to the memory factors, PPE uses a power function to scale the effect of prior practice. Thus, PPE combines a flexible practice curve with a similarly flexible forgetting function.

There are also two noticeable patterns in model fit across the different content domains. Specifically, the models were notably worse for the Chinese tones for capturing learning, with only trivial differences in the fit's quality for different models. We suspect this is due to the categorical learning task involved, with only four skills for the four tones. In this sort of learning, we might not expect much progress with each repetition (slow learning), so the learning terms do not help much. Even when they do, the learning models do not capture transfer between KCs, which may be an important part of category learning (i.e., if a student learns tone 2, tones 1, 3, and 4 all become easier). Similarly, since it is a perceptual task, it is more similar to procedural tasks where forgetting is typically low, so memory factors help little in prediction. Finally, there is strong evidence that the similarity between the present item and recently presented items has important effects on learning when learning categories. For instance, if categories A and B are similar, presenting examples to facilitate comparison across exposures (e.g., ABABAB) may benefit learning more than blocking them (e.g., AAABBB) if the categories are highly similar [62]. This aspect of category learning is distinct from learning in the other datasets and was not directly accounted for with the included model features. Model features could undoubtedly be generated to account for such effects (e.g., [63]). We also expect a model with transfer between the KC would do better for the Chinese tones.

The second pattern is the difference between the memory-based tasks (MHE and Cloze datasets) and the other tasks that are more procedural/conceptual/perceptual. While recency has some benefits in most of the datasets, this benefit, and the benefits from general forgetting (which is colinear with recency) in the model are most strong for these two datasets. In both datasets, the KCs were individual items, so it was quite sensible that memory factors play a crucial role since the items can be memorized to succeed in the task. For both datasets, the practice's intent was meaningful processing of the verbatim content to produce deep learning, but this does not prevent memory from being a crucial factor in such learning.

B. Using LKT

LKT is intended to accelerate future research by making the process of designing adaptive learner models more transparent and systematic. In the past, designers of learner models have moved forward slowly due to the large overhead costs of organizing data and coding the model features with custom-designed code. With LKT, researchers can quickly test many different learner model configurations. In particular, nonlinear features are easy to use and combine in the system, whereas standard logistic regression modeling does not allow for this. The ability to easily fit and compare multiple models may also reveal the subtle behavior of existing features. For instance, although the propdec feature that is part of R-PFA does not track the time between attempts, it does adjust based on recent performance. In many cases, this ability was enough to perform similarly to models that track actual time between attempts.

Interacting with LKT is possible at two levels. First, LKT is implemented in LearnSphere and is immediately available to run on most of the more than 3400 datasets on the DataShop data repository. If the data are in DataShop format, it can be uploaded into the LearnSphere even if it is not already in the DataShop repository, so any data converted to DataShop format can be immediately analyzed. LKT code is also publicly shared as an R package [61]. Recent upgrades to both implementations make LKT extremely fast by relying on sparse model matrices and the data table and LibLineaR packages. These upgrades are allowing analyses previously impossible in base R glm logistic regression.

C. Limitations and Future Directions

It is important to clarify that this work fits learner models given specific features and an already determined hierarchy (i.e., designations of KCs and students). Another large learner modeling area is concerned with specifying the domain model given the data [7], [64]. In domain model research, the goal is to group the items into KCs, or other often hierarchical groupings, which we assume as input in this article. Adding such automatic domain model improvement is one future direction we are working on. Our current approach first groups existing KCs or items to form a nonorthogonal Q-matrix where KCs are not independent and then computes an averaged feature as a function of the KCs involved for any observed performance. Recent work has also included other model enhancement features, such as options for testing the model with elastic net fitting, allowing reduction of the model to represent the set of relevant predictors more compactly.

Another limitation is the limited support for random effects, with only intercepts (e.g., random-effect constants) permitted in the syntax. This limitation might be a problem for some theoretical model comparisons. Our primary interests in this article were evaluating learner models that could be used in an applied context. So we avoided using subject fixed- or random-effects because they are usually difficult to estimate ahead of time. Since the datasets in this article had many observations for each KC, we choose to fit KC effects as fixed-effect constants since there are typically enough examples for each KC across students to get a reliable fixed estimate. It is also arguable that KCs should be represented as fixed effects because they are independent skills and should not be subjected to random effects shrinkage to a common mean [65]. However, researchers can use random intercepts for KCs when fitting models with LKT.

A next step in this research is to include a latency model to allow users to predict the costs of practice (in units of time) and estimate practice efficiency in terms of a gain per unit of time. With latency predictions, it becomes possible to predict the gain/cost (i.e., the efficiency) for possible practice selections. These predictions can be used to determine practice selection in an adaptive learning system such as ACT-R memory models used in prior work [15]. The models presented in this article are more suitable for mastery determination purposes in their current form, which is a crucial step in the

mastery learning algorithm [13], [48]. A goal of the present research was to bring EDM models together with the more complex memory-related features to create a simple and general framework. This article is the completion of an initial stage in that process.

Finally, after having completed this stage, it has become apparent that the feature specification methods can be enhanced. Currently, interactive features such as base, which multiplies log of the count of prior trials by a forgetting term (see Table I), are fixed in their current formulation. This hardcoding means that making new features that are simple interactions of other features currently requires modifying the underlying R code. A future version of LKT will include enhanced functionality to make interaction terms by composing simple features to create features such as base4 or PPE without having to code them in R.

ACKNOWLEDGMENT

Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of NSF of IES. The authors would also like to thank the High Performance Computing Center at the University of Memphis, which provided computer time for the analyses.

REFERENCES

- [1] R. Pelánek, "Bayesian knowledge tracing, logistic models, and beyond: An overview of learner modeling techniques," *User Model. User-Adapted Interact.*, vol. 27, no. 3–5, pp. 313–350, Dec. 2017, doi: [10.1007/s11257-017-9193-2](https://doi.org/10.1007/s11257-017-9193-2).
- [2] K. R. Koedinger, M. V. Yudelson, and P. I. Pavlik, "Testing theories of transfer using error rate learning curves," *Topics Cogn. Sci.*, vol. 8, no. 3, pp. 589–669, Jul. 2016, doi: [10.1111/tops.12208](https://doi.org/10.1111/tops.12208).
- [3] A. Galyardt and I. Goldin, "Move your lamp post: Recent data reflects learner knowledge better than older data," *J. Educ. Data Mining*, vol. 7, no. 2, pp. 83–108, Sep. 2015, doi: [10.5281/zenodo.3554671](https://doi.org/10.5281/zenodo.3554671).
- [4] Y. Gong, J. E. Beck, and N. T. Heffernan, "How to construct more accurate student models: Comparing and optimizing knowledge tracing and performance factor analysis," *Int. J. Artif. Intell. Educ.*, vol. 21, no. 1/2, pp. 27–46, Jan. 2011, doi: [10.3233/JAI-2011-016](https://doi.org/10.3233/JAI-2011-016).
- [5] P. De Boeck et al., "The estimation of item response models with the lmer function from the lme4 package in R," *J. Stat. Softw.*, vol. 39, no. 12, pp. 1–28, Dec. 2011, doi: [10.18637/jss.v039.i12](https://doi.org/10.18637/jss.v039.i12).
- [6] P. I. Pavlik Jr., H. Cen, and K. R. Koedinger, "Performance factors analysis – A new alternative to knowledge tracing," in *Proc. 14th Int. Conf. Artif. Intell. Educ.*, 2009, pp. 531–538. [Online]. Available: <https://files.eric.ed.gov/fulltext/ED506305.pdf>
- [7] H. Cen, K. R. Koedinger, and B. Junker, "Is over practice necessary? – Improving learning efficiency with the cognitive tutor through educational data mining," in *Proc. 13th Int. Conf. Artif. Intell. Educ.*, 2007, pp. 511–518. [Online]. Available: <https://pslcdatashop.web.cmu.edu/DownloadPaper?fileName=LFA%20Efficiency%20Study%203.61%20use%20the%20official%20template.pdf&fileId=43&datasetId=76>
- [8] K. R. Koedinger, R. S. Baker, K. Cunningham, A. Skogsholm, B. Leber, and J. Stamper, "A data repository for the EDM community: The PSLC datashop," in *Handbook of Educational Data Mining*, C. Romero, S. Ventura, and M. Pechenizkiy, Eds. Boca Raton, FL, USA: CRC Press, 2010, pp. 43–56.
- [9] J. Stamper and K. Koedinger, "Human-machine student model discovery and improvement using datashop," in *Proc. 15th Int. Conf. Artif. Intell. Educ.*, G. Biswas, S. Bull, J. Kay, and A. Mitrovic, Eds. Auckland, New Zealand, 2011, pp. 353–360, doi: [10.1007/978-3-642-21869-9_46](https://doi.org/10.1007/978-3-642-21869-9_46).
- [10] J. Stamper et al., "Educational data analysis using learnsphere workshop," in *Proc. 9th Int. Conf. Educ. Data Mining*, J. Rowe and E. Snow, Eds. Raleigh, NC, USA, 2016. [Online]. Available: <http://ceur-ws.org/Vol-1633/>
- [11] C. R. Kelley, "What is adaptive training?," *Hum. Factors*, vol. 11, no. 6, pp. 547–556, Dec. 1969, doi: [10.1177/001872086901100602](https://doi.org/10.1177/001872086901100602).
- [12] R. C. Atkinson, "Ingredients for a theory of instruction," *Amer. Psychol.*, vol. 27, no. 10, pp. 921–931, Oct. 1972, doi: [10.1037/h0033572](https://doi.org/10.1037/h0033572).
- [13] A. T. Corbett and J. R. Anderson, "Student modeling and mastery learning in a computer-based programming tutor," in *Proc. 2nd Int. Conf. Intell. Tutoring Syst.*, 1992, pp. 413–420. [Online]. Available: https://link.springer.com/chapter/10.1007%2F3-540-55606-0_49
- [14] M. M. Khajah, R. V. Lindsey, and M. C. Mozer, "Maximizing students' retention via spaced review: Practical guidance from computational models of memory," *Topics Cogn. Sci.*, vol. 6, no. 1, pp. 157–169, Jan. 2014, doi: [10.1111/tops.12077](https://doi.org/10.1111/tops.12077).
- [15] P. I. Pavlik Jr. and J. R. Anderson, "Using a model to compute the optimal schedule of practice," *J. Exp. Psychol. Appl.*, vol. 14, no. 2, pp. 101–117, Jun. 2008, doi: [10.1037/1076-898X.14.2.101](https://doi.org/10.1037/1076-898X.14.2.101).
- [16] L. G. Eglington and P. I. Pavlik Jr., "Optimizing practice scheduling requires quantitative tracking of individual item performance," *Npj Sci. Learn.*, vol. 5, Oct. 2020, Art. no. 15, doi: [10.1038/s41539-020-00074-4](https://doi.org/10.1038/s41539-020-00074-4).
- [17] P. I. Pavlik Jr., A. M. Olney, A. Banker, L. Eglington, and J. Yarbrow, "The mobile fact and concept textbook system (MoFaCTS)," in *Proc. 21st Int. Conf. Artif. Intell. Educ.*, 2020, pp. 35–49. [Online]. Available: <http://ceur-ws.org/Vol-2674/>
- [18] A. Mitrovic and B. Martin, "Evaluating the effect of open student models on self-assessment," *Int. J. Artif. Intell. Educ.*, vol. 17, no. 2, pp. 121–144, Jan. 2007, doi: [10.1.1.471.2146](https://doi.org/10.1.1.471.2146).
- [19] G. Rasch, "An item analysis which takes individual differences into account," *Brit. J. Math. Stat. Psychol.*, vol. 19, no. 1, pp. 49–57, May 1966, doi: [10.1111/j.2044-8317.1966.tb00354.x](https://doi.org/10.1111/j.2044-8317.1966.tb00354.x).
- [20] F. M. Lord, "The relation of test score to the trait underlying the test," *Educ. Psychol. Meas.*, vol. 13, no. 4, pp. 517–549, Dec. 1953, doi: [10.1177/001316445301300401](https://doi.org/10.1177/001316445301300401).
- [21] G. H. Fischer, "The linear logistic test model as an instrument in educational research," *Acta Psychol.*, vol. 37, no. 6, pp. 359–374, Dec. 1973, doi: [10.1016/0001-6918\(73\)90003-6](https://doi.org/10.1016/0001-6918(73)90003-6).
- [22] K. K. Tatsuoka, "Rule space: An approach for dealing with misconceptions based on item response theory," *J. Educ. Meas.*, vol. 20, no. 4, pp. 345–354, 1983, doi: [10.1111/j.1745-3984.1983.tb00212.x](https://doi.org/10.1111/j.1745-3984.1983.tb00212.x).
- [23] T. Barnes, "The Q-matrix method: Mining student response data for knowledge," in *Proc. 20th Nat. Conf. Amer. Assoc. Artif. Intell. Educ. Data Mining Workshop*, 2005, pp. 39–46. [Online]. Available: <https://www.aaai.org/Papers/Workshops/2005/WS-05-02/WS05-02-006.pdf>
- [24] K. R. Koedinger, A. T. Corbett, and C. Perfetti, "The knowledge-learning-instruction framework: Bridging the science-practice chasm to enhance robust student learning," *Cogn. Sci.*, vol. 36, no. 5, pp. 757–798, Jul. 2012, doi: [10.1111/j.1551-6709.2012.01245.x](https://doi.org/10.1111/j.1551-6709.2012.01245.x).
- [25] H. Scheiblechner, "Das lernen und losen komplexer denkaufgaben," *J. Exp. Appl. Psychol.*, vol. 19, pp. 476–506, 1972.
- [26] H. Spada and B. McGaw, "The assessment of learning effects with linear logistic test models," in *Test Design: Developments in Psychology and Psychometrics*, S. Embretson, Ed. Orlando, FL, USA: Academic, 1985, pp. 169–194.
- [27] Y. Gong, J. Beck, and N. T. Heffernan, "Comparing knowledge tracing and performance factor analysis by using multiple model fitting procedures," in *Proc. 10th Int. Conf. Intell. Tutoring Syst.*, 2010, pp. 35–44, doi: [10.1007/978-3-642-13388-6_8](https://doi.org/10.1007/978-3-642-13388-6_8).
- [28] C. P. Thompson, S. K. Wenger, and C. A. Bartling, "How recall facilitates subsequent recall: A reappraisal," *J. Exp. Psychol. Hum. Learn. Memory*, vol. 4, no. 3, pp. 210–221, May 1978, doi: [10.1037/0278-7393.4.3.210](https://doi.org/10.1037/0278-7393.4.3.210).
- [29] P. I. Pavlik Jr., "Understanding and applying the dynamics of test practice and study practice," *Instructional Sci.*, vol. 35, no. 5, pp. 407–441, Sep. 2007, doi: [10.1007/s11251-006-9013-2](https://doi.org/10.1007/s11251-006-9013-2).
- [30] S. K. Carpenter, H. Pashler, J. T. Wixted, and E. Vul, "The effects of tests on learning and forgetting," *Memory Cognition*, vol. 36, no. 2, pp. 438–448, Mar. 2008, doi: [10.3758/mc.36.2.438](https://doi.org/10.3758/mc.36.2.438).
- [31] T. C. Rickard, "A CMPL alternative account of practice effects in numerosity judgment tasks," *J. Exp. Psychol. Learn. Memory Cognition*, vol. 25, no. 2, pp. 532–542, Feb. 1999, doi: [10.1037/0278-7393.25.2.532](https://doi.org/10.1037/0278-7393.25.2.532).
- [32] L. R. Peterson, "Paired-associate latencies after the last error," *Psychonomic Sci.*, vol. 2, no. 6, pp. 167–168, Jan. 1965, doi: [10.3758/BF03343385](https://doi.org/10.3758/BF03343385).
- [33] T. C. Rickard, "Bending the power law: A CMPL theory of strategy shifts and the automatization of cognitive skills," *J. Exp. Psychol. General*, vol. 126, no. 3, pp. 288–311, Mar. 1997, doi: [10.1037/0096-3445.126.3.288](https://doi.org/10.1037/0096-3445.126.3.288).

- [34] N. S. Segalowitz and S. J. Segalowitz, "Skilled performance, practice, and the differentiation of speed-up from automatization effects - Evidence from 2nd-language word recognition," *Appl. Psycholinguistics*, vol. 14, no. 3, pp. 369–385, Sep. 1993, doi: [10.1017/S0142716400010845](https://doi.org/10.1017/S0142716400010845).
- [35] N. A. Taatgen and F. J. Lee, "Production compilation: Simple mechanism to model complex skill acquisition," *Hum. Factors*, vol. 45, no. 1, pp. 61–76, Mar. 2003, doi: [10.1518/hfes.45.1.61.27224](https://doi.org/10.1518/hfes.45.1.61.27224).
- [36] M. Chi, K. R. Koedinger, G. Gordon, P. Jordan, and K. VanLehn, "Instructional factors analysis: A cognitive model for multiple instructional interventions," in *Proc. 4th Int. Conf. Educ. Data Mining*, 2011, pp. 61–70. [Online]. Available: https://educationaldatamining.org/EDM2011/wp-content/uploads/proc/edm2011_paper1_full_Chi.pdf
- [37] R. V. Lindsey, J. D. Shroyer, H. Pashler, and M. C. Mozer, "Improving students' long-term knowledge retention through personalized review," *Psychol. Sci.*, vol. 3, no. 3, pp. 639–647, Jan. 2014, doi: [10.1177/0956797613504302](https://doi.org/10.1177/0956797613504302).
- [38] M. M. Walsh *et al.*, "Mechanisms underlying the spacing effect in learning: A comparison of three computational models," *J. Exp. Psychol. General*, vol. 147, no. 9, pp. 1325–1348, Sep. 2018, doi: [10.1037/xge0000416](https://doi.org/10.1037/xge0000416).
- [39] W. A. Wickelgren, "Single-trace fragility theory of memory dynamics," *Memory Cognition*, vol. 2, no. 4, pp. 775–780, Jul. 1974, doi: [10.3758/BF03198154](https://doi.org/10.3758/BF03198154).
- [40] J. R. Anderson, J. M. Fincham, and S. Douglass, "Practice and retention: A unifying analysis," *J. Exp. Psychol. Learn. Memory Cognition*, vol. 25, no. 5, pp. 1120–1136, May 1999, doi: [10.1037/0278-7393.25.5.1120](https://doi.org/10.1037/0278-7393.25.5.1120).
- [41] P. I. Pavlik Jr. and J. R. Anderson, "Practice and forgetting effects on vocabulary memory: An activation-based model of the spacing effect," *Cogn. Sci.*, vol. 29, no. 4, pp. 559–586, Jul. 2005, doi: [10.1207/s15516709cog0000_14](https://doi.org/10.1207/s15516709cog0000_14).
- [42] T. D. Wickens and C. Izawa, "Measuring the time course of retention," in *On Human Memory: Evolution, Progress, and Reflections on the 30th Anniversary of the Atkinson-Shiffrin Model*. Mahwah, NJ, USA: Lawrence Erlbaum, 1999, pp. 245–266.
- [43] M. G. Collins, K. A. Gluck, M. Walsh, M. Krusmark, and G. Gunzelmann, "Using prior data to inform model parameters in the predictive performance equation," in *Proc. 38th Mtg. Cogn. Sci. Soc.*, 2016, pp. 75–80. [Online]. Available: <https://cogsci.mindmodeling.org/2016/papers/0026/index.html>
- [44] T. Gervet, K. Koedinger, J. Schneider, and T. Mitchell, "When is deep learning the best approach to knowledge tracing?," *J. Educ. Data Mining*, vol. 12, no. 3, pp. 31–54, Oct. 2020, doi: [10.5281/zenodo.4143614](https://doi.org/10.5281/zenodo.4143614).
- [45] M. Cao, P. I. Pavlik Jr., and G. M. Bidelman, "Incorporating prior practice difficulty into performance factor analysis to model mandarin tone learning," in *Proc. 11th Int. Conf. Educ. Data Mining*, 2019, pp. 516–519. [Online]. Available: <https://educationaldatamining.org/edm2019/proceedings/>
- [46] P. I. Pavlik Jr., T. Bolster, S. Wu, K. R. Koedinger, and B. MacWhinney, "Using optimally selected drill practice to train basic facts," in *Proc. 9th Int. Conf. Intell. Tutoring Syst.*, 2008, pp. 593–602, doi: [10.1007/978-3-540-69132-7_62](https://doi.org/10.1007/978-3-540-69132-7_62).
- [47] C. P. Rosé, E. A. McLaughlin, R. Liu, and K. R. Koedinger, "Explanatory learner models: Why machine learning (alone) is not the answer," *Brit. J. Educ. Tech.*, vol. 50, no. 6, pp. 2943–2958, Nov. 2019, doi: [10.1111/bjet.12858](https://doi.org/10.1111/bjet.12858).
- [48] A. T. Corbett and J. R. Anderson, "Knowledge tracing: Modeling the acquisition of procedural knowledge," *User Model. User-Adapted Interact.*, vol. 4, no. 4, pp. 253–278, Dec. 1994, doi: [10.1007/BF01099821](https://doi.org/10.1007/BF01099821).
- [49] B. Settles and B. Meeder, "A trainable spaced repetition model for language learning," in *Proc. 54th Assoc. Comput. Linguistics*, 2016, pp. 1848–1858, doi: [10.18653/v1/P16-1174](https://doi.org/10.18653/v1/P16-1174).
- [50] P. I. Pavlik Jr., M. Yudelson, and K. R. Koedinger, "Using contextual factors analysis to explain transfer of least common multiple skills," in *Proc. 15th Int. Conf. Artif. Intell. Educ.*, 2011, pp. 256–263, doi: [10.1007/978-3-642-21869-9_34](https://doi.org/10.1007/978-3-642-21869-9_34).
- [51] P. I. Pavlik Jr., M. Yudelson, and K. R. Koedinger, "A measurement model of microgenetic transfer for improving instructional outcomes," *Int. J. Artif. Intell. Educ.*, vol. 25, no. 3, pp. 346–379, Mar. 2015, doi: [10.1007/s40593-015-0039-y](https://doi.org/10.1007/s40593-015-0039-y).
- [52] A. Galyardt and I. Goldin, "Recent-performance factors analysis," in *Proc. 7th Int. Conf. Educ. Data Mining*, 2014, pp. 411–412. [Online]. Available: https://educationaldatamining.org/EDM2014/uploads/procs2014/posters/87_EDM-2014-Poster.pdf
- [53] I. M. Goldin and A. Galyardt, "Convergent validity of a student model: Recent-performance factors analysis," in *Proc. 8th Int. Conf. Educ. Data Mining*, 2015, pp. 548–551. [Online]. Available: <https://www.educationaldatamining.org/EDM2015/proceedings/short548-551.pdf>
- [54] Pittsburgh Science of Learning Center, "DataShop@Memphis," cmu.edu, Accessed: Dec. 1, 2020. [Online]. Available: <https://datashop.memphis.edu>
- [55] Pittsburgh Science Learning Center, "DataShop@CMU," cmu.edu. Accessed: Dec. 1, 2020. [Online]. Available: <https://pslclatashop.web.cmu.edu/>
- [56] Y. Benjamini and D. Yekutieli, "The control of the false discovery rate in multiple testing under dependency," *Ann. Statist.*, vol. 29, no. 4, pp. 1165–1188, Aug. 2001, doi: [10.1214/aos/1013699998](https://doi.org/10.1214/aos/1013699998).
- [57] L. R. Squire, "Declarative and nondeclarative memory: Multiple brain systems supporting learning and memory," *J. Cogn. Neurosci.*, vol. 4, no. 3, pp. 232–243, 1992, doi: [10.1162/jocn.1992.4.3.232](https://doi.org/10.1162/jocn.1992.4.3.232).
- [58] L. Razzaq *et al.*, "The assistment project: Blending assessment and assisting," in *Proc. 12th Int. Conf. Artif. Intell. Educ.*, 2005, pp. 555–562, [Online]. Available: https://www.researchgate.net/publication/221297608_Blending_Assessment_and_Instructional_Assisting
- [59] J. Stamper and Z. Pardos, "The 2010 KDD cup competition dataset: Engaging the machine learning community in predictive learning analytics," *J. Learn. Analytics*, vol. 3, no. 2, pp. 312–316, Sep. 2016, doi: [10.18608/jla.2016.32.16](https://doi.org/10.18608/jla.2016.32.16).
- [60] S. Katz, J. Connelly, and C. Wilson, "Out of the lab and into the classroom: An evaluation of reflective dialogue in Andes," *Front. Artif. Intell. Appl.*, vol. 158, pp. 425–432, Jun. 2007, doi: [10.5555/1563601.1563669](https://doi.org/10.5555/1563601.1563669).
- [61] P. I. Pavlik Jr. and L. G. Eglington, "LKT: Logistic knowledge tracing," R package version 1.0, Aug. 15, 2021. [Online]. Available: <https://CRAN.R-project.org/package=LKT>
- [62] V. X. Yan, B. A. Schuetze, and L. G. Eglington, "A review of the interleaving effect: Theories and lessons for future research," *PsyArXiv*, Dec. 10, 2020, doi: [10.31234/osf.io/ur6g7](https://doi.org/10.31234/osf.io/ur6g7).
- [63] P. F. Carvalho and R. L. Goldstone, "A computational model of context-dependent encodings during category learning," *PsyArXiv*, Sep. 13 2019, doi: [10.31234/osf.io/8psa4](https://doi.org/10.31234/osf.io/8psa4).
- [64] Z. Pardos and A. Dadu, "dAFM: Fusing psychometric and connectionist modeling for Q-matrix refinement," *J. Educ. Data Mining*, vol. 10, no. 2, pp. 1–27, Oct. 2018, doi: [10.5281/zenodo.3554689](https://doi.org/10.5281/zenodo.3554689).
- [65] A. Gelman and J. Hill, *Data Analysis Using Regression and Multilevel/Hierarchical Models*. Cambridge, U.K.: Cambridge Univ. Press, 2006.



Philip I. Pavlik, Jr. received the B.A. degree in economics from the University of Michigan, Ann Arbor, MI, USA, in 1992, and the Ph.D. degree in cognitive psychology from Carnegie Mellon University (CMU), Pittsburgh, PA, USA, in 2005.

From 2006 to 2011, he was a Postdoctoral Fellow and Systems Scientist at the CMU's Human-Computer Interaction Institute, and a Member of the Pittsburgh Science of Learning Center, Pittsburgh. Since 2011, he has been with the University of Memphis, Memphis, TN, USA, where he was first an Assistant

Professor with the Institute for Intelligent Systems and Department of Psychology before being promoted to Associate Professor in 2017. He has published more than 50 articles. His research interests include memory, learning, practice, forgetting, spacing effects, adaptive personalization, mathematical models of learning, and classroom applications of learning technology.

Dr. Pavlik has been an Associate Editor for the IEEE TRANSACTIONS ON LEARNING TECHNOLOGY. He is a Member of the International Society of Educational Data Mining, International Society of Artificial Intelligence in Education, and the Psychonomic Society.



Luke G. Eglington received the B.S. degree in cognitive science from the University of Massachusetts, Boston, MA, USA, in 2013, and the Ph.D. degree in psychological and brain sciences from Dartmouth College, Hanover, NH, USA in 2018.

From 2018 to 2021, he was a Schmidt Futures Learning Engineering Postdoctoral Fellow at the Institute for Intelligent Systems, University of Memphis, Memphis, TN, USA. Since 2021, he has been a Research Scientist with Georgia Tech, Atlanta, GA, USA. His research interests include personalized and

adaptive digital learning environments, mathematical models of learning, category learning, spacing effects, testing effects, mind-wandering, and interactions between attention and memory.

Dr. Eglington has been a Guest Editor for the *Journal of Educational Data Mining*. He is a Member of the Association for the Advancement of Artificial Intelligence, the International Society of Educational Data Mining, the International Society of Artificial Intelligence in Education, and the Psychonomic Society.



Leigh M. Harrell-Williams received the B.A. degree in psychology and business from Virginia Wesleyan College (now University), Norfolk, VA, USA, in 1997, the M.S. degree in statistics from the University of Georgia, Athens, GA, USA, in 2004, and the Ph.D. degree in educational research and evaluation from Virginia Tech, Blacksburg, VA, USA, in 2009.

From 2004 to 2012, she was the Undergraduate Coordinator and Instructor in the Department of Statistics, Virginia Tech. From 2012 to 2014, she was a Postdoctoral Research Assistant at Georgia State

University, Atlanta, GA. Since 2014, she has been with the University of Memphis, Memphis, TN, USA, where she was first an Assistant Professor before being promoted to Associate Professor in 2020. Her research interests include statistics and mathematics education, social cognitive theory, motivation, and teacher and student beliefs and attitudes.

Dr. Harrell-Williams is an Associate Editor for the *Statistics Education Research Journal*. She is a Member of the American Educational Research Association, the American Statistical Association, the Association for Psychological Science, and the Association for Statistics Education.