Faust Standard Libraries

March 17, 2017

Contents

Faust Libraries **15**

Using the Faust Libraries . . . 16

Contributing . . . 17

New Functions . . . 17

New Libraries . . . 18

General Organization . . . 18

Coding Conventions . . . 19

Documentation . . . 20

Library Import . . . 20

"Demo" Functions . . . 21

"Standard" Functions . . . 21

Copyright / License . . . 21

Standard Functions **21**

Analysis Tools . . . 22

Basic Elements . . . 22

Conversion . . . 23

Effects . . . 23

Envelope Generators . . . 24

Filters . . . 24

Oscillators/Sound Generators . . . 25

Synths . . . 25

analyzers.lib **26**
Amplitude Tracking . . . 26
amp_follower . . . 26
amp_follower_ud . . . 27
Spectrum-Analyzers . . . 27
mth_octave_analyzer . . . 28
Mth-Octave Spectral Level . . . 29
mth_octave_spectral_level6e . . . 29
[third|half]_octave_[analyzer|filterbank] . . . 29
Arbitrary-Crossover Filter-Banks and Spectrum Analyzers . . . 30
analyzer . . . 30
amp_follower_ar . . . 30

basics.lib **31**
Conversion Tools . . . 31
samp2sec . . . 31
sec2samp . . . 31
db2linear . . . 32
linear2db . . . 32
lin2LogGain . . . 32
log2LinGain . . . 33
tau2pole . . . 33
pole2tau . . . 33
midikey2hz . . . 34
pianokey2hz . . . 34
hz2pianokey . . . 34
Counters and Time/Tempo Tools . . . 35
countdown . . . 35
countup . . . 35
sweep . . . 35
time . . . 36

tempo 36
period 36
pulse 37
pulsen 37
beat 37
pulse_countup 38
pulse_countdown 38
pulse_countup_loop 38
pulse_countdown_loop 39
Array Processing/Pattern Matching 39
count 39
take 40
subseq 40
Selectors (Conditions) 40
if 40
selector 41
selectn 41
select2stereo 42
Other 42
latch 42
sAndH 42
downSample 43
peakhold 43
peakholder 44
impulsify 44
automat 44
bpf 44
bypass1 45
bypass2 46
toggle 46
on_and_off 46
selectoutn 47

compressors.lib **47**

Functions Reference 47

`compressor_mono` 47

`compressor_stereo` 48

`limiter_1176_R4_mono` 49

`limiter_1176_R4_stereo` 49

delays.lib **50**

Basic Delay Functions 50

`delay` 50

`fdelay` 50

`sdelay` 51

Lagrange Interpolation 51

`fdelaylti` and `fdelayltv` 51

`fdelay[n]` 52

Thiran Allpass Interpolation 52

`fdelay[n]a` 52

demos.lib **53**

Analyzers 53

`mth_octave_spectral_level_demo` 53

Filters 53

`parametric_eq_demo` 53

`spectral_tilt_demo` 54

`mth_octave_filterbank_demo` and `filterbank_demo` 54

Effects 54

`cubicnl_demo` 54

`gate_demo` 55

`compressor_demo` 55

`moog_vcf_demo` 55

`wah4_demo` 55

`crybaby_demo` 56

flanger_demo 56
phaser2_demo 56
stereo_reverb_tester 56
fdnrev0_demo 57
zita_rev_fdn_demo 57
zita_rev1 57
Generators 58
sawtooth_demo 58
virtual_analog_oscillator_demo 58
oscrs_demo 58
velvet_noise_demo 59
latch_demo 59
envelopes_demo 59
exciter 59
vocoder_demo 60
freeverb_demo 60

envelopes.lib **60**
Functions Reference 61
smoothEnvelope 61
ar 61
asr 61
adsr 62
adsre 62

filters.lib **63**
Basic Filters 63
zero 63
pole 64
integrator 64
dcblockerat 64
dcblocker 65

Comb Filters 65
    ff_comb 65
    ff_fcomb 66
    ffcombfilter 66
    fb_comb 66
    fb_fcomb 67
    rev1 67
    fbcombfilter and ffbcombfilter 67
    allpass_comb 68
    allpass_fcomb 69
    rev2 69
    allpass_fcomb5 and allpass_fcomb1a 70
Direct-Form Digital Filter Sections 70
    iir 70
    fir 70
    conv and convN 71
    tf1, tf2 and tf3 71
    notchw 72
Direct-Form Second-Order Biquad Sections 72
    tf21, tf22, tf22t and tf21t 73
Ladder/Lattice Digital Filters 73
    av2sv 73
    bvav2nuv 74
    iir_lat2 74
    allpassnt 75
    iir_kl 75
    allpassnklt 75
    iir_lat1 76
    allpassn1mt 76
    iir_nl 76
    allpassnnlt 77

Useful Special Cases 77
tf2np 77
wgr 78
nlf2 78
apnl 79
Ladder/Lattice Allpass Filters 79
allpassn 80
allpassnn 80
allpasskl 81
allpass1m 81
Digital Filter Sections Specified as Analog Filter Sections 81
tf2s and tf2snp 81
tf3slf 82
tf1s 83
tf2sb 84
tf1sb 84
Simple Resonator Filters 84
resonlp 84
resonhp 85
resonbp 85
Butterworth Lowpass/Highpass Filters 86
lowpass 86
highpass 86
lowpass0_highpass1 87
Special Filter-Bank Delay-Equalizing Allpass Filters 87
lowpass_plus|minus_highpass 87
Elliptic (Cauer) Lowpass Filters 87
lowpass3e 87
lowpass6e 88
Elliptic Highpass Filters 88
highpass3e 88

highpass6e 88
Butterworth Bandpass/Bandstop Filters 89
bandpass 89
bandstop 89
Elliptic Bandpass Filters 90
bandpass6e 90
bandpass12e 90
Parametric Equalizers (Shelf, Peaking) 90
low_shelf 91
high_shelf 91
peak_eq 92
peak_eq_cq 92
peak_eq_rm 93
spectral_tilt 93
levelfilter 94
levelfilterN 95
Mth-Octave Filter-Banks 95
mth_octave_filterbank[n] 96
Arbitrary-Crossover Filter-Banks and Spectrum Analyzers 97
filterbank 97
filterbanki 97

hoa.lib **98**
encoder 98
decoder 98
decoderStereo 99
Optimization Functions 99
optimBasic 99
optimMaxRe 99
optimInPhase 100
Usage 100

wider . . . 100
map . . . 101
rotate . . . 101

maths.lib **101**

Functions Reference . . . 102
SR . . . 102
BS . . . 102
PI . . . 102
FTZ . . . 102
neg . . . 103
sub(x,y) . . . 103
inv . . . 103
cbrt . . . 103
hypot . . . 104
ldexp . . . 104
scalb . . . 104
log1p . . . 104
logb . . . 105
ilogb . . . 105
log2 . . . 105
expm1 . . . 105
acosh . . . 106
asinh . . . 106
atanh . . . 106
sinh . . . 106
cosh . . . 107
tanh . . . 107
erf . . . 107
erfc . . . 107
gamma . . . 108

lgamma . . . 108
J0 . . . 108
J1 . . . 108
Jn . . . 109
Y0 . . . 109
Y1 . . . 109
Yn . . . 110
fabs, fmax, fmin . . . 110
np2 . . . 110
frac . . . 110
isnan . . . 111
chebychev . . . 111
chebychevpoly . . . 112
diffn . . . 112
signum . . . 112

misceffects.lib **113**
Dynamic . . . 113
cubicnl . . . 113
gate_mono . . . 113
gate_stereo . . . 114
Filtering . . . 115
speakerbp . . . 115
piano_dispersion_filter . . . 115
stereo_width . . . 116
Time Based . . . 116
echo . . . 116
Pitch Shifting . . . 117
transpose . . . 117
Meshes . . . 117
mesh_square . . . 117

noises.lib 118

Functions Reference . . . 118

`noise` . . . 118

`multirandom` . . . 119

`multinoise` . . . 119

`noises` . . . 119

`pink_noise` . . . 120

`pink_noise_vm` . . . 120

`lfnoise`, `lfnoise0` and `lfnoiseN` . . . 120

`sparse_noise_vm` . . . 121

`velvet_noise_vm` . . . 121

`gnoise` . . . 122

oscillators.lib 122

Wave-Table-Based Oscillators . . . 123

`sinwaveform` . . . 123

`coswaveform` . . . 123

`phasor` . . . 123

`oscsin` . . . 124

`osccos` . . . 124

`oscp` . . . 124

`osci` . . . 125

LFOs . . . 125

`lf_imptrain` . . . 125

`lf_pulsetrainpos` . . . 125

`lf_squarewavepos` . . . 126

`lf_squarewave` . . . 126

`lf_trianglepos` . . . 127

Low Frequency Sawtooths . . . 127

`lf_rawsaw` . . . 127

`lf_sawpos_phase` . . . 128

Bandlimited Sawtooth . . . 128
sawNp . . . 129
saw2dpw . . . 129
saw3 . . . 129
sawtooth . . . 130
saw2f2 . . . 130
saw2f4 . . . 130
Bandlimited Pulse, Square, and Impulse Trains . . . 130
pulsetrainN . . . 131
pulsetrain . . . 131
squareN . . . 131
square . . . 132
impulse . . . 132
imptrainN . . . 132
imptrain . . . 132
triangleN . . . 133
triangle . . . 133
Filter-Based Oscillators . . . 133
oscb . . . 134
oscrq . . . 134
oscrs . . . 135
oscrc . . . 135
osc . . . 136
oscs . . . 136
Waveguide-Resonator-Based Osccilators . . . 136
oscw . . . 136
oscws . . . 137
oscwq . . . 137
oscw . . . 138
lf_sawpos . . . 138
lf_saw . . . 139
lf_triangle . . . 139

phaflangers.lib **139**

Functions Reference 139

`flanger_mono` 139

`flanger_stereo` 140

`phaser2_mono` 140

`phaser2_stereo` 141

physmodels.lib **142**

chain(A:B:. . .) 142

Requires 143

input(x) 143

output() 143

terminations(a,b,c) 143

Requires 144

fullTerminations(a,b,c) 144

Requires 144

leftTermination(a,b) 144

Requires 144

rightTermination(b,c) 145

Requires 145

waveguide(nMax,n) 145

idealString(length,reflexion,xPosition,x) 145

reverbs.lib **146**

Schroeder Reverberators 146

`jcrev` 146

`satrev` 146

Feedback Delay Network (FDN) Reverberators 147

`fdnrev0` 147

`zita_rev_fdn` 147

`zita_rev1_stereo` 148

`zita_rev1_ambi` 148

Freeverb 149
mono_freeverb 149
stereo_freeverb 149

routes.lib 150

Functions Reference 150
cross 150
crossnn 150
crossn1 151
interleave 151
butterfly 152
hadamard 152
recursivize 152

signals.lib 153

Functions Reference 153
bus 153
block 153
interpolate 153
smoo 154
polySmooth 154
smoothAndH 155
bsmooth 155
dot 155
smooth 156
lag_ud 156

spats.lib 156

panner 157
spat 157
stereoize 157

synths.lib 158

`popFilterPerc` . . . 158

`dubDub` . . . 158

`sawTrombone` . . . 159

`combString` . . . 159

`additiveDrum` . . . 159

`fm` . . . 160

vaeffects.lib 160

Functions Reference . . . 161

`moog_vcf` . . . 161

`moog_vcf_2b[n]` . . . 161

`wah4` . . . 162

`autowah` . . . 162

`crybaby` . . . 163

`vocoder` . . . 163

Licenses 164

STK 4.3 License . . . 164

LGPL License . . . 164

Faust Libraries

NOTE: this documentation was automatically generated.

This page provides information on how to use the Faust libraries.

The `/libraries` folder contains the different Faust libraries. If you wish to add your own functions to this library collection, you can refer to the "Contributing" section providing a set of coding conventions.

WARNING: These libraries replace the "old" Faust libraries. They are still being beta tested so you might encounter bugs while using them. If your codes still use the "old" Faust libraries, you might want to try to use Bart Brouns' script that automatically makes an old Faust code compatible with the new libraries: https://github.com/magnetophon/faustCompressors/blob/master/newlib.sh. If you find a bug, please report it at rmichon_at_ccrma_dot_stanford_dot_edu. Thanks ;)!

Using the Faust Libraries

The easiest and most standard way to use the Faust libraries is to import `stdfaust.lib` in your Faust code:

```
import("stdfaust.lib");
```

This will give you access to all the Faust libraries through a series of environments:

- `sf`: `all.lib`
- `an`: `analyzers.lib`
- `ba`: `basics.lib`
- `co`: `compressors.lib`
- `de`: `delays.lib`
- `dm`: `demos.lib`
- `en`: `envelopes.lib`
- `fi`: `filters.lib`
- `ho`: `hoa.lib`
- `ma`: `maths.lib`
- `ef`: `misceffects.lib`
- `os`: `oscillators.lib`
- `no`: `noises.lib`
- `pf`: `phaflangers.lib`
- `pm`: `physmodels.lib`
- `re`: `reverbs.lib`
- `ro`: `routes.lib`
- `si`: `signals.lib`
- `sp`: `spats.lib`
- `sy`: `synths.lib`
- `ve`: `vaeffects.lib`

Environments can then be used as follows in your Faust code:

```
import("stdfaust.lib");
process = os.osc(440);
```

In this case, we're calling the `osc` function from `oscillators.lib`.

You can also access all the functions of all the libraries directly using the `sf` environment:

```
import("stdfaust.lib");
process = sf.osc(440);
```

Alternatively, environments can be created by hand:

```
os = library("oscillators.lib");
process = os.osc(440);
```

Finally, libraries can be simply imported in the Faust code (not recommended):

```
import("oscillators.lib");
process = osc(440);
```

Contributing

If you wish to add a function to any of these libraries or if you plan to add a new library, make sure that you follow the following conventions:

New Functions

- All functions must be preceded by a markdown documentation header respecting the following format (open the source code of any of the libraries for an example):

```
//-----------------functionName--------------------
// Description
//
// #### Usage
//
// ```
// Usage Example
// ```
//
// Where:
//
// * argument1: argument 1 description
//-------------------------------------------------
```

- Every time a new function is added, the documentation should be updated simply by running `make doclib`.
- The environment system (e.g. `os.osc`) should be used when calling a function declared in another library (see the section on *Using the Faust Libraries*).
- Try to reuse exisiting functions as much as possible.
- If you have any question, send an e-mail to rmichon_at_ccrma_dot_stanford_dot_edu.

New Libraries

- Any new “standard” library should be declared in `stdfaust.lib` with its own environment (2 letters - see `stdfaust.lib`).
- Any new “standard” library must be added to `generateDoc`.
- Functions must be organized by sections.
- Any new library should at least `declare` a `name` and a `version`.
- The comment based markdown documentation of each library must respect the following format (open the source code of any of the libraries for an example):

```
//############### libraryName ##################
// Description
//
// * Section Name 1
// * Section Name 2
// * ...
//
// It should be used using the `[...]` environment:
//
// ```
// [...] = library("libraryName");
// process = [...].functionCall;
// ```
//
// Another option is to import `stdfaust.lib` which already contains the `[...]`
// environment:
//
// ```
// import("stdfaust.lib");
// process = [...].functionCall;
// ```
//##############################################

//================= Section Name ===============
// Description
//==============================================
```

- If you have any question, send an e-mail to rmichon_at_ccrma_dot_stanford_dot_edu.

General Organization

Only the libraries that are considered to be “standard” are documented:

- `analyzers.lib`
- `basics.lib`
- `compressors.lib`
- `delays.lib`
- `demos.lib`
- `envelopes.lib`
- `filters.lib`
- `hoa.lib`
- `maths.lib`
- `misceffects.lib`
- `oscillators.lib`
- `noises.lib`
- `phaflangers.lib`
- `physmodels.lib`
- `reverbs.lib`
- `routes.lib`
- `signals.lib`
- `spats.lib`
- `synths.lib`
- `tonestacks.lib` (not documented but example in `/examples/misc`)
- `tubes.lib` (not documented but example in `/examples/misc`)
- `vaeffects.lib`

Other deprecated libraries such as `music.lib`, etc. are present but are not documented to not confuse new users.

The doumentation of each library can be found in `/documentation/library.html` or in `/documentation/library.pdf`.

The `/examples` directory contains all the examples from the `/examples` folder of the Faust distribution as well as new ones. Most of them were updated to reflect the coding conventions described in the next section. Examples are organized by types in different folders. The `/old` folder contains examples that are fully deprecated, probably because they were integrated to the libraries and fully rewritten (see `freeverb.dsp` for example). Examples using deprecated libraries were integrated to the general tree but a warning comment was added at their beginning to point readers to the right library and function.

Coding Conventions

In order to have a uniformized library system, we established the following conventions (that hopefully will be followed by others when making modifications to them :-)).

Documentation

- All the functions that we want to be "public" are documented.
- We used the `faust2md` "standards" for each library: `//###` for main title (library name - equivalent to `#` in markdown), `//===` for section declarations (equivalent to `##` in markdown) and `//---` for function declarations (equivalent to `####` in markdown - see `basics.lib` for an example).
- Sections in function documentation should be declared as `####` markdown title.
- Each function documentation provides a "Usage" section (see `basics.lib`).

Library Import

To prevent cross-references between libraries we generalized the use of the `library("")` system for function calls in all the libraries. This means that everytime a function declared in another library is called, the environment corresponding to this library needs to be called too. To make things easier, a `stdfaust.lib` library was created and is imported by all the libraries:

```
an = library("analyzers.lib");
ba = library("basics.lib");
co = library("compressors.lib");
de = library("delays.lib");
dm = library("demos.lib");
en = library("envelopes.lib");
fi = library("filters.lib");
ho = library("hoa.lib");
ma = library("maths.lib");
ef = library("misceffects.lib");
os = library("oscillators.lib");
no = library("noises.lib");
pf = library("phaflangers.lib");
pm = library("physmodels.lib");
re = library("reverbs.lib");
ro = library("routes.lib");
sp = library("spats.lib");
si = library("signals.lib");
sy = library("synths.lib");
ve = library("vaeffects.lib");
```

For example, if we wanted to use the `smooth` function which is now declared in `signals.lib`, we would do the following:

```
import("stdfaust.lib");
```

```
process = si.smooth(0.999);
```

This standard is only used within the libraries: nothing prevents coders to still import `signals.lib` directly and call `smooth` without `ro.`, etc.

"Demo" Functions

"Demo" functions are placed in `demos.lib` and have a built-in user interface (UI). Their name ends with the `_demo` suffix. Each of these function have a `.dsp` file associated to them in the `/examples` folder.

Any function containing UI elements should be placed in this library and respect these standards.

"Standard" Functions

"Standard" functions are here to simplify the life of new (or not so new) Faust coders. They are declared in `/libraries/doc/standardFunctions.md` and allow to point programmers to preferred functions to carry out a specific task. For example, there are many different types of lowpass filters declared in `filters.lib` and only one of them is considered to be standard, etc.

Copyright / License

Now that Faust libraries are less author specific, each function will normally have its own copyright-and-license line in the library source (the `.lib` file, such as `analyzers.lib`). If not, see if the function is defined within a section of the `.lib` file stating the license in source-code comments. If not, then the copyright and license given at the beginning of the `.lib` file may be assumed, when present. If not, run `git blame` on the `.lib` file and ask the person who last edited the function!

Note that it is presently possible for a library function released under one license to utilize another library function having some different license. There is presently no indication of this situation in the Faust compiler output, but such notice is planned. For now, library contributors should strive to use only library functions having compatible licenses, and concerned end-users must manually determine the union of licenses applicable to the library functions they are using.

Standard Functions

Dozens of functions are implemented in the Faust libraries and many of them are very specialized and not useful to beginners or to people who only need to use

Faust for basic applications. This section offers an index organized by categories of the "standard Faust functions" (basic filters, effects, synthesizers, etc.). This index only contains functions without a user interface (UI). Faust functions with a built-in UI can be found in `demos.lib`.

Analysis Tools

Function Type	Function Name	Description
Amplitude Follower	`an.amp_follower`	Classic analog audio envelope follower
Octave Analyzers	`an.mth_octave_analyzer[N]`	Octave analyzers

Basic Elements

Function Type	Function Name	Description
Beats	`ba.beat`	Pulses at a specific tempo
Block	`si.block`	Terminate n signals
Break Point Function	`ba.bpf`	Beak Point Function (BPF)
Bus	`si.bus`	Bus of n signals
Bypass (Mono)	`ba.bypass1`	Mono bypass
Bypass (Stereo)	`ba.bypass2`	Stereo bypass
Count Elements	`ba.count`	Count elements in a list
Count Down	`ba.countdown`	Samples count down
Count Up	`ba.countup`	Samples count up
Delay (Integer)	`de.delay`	Integer delay
Delay (Float)	`de.fdelay`	Fractional delay
Down Sample	`ba.downSample`	Down sample a signal
Impulsify	`ba.impulsify`	Turns a signal into an impulse
Sample and Hold	`ba.sAndH`	Sample and hold
Signal Crossing	`ro.cross`	Cross n signals
Smoother (Default)	`si.smoo`	Exponential smoothing
Smoother	`si.smooth`	Exponential smoothing with controllable pole
Take Element	`ba.take`	Take en element from a list
Time	`ba.time`	A simple timer

Function Type	Function Name	Description

Conversion

Function Type	Function Name	Description
dB to Linear	`ba.db2linear`	Converts dB to linear values
Linear to dB	`ba.linear2db`	Converts linear values to dB
MIDI Key to Hz	`ba.midikey2hz`	Converts a MIDI key number into a frequency
Pole to T60	`ba.pole2tau`	Converts a pole into a time constant (t60)
Samples to Seconds	`ba.samp2sec`	Converts samples to seconds
Seconds to Samples	`ba.sec2samp`	Converts seconds to samples
T60 to Pole	`ba.tau2pole`	Converts a time constant (t60) into a pole

Effects

Function Type	Function Name	Description
Auto Wah	`ve.autowah`	Auto-Wah effect
Compressor	`co.compressor_mono`	Dynamic range compressor
Distortion	`ef.cubicnl`	Cubic nonlinearity distortion
Crybaby	`ve.crybaby`	Crybaby wah pedal
Echo	`ef.echo`	Simple echo
Flanger	`pf.flanger_stereo`	Flanging effect
Gate	`ef.gate_mono`	Mono signal gate
Limiter	`co.limiter_1176_R4_mono`	Limiter
Phaser	`pf.phaser2_stereo`	Phaser effect
Reverb (FDN)	`re.fdnrev0`	Feedback delay network reverberator
Reverb (Freeverb)	`re.mono_freeverb`	Most “famous” Schroeder reverberator
Reverb (Simple)	`re.jcrev`	Simple Schroeder reverberator
Reverb (Zita)	`re.zita_rev1_stereo`	High quality FDN reverberator
Panner	`sp.panner`	Linear stereo panner
Pitch Shift	`ef.transpose`	Simple pitch shifter

Function Type	Function Name	Description
Panner	`sp.spat`	N outputs spatializer
Speaker Simulator	`ef.speakerbp`	Simple speaker simulator
Stereo Width	`ef.stereo_width`	Stereo width effect
Vocoder	`ve.vocoder`	Simple vocoder
Wah	`ve.wah4`	Wah effect

Envelope Generators

Function Type	Function Name	Description
ADSR	`en.adsr`	Attack/Decay/Sustain/Release envelope generator
AR	`en.ar`	Attack/Release envelope generator
ASR	`en.asr`	Attack/Sustain/Release envelope generator
Exponential	`en.smoothEnvelope`	Exponential envelope generator

Filters

Function Type	Function Name	Description
Bandpass (Butterworth)	`fi.bandpass`	Generic butterworth bandpass
Bandpass (Resonant)	`fi.resonbp`	Virtual analog resonant bandpass
Bandstop (Butterworth)	`fi.bandstop`	Generic butterworth bandstop
Biquad	`fi.tf2`	"Standard" biquad filter
Comb (Allpass)	`fi.allpass_fcomb`	Schroeder allpass comb filter
Comb (Feedback)	`fi.fb_fcomb`	Feedback comb filter
Comb (Feedforward)	`fi.ff_fcomb`	Feed-forward comb filter.
DC Blocker	`fi.dcblocker`	Default dc blocker
Filterbank	`fi.filterbank`	Generic filter bank
FIR (Arbitrary Order)	`fi.fir`	Nth-order FIR filter
High Shelf	`fi.high_shelf`	High shelf
Highpass (Butterworth)	`fi.highpass`	Nth-order Butterworth highpass
Highpass (Resonant)	`fi.resonhp`	Virtual analog resonant highpass

Function Type	Function Name	Description
IIR (Arbitrary Order)	`fi.iir`	Nth-order IIR filter
Level Filter	`fi.levelfilter`	Dynamic level lowpass
Low Shelf	`fi.low_shelf`	Low shelf
Lowpass (Butterworth)	`fi.lowpass`	Nth-order Butterworth lowpass
Lowpass (Resonant)	`fi.resonlp`	Virtual analog resonant lowpass
Notch Filter	`fi.notchw`	Simple notch filter
Peak Equalizer	`fi.peak_eq`	Peaking equalizer section

Oscillators/Sound Generators

Function Type	Function Name	Description
Impulse	`os.impulse`	Generate an impulse on start-up
Impulse Train	`os.imptrain`	Band-limited impulse train
Phasor	`os.phasor`	Simple phasor
Pink Noise	`no.pink_noise`	Pink noise generator
Pulse Train	`os.pulsetrain`	Band-limited pulse train
Pulse Train (Low Frequency)	`os.lf_imptrain`	Low-frequency pulse train
Sawtooth	`os.sawtooth`	Band-limited sawtooth wave
Sawtooth (Low Frequency)	`os.lf_saw`	Low-frequency sawtooth wave
Sine (Filter-Based)	`os.osc`	Sine oscillator (filter-based)
Sine (Table-Based)	`os.oscsin`	Sine oscillator (table-based)
Square	`os.square`	Band-limited square wave
Square (Low Frequency)	`os.lf_squarewave`	Low-frequency square wave
Triangle	`os.triangle`	Band-limited triangle wave
Triangle (Low Frequency)	`os.lf_triangle`	Low-frequency triangle wave
White Noise	`no.noise`	White noise generator

Synths

Function Type	Function Name	Description
Additive Drum	`sy.additiveDrum`	Additive synthesis drum
Bandpassed Sawtooth	`sy.dubDub`	Sawtooth through resonant bandpass
Comb String	`sy.combString`	String model based on a comb filter
FM	`sy.fm`	Frequency modulation synthesizer
Lowpassed Sawtooth	`sy.sawTrombone`	"Trombone" based on a filtered sawtooth
Popping Filter	`sy.popFilterPerc`	Popping filter percussion instrument

analyzers.lib

Faust Analyzers library. Its official prefix is `an`.

Amplitude Tracking

`amp_follower`

Classic analog audio envelope follower with infinitely fast rise and exponential decay. The amplitude envelope instantaneously follows the absolute value going up, but then floats down exponentially. `amp_follower` is a standard Faust function.

Usage

```
_ : amp_follower(rel) : _
```

Where:

- `rel`: release time = amplitude-envelope time-constant (sec) going down

Reference

- Musical Engineer's Handbook, Bernie Hutchins, Ithaca NY, 1975 Electronotes Newsletter, Bernie Hutchins

---

`amp_follower_ud`

Envelope follower with different up and down time-constants (also called a "peak detector").

Usage

```
_ : amp_follower_ud(att,rel) : _
```

Where:

- `att`: attack time = amplitude-envelope time constant (sec) going up
- `rel`: release time = amplitude-envelope time constant (sec) going down

Note We assume rel >> att. Otherwise, consider rel ~ max(rel,att). For audio, att is normally faster (smaller) than rel (e.g., 0.001 and 0.01). Use `amp_follower_ar` below to remove this restriction.

Reference

- "Digital Dynamic Range Compressor Design — A Tutorial and Analysis", by Dimitrios Giannoulis, Michael Massberg, and Joshua D. Reiss http://www.eecs.qmul.ac.uk/~josh/documents/GiannoulisMassbergReiss-dynamicrangecompression-JAES2012.pdf

---

Spectrum-Analyzers

Spectrum-analyzers split the input signal into a bank of parallel signals, one for each spectral band. They are related to the Mth-Octave Filter-Banks in `filters.lib`. The documentation of this library contains more details about the implementation. The parameters are:

- `M`: number of band-slices per octave (>1)
- `N`: total number of bands (>2)
- `ftop` = upper bandlimit of the Mth-octave bands (<SR/2)

In addition to the Mth-octave output signals, there is a highpass signal containing frequencies from ftop to SR/2, and a "dc band" lowpass signal containing frequencies from 0 (dc) up to the start of the Mth-octave bands. Thus, the N output signals are

```
highpass(ftop), MthOctaveBands(M,N-2,ftop), dcBand(ftop*2^(-M*(N-1)))
```

A Spectrum-Analyzer is defined here as any band-split whose bands span the relevant spectrum, but whose band-signals do not necessarily sum to the original signal, either exactly or to within an allpass filtering. Spectrum analyzer outputs are normally at least nearly "power complementary", i.e., the power spectra of the individual bands sum to the original power spectrum (to within some negligible tolerance).

Increasing Channel Isolation Go to higher filter orders - see Regalia et al. or Vaidyanathan (cited below) regarding the construction of more aggressive recursive filter-banks using elliptic or Chebyshev prototype filters.

References

- "Tree-structured complementary filter banks using all-pass sections", Regalia et al., IEEE Trans. Circuits & Systems, CAS-34:1470-1484, Dec. 1987
- "Multirate Systems and Filter Banks", P. Vaidyanathan, Prentice-Hall, 1993
- Elementary filter theory: https://ccrma.stanford.edu/~jos/filters/

`mth_octave_analyzer`

Octave analyzer. `mth_octave_analyzer[N]` are standard Faust functions.

Usage

```
_ : mth_octave_analyzer(O,M,ftop,N) : par(i,N,_); // Oth-order Butterworth
_ : mth_octave_analyzer6e(M,ftop,N) : par(i,N,_); // 6th-order elliptic
```

Also for convenience:

```
_ : mth_octave_analyzer3(M,ftop,N) : par(i,N,_); // 3d-order Butterworth
_ : mth_octave_analyzer5(M,ftop,N) : par(i,N,_); // 5th-roder Butterworth
mth_octave_analyzer_default = mth_octave_analyzer6e;
```

Where:

- `O`: order of filter used to split each frequency band into two
- `M`: number of band-slices per octave
- `ftop`: highest band-split crossover frequency (e.g., 20 kHz)
- `N`: total number of bands (including dc and Nyquist)

Mth-Octave Spectral Level

Spectral Level: Display (in bar graphs) the average signal level in each spectral band.

mth_octave_spectral_level6e

Spectral level display.

Usage:

```
_ : mth_octave_spectral_level6e(M,ftop,NBands,tau,dB_offset) : _;
```

Where:

- `M`: bands per octave
- `ftop`: lower edge frequency of top band
- `NBands`: number of passbands (including highpass and dc bands),
- `tau`: spectral display averaging-time (time constant) in seconds,
- `dB_offset`: constant dB offset in all band level meters.

Also for convenience:

```
mth_octave_spectral_level_default = mth_octave_spectral_level6e;
spectral_level = mth_octave_spectral_level(2,10000,20);
```

[third|half]_octave_[analyzer|filterbank]

A bunch of special cases based on the different analyzer functions described above:

```
third_octave_analyzer(N) = mth_octave_analyzer_default(3,10000,N);
third_octave_filterbank(N) = mth_octave_filterbank_default(3,10000,N);
half_octave_analyzer(N) = mth_octave_analyzer_default(2,10000,N);
half_octave_filterbank(N) = mth_octave_filterbank_default(2,10000,N);
octave_filterbank(N) = mth_octave_filterbank_default(1,10000,N);
octave_analyzer(N) = mth_octave_analyzer_default(1,10000,N);
```

Usage See `mth_octave_spectral_level_demo`.

Arbitrary-Crossover Filter-Banks and Spectrum Analyzers

These are similar to the Mth-octave analyzers above, except that the band-split frequencies are passed explicitly as arguments.

`analyzer`

Analyzer.

Usage

```
_ : analyzer(O,freqs) : par(i,N,_); // No delay equalizer
```

Where:

- `O`: band-split filter order (ODD integer required for filterbank[i])
- `freqs`: (fc1,fc2,…,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : analyzer(3,(fc1,fc2)) : _,_,_
```

`amp_follower_ar`

Envelope follower with independent attack and release times. The release can be shorter than the attack (unlike in `amp_follower_ud` above).

Usage

```
_ : amp_follower_ar(att,rel) : _;
```

- Author Jonatan Liljedahl, revised by RM

---

basics.lib

A library of basic elements for Faust organized in 5 sections:

- Conversion Tools
- Counters and Time/Tempo Tools
- Array Processing/Pattern Matching
- Selectors (Conditions)
- Other Tools (Misc)

The official prefix of this library is `ba`.

Conversion Tools

`samp2sec`

Converts a number of samples to a duration in seconds. `samp2sec` is a standard Faust function.

Usage

```
samp2sec(n) : _
```

Where:

- `n`: number of samples

`sec2samp`

Converts a duration in seconds to a number of samples. `samp2sec` is a standard Faust function.

Usage

```
sec2samp(d) : _
```

Where:

- `d`: duration in seconds

`db2linear`

Converts a loudness in dB to a linear gain (0-1). `db2linear` is a standard Faust function.

Usage

```
db2linear(l) : _
```

Where:

- `l`: loudness in dB

`linear2db`

Converts a linear gain (0-1) to a loudness in dB. `linear2db` is a standard Faust function.

Usage

```
linear2db(g) : _
```

Where:

- `g`: a linear gain

`lin2LogGain`

Converts a linear gain (0-1) to a log gain (0-1).

Usage

```
_ : lin2LogGain : _
```

`log2LinGain`

Converts a log gain (0-1) to a linear gain (0-1).

Usage

```
_ : log2LinGain : _
```

`tau2pole`

Returns a real pole giving exponential decay. Note that t60 (time to decay 60 dB) is ~6.91 time constants. `tau2pole` is a standard Faust function.

Usage

```
_ : smooth(tau2pole(tau)) : _
```

Where:

- `tau`: time-constant in seconds

`pole2tau`

Returns the time-constant, in seconds, corresponding to the given real, positive pole in (0,1). `pole2tau` is a standard Faust function.

Usage

```
pole2tau(pole) : _
```

Where:

- `pole`: the pole

`midikey2hz`

Converts a MIDI key number to a frequency in Hz (MIDI key 69 = A440). `midikey2hz` is a standard Faust function.

Usage

```
midikey2hz(mk) : _
```

Where:

- `mk`: the MIDI key number

`pianokey2hz`

Converts a piano key number to a frequency in Hz (piano key 49 = A440).

Usage

```
pianokey2hz(pk) : _
```

Where:

- `pk`: the piano key number

`hz2pianokey`

Converts a frequency in Hz to a piano key number (piano key 49 = A440).

Usage

```
hz2pianokey(f) : _
```

Where:

- `f`: frequency in Hz

Counters and Time/Tempo Tools

`countdown`

Starts counting down from n included to 0. While trig is 1 the output is n. The countdown starts with the transition of trig from 1 to 0. At the end of the countdown the output value will remain at 0 until the next trig. `countdown` is a standard Faust function.

Usage

```
countdown(n,trig) : _
```

Where:

- `count`: the starting point of the countdown
- `trig`: the trigger signal (1: start at `n`; 0: decrease until 0)

`countup`

Starts counting up from 0 to n included. While trig is 1 the output is 0. The countup starts with the transition of trig from 1 to 0. At the end of the countup the output value will remain at n until the next trig. `countup` is a standard Faust function.

Usage

```
countup(n,trig) : _
```

Where:

- `count`: the starting point of the countup
- `trig`: the trigger signal (1: start at 0; 0: increase until `n`)

`sweep`

Counts from 0 to `period` samples repeatedly, while `run` is 1. Outsputs zero while `run` is 0.

Usage

```
sweep(period,run) : _
```

`time`

A simple timer that counts every samples from the beginning of the process. `time` is a standard Faust function.

Usage

```
time : _
```

`tempo`

Converts a tempo in BPM into a number of samples.

Usage

```
tempo(t) : _
```

Where:

- `t`: tempo in BPM

`period`

Basic sawtooth wave of period `p`.

Usage

```
period(p) : _
```

Where:

- `p`: period as a number of samples

`pulse`

Pulses (10000) generated at period `p`.

Usage

```
pulse(p) : _
```

Where:

- `p`: period as a number of samples

`pulsen`

Pulses (11110000) of length `n` generated at period `p`.

Usage

```
pulsen(n,p) : _
```

Where:

- `n`: the length of the pulse as a number of samples
- `p`: period as a number of samples

`beat`

Pulses at tempo `t`. `beat` is a standard Faust function.

Usage

```
beat(t) : _
```

Where:

- `t`: tempo in BPM

`pulse_countup`

Starts counting up pulses. While trig is 1 the output is counting up, while trig is 0 the counter is reset to 0.

Usage

```
_ : pulse_countup(trig) : _
```

Where:

- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

`pulse_countdown`

Starts counting down pulses. While trig is 1 the output is counting down, while trig is 0 the counter is reset to 0.

Usage

```
_ : pulse_countdown(trig) : _
```

Where:

- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

`pulse_countup_loop`

Starts counting up pulses from 0 to n included. While trig is 1 the output is counting up, while trig is 0 the counter is reset to 0. At the end of the countup (n) the output value will be reset to 0.

Usage

```
_ : pulse_countup_loop(n,trig) : _
```

Where:

- `n`: the highest number of the countup (included) before reset to 0.
- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

---

pulse_countdown_loop

Starts counting down pulses from 0 to n included. While trig is 1 the output is counting down, while trig is 0 the counter is reset to 0. At the end of the countdown (n) the output value will be reset to 0.

Usage

```
_ : pulse_coundown_loop(n,trig) : _
```

Where:

- `n`: the highest number of the countup (included) before reset to 0.
- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

Array Processing/Pattern Matching

count

Count the number of elements of list l. `count` is a standard Faust function.

Usage

```
count(l)
count ((10,20,30,40)) -> 4
```

Where:

- `l`: list of elements

`take`

Take an element from a list. `take` is a standard Faust function.

Usage

```
take(e,l)
take(3,(10,20,30,40)) -> 30
```

Where:

- `p`: position (starting at 1)
- `l`: list of elements

`subseq`

Extract a part of a list.

Usage

```
subseq(l, p, n)
subseq((10,20,30,40,50,60), 1, 3) -> (20,30,40)
subseq((10,20,30,40,50,60), 4, 1) -> 50
```

Where:

- `l`: list
- `p`: start point (0: begin of list)
- `n`: number of elements

Note: Faust doesn't have proper lists. Lists are simulated with parallel compositions and there is no empty list

---

Selectors (Conditions)

`if`

if-then-else implemented with a select2.

Usage

- `if(c, t, e) : _`

Where:

- `c`: condition
- `t`: signal selected while c is true
- `e`: signal selected while c is false

`selector`

Selects the ith input among n at compile time.

Usage

```
selector(i,n)
_,_,_,_ : selector(2,4) : _  // selects the 3rd input among 4
```

Where:

- `i`: input to select (`int`, numbered from 0, known at compile time)
- `n`: number of inputs (`int`, known at compile time, `n > i`)

`selectn`

Selects the ith input among N at run time.

Usage

```
selectn(N,i)
_,_,_,_ : selectn(4,2) : _  // selects the 3rd input among 4
```

Where:

- `N`: number of inputs (int, known at compile time, $N > 0$)
- `i`: input to select (int, numbered from 0)

Example test program

```
N=64;
process = par(n,N, (par(i,N,i) : selectn(N,n)));
```

`select2stereo`

Select between 2 stereo signals.

Usage

```
_,_,_,_ : select2stereo(bpc) : _,_,_,_
```

Where:

- `bpc`: the selector switch (0/1)

Other

`latch`

Latch input on positive-going transition of "clock" ("sample-and-hold").

Usage

```
_ : latch(clocksig) : _
```

Where:

- `clocksig`: hold trigger (0 for hold, 1 for bypass)

`sAndH`

Sample And Hold. `sAndH` is a standard Faust function.

Usage

```
_ : sAndH(t) : _
```

Where:

- `t`: hold trigger (0 for hold, 1 for bypass)

`downSample`

Down sample a signal. WARNING: this function doesn't change the rate of a signal, it just holds samples… `downSample` is a standard Faust function.

Usage

```
_ : downSample(freq) : _
```

Where:

- `freq`: new rate in Hz

`peakhold`

Outputs current max value above zero.

Usage

```
_ : peakhold(mode) : _;
```

Where:

`mode` means: 0 - Pass through. A single sample 0 trigger will work as a reset. 1 - Track and hold max value.

`peakholder`

Tracks abs peak and holds peak for 'holdtime' samples.

Usage

```
_ : peakholder(holdtime) : _;
```

`impulsify`

Turns the signal from a button into an impulse (1,0,0,... when button turns on). `impulsify` is a standard Faust function.

Usage

```
button("gate") : impulsify ;
```

`automat`

Record and replay to the values the input signal in a loop.

Usage

```
hslider(...) : automat(bps, size, init) : _
```

`bpf`

bpf is an environment (a group of related definitions) that can be used to create break-point functions. It contains three functions :

- `start(x,y)` to start a break-point function
- `end(x,y)` to end a break-point function
- `point(x,y)` to add intermediate points to a break-point function

A minimal break-point function must contain at least a start and an end point :

```
f = bpf.start(x0,y0) : bpf.end(x1,y1);
```

A more involved break-point function can contains any number of intermediate points:

```
f = bpf.start(x0,y0) : bpf.point(x1,y1) : bpf.point(x2,y2) : bpf.end(x3,y3);
```

In any case the `x_{i}` must be in increasing order (for all `i`, `x_{i} < x_{i+1}`). For example the following definition :

```
f = bpf.start(x0,y0) : ... : bpf.point(xi,yi) : ... : bpf.end(xn,yn);
```

implements a break-point function f such that :

- `f(x) = y_{0}` when `x < x_{0}`
- `f(x) = y_{n}` when `x > x_{n}`
- `f(x) = y_{i} + (y_{i+1}-y_{i})*(x-x_{i})/(x_{i+1}-x_{i})` when `x_{i} <= x` and `x < x_{i+1}`

`bpf` is a standard Faust function.

`bypass1`

Takes a mono input signal, route it to `e` and bypass it if `bpc = 1`. `bypass1` is a standard Faust function.

Usage

```
_ : bypass1(bpc,e) : _
```

Where:

- `bpc`: bypass switch (0/1)
- `e`: a mono effect

`bypass2`

Takes a stereo input signal, route it to `e` and bypass it if `bpc = 1`. `bypass2` is a standard Faust function.

Usage

```
_,_ : bypass2(bpc,e) : _,_
```

Where:

- `bpc`: bypass switch (0/1)
- `e`: a stereo effect

`toggle`

Triggered by the change of 0 to 1, it toggles the output value between 0 and 1.

Usage

```
_ : toggle : _
```

Examples

```
button("toggle") : toggle : vbargraph("output", 0, 1)
(an.amp_follower(0.1) > 0.01) : toggle : vbargraph("output", 0, 1) // takes audio input
```

`on_and_off`

The first channel set the output to 1, the second channel to 0.

Usage

```
_ , _ : on_and_off : _
```

Example

```
button("on"), button("off") : on_and_off : vbargraph("output", 0, 1)
```

`selectoutn`

Route input to the output among N at run time.

Usage

```
_ : selectoutn(n, s) : _,_,...n
```

Where:

- `n`: number of outputs (int, known at compile time, N > 0)
- `s`: output number to route to (int, numbered from 0) (i.e. slider)

Example

```
process = 1 : selectoutn(3, sel) : par(i,3,bar) ;
sel = hslider("volume",0,0,2,1) : int;
bar = vbargraph("v.bargraph", 0, 1);
```

---

compressors.lib

A library of compressor effects. Its official prefix is `co`.

Functions Reference

`compressor_mono`

Mono dynamic range compressors. `compressor_mono` is a standard Faust function

Usage

```
_ : compressor_mono(ratio,thresh,att,rel) : _
```

Where:

- `ratio`: compression ratio (1 = no compression, >1 means compression)
- `thresh`: dB level threshold above which compression kicks in (0 dB = max level)
- `att`: attack time = time constant (sec) when level & compression going up
- `rel`: release time = time constant (sec) coming out of compression

References

- http://en.wikipedia.org/wiki/Dynamic_range_compression
- https://ccrma.stanford.edu/~jos/filters/Nonlinear_Filter_Example_Dynamic.html
- Albert Graef's "faust2pd"/examples/synth/compressor_.dsp
- More features: https://github.com/magnetophon/faustCompressors

---

`compressor_stereo`

Stereo dynamic range compressors.

Usage

```
_,_ : compressor_stereo(ratio,thresh,att,rel) : _,_
```

Where:

- `ratio`: compression ratio (1 = no compression, >1 means compression)
- `thresh`: dB level threshold above which compression kicks in (0 dB = max level)
- `att`: attack time = time constant (sec) when level & compression going up
- `rel`: release time = time constant (sec) coming out of compression

References

- http://en.wikipedia.org/wiki/Dynamic_range_compression
- https://ccrma.stanford.edu/~jos/filters/Nonlinear_Filter_Example_Dynamic.html
- Albert Graef's "faust2pd"/examples/synth/compressor_.dsp
- More features: https://github.com/magnetophon/faustCompressors

---

`limiter_1176_R4_mono`

A limiter guards against hard-clipping. It can be can be implemented as a compressor having a high threshold (near the clipping level), fast attack and release, and high ratio. Since the ratio is so high, some knee smoothing is desirable ("soft limiting"). This example is intended to get you started using compressor_* as a limiter, so all parameters are hardwired to nominal values here. Ratios: 4 (moderate compression), 8 (severe compression), 12 (mild limiting), or 20 to 1 (hard limiting) Att: 20-800 MICROseconds (Note: scaled by ratio in the 1176) Rel: 50-1100 ms (Note: scaled by ratio in the 1176) Mike Shipley likes 4:1 (Grammy-winning mixer for Queen, Tom Petty, etc.) Faster attack gives "more bite" (e.g. on vocals) He hears a bright, clear eq effect as well (not implemented here) `limiter_1176_R4_mono` is a standard Faust function.

Usage

```
_ : limiter_1176_R4_mono : _;
```

Reference: http://en.wikipedia.org/wiki/1176_Peak_Limiter

`limiter_1176_R4_stereo`

A limiter guards against hard-clipping. It can be can be implemented as a compressor having a high threshold (near the clipping level), fast attack and release, and high ratio. Since the ratio is so high, some knee smoothing is desirable ("soft limiting"). This example is intended to get you started using compressor_* as a limiter, so all parameters are hardwired to nominal values here. Ratios: 4 (moderate compression), 8 (severe compression), 12 (mild limiting), or 20 to 1 (hard limiting) Att: 20-800 MICROseconds (Note: scaled by ratio in the 1176) Rel: 50-1100 ms (Note: scaled by ratio in the 1176) Mike Shipley likes 4:1

(Grammy-winning mixer for Queen, Tom Petty, etc.) Faster attack gives “more bite” (e.g. on vocals) He hears a bright, clear eq effect as well (not implemented here)

Usage

```
_,_ : limiter_1176_R4_stereo : _,_;
```

Reference: http://en.wikipedia.org/wiki/1176_Peak_Limiter

---

delays.lib

This library contains a collection of delay functions. Its official prefix is `de`.

Basic Delay Functions

`delay`

Simple `d` samples delay where `n` is the maximum delay length as a number of samples (it needs to be a power of 2). Unlike the `@` delay operator, this function allows to preallocate memory which means that `d` can be changed dynamically at run time as long as it remains smaller than `n`. `delay` is a standard Faust function.

Usage

```
_ : delay(n,d) : _
```

Where:

- `n`: the max delay length as a power of 2
- `d`: the delay length as a number of samples (integer)

`fdelay`

Simple `d` samples fractional delay based on 2 interpolated delay lines where `n` is the maximum delay length as a number of samples (it needs to be a power of 2 - see `delay()`). `fdelay` is a standard Faust function.

Usage

```
_ : fdelay(n,d) : _
```

Where:

- `n`: the max delay length as a power of 2
- `d`: the delay length as a number of samples (float)

`sdelay`

s(mooth)delay: a mono delay that doesn't click and doesn't transpose when the delay time is changed.

Usage

```
_ : sdelay(N,it,dt) : _
```

Where :

- `N`: maximal delay in samples (must be a constant power of 2, for example 65536)
- `it`: interpolation time (in samples) for example 1024
- `dt`: delay time (in samples)

Lagrange Interpolation

`fdelaylti` and `fdelayltv`

Fractional delay line using Lagrange interpolation.

Usage

```
_ : fdelaylt[i|v](order, maxdelay, delay, inputsignal) : _
```

Where `order=1,2,3,...` is the order of the Lagrange interpolation polynomial.

`fdelaylti` is most efficient, but designed for constant/slowly-varying delay. `fdelayltv` is more expensive and more robust when the delay varies rapidly.

NOTE: The requested delay should not be less than `(N-1)/2`.

References

- https://ccrma.stanford.edu/~jos/pasp/Lagrange_Interpolation.html
- Timo I. Laakso et al., "Splitting the Unit Delay - Tools for Fractional Delay Filter Design", IEEE Signal Processing Magazine, vol. 13, no. 1, pp. 30-60, Jan 1996.
- Philippe Depalle and Stephan Tassart, "Fractional Delay Lines using Lagrange Interpolators", ICMC Proceedings, pp. 341-343, 1996.

`fdelay[n]`

For convenience, `fdelay1`, `fdelay2`, `fdelay3`, `fdelay4`, `fdelay5` are also available where n is the order of the interpolation.

Thiran Allpass Interpolation

Thiran Allpass Interpolation

Reference https://ccrma.stanford.edu/~jos/pasp/Thiran_Allpass_Interpolators.html

`fdelay[n]a`

Delay lines interpolated using Thiran allpass interpolation.

Usage

```
_ : fdelay[N]a(maxdelay, delay, inputsignal) : _
```

(exactly like `fdelay`)

Where:

- `N`=1,2,3, or 4 is the order of the Thiran interpolation filter, and the delay argument is at least N - 1/2.

Note The interpolated delay should not be less than `N - 1/2`. (The allpass delay ranges from `N - 1/2` to `N + 1/2`.) This constraint can be alleviated by altering the code, but be aware that allpass filters approach zero delay by means of pole-zero cancellations. The delay range `[N-1/2,N+1/2]` is not optimal. What is?

Delay arguments too small will produce an UNSTABLE allpass!

Because allpass interpolation is recursive, it is not as robust as Lagrange interpolation under time-varying conditions. (You may hear clicks when changing the delay rapidly.)

First-order allpass interpolation, delay d in [0.5,1.5]

---

demos.lib

This library contains a set of demo functions based on examples located in the `/examples` folder. Its official prefix is `dm`.

Analyzers

`mth_octave_spectral_level_demo`

Demonstrate mth_octave_spectral_level in a standalone GUI.

Usage

```
_ : mth_octave_spectral_level_demo(BandsPerOctave);
_ : spectral_level_demo : _; // 2/3 octave
```

Filters

`parametric_eq_demo`

A parametric equalizer application.

Usage:

```
_ : parametric_eq_demo : _ ;
```

`spectral_tilt_demo`

A spectral tilt application.

Usage

```
_ : spectral_tilt_demo(N) : _ ;
```

Where:

- `N`: filter order (integer)

All other parameters interactive

`mth_octave_filterbank_demo` and `filterbank_demo`

Graphic Equalizer: Each filter-bank output signal routes through a fader.

Usage

```
_ : mth_octave_filterbank_demo(M) : _
_ : filterbank_demo : _
```

Where:

- `N`: number of bands per octave

Effects

`cubicnl_demo`

Distortion demo application.

Usage:

```
_ : cubicnl_demo : _;
```

`gate_demo`

Gate demo application.

Usage

```
_,_ : gate_demo : _,_;
```

`compressor_demo`

Compressor demo application.

Usage

```
_,_ : compressor_demo : _,_;
```

`moog_vcf_demo`

Illustrate and compare all three Moog VCF implementations above.

Usage

```
_ : moog_vcf_demo : _;
```

`wah4_demo`

Wah pedal application.

Usage

```
_ : wah4_demo : _;
```

---

crybaby_demo

Crybaby effect application.

Usage

```
_ : crybaby_demo : _ ;
```

---

flanger_demo

Flanger effect application.

Usage

```
_,_ : flanger_demo : _,_;
```

---

phaser2_demo

Phaser effect demo application.

Usage

```
_,_ : phaser2_demo : _,_;
```

---

stereo_reverb_tester

Handy test inputs for reverberator demos below.

Usage

```
_ : stereo_reverb_tester : _
```

---

fdnrev0_demo

A reverb application using `fdnrev0`.

Usage

```
_,_ : fdnrev0_demo(N,NB,BBSO) : _,_
```

Where:

- `n`: Feedback Delay Network (FDN) order / number of delay lines used = order of feedback matrix / 2, 4, 8, or 16 [extend primes array below for 32, 64, ...]
- `nb`: Number of frequency bands / Number of (nearly) independent T60 controls / Integer 3 or greater
- `bbso` = Butterworth band-split order / order of lowpass/highpass bandsplit used at each crossover freq / odd positive integer

---

zita_rev_fdn_demo

Reverb demo application based on `zita_rev_fdn`.

Usage

```
si.bus(8) : zita_rev_fdn_demo : si.bus(8)
```

---

zita_rev1

Example GUI for `zita_rev1_stereo` (mostly following the Linux `zita-rev1` GUI).

Only the dry/wet and output level parameters are "dezippered" here. If parameters are to be varied in real time, use `smooth(0.999)` or the like in the same way.

Usage

```
_,_ : zita_rev1 : _,_
```

Reference http://www.kokkinizita.net/linuxaudio/zita-rev1-doc/quickguide.html

---

Generators

sawtooth_demo

An application demonstrating the different sawtooth oscillators of Faust.

Usage

```
sawtooth_demo : _
```

---

virtual_analog_oscillator_demo

Virtual analog oscillator demo application.

Usage

```
virtual_analog_oscillator_demo : _
```

---

oscrs_demo

Simple application demoing filter based oscillators.

Usage

```
oscrs_demo : _
```

---

velvet_noise_demo

Listen to velvet_noise!

Usage

```
velvet_noise_demo : _
```

---

latch_demo

Illustrate latch operation

Usage

```
echo 'import("stdfaust.lib");' > latch_demo.dsp
echo 'process = dm.latch_demo;' >> latch_demo.dsp
faust2octave latch_demo.dsp
Octave:1> plot(faustout);
```

---

envelopes_demo

Illustrate various envelopes overlaid

Usage

```
echo 'import("stdfaust.lib");' > envelopes_demo.dsp
echo 'process = dm.envelopes_demo;' >> envelopes_demo.dsp
faust2octave envelopes_demo.dsp
Octave:1> plot(faustout);
```

---

exciter

Psychoacoustic harmonic exciter, with GUI.

Usage

```
_ : exciter : _
```

References

- https://secure.aes.org/forum/pubs/ebriefs/?elib=16939
- https://www.researchgate.net/publication/258333577_Modeling_the_Harmonic_Exciter

---

`vocoder_demo`

Use example of the vocoder function where an impulse train is used as excitation.

Usage

```
_ : vocoder_demo : _;
```

`freeverb_demo`

Freeverb demo application.

Usage

```
_,_ : freeverb_demo : _,_;
```

---

envelopes.lib

This library contains a collection of envelope generators. Its official prefix is `en`.

Functions Reference

`smoothEnvelope`

An envelope with an exponential attack and release. `smoothEnvelope` is a standard Faust function.

Usage

```
smoothEnvelope(ar,t) : _
```

- `ar`: attack and release duration (s)
- `t`: trigger signal (0-1)

`ar`

AR (Attack, Release) envelope generator (useful to create percussion envelopes). `ar` is a standard Faust function.

Usage

```
ar(a,r,t) : _
```

Where:

- `a`: attack (sec)
- `r`: release (sec)
- `t`: trigger signal (0 or 1)

`asr`

ASR (Attack, Sustain, Release) envelope generator. `asr` is a standard Faust function.

Usage

```
asr(a,s,r,g) : _
```

Where:

- `a`, `s`, `r`: attack (sec), sustain (percentage of g), release (sec)
- `g`: trigger signal (>0 for attack, then release is when g back to 0)

`adsr`

ADSR (Attack, Decay, Sustain, Release) envelope generator. `adsr` is a standard Faust function.

Usage

```
adsr(a,d,s,r,g) : _
```

Where:

- `a`, `d`, `s`, `r`: attack (sec), decay (sec), sustain level (percentage of max), release (sec)
- `g`: gate signal (>0 for attack, then release is when g back to 0)

`adsre`

ADSRE (Attack, Decay, Sustain, Release) envelope generator with Exponential segments. `adsre` is a standard Faust function.

Usage

```
adsre(a,d,s,r,g) : _
```

Where:

- `a`, `d`, `s`, `r`: attack (sec), decay (sec), sustain level (percentage of max), release (sec)
- `g`: gate signal (>0 for attack, then release is when g back to 0)

---

filters.lib

Faust Filters library; Its official prefix is `fi`.

The Filters library is organized into 18 sections:

- Basic Filters
- Comb Filters
- Direct-Form Digital Filter Sections
- Direct-Form Second-Order Biquad Sections
- Ladder/Lattice Digital Filters
- Useful Special Cases
- Ladder/Lattice Allpass Filters
- Digital Filter Sections Specified as Analog Filter Sections
- Simple Resonator Filters
- Butterworth Lowpass/Highpass Filters
- Special Filter-Bank Delay-Equalizing Allpass Filters
- Elliptic (Cauer) Lowpass Filters
- Elliptic Highpass Filters
- Butterworth Bandpass/Bandstop Filters
- Elliptic Bandpass Filters
- Parametric Equalizers (Shelf, Peaking)
- Mth-Octave Filter-Banks
- Arbitrary-Crossover Filter-Banks and Spectrum Analyzers

For more information, see ../documentation/library.pdf

Basic Filters

`zero`

One zero filter. Difference equation: y(n) = x(n) - z * x(n-1).

Usage

```
_ : zero(z) : _
```

Where:

- `z`: location of zero along real axis in z-plane

Reference https://ccrma.stanford.edu/~jos/filters/One_Zero.html

---

`pole`

One pole filter. Could also be called a "leaky integrator". Difference equation: y(n) = x(n) + p * y(n-1).

Usage

```
_ : pole(z) : _
```

Where:

- `p`: pole location = feedback coefficient

Reference https://ccrma.stanford.edu/~jos/filters/One_Pole.html

---

`integrator`

Same as `pole(1)` [implemented separately for block-diagram clarity].

`dcblockerat`

DC blocker with configurable break frequency. The amplitude response is substantially flat above fb, and sloped at about +6 dB/octave below fb. Derived from the analog transfer function H(s) = s / (s + 2PIfb) by the low-frequency-matching bilinear transform method (i.e., the standard frequency-scaling constant 2*SR).

Usage

```
_ : dcblockerat(fb) : _
```

Where:

- `fb`: "break frequency" in Hz, i.e., -3 dB gain frequency.

Reference https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

---

`dcblocker`

DC blocker. Default dc blocker has -3dB point near 35 Hz (at 44.1 kHz) and high-frequency gain near 1.0025 (due to no scaling). `dcblocker` is as standard Faust function.

Usage

```
_ : dcblocker : _
```

Comb Filters

`ff_comb`

Feed-Forward Comb Filter. Note that `ff_comb` requires integer delays (uses `delay` internally). `ff_comb` is a standard Faust function.

Usage

```
_ : ff_comb(maxdel,intdel,b0,bM) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input
- `bM`: gain applied to delay-line output and then summed with input

Reference https://ccrma.stanford.edu/~jos/pasp/Feedforward_Comb_Filters.html

---

`ff_fcomb`

Feed-Forward Comb Filter. Note that `ff_fcomb` takes floating-point delays (uses `fdelay` internally). `ff_fcomb` is a standard Faust function.

Usage

```
_ : ff_fcomb(maxdel,del,b0,bM) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input
- `bM`: gain applied to delay-line output and then summed with input

Reference https://ccrma.stanford.edu/~jos/pasp/Feedforward_Comb_Filters.html

---

`ffcombfilter`

Typical special case of `ff_comb()` where: `b0 = 1`.

`fb_comb`

Feed-Back Comb Filter (integer delay).

Usage

```
_ : fb_comb(maxdel,intdel,b0,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input and forwarded to output
- `aN`: minus the gain applied to delay-line output before summing with the input and feeding to the delay line

Reference https://ccrma.stanford.edu/~jos/pasp/Feedback_Comb_Filters.html

---

`fb_fcomb`

Feed-Back Comb Filter (floating point delay).

Usage

```
_ : fb_fcomb(maxdel,del,b0,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input and forwarded to output
- `aN`: minus the gain applied to delay-line output before summing with the input and feeding to the delay line

Reference https://ccrma.stanford.edu/~jos/pasp/Feedback_Comb_Filters.html

---

`rev1`

Special case of `fb_comb` (`rev1(maxdel,N,g)`). The "rev1 section" dates back to the 1960s in computer-music reverberation. See the `jcrev` and `brassrev` in `reverbs.lib` for usage examples.

`fbcombfilter` and `ffbcombfilter`

Other special cases of Feed-Back Comb Filter.

Usage

```
_ : fbcombfilter(maxdel,intdel,g) : _
_ : ffbcombfilter(maxdel,del,g) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `g`: feedback gain

Reference https://ccrma.stanford.edu/~jos/pasp/Feedback_Comb_Filters.html

---

`allpass_comb`

Schroeder Allpass Comb Filter. Note that

```
allpass_comb(maxlen,len,aN) = ff_comb(maxlen,len,aN,1) : fb_comb(maxlen,len-1,1,aN);
```

which is a direct-form-1 implementation, requiring two delay lines. The implementation here is direct-form-2 requiring only one delay line.

Usage

```
_ : allpass_comb (maxdel,intdel,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `aN`: minus the feedback gain

References

- https://ccrma.stanford.edu/~jos/pasp/Allpass_Two_Combs.html
- https://ccrma.stanford.edu/~jos/pasp/Schroeder_Allpass_Sections.html
- https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

---

allpass_fcomb

Schroeder Allpass Comb Filter. Note that

```
allpass_comb(maxlen,len,aN) = ff_comb(maxlen,len,aN,1) : fb_comb(maxlen,len-1,1,aN);
```

which is a direct-form-1 implementation, requiring two delay lines. The implementation here is direct-form-2 requiring only one delay line.

`allpass_fcomb` is a standard Faust library.

Usage

```
_ : allpass_comb (maxdel,intdel,aN) : _
_ : allpass_fcomb(maxdel,del,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (float) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `aN`: minus the feedback gain

References

- https://ccrma.stanford.edu/~jos/pasp/Allpass_Two_Combs.html
- https://ccrma.stanford.edu/~jos/pasp/Schroeder_Allpass_Sections.html
- https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

---

rev2

Special case of `allpass_comb` (`rev2(maxlen,len,g)`). The "rev2 section" dates back to the 1960s in computer-music reverberation. See the `jcrev` and `brassrev` in `reverbs.lib` for usage examples.

---

allpass_fcomb5 and allpass_fcomb1a

Same as `allpass_fcomb` but use `fdelay5` and `fdelay1a` internally (Interpolation helps - look at an fft of faust2octave on

```
`1-1' <: allpass_fcomb(1024,10.5,0.95), allpass_fcomb5(1024,10.5,0.95);`).
```

Direct-Form Digital Filter Sections

iir

Nth-order Infinite-Impulse-Response (IIR) digital filter, implemented in terms of the Transfer-Function (TF) coefficients. Such filter structures are termed "direct form".

`iir` is a standard Faust function.

Usage

```
_ : iir(bcoeffs,acoeffs) : _
```

Where:

- `order`: filter order (int) = max(#poles,#zeros)
- `bcoeffs`: (b0,b1,...,b_order) = TF numerator coefficients
- `acoeffs`: (a1,...,a_order) = TF denominator coeffs (a0=1)

Reference https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

---

fir

FIR filter (convolution of FIR filter coefficients with a signal)

Usage

```
_ : fir(bv) : _
```

`fir` is standard Faust function.

Where:

- `bv` = b0,b1,…,bn is a parallel bank of coefficient signals.

Note `bv` is processed using pattern-matching at compile time, so it must have this normal form (parallel signals).

Example Smoothing white noise with a five-point moving average:

```
bv = .2,.2,.2,.2,.2;
process = noise : fir(bv);
```

Equivalent (note double parens):

```
process = noise : fir((.2,.2,.2,.2,.2));
```

`conv` and `convN`

Convolution of input signal with given coefficients.

Usage

```
_ : conv((k1,k2,k3,...,kN)) : _; // Argument = one signal bank
_ : convN(N,(k1,k2,k3,...)) : _; // Useful when N < count((k1,...))
```

`tf1`, `tf2` and `tf3`

tfN = N'th-order direct-form digital filter.

Usage

```
_ : tf1(b0,b1,a1) : _
_ : tf2(b0,b1,b2,a1,a2) : _
_ : tf3(b0,b1,b2,b3,a1,a2,a3) : _
```

Where:

- `a`: the poles
- `b`: the zeros

Reference https://ccrma.stanford.edu/~jos/fp/Direct_Form_I.html

---

`notchw`

Simple notch filter based on a biquad (`tf2`). `notchw` is a standard Faust function.

Usage:

```
_ : notchw(width,freq) : _
```

Where:

- `width`: "notch width" in Hz (approximate)
- `freq`: "notch frequency" in Hz

Reference https://ccrma.stanford.edu/~jos/pasp/Phasing_2nd_Order_Allpass_Filters.html

---

Direct-Form Second-Order Biquad Sections

Direct-Form Second-Order Biquad Sections

Reference https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

`tf21`, `tf22`, `tf22t` and `tf21t`

tfN = N'th-order direct-form digital filter where:

- `tf21` is tf2, direct-form 1
- `tf22` is tf2, direct-form 2
- `tf22t` is tf2, direct-form 2 transposed
- `tf21t` is tf2, direct-form 1 transposed

Usage

```
_ : tf21(b0,b1,b2,a1,a2) : _
_ : tf22(b0,b1,b2,a1,a2) : _
_ : tf22t(b0,b1,b2,a1,a2) : _
_ : tf21t(b0,b1,b2,a1,a2) : _
```

Where:

- `a`: the poles
- `b`: the zeros

Reference https://ccrma.stanford.edu/~jos/fp/Direct_Form_I.html

---

Ladder/Lattice Digital Filters

Ladder and lattice digital filters generally have superior numerical properties relative to direct-form digital filters. They can be derived from digital waveguide filters, which gives them a physical interpretation.

`av2sv`

Compute reflection coefficients sv from transfer-function denominator av.

Usage

```
sv = av2sv(av)
```

Where:

- `av`: parallel signal bank `a1,...,aN`
- `sv`: parallel signal bank `s1,...,sN`

where `ro = ith` reflection coefficient, and `ai` = coefficient of `z^(-i)` in the filter transfer-function denominator `A(z)`.

Reference https://ccrma.stanford.edu/~jos/filters/Step_Down_Procedure.html (where reflection coefficients are denoted by k rather than s).

`bvav2nuv`

Compute lattice tap coefficients from transfer-function coefficients.

Usage

```
nuv = bvav2nuv(bv,av)
```

Where:

- `av`: parallel signal bank `a1,...,aN`
- `bv`: parallel signal bank `b0,b1,...,aN`
- `nuv`: parallel signal bank `nu1,...,nuN`

where `nui` is the i'th tap coefficient, `bi` is the coefficient of `z^(-i)` in the filter numerator, `ai` is the coefficient of `z^(-i)` in the filter denominator

---

`iir_lat2`

Two-multiply latice IIR filter or arbitrary order.

Usage

```
_ : iir_lat2(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

`allpassnt`

Two-multiply lattice allpass (nested order-1 direct-form-ii allpasses).

Usage

```
_ : allpassnt(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

`iir_kl`

Kelly-Lochbaum ladder IIR filter or arbitrary order.

Usage

```
_ : iir_kl(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

`allpassnklt`

Kelly-Lochbaum ladder allpass.

Usage:

```
_ : allpassklt(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

---

iir_lat1

One-multiply latice IIR filter or arbitrary order.

Usage

```
_ : iir_lat1(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

---

allpassn1mt

One-multiply lattice allpass with tap lines.

Usage

```
_ : allpassn1mt(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

---

iir_nl

Normalized ladder filter of arbitrary order.

Usage

```
_ : iir_nl(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

References

- J. D. Markel and A. H. Gray, Linear Prediction of Speech, New York: Springer Verlag, 1976.
- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

`allpassnnlt`

Normalized ladder allpass filter of arbitrary order.

Usage:

```
_ : allpassnnlt(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1,1)

References

- J. D. Markel and A. H. Gray, Linear Prediction of Speech, New York: Springer Verlag, 1976.
- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

Useful Special Cases

`tf2np`

Biquad based on a stable second-order Normalized Ladder Filter (more robust to modulation than `tf2` and protected against instability).

Usage

```
_ : tf2np(b0,b1,b2,a1,a2) : _
```

Where:

- `a`: the poles
- `b`: the zeros

`wgr`

Second-order transformer-normalized digital waveguide resonator.

Usage

```
_ : wgr(f,r) : _
```

Where:

- `f`: resonance frequency (Hz)
- `r`: loss factor for exponential decay (set to 1 to make a numerically stable oscillator)

References

- https://ccrma.stanford.edu/~jos/pasp/Power_Normalized_Waveguide_Filters.html
- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

`nlf2`

Second order normalized digital waveguide resonator.

Usage

```
_ : nlf2(f,r) : _
```

Where:

- `f`: resonance frequency (Hz)
- `r`: loss factor for exponential decay (set to 1 to make a sinusoidal oscillator)

Reference https://ccrma.stanford.edu/~jos/pasp/Power_Normalized_Waveguide_Filters.html

---

`apnl`

Passive Nonlinear Allpass based on Pierce switching springs idea. Switch between allpass coefficient `a1` and `a2` at signal zero crossings.

Usage

```
_ : apnl(a1,a2) : _
```

Where:

- `a1` and `a2`: allpass coefficients

Reference

- "A Passive Nonlinear Digital Filter Design ... " by John R. Pierce and Scott A. Van Duyne, JASA, vol. 101, no. 2, pp. 1120-1126, 1997

Ladder/Lattice Allpass Filters

An allpass filter has gain 1 at every frequency, but variable phase. Ladder/lattice allpass filters are specified by reflection coefficients. They are defined here as nested allpass filters, hence the names allpassn*.

References

- https://ccrma.stanford.edu/~jos/pasp/Conventional_Ladder_Filters.html
- https://ccrma.stanford.edu/~jos/pasp/Nested_Allpass_Filters.html
- Linear Prediction of Speech, Markel and Gray, Springer Verlag, 1976

`allpassn`

Two-multiply lattice - each section is two multiply-adds.

Usage:

```
_ : allpassn(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

References

- J. O. Smith and R. Michon, "Nonlinear Allpass Ladder Filters in FAUST", in Proceedings of the 14th International Conference on Digital Audio Effects (DAFx-11), Paris, France, September 19-23, 2011.

`allpassnn`

Normalized form - four multiplies and two adds per section, but coefficients can be time varying and nonlinear without "parametric amplification" (modulation of signal energy).

Usage:

```
_ : allpassnn(n,tv) : _
```

Where:

- `n`: the order of the filter
- `tv`: the reflexion coefficients (-PI PI)

---

allpasskl

Kelly-Lochbaum form - four multiplies and two adds per section, but all signals have an immediate physical interpretation as traveling pressure waves, etc.

Usage:

```
_ : allpassnkl(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

---

allpass1m

One-multiply form - one multiply and three adds per section. Normally the most efficient in special-purpose hardware.

Usage:

```
_ : allpassn1m(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

Digital Filter Sections Specified as Analog Filter Sections

tf2s and tf2snp

Second-order direct-form digital filter, specified by ANALOG transfer-function polynomials B(s)/A(s), and a frequency-scaling parameter. Digitization via the bilinear transform is built in.

Usage

```
_ : tf2s(b2,b1,b0,a1,a0,w1) : _
```

Where:

```
        b2 s^2 + b1 s + b0
H(s) = --------------------
           s^2 + a1 s + a0
```

and `w1` is the desired digital frequency (in radians/second) corresponding to analog frequency 1 rad/sec (i.e., `s = j`).

Example A second-order ANALOG Butterworth lowpass filter, normalized to have cutoff frequency at 1 rad/sec, has transfer function

```
             1
H(s) = -----------------
        s^2 + a1 s + 1
```

where `a1 = sqrt(2)`. Therefore, a DIGITAL Butterworth lowpass cutting off at `SR/4` is specified as `tf2s(0,0,1,sqrt(2),1,PI*SR/2);`

Method Bilinear transform scaled for exact mapping of w1.

Reference https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

---

`tf3slf`

Analogous to tf2s above, but third order, and using the typical low-frequency-matching bilinear-transform constant 2/T ("lf" series) instead of the specific-frequency-matching value used in tf2s and tf1s. Note the lack of a "w1" argument.

Usage

```
_ : tf3slf(b3,b2,b1,b0,a3,a2,a1,a0) : _
```

`tf1s`

First-order direct-form digital filter, specified by ANALOG transfer-function polynomials B(s)/A(s), and a frequency-scaling parameter.

Usage

```
tf1s(b1,b0,a0,w1)
```

Where:

```
b1 s + b0
```

H(s) = ——— s + a0

and `w1` is the desired digital frequency (in radians/second) corresponding to analog frequency 1 rad/sec (i.e., `s = j`).

Example A first-order ANALOG Butterworth lowpass filter, normalized to have cutoff frequency at 1 rad/sec, has transfer function

```
1
```

H(s) = —— s + 1

so `b0 = a0 = 1` and `b1 = 0`. Therefore, a DIGITAL first-order Butterworth lowpass with gain -3dB at `SR/4` is specified as

```
tf1s(0,1,1,PI*SR/2); // digital half-band order 1 Butterworth
```

Method Bilinear transform scaled for exact mapping of w1.

Reference https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

---

`tf2sb`

Bandpass mapping of `tf2s`: In addition to a frequency-scaling parameter `w1` (set to HALF the desired passband width in rad/sec), there is a desired center-frequency parameter wc (also in rad/s). Thus, `tf2sb` implements a fourth-order digital bandpass filter section specified by the coefficients of a second-order analog lowpass prototpe section. Such sections can be combined in series for higher orders. The order of mappings is (1) frequency scaling (to set lowpass cutoff w1), (2) bandpass mapping to wc, then (3) the bilinear transform, with the usual scale parameter `2*SR`. Algebra carried out in maxima and pasted here.

Usage

```
_ : tf2sb(b2,b1,b0,a1,a0,w1,wc) : _
```

`tf1sb`

First-to-second-order lowpass-to-bandpass section mapping, analogous to tf2sb above.

Usage

```
_ : tf1sb(b1,b0,a0,w1,wc) : _
```

Simple Resonator Filters

`resonlp`

Simple resonant lowpass filter based on `tf2s` (virtual analog). `resonlp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

`resonhp`

Simple resonant highpass filters based on `tf2s` (virtual analog). `resonhp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

`resonbp`

Simple resonant bandpass filters based on `tf2s` (virtual analog). `resonbp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

Butterworth Lowpass/Highpass Filters

`lowpass`

Nth-order Butterworth lowpass filter. `lowpass` is a standard Faust function.

Usage

```
_ : lowpass(N,fc) : _
```

Where:

- `N`: filter order (number of poles) [nonnegative constant integer]
- `fc`: desired cut-off frequency (-3dB frequency) in Hz

References

- https://ccrma.stanford.edu/~jos/filters/Butterworth_Lowpass_Design.html
- `butter` function in Octave (`"[z,p,g] = butter(N,1,'s');"`)

`highpass`

Nth-order Butterworth highpass filters. `highpass` is a standard Faust function.

Usage

```
_ : highpass(N,fc) : _
```

Where:

- `N`: filter order (number of poles) [nonnegative constant integer]
- `fc`: desired cut-off frequency (-3dB frequency) in Hz

References

- https://ccrma.stanford.edu/~jos/filters/Butterworth_Lowpass_Design.html
- `butter` function in Octave (`"[z,p,g] = butter(N,1,'s');"`)

`lowpass0_highpass1`

Special Filter-Bank Delay-Equalizing Allpass Filters

These special allpass filters are needed by filterbank et al. below. They are equivalent to (`lowpass(N,fc)` +|- `highpass(N,fc))/2`, but with canceling pole-zero pairs removed (which occurs for odd N).

`lowpass_plus|minus_highpass`

Elliptic (Cauer) Lowpass Filters

Elliptic (Cauer) Lowpass Filters

References

- <http://en.wikipedia.org/wiki/Elliptic_filter
- functions `ncauer` and `ellip` in Octave

`lowpass3e`

Third-order Elliptic (Cauer) lowpass filter.

Usage

```
_ : lowpass3e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

Design For spectral band-slice level display (see `octave_analyzer3e`):

```
[z,p,g] = ncauer(Rp,Rs,3);  % analog zeros, poles, and gain, where
Rp = 60  % dB ripple in stopband
Rs = 0.2 % dB ripple in passband
```

`lowpass6e`

Sixth-order Elliptic/Cauer lowpass filter.

Usage

```
_ : lowpass6e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

Design For spectral band-slice level display (see octave_analyzer6e):

```
[z,p,g] = ncauer(Rp,Rs,6);  % analog zeros, poles, and gain, where
 Rp = 80  % dB ripple in stopband
 Rs = 0.2 % dB ripple in passband
```

Elliptic Highpass Filters

`highpass3e`

Third-order Elliptic (Cauer) highpass filter. Inversion of `lowpass3e` wrt unit circle in s plane (s <- 1/s)

Usage

```
_ : highpass3e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

`highpass6e`

Sixth-order Elliptic/Cauer highpass filter. Inversion of lowpass3e wrt unit circle in s plane (s <- 1/s)

Usage

```
_ : highpass6e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

Butterworth Bandpass/Bandstop Filters

`bandpass`

Order 2*Nh Butterworth bandpass filter made using the transformation `s <- s + wc^2/s` on `lowpass(Nh)`, where `wc` is the desired bandpass center frequency. The `lowpass(Nh)` cutoff `w1` is half the desired bandpass width. `bandpass` is a standard Faust function.

Usage

```
_ : bandpass(Nh,fl,fu) : _
```

Where:

- `Nh`: HALF the desired bandpass order (which is therefore even)
- `fl`: lower -3dB frequency in Hz
- `fu`: upper -3dB frequency in Hz Thus, the passband width is `fu-fl`, and its center frequency is `(fl+fu)/2`.

Reference http://cnx.org/content/m16913/latest/

`bandstop`

Order 2*Nh Butterworth bandstop filter made using the transformation `s <- s + wc^2/s` on `highpass(Nh)`, where `wc` is the desired bandpass center frequency. The `highpass(Nh)` cutoff `w1` is half the desired bandpass width. `bandstop` is a standard Faust function.

Usage

```
_ : bandstop(Nh,fl,fu) : _
```

Where:

- `Nh`: HALF the desired bandstop order (which is therefore even)
- `fl`: lower -3dB frequency in Hz
- `fu`: upper -3dB frequency in Hz Thus, the passband (stopband) width is `fu-fl`, and its center frequency is `(fl+fu)/2`.

Reference http://cnx.org/content/m16913/latest/

Elliptic Bandpass Filters

`bandpass6e`

Order 12 elliptic bandpass filter analogous to `bandpass(6)`.

`bandpass12e`

Order 24 elliptic bandpass filter analogous to `bandpass(6)`.

Parametric Equalizers (Shelf, Peaking)

Parametric Equalizers (Shelf, Peaking)

References

- http://en.wikipedia.org/wiki/Equalization
- http://www.musicdsp.org/files/Audio-EQ-Cookbook.txt
- Digital Audio Signal Processing, Udo Zolzer, Wiley, 1999, p. 124
- https://ccrma.stanford.edu/~jos/filters/Low_High_Shelving_Filters.html>
- https://ccrma.stanford.edu/~jos/filters/Peaking_Equalizers.html>
- maxmsp.lib in the Faust distribution
- bandfilter.dsp in the faust2pd distribution

low_shelf

First-order "low shelf" filter (gain boost|cut between dc and some frequency) `low_shelf` is a standard Faust function.

Usage

```
_ : lowshelf(N,L0,fx) : _
_ : low_shelf(L0,fx) : _ // default case (order 3)
_ : lowshelf_other_freq(N,L0,fx) : _
```

Where: * `N`: filter order 1, 3, 5, ... (odd only). (default should be 3) * `L0`: desired level (dB) between dc and fx (boost `L0>0` or cut `L0<0`) * `fx`: -3dB frequency of lowpass band (`L0>0`) or upper band (`L0<0`) (see "SHELF SHAPE" below).

The gain at SR/2 is constrained to be 1. The generalization to arbitrary odd orders is based on the well known fact that odd-order Butterworth band-splits are allpass-complementary (see filterbank documentation below for references).

Shelf Shape The magnitude frequency response is approximately piecewise-linear on a log-log plot ("BODE PLOT"). The Bode "stick diagram" approximation L(lf) is easy to state in dB versus dB-frequency lf = dB(f):

- L0 > 0:
- L(lf) = L0, f between 0 and fx = 1st corner frequency;
- L(lf) = L0 - N * (lf - lfx), f between fx and f2 = 2nd corner frequency;
- L(lf) = 0, lf > lf2.
- lf2 = lfx + L0/N = dB-frequency at which level gets back to 0 dB.
- L0 < 0:
- L(lf) = L0, f between 0 and f1 = 1st corner frequency;
- L(lf) = - N * (lfx - lf), f between f1 and lfx = 2nd corner frequency;
- L(lf) = 0, lf > lfx.
- lf1 = lfx + L0/N = dB-frequency at which level goes up from L0.

See `lowshelf_other_freq`.

---

high_shelf

First-order "high shelf" filter (gain boost|cut above some frequency). `high_shelf` is a standard Faust function.

Usage

```
_ : highshelf(N,Lpi,fx) : _
_ : high_shelf(L0,fx) : _ // default case (order 3)
_ : highshelf_other_freq(N,Lpi,fx) : _
```

Where:

- `N`: filter order 1, 3, 5, … (odd only).
- `Lpi`: desired level (dB) between fx and SR/2 (boost Lpi>0 or cut Lpi<0)
- `fx`: -3dB frequency of highpass band (L0>0) or lower band (L0<0) (Use highshelf_other_freq() below to find the other one.)

The gain at dc is constrained to be 1. See `lowshelf` documentation above for more details on shelf shape.

`peak_eq`

Second order "peaking equalizer" section (gain boost or cut near some frequency) Also called a "parametric equalizer" section. `peak_eq` is a standard Faust function.

Usage

```
_ : peak_eq(Lfx,fx,B) : _;
```

Where:

- `Lfx`: level (dB) at fx (boost Lfx>0 or cut Lfx<0)
- `fx`: peak frequency (Hz)
- `B`: bandwidth (B) of peak in Hz

`peak_eq_cq`

Constant-Q second order peaking equalizer section.

Usage

```
_ : peak_eq_cq(Lfx,fx,Q) : _;
```

Where:

- `Lfx`: level (dB) at fx
- `fx`: boost or cut frequency (Hz)
- `Q`: "Quality factor" = fx/B where B = bandwidth of peak in Hz

---

`peak_eq_rm`

Regalia-Mitra second order peaking equalizer section

Usage

```
_ : peak_eq_rm(Lfx,fx,tanPiBT) : _;
```

Where:

- `Lfx`: level (dB) at fx
- `fx`: boost or cut frequency (Hz)
- `tanPiBT`: `tan(PI*B/SR)`, where B = -3dB bandwidth (Hz) when 10^(Lfx/20) = 0 ~ PI*B/SR for narrow bandwidths B

Reference P.A. Regalia, S.K. Mitra, and P.P. Vaidyanathan, "The Digital All-Pass Filter: A Versatile Signal Processing Building Block" Proceedings of the IEEE, 76(1):19-37, Jan. 1988. (See pp. 29-30.)

`spectral_tilt`

Spectral tilt filter, providing an arbitrary spectral rolloff factor alpha in (-1,1), where -1 corresponds to one pole (-6 dB per octave), and +1 corresponds to one zero (+6 dB per octave). In other words, alpha is the slope of the ln magnitude versus ln frequency. For a "pinking filter" (e.g., to generate 1/f noise from white noise), set alpha to -1/2.

Usage

```
_ : spectral_tilt(N,f0,bw,alpha) : _
```

Where:

- `N`: desired integer filter order (fixed at compile time)
- `f0`: lower frequency limit for desired roll-off band
- `bw`: bandwidth of desired roll-off band
- `alpha`: slope of roll-off desired in nepers per neper (ln mag / ln radian freq)

Examples See `spectral_tilt_demo`.

Reference J.O. Smith and H.F. Smith, "Closed Form Fractional Integration and Differentiation via Real Exponentially Spaced Pole-Zero Pairs", arXiv.org publication arXiv:1606.06154 [cs.CE], June 7, 2016, http://arxiv.org/abs/1606.06154

`levelfilter`

Dynamic level lowpass filter. `levelfilter` is a standard Faust function.

Usage

```
_ : levelfilter(L,freq) : _
```

Where:

- `L`: desired level (in dB) at Nyquist limit (SR/2), e.g., -60
- `freq`: corner frequency (-3dB point) usually set to fundamental freq
- `N`: Number of filters in series where L = L/N

Reference https://ccrma.stanford.edu/realsimple/faust_strings/Dynamic_Level_Lowpass_Filter.html

---

levelfilterN

Dynamic level lowpass filter.

Usage

```
_ : levelfilterN(N,freq,L) : _
```

Where:

- `L`: desired level (in dB) at Nyquist limit (SR/2), e.g., -60
- `freq`: corner frequency (-3dB point) usually set to fundamental freq
- `N`: Number of filters in series where L = L/N

Reference https://ccrma.stanford.edu/realsimple/faust_strings/Dynamic_Level_Lowpass_Filter.html

---

Mth-Octave Filter-Banks

Mth-octave filter-banks split the input signal into a bank of parallel signals, one for each spectral band. They are related to the Mth-Octave Spectrum-Analyzers in `analysis.lib`. The documentation of this library contains more details about the implementation. The parameters are:

- `M`: number of band-slices per octave (>1)
- `N`: total number of bands (>2)
- `ftop`: upper bandlimit of the Mth-octave bands (<SR/2)

In addition to the Mth-octave output signals, there is a highpass signal containing frequencies from ftop to SR/2, and a "dc band" lowpass signal containing frequencies from 0 (dc) up to the start of the Mth-octave bands. Thus, the N output signals are

```
highpass(ftop), MthOctaveBands(M,N-2,ftop), dcBand(ftop*2^(-M*(N-1)))
```

A Filter-Bank is defined here as a signal bandsplitter having the property that summing its output signals gives an allpass-filtered version of the filter-bank input signal. A more conventional term for this is an "allpass-complementary filter bank". If the allpass filter is a pure delay (and possible scaling), the filter bank is said to be a "perfect-reconstruction filter bank" (see Vaidyanathan-1993 cited below for details). A "graphic equalizer", in which band signals are scaled by gains and summed, should be based on a filter bank.

The filter-banks below are implemented as Butterworth or Elliptic spectrum-analyzers followed by delay equalizers that make them allpass-complementary.

Increasing Channel Isolation Go to higher filter orders - see Regalia et al. or Vaidyanathan (cited below) regarding the construction of more aggressive recursive filter-banks using elliptic or Chebyshev prototype filters.

References

- "Tree-structured complementary filter banks using all-pass sections", Regalia et al., IEEE Trans. Circuits & Systems, CAS-34:1470-1484, Dec. 1987
- "Multirate Systems and Filter Banks", P. Vaidyanathan, Prentice-Hall, 1993
- Elementary filter theory: https://ccrma.stanford.edu/~jos/filters/

`mth_octave_filterbank[n]`

Allpass-complementary filter banks based on Butterworth band-splitting. For Butterworth band-splits, the needed delay equalizer is easily found.

Usage

```
_ : mth_octave_filterbank(O,M,ftop,N) : par(i,N,_); // Oth-order
_ : mth_octave_filterbank_alt(O,M,ftop,N) : par(i,N,_); // dc-inverted version
```

Also for convenience:

```
_ : mth_octave_filterbank3(M,ftop,N) : par(i,N,_); // 3d-order Butterworth
_ : mth_octave_filterbank5(M,ftop,N) : par(i,N,_); // 5th-roder Butterworth
mth_octave_filterbank_default = mth_octave_analyzer6e;
```

Where:

- `O`: order of filter used to split each frequency band into two
- `M`: number of band-slices per octave
- `ftop`: highest band-split crossover frequency (e.g., 20 kHz)
- `N`: total number of bands (including dc and Nyquist)

Arbitrary-Crossover Filter-Banks and Spectrum Analyzers

These are similar to the Mth-octave analyzers above, except that the band-split frequencies are passed explicitly as arguments.

`filterbank`

Filter bank. `filterbank` is a standard Faust function.

Usage

```
_ : filterbank (O,freqs) : par(i,N,_); // Butterworth band-splits
```

Where:

- `O`: band-split filter order (ODD integer required for filterbank[i])
- `freqs`: (fc1,fc2,...,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : filterbank(3,(fc1,fc2)) : _,_,_
```

`filterbanki`

Inverted-dc filter bank.

Usage

```
_ : filterbanki(O,freqs) : par(i,N,_); // Inverted-dc version
```

Where:

- `O`: band-split filter order (ODD integer required for `filterbank[i]`)
- `freqs`: (fc1,fc2,...,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : filterbanki(3,(fc1,fc2)) : _,_,_
```

---

hoa.lib

Faust library for high order ambisonic. Its official prefix is `ho`.

`encoder`

Ambisonic encoder. Encodes a signal in the circular harmonics domain depending on an order of decomposition and an angle.

Usage

```
encoder(n, x, a) : _
```

Where:

- `n`: the order
- `x`: the signal
- `a`: the angle

`decoder`

Decodes an ambisonics sound field for a circular array of loudspeakers.

Usage

```
_ : decoder(n, p) : _
```

Where:

- `n`: the order
- `p`: the number of speakers

Note Number of loudspeakers must be greater or equal to 2n+1. It's preferable to use 2n+2 loudspeakers.

---

decoderStereo

Decodes an ambisonic sound field for stereophonic configuration. An "home made" ambisonic decoder for stereophonic restitution (30° - 330°) : Sound field lose energy around 180°. You should use `inPhase` optimization with ponctual sources. #### Usage

```
_ : decoderStereo(n) : _
```

Where:

- `n`: the order

Optimization Functions

Functions to weight the circular harmonics signals depending to the ambisonics optimization. It can be `basic` for no optimization, `maxRe` or `inPhase`.

optimBasic

The basic optimization has no effect and should be used for a perfect circle of loudspeakers with one listener at the perfect center loudspeakers array.

Usage

```
_ : optimBasic(n) : _
```

Where:

- `n`: the order

---

optimMaxRe

The maxRe optimization optimize energy vector. It should be used for an auditory confined in the center of the loudspeakers array.

Usage

```
_ : optimMaxRe(n) : _
```

Where:

- `n`: the order

`optimInPhase`

The inPhase Optimization optimize energy vector and put all loudspeakers signals n phase. It should be used for an auditory.

Usage

```
:  optimInPhase(n) :  _
```

here:

`n`: the order

`wider`

Can be used to wide the diffusion of a localized sound. The order depending signals are weighted and appear in a logarithmic way to have linear changes.

Usage

```
_ : wider(n,w) : _
```

Where:

- `n`: the order
- `w`: the width value between 0 - 1

`map`

It simulate the distance of the source by applying a gain on the signal and a wider processing on the soundfield.

Usage

```
map(n, x, r, a)
```

Where:

- `n`: the order
- `x`: the signal
- `r`: the radius
- `a`: the angle in radian

`rotate`

Rotates the sound field.

Usage

```
_ : rotate(n, a) : _
```

Where:

- `n`: the order
- `a`: the angle in radian

---

maths.lib

Mathematic library for Faust. Some functions are implemenented as Faust foreign functions of `math.h` functions that are not part of Faust's primitives. Defines also various constants and several utilities.

The official prefix of this library is `ma`.

Functions Reference

`SR`

Current sampling rate (between 1Hz and 192000Hz). Constant during program execution.

Usage

```
SR : _
```

`BS`

Current block-size. Can change during the execution.

Usage

```
BS : _
```

`PI`

Constant PI in double precisio.n

Usage

```
PI : _
```

`FTZ`

Flush to zero: force samples under the "maximum subnormal number" to be zero. Usually not needed in C++ because the architecture file take care of this, but can be useful in javascript for instance.

Usage

```
_ : ftz : _
```

See : http://docs.oracle.com/cd/E19957-01/806-3568/ncg_math.html

---

`neg`

Invert the sign (-x) of a signal.

Usage

```
_ : neg : _
```

`sub(x,y)`

Subtract `x` and `y`.

`inv`

Compute the inverse (1/x) of the input signal.

Usage

```
_ : inv : _
```

`cbrt`

Computes the cube root of of the input signal.

Usage

```
_ : cbrt : _
```

---

hypot

Computes the euclidian distance of the two input signals sqrt(x*x+y*y) without undue overflow or underflow.

Usage

```
_,_ : hypot : _
```

---

ldexp

Takes two input signals: x and n, and multiplies x by 2 to the power n.

Usage

```
_,_ : ldexp : _
```

---

scalb

Takes two input signals: x and n, and multiplies x by 2 to the power n.

Usage

```
_,_ : scalb : _
```

---

log1p

Computes log(1 + x) without undue loss of accuracy when x is nearly zero.

Usage

```
_ : log1p : _
```

`logb`

Return exponent of the input signal as a floating-point number.

Usage

```
_ : logb : _
```

`ilogb`

Return exponent of the input signal as an integer number.

Usage

```
_ : ilogb : _
```

`log2`

Returns the base 2 logarithm of x.

Usage

```
_ : log2 : _
```

`expm1`

Return exponent of the input signal minus 1 with better precision.

Usage

```
_ : expm1 : _
```

`acosh`

Computes the principle value of the inverse hyperbolic cosine of the input signal.

Usage

```
_ : acosh : _
```

`asinh`

Computes the inverse hyperbolic sine of the input signal.

Usage

```
_ : asinh : _
```

`atanh`

Computes the inverse hyperbolic tangent of the input signal.

Usage

```
_ : atanh : _
```

`sinh`

Computes the hyperbolic sine of the input signal.

Usage

```
_ : sinh : _
```

`cosh`

Computes the hyperbolic cosine of the input signal.

Usage

```
_ : cosh : _
```

`tanh`

Computes the hyperbolic tangent of the input signal.

Usage

```
_ : tanh : _
```

`erf`

Computes the error function of the input signal.

Usage

```
_ : erf : _
```

`erfc`

Computes the complementary error function of the input signal.

Usage

```
_ : erfc : _
```

---

gamma

Computes the gamma function of the input signal.

Usage

```
_ : gamma : _
```

---

lgamma

Calculates the natural logorithm of the absolute value of the gamma function of the input signal.

Usage

```
_ : lgamma : _
```

J0

Computes the Bessel function of the first kind of order 0 of the input signal.

Usage

```
_ : J0 : _
```

J1

Computes the Bessel function of the first kind of order 1 of the input signal.

Usage

```
_ : J1 : _
```

`Jn`

Computes the Bessel function of the first kind of order n (first input signal) of the second input signal.

Usage

```
_,_ : Jn : _
```

`Y0`

Computes the linearly independent Bessel function of the second kind of order 0 of the input signal.

Usage

```
_ : Y0 : _
```

`Y1`

Computes the linearly independent Bessel function of the second kind of order 1 of the input signal.

Usage

```
_ : Y0 : _
```

`Yn`

Computes the linearly independent Bessel function of the second kind of order n (first input signal) of the second input signal.

Usage

```
_,_ : Yn : _
```

`fabs, fmax, fmin`

Just for compatibility…

```
fabs = abs
fmax = max
fmin = min
```

`np2`

Gives the next power of 2 of x.

Usage

```
np2(n) : _
```

Where:

- `n`: an integer

`frac`

Gives the fractional part of n.

Usage

```
frac(n) : _
```

Where:

- `n`: a decimal number

`isnan`

Return non-zero if and only if x is a NaN.

Usage

```
isnan(x)
_ : isnan : _
```

Where:

- `x`: signal to analyse

`chebychev`

Chebychev transformation of order n.

Usage

```
_ : chebychev(n) : _
```

Where:

- `n`: the order of the polynomial

Semantics

```
T[0](x) = 1,
T[1](x) = x,
T[n](x) = 2x*T[n-1](x) - T[n-2](x)
```

Reference http://en.wikipedia.org/wiki/Chebyshev_polynomial

`chebychevpoly`

Linear combination of the first Chebyshev polynomials.

Usage

```
_ : chebychevpoly((c0,c1,...,cn)) : _
```

Where:

- `cn`: the different Chebychevs polynomials such that: chebychevpoly((c0,c1,...,cn)) = Sum of chebychev(i)*ci

Reference http://www.csounds.com/manual/html/chebyshevpoly.html

---

`diffn`

Negated first-order difference.

Usage

```
_ : diffn : _
```

`signum`

The signum function signum(x) is defined as -1 for x<0, 0 for x==0, and 1 for x>0;

Usage

```
_ : signum : _
```

---

misceffects.lib

This library contains a collection of audio effects. Its official prefix is `ef`.

Dynamic

`cubicnl`

Cubic nonlinearity distortion. `cubicnl` is a standard Faust library.

Usage:

```
_ : cubicnl(drive,offset) : _
_ : cubicnl_nodc(drive,offset) : _
```

Where:

- `drive`: distortion amount, between 0 and 1
- `offset`: constant added before nonlinearity to give even harmonics. Note: offset can introduce a nonzero mean - feed cubicnl output to dcblocker to remove this.

References:

- https://ccrma.stanford.edu/~jos/pasp/Cubic_Soft_Clipper.html
- https://ccrma.stanford.edu/~jos/pasp/Nonlinear_Distortion.html

---

`gate_mono`

Mono signal gate. `gate_mono` is a standard Faust function.

Usage

```
_ : gate_mono(thresh,att,hold,rel) : _
```

Where:

- `thresh`: dB level threshold above which gate opens (e.g., -60 dB)

- `att`: attack time = time constant (sec) for gate to open (e.g., 0.0001 s = 0.1 ms)
- `hold`: hold time = time (sec) gate stays open after signal level < thresh (e.g., 0.1 s)
- `rel`: release time = time constant (sec) for gate to close (e.g., 0.020 s = 20 ms)

References

- http://en.wikipedia.org/wiki/Noise_gate
- http://www.soundonsound.com/sos/apr01/articles/advanced.asp
- http://en.wikipedia.org/wiki/Gating_(sound_engineering)

`gate_stereo`

Stereo signal gates. `gate_stereo` is a standard Faust function.

Usage

```
_,_ : gate_stereo(thresh,att,hold,rel) : _,_
```

Where:

- `thresh`: dB level threshold above which gate opens (e.g., -60 dB)
- `att`: attack time = time constant (sec) for gate to open (e.g., 0.0001 s = 0.1 ms)
- `hold`: hold time = time (sec) gate stays open after signal level < thresh (e.g., 0.1 s)
- `rel`: release time = time constant (sec) for gate to close (e.g., 0.020 s = 20 ms)

References

- http://en.wikipedia.org/wiki/Noise_gate
- http://www.soundonsound.com/sos/apr01/articles/advanced.asp
- http://en.wikipedia.org/wiki/Gating_(sound_engineering)

Filtering

`speakerbp`

Dirt-simple speaker simulator (overall bandpass eq with observed roll-offs above and below the passband).

Low-frequency speaker model = +12 dB/octave slope breaking to flat near f1. Implemented using two dc blockers in series.

High-frequency model = -24 dB/octave slope implemented using a fourth-order Butterworth lowpass.

Example based on measured Celestion G12 (12" speaker):

`speakerbp` is a standard Faust function

Usage

```
speakerbp(f1,f2)
_ : speakerbp(130,5000) : _
```

`piano_dispersion_filter`

Piano dispersion allpass filter in closed form.

Usage

```
piano_dispersion_filter(M,B,f0)
_ : piano_dispersion_filter(1,B,f0) : +(totalDelay),_ : fdelay(maxDelay) : _
```

Where:

- `M`: number of first-order allpass sections (compile-time only) Keep below 20. 8 is typical for medium-sized piano strings.
- `B`: string inharmonicity coefficient (0.0001 is typical)
- `f0`: fundamental frequency in Hz

Outputs

- MINUS the estimated delay at `f0` of allpass chain in samples, provided in negative form to facilitate subtraction from delay-line length.
- Output signal from allpass chain

`stereo_width`

Stereo Width effect using the Blumlein Shuffler technique. `stereo_width` is a standard Faust function.

Usage

```
_,_ : stereo_width(w) : _,_
```

Where:

- `w`: stereo width between 0 and 1

At `w=0`, the output signal is mono ((left+right)/2 in both channels). At `w=1`, there is no effect (original stereo image). Thus, w between 0 and 1 varies stereo width from 0 to "original".

Reference

- "Applications of Blumlein Shuffling to Stereo Microphone Techniques" Michael A. Gerzon, JAES vol. 42, no. 6, June 1994

Time Based

`echo`

A simple echo effect.

`echo` is a standard Faust function

Usage

```
_ : echo(maxDuration,duration,feedback) : _
```

Where:

- `maxDuration`: the max echo duration in seconds
- `duration`: the echo duration in seconds
- `feedback`: the feedback coefficient

Pitch Shifting

transpose

A simple pitch shifter based on 2 delay lines. `transpose` is a standard Faust function.

Usage

```
_ : transpose(w, x, s) : _
```

Where:

- `w`: the window length (samples)
- `x`: crossfade duration duration (samples)
- `s`: shift (semitones)

Meshes

mesh_square

Square Rectangular Digital Waveguide Mesh.

Usage

```
bus(4*N) : mesh_square(N) : bus(4*N);
```

Where:

- `N`: number of nodes along each edge - a power of two (1,2,4,8,...)

Reference https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Mesh.html

Signal Order In and Out The mesh is constructed recursively using 2x2 embeddings. Thus, the top level of `mesh_square(M)` is a block 2x2 mesh, where each block is a `mesh(M/2)`. Let these blocks be numbered 1,2,3,4 in the geometry NW,NE,SW,SE, i.e., as 1 2 3 4 Each block has four vector inputs and four vector outputs, where the length of each vector is `M/2`. Label the input vectors as Ni,Ei,Wi,Si, i.e., as the inputs from the North, East South, and West, and similarly for the outputs. Then, for example, the upper left input block of M/2 signals is labeled 1Ni. Most of the connections are internal, such as 1Eo -> 2Wi. The `8*(M/2)` input signals are grouped in the order 1Ni 2Ni 3Si 4Si 1Wi 3Wi 2Ei 4Ei and the output signals are 1No 1Wo 2No 2Eo 3So 3Wo 4So 4Eo or

In: 1No 1Wo 2No 2Eo 3So 3Wo 4So 4Eo

Out: 1Ni 2Ni 3Si 4Si 1Wi 3Wi 2Ei 4Ei

Thus, the inputs are grouped by direction N,S,W,E, while the outputs are grouped by block number 1,2,3,4, which can also be interpreted as directions NW, NE, SW, SE. A simple program illustrating these orderings is `process = mesh_square(2);`.

Example Reflectively terminated mesh impulsed at one corner:

```
mesh_square_test(N,x) = mesh_square(N)~(busi(4*N,x)) // input to corner
with { busi(N,x) = bus(N) : par(i,N,*(-1)) : par(i,N-1,_), +(x); };
process = 1-1' : mesh_square_test(4); // all modes excited forever
```

In this simple example, the mesh edges are connected as follows:

1No -> 1Ni, 1Wo -> 2Ni, 2No -> 3Si, 2Eo -> 4Si,

3So -> 1Wi, 3Wo -> 3Wi, 4So -> 2Ei, 4Eo -> 4Ei

A routing matrix can be used to obtain other connection geometries.

---

noises.lib

Faust Noise Generator Library. Its official prefix is `no`.

Functions Reference

`noise`

White noise generator (outputs random number between -1 and 1). `Noise` is a standard Faust function.

Usage

```
noise : _
```

`multirandom`

Generates multiple decorrelated random numbers in parallel.

Usage

```
multirandom(n) : si.bus(n)
```

Where:

- `n`: the number of decorrelated random numbers in parallel

`multinoise`

Generates multiple decorrelated noises in parallel.

Usage

```
multinoise(n) : si.bus(n)
```

Where:

- `n`: the number of decorrelated random numbers in parallel

`noises`

TODO.

`pink_noise`

Pink noise (1/f noise) generator (third-order approximation) `pink_noise` is a standard Faust function.

Usage

```
pink_noise : _;
```

Reference: https://ccrma.stanford.edu/~jos/sasp/Example_Synthesis_1_F_Noise.html

---

`pink_noise_vm`

Multi pink noise generator.

Usage

```
pink_noise_vm(N) : _;
```

Where:

- `N`: number of latched white-noise processes to sum, not to exceed sizeof(int) in C++ (typically 32).

References

- http://www.dsprelated.com/showarticle/908.php
- http://www.firstpr.com.au/dsp/pink-noise/#Voss-McCartney

`lfnoise`, `lfnoise0` and `lfnoiseN`

Low-frequency noise generators (Butterworth-filtered downsampled white noise)

Usage

```
lfnoise0(rate) : _;   // new random number every int(SR/rate) samples or so
lfnoiseN(N,rate) : _; // same as "lfnoise0(rate) : lowpass(N,rate)" [see filters.lib]
lfnoise(rate) : _;    // same as "lfnoise0(rate) : seq(i,5,lowpass(N,rate))" (no overshoot)
```

Example (view waveforms in faust2octave):

```
rate = SR/100.0; // new random value every 100 samples (SR from music.lib)
process = lfnoise0(rate),   // sampled/held noise (piecewise constant)
          lfnoiseN(3,rate), // lfnoise0 smoothed by 3rd order Butterworth LPF
          lfnoise(rate);    // lfnoise0 smoothed with no overshoot
```

`sparse_noise_vm`

sparse noise generator.

Usage

```
sparse_noise(f0) : _;
```

Where:

- `f0`: average frequency of noise impulses per second

Random impulses in the amplitude range -1 to 1 are generated at an average rate of f0 impulses per second.

Reference

- See velvet_noise

`velvet_noise_vm`

velvet noise generator.

Usage

```
velvet_noise(amp,f0) : _;
```

Where:

- `amp`: amplitude of noise impulses (positive and negative)
- `f0`: average frequency of noise impulses per second

Reference

- Matti Karjalainen and Hanna Jarvelainen, "Reverberation Modeling Using Velvet Noise", in Proc. 30th Int. Conf. Intelligent Audio Environments (AES07), March 2007.

`gnoise`

approximate zero-mean, unit-variance Gaussian white noise generator

Usage

```
gnoise(N) : _;
```

Where:

- `N`: number of uniform random numbers added to approximate Gaussian white noise

Reference

- See Central Limit Theorem

---

oscillators.lib

This library contains a collection of sound generators. Its official prefix is `os`.

Wave-Table-Based Oscillators

`sinwaveform`

Sine waveform ready to use with a `rdtable`.

Usage

```
sinwaveform(tablesize) : _
```

Where:

- `tablesize`: the table size

`coswaveform`

Cosine waveform ready to use with a `rdtable`.

Usage

```
coswaveform(tablesize) : _
```

Where:

- `tablesize`: the table size

`phasor`

A simple phasor to be used with a `rdtable`. `phasor` is a standard Faust function.

Usage

```
phasor(tablesize,freq) : _
```

Where:

- `tablesize`: the table size
- `freq`: the frequency of the wave (Hz)

`oscsin`

Sine wave oscillator. `oscsin` is a standard Faust function.

Usage

```
oscsin(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

`osccos`

Cosine wave oscillator.

Usage

```
osccos(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

`oscp`

A sine wave generator with controllable phase.

Usage

```
oscp(freq,p) : _
```

Where:

- `freq`: the frequency of the wave (Hz)
- `p`: the phase in radian

`osci`

Interpolated phase sine wave oscillator.

Usage

```
osci(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

LFOs

Low-frequency oscillators have prefix `lf_` (no aliasing suppression, signal-means not necessarily zero).

`lf_imptrain`

Unit-amplitude low-frequency impulse train. `lf_imptrain` is a standard Faust function.

Usage

```
lf_imptrain(freq) : _
```

Where:

- `freq`: frequency in Hz

`lf_pulsetrainpos`

Unit-amplitude nonnegative LF pulse train, duty cycle between 0 and 1

Usage

```
lf_pulsetrainpos(freq,duty) : _
```

Where:

- `freq`: frequency in Hz
- `duty`: duty cycle between 0 and 1

`lf_squarewavepos`

Positive LF square wave in [0,1]

Usage

```
lf_squarewavepos(freq) : _
```

Where:

- `freq`: frequency in Hz

`lf_squarewave`

Zero-mean unit-amplitude LF square wave. `lf_squarewave` is a standard Faust function.

Usage

```
lf_squarewave(freq) : _
```

Where:

- `freq`: frequency in Hz

`lf_trianglepos`

Positive unit-amplitude LF positive triangle wave

Usage

```
lf_trianglepos(freq) : _
```

Where:

- `freq`: frequency in Hz

Low Frequency Sawtooths

Sawtooth waveform oscillators for virtual analog synthesis et al. The 'simple' versions (`lf_rawsaw`, `lf_sawpos` and `saw1`), are mere samplings of the ideal continuous-time ("analog") waveforms. While simple, the aliasing due to sampling is quite audible. The differentiated polynomial waveform family (`saw2`, `sawN`, and derived functions) do some extra processing to suppress aliasing (not audible for very low fundamental frequencies). According to Lehtonen et al. (JASA 2012), the aliasing of `saw2` should be inaudible at fundamental frequencies below 2 kHz or so, for a 44.1 kHz sampling rate and 60 dB SPL presentation level; fundamentals 415 and below required no aliasing suppression (i.e., `saw1` is ok).

`lf_rawsaw`

Simple sawtooth waveform oscillator between 0 and period in samples.

Usage

```
lf_rawsaw(periodsamps)
```

Where:

- `periodsamps`: number of periods per samples

---

lf_sawpos_phase

Simple sawtooth waveform oscillator between 0 and 1 with phase control.

Usage

`lf_sawpos_phase(freq,phase)`

Where:

- `freq`: frequency
- `phase`: phase

Bandlimited Sawtooth

//————————sawN———————————— Bandlimited Sawtooth

`sawN(N,freq)`, `sawNp`, `saw2dpw(freq)`, `saw2(freq)`, `saw3(freq)`, `saw4(freq)`, `saw5(freq)`, `saw6(freq)`, `sawtooth(freq)`, `saw2f2(freq)` `saw2f4(freq)`

Method 1 (saw2) Polynomial Transition Regions (PTR) (for aliasing suppression)

Reference

- Kleimola, J.; Valimaki, V., "Reducing Aliasing from Synthetic Audio Signals Using Polynomial Transition Regions," in Signal Processing Letters, IEEE , vol.19, no.2, pp.67-70, Feb. 2012
- https://aaltodoc.aalto.fi/bitstream/handle/123456789/7747/publication6.pdf?sequence=9
- http://research.spa.aalto.fi/publications/papers/spl-ptr/

Method 2 (sawN) Differentiated Polynomial Waves (DPW) (for aliasing suppression)

Reference "Alias-Suppressed Oscillators based on Differentiated Polynomial Waveforms", Vesa Valimaki, Juhan Nam, Julius Smith, and Jonathan Abel, IEEE Tr. Acoustics, Speech, and Language Processing (IEEE-ASLP), Vol. 18, no. 5, May 2010.

Other Cases Correction-filtered versions of `saw2`: `saw2f2`, `saw2f4` The correction filter compensates "droop" near half the sampling rate. See reference for sawN.

Usage

```
sawN(N,freq) : _
sawNp(N,freq,phase) : _
saw2dpw(freq) : _
saw2(freq) : _
saw3(freq) : _ // based on sawN
saw4(freq) : _ // based on sawN
saw5(freq) : _ // based on sawN
saw6(freq) : _ // based on sawN
sawtooth(freq) : _ // = saw2
saw2f2(freq) : _
saw2f4(freq) : _
```

Where:

- `N`: polynomial order
- `freq`: frequency in Hz
- `phase`: phase

`sawNp`

TODO: MarkDown doc in comments

`saw2dpw`

TODO: MarkDown doc in comments

`saw3`

TODO: MarkDown doc in comments

`sawtooth`

Alias-free sawtooth wave. 2nd order interpolation (based on `saw2`). `sawtooth` is a standard Faust function.

Usage

```
sawtooth(freq) : _
```

Where:

- `freq`: frequency

`saw2f2`

TODO: MarkDown doc in comments

`saw2f4`

TODO: MarkDown doc in comments

Bandlimited Pulse, Square, and Impulse Trains

Bandlimited Pulse, Square, and Impulse Trains

`pulsetrainN`, `pulsetrain`, `squareN`, `square`, `imptrain`, `imptrainN`, `triangle`, `triangleN`

All are zero-mean and meant to oscillate in the audio frequency range. Use simpler sample-rounded lf_* versions above for LFOs.

Usage

```
pulsetrainN(N,freq,duty) : _
pulsetrain(freq, duty) : _ // = pulsetrainN(2)
squareN(N, freq) : _
square : _ // = squareN(2)
imptrainN(N,freq) : _
imptrain : _ // = imptrainN(2)
triangleN(N,freq) : _
triangle : _ // = triangleN(2)
```

Where:

- `N`: polynomial order
- `freq`: frequency in Hz

`pulsetrainN`

TODO: MarkDown doc in comments

`pulsetrain`

Bandlimited pulse train oscillator. Based on `pulsetrainN(2)`. `pulsetrain` is a standard Faust function.

Usage

```
pulsetrain(freq, duty) : _
```

Where:

- `freq`: frequency
- `duty`: duty cycle between 0 and 1

`squareN`

TODO: MarkDown doc in comments

`square`

Bandlimited square wave oscillator. Based on `squareN(2)`. `square` is a standard Faust function.

Usage

```
square(freq) : _
```

Where:

- `freq`: frequency

`impulse`

One-time impulse generated when the Faust process is started. `impulse` is a standard Faust function.

Usage

```
impulse : _
```

`imptrainN`

TODO: MarkDown doc in comments

`imptrain`

Bandlimited impulse train generator. Based on `imptrainN(2)`. `imptrain` is a standard Faust function.

Usage

```
imptrain(freq) : _
```

Where:

- `freq`: frequency

`triangleN`

TODO: MarkDown doc in comments

`triangle`

Bandlimited triangle wave oscillator. Based on `triangleN(2)`. `triangle` is a standard Faust function.

Usage

```
triangle(freq) : _
```

Where:

- `freq`: frequency

Filter-Based Oscillators

Filter-Based Oscillators

Usage

```
osc[b|r|rs|rc|s|w](f), where f = frequency in Hz.
```

References

- http://lac.linuxaudio.org/2012/download/lac12-slides-jos.pdf
- https://ccrma.stanford.edu/~jos/pdf/lac12-paper-jos.pdf

`oscb`

Sinusoidal oscillator based on the biquad.

Usage

```
oscb(freq) : _
```

Where:

- `freq`: frequency

`oscrq`

Sinusoidal (sine and cosine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

```
oscrq(freq) : _,_
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

`oscrs`

Sinusoidal (sine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

```
oscrs(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

`oscrc`

Sinusoidal (cosine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

```
oscrc(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

`osc`

Default sine wave oscillator (same as oscrs). `osc` is a standard Faust function.

Usage

```
osc(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

`oscs`

Sinusoidal oscillator based on the state variable filter = undamped "modified-coupled-form" resonator = "magic circle" algorithm used in graphics

---

Waveguide-Resonator-Based Osccilators

Sinusoidal oscillator based on the waveguide resonator `wgr`.

`oscw`

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine oscillator.

Usage

```
oscwc(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

`oscws`

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude sine oscillator

Usage

```
oscws(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

`oscwq`

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine and sine (quadrature) oscillator.

Usage

```
oscwq(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

`oscw`

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine oscillator (default)

Usage

```
oscw(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

`lf_sawpos`

Simple sawtooth waveform oscillator between 0 and 1.

Usage

```
lf_sawpos(freq)
```

Where:

- `freq`: frequency

`lf_saw`

Simple sawtooth waveform. `lf_saw` is a standard Faust function.

Usage

```
lf_saw(freq)
```

Where:

- `freq`: frequency

`lf_triangle`

Positive unit-amplitude LF triangle wave `lf_triangle` is a standard Faust function.

Usage

```
lf_triangle(freq) : _
```

Where:

- `freq`: frequency in Hz

---

phaflangers.lib

A library of phasor and flanger effects. Its official prefix is `pf`.

Functions Reference

`flanger_mono`

Mono flanging effect.

Usage:

```
_ : flanger_mono(dmax,curdel,depth,fb,invert) : _;
```

Where:

- `dmax`: maximum delay-line length (power of 2) - 10 ms typical
- `curdel`: current dynamic delay (not to exceed dmax)
- `depth`: effect strength between 0 and 1 (1 typical)
- `fb`: feedback gain between 0 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference https://ccrma.stanford.edu/~jos/pasp/Flanging.html

`flanger_stereo`

Stereo flanging effect. `flanger_stereo` is a standard Faust function.

Usage:

```
_,_ : flanger_stereo(dmax,curdel1,curdel2,depth,fb,invert) : _,_;
```

Where:

- `dmax`: maximum delay-line length (power of 2) - 10 ms typical
- `curdel`: current dynamic delay (not to exceed dmax)
- `depth`: effect strength between 0 and 1 (1 typical)
- `fb`: feedback gain between 0 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference https://ccrma.stanford.edu/~jos/pasp/Flanging.html

`phaser2_mono`

Mono phasing effect.

Phaser

```
_ : phaser2_mono(Notches,phase,width,frqmin,fratio,frqmax,speed,depth,fb,invert) : _;
```

Where:

- `Notches`: number of spectral notches (MACRO ARGUMENT - not a signal)
- `phase`: phase of the oscillator (0-1)
- `width`: approximate width of spectral notches in Hz
- `frqmin`: approximate minimum frequency of first spectral notch in Hz
- `fratio`: ratio of adjacent notch frequencies
- `frqmax`: approximate maximum frequency of first spectral notch in Hz
- `speed`: LFO frequency in Hz (rate of periodic notch sweep cycles)
- `depth`: effect strength between 0 and 1 (1 typical) (aka "intensity") when depth=2, "vibrato mode" is obtained (pure allpass chain)
- `fb`: feedback gain between -1 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference:

- https://ccrma.stanford.edu/~jos/pasp/Phasing.html
- http://www.geofex.com/Article_Folders/phasers/phase.html
- 'An Allpass Approach to Digital Phasing and Flanging', Julius O. Smith III, Proc. Int. Computer Music Conf. (ICMC-84), pp. 103-109, Paris, 1984.
- CCRMA Tech. Report STAN-M-21: https://ccrma.stanford.edu/STANM/stanms/stanm21/

`phaser2_stereo`

Stereo phasing effect. `phaser2_stereo` is a standard Faust function.

Phaser

```
_ : phaser2_stereo(Notches,phase,width,frqmin,fratio,frqmax,speed,depth,fb,invert) : _;
```

Where:

- `Notches`: number of spectral notches (MACRO ARGUMENT - not a signal)

- `phase`: phase of the oscillator (0-1)
- `width`: approximate width of spectral notches in Hz
- `frqmin`: approximate minimum frequency of first spectral notch in Hz
- `fratio`: ratio of adjacent notch frequencies
- `frqmax`: approximate maximum frequency of first spectral notch in Hz
- `speed`: LFO frequency in Hz (rate of periodic notch sweep cycles)
- `depth`: effect strength between 0 and 1 (1 typical) (aka “intensity”) when depth=2, “vibrato mode” is obtained (pure allpass chain)
- `fb`: feedback gain between -1 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference:

- https://ccrma.stanford.edu/~jos/pasp/Phasing.html
- http://www.geofex.com/Article_Folders/phasers/phase.html
- ‘An Allpass Approach to Digital Phasing and Flanging’, Julius O. Smith III, Proc. Int. Computer Music Conf. (ICMC-84), pp. 103-109, Paris, 1984.
- CCRMA Tech. Report STAN-M-21: https://ccrma.stanford.edu/STANM/stanms/stanm21/

---

physmodels.lib

Faust physical modeling library. Its official prefix is `pm`.

chain(A:B:...)

Creates a chain of bidirectional blocks. Blocks must have 3 inputs and outputs. The first input/output correspond to the left going signal, the second input/output correspond to the right going signal and the third input/output is the mix of the main signal output. The implied one sample delay created by the `~` operator is generalized to the left and right going waves. Thus, n blocks in `chain()` will add an n samples delay to both the left and right going waves. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : chain(A:B) : rightGoingWaves,leftGoingWaves,mix
with{
    A = _,_,_;
    B = _,_,_;
};
```

Requires

`routes.lib` (`crossnn`)

---

input(x)

Adds a waveguide input anywhere between 2 blocks in a chain of blocks (see `chain()`). ### Usage

```
string(x) = chain(A:input(x):B)
```

Where `x` is the input signal to be added to the chain.

---

output()

Adds a waveguide output anywhere between 2 blocks in a chain of blocks and sends it to the mix output channel (see `chain()`). ### Usage

```
chain(A:output:B)
```

---

terminations(a,b,c)

Creates terminations on both sides of a `chain()` without closing the inputs and outputs of the bidirectional signals chain. As for `chain()`, this function adds a 1 sample delay to the bidirectional signal both ways. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(a,b,c) : rightGoingWaves,leftGoing
with{
     a = *(-1); // left termination
     b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
     c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

fullTerminations(a,b,c)

Same as `terminations()` but closes the inputs and outputs of the bidirectional chain (only the mixed output remains). ### Usage

```
terminations(a,b,c) : _
with{
     a = *(-1); // left termination
     b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
     c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

leftTermination(a,b)

Creates a termination on the left side of a `chain()` without closing the inputs and outputs of the bidirectional signals chain. This function adds a 1 sample delay near the termination. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(a,b) : rightGoingWaves,leftGoingWa
with{
     a = *(-1); // left termination
     b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
};
```

Requires

`routes.lib` (`crossnn`)

---

rightTermination(b,c)

Creates a termination on the right side of a `chain()` without closing the inputs and outputs of the bidirectional signals chain. This function adds a 1 sample delay near the termination. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(b,c) : rightGoingWaves,leftGoingWa
with{
     b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
     c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

waveguide(nMax,n)

A simple waveguide block based on a 4th order fractional delay. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : waveguide(nMax,n) : rightGoingWaves,leftGoingWa
```

With: * `nMax`: the maximum length of the waveguide in samples * `n` the length of the waveguide in samples. ### Requires `delays.lib` (`fdelay4`)

---

idealString(length,reflexion,xPosition,x)

An ideal string with rigid terminations and where the plucking position and the pick-up position are the same. ### Usage

```
1-1' : idealString(length,reflexion,xPosition,x)
```

With: * `length`: the length of the string in meters * `reflexion`: the coefficient of reflexion (0-0.99999999) * `pluckPosition`: the plucking position (0.001-0.999) * `x`: the input signal for the excitation ### Requires `routes.lib` (`crossnn`) `delays.lib` (`fdelay4`)

---

reverbs.lib

A library of reverb effects. Its official prefix is `re`.

Schroeder Reverberators

`jcrev`

This artificial reverberator take a mono signal and output stereo (`satrev`) and quad (`jcrev`). They were implemented by John Chowning in the MUS10 computer-music language (descended from Music V by Max Mathews). They are Schroeder Reverberators, well tuned for their size. Nowadays, the more expensive freeverb is more commonly used (see the Faust examples directory).

`jcrev` reverb below was made from a listing of "RV", dated April 14, 1972, which was recovered from an old SAIL DART backup tape. John Chowning thinks this might be the one that became the well known and often copied JCREV.

`jcrev` is a standard Faust function

Usage

```
_ : jcrev : _,_,_,_
```

`satrev`

This artificial reverberator take a mono signal and output stereo (`satrev`) and quad (`jcrev`). They were implemented by John Chowning in the MUS10 computer-music language (descended from Music V by Max Mathews). They are Schroeder Reverberators, well tuned for their size. Nowadays, the more expensive freeverb is more commonly used (see the Faust examples directory).

`satrev` was made from a listing of "SATREV", dated May 15, 1971, which was recovered from an old SAIL DART backup tape. John Chowning thinks this might be the one used on his often-heard brass canon sound examples, one of which can be found at https://ccrma.stanford.edu/~jos/wav/FM_BrassCanon2.wav

Usage

```
_ : satrev : _,_
```

Feedback Delay Network (FDN) Reverberators

`fdnrev0`

Pure Feedback Delay Network Reverberator (generalized for easy scaling). `fdnrev0` is a standard Faust function.

Usage

```
<1,2,4,...,N signals> <:
fdnrev0(MAXDELAY,delays,BBSO,freqs,durs,loopgainmax,nonl) :>
<1,2,4,...,N signals>
```

Where:

- `N`: 2, 4, 8, ... (power of 2)
- `MAXDELAY`: power of 2 at least as large as longest delay-line length
- `delays`: N delay lines, N a power of 2, lengths perferably coprime
- `BBSO`: odd positive integer = order of bandsplit desired at freqs
- `freqs`: NB-1 crossover frequencies separating desired frequency bands
- `durs`: NB decay times (t60) desired for the various bands
- `loopgainmax`: scalar gain between 0 and 1 used to "squelch" the reverb
- `nonl`: nonlinearity (0 to 0.999..., 0 being linear)

Reference https://ccrma.stanford.edu/~jos/pasp/FDN_Reverberation.html

---

`zita_rev_fdn`

Internal 8x8 late-reverberation FDN used in the FOSS Linux reverb zita-rev1 by Fons Adriaensen fons@linuxaudio.org. This is an FDN reverb with allpass comb filters in each feedback delay in addition to the damping filters.

Usage

```
bus(8) : zita_rev_fdn(f1,f2,t60dc,t60m,fsmax) : bus(8)
```

Where:

- `f1`: crossover frequency (Hz) separating dc and midrange frequencies

- `f2`: frequency (Hz) above f1 where T60 = t60m/2 (see below)
- `t60dc`: desired decay time (t60) at frequency 0 (sec)
- `t60m`: desired decay time (t60) at midrange frequencies (sec)
- `fsmax`: maximum sampling rate to be used (Hz)

Reference

- http://www.kokkinizita.net/linuxaudio/zita-rev1-doc/quickguide.html
- https://ccrma.stanford.edu/~jos/pasp/Zita_Rev1.html

`zita_rev1_stereo`

Extend `zita_rev_fdn` to include `zita_rev1` input/output mapping in stereo mode. `zita_rev1_stereo` is a standard Faust function.

Usage

```
_,_ : zita_rev1_stereo(rdel,f1,f2,t60dc,t60m,fsmax) : _,_
```

Where:

`rdel` = delay (in ms) before reverberation begins (e.g., 0 to ~100 ms) (remaining args and refs as for `zita_rev_fdn` above)

`zita_rev1_ambi`

Extend zita_rev_fdn to include zita_rev1 input/output mapping in "ambisonics mode", as provided in the Linux C++ version.

Usage

```
_,_ : zita_rev1_ambi(rgxyz,rdel,f1,f2,t60dc,t60m,fsmax) : _,_,_,_
```

Where:

`rgxyz` = relative gain of lanes 1,4,2 to lane 0 in output (e.g., -9 to 9) (remaining args and references as for zita_rev1_stereo above)

Freeverb

`mono_freeverb`

A simple Schroeder reverberator primarily developed by "Jezar at Dreampoint" that is extensively used in the free-software world. It uses four Schroeder allpasses in series and eight parallel Schroeder-Moorer filtered-feedback comb-filters for each audio channel, and is said to be especially well tuned.

`mono_freeverb` is a standard Faust function.

Usage

```
_ : mono_freeverb(fb1, fb2, damp, spread) : _;
```

Where:

- `fb1`: coefficient of the lowpass comb filters (0-1)
- `fb2`: coefficient of the allpass comb filters (0-1)
- `damp`: damping of the lowpass comb filter (0-1)
- `spread`: spatial spread in number of samples (for stereo)

License While this version is licensed LGPL (with exception) along with other GRAME library functions, the file freeverb.dsp in the examples directory of older Faust distributions, such as faust-0.9.85, was released under the BSD license, which is less restrictive.

`stereo_freeverb`

A simple Schroeder reverberator primarily developed by "Jezar at Dreampoint" that is extensively used in the free-software world. It uses four Schroeder allpasses in series and eight parallel Schroeder-Moorer filtered-feedback comb-filters for each audio channel, and is said to be especially well tuned.

Usage

```
_,_ : stereo_freeverb(fb1, fb2, damp, spread) : _,_;
```

Where:

* `fb1`: coefficient of the lowpass comb filters (0-1)
* `fb2`: coefficient of the allpass comb filters (0-1)
* `damp`: damping of the lowpass comb filter (0-1)
* `spread`: spatial spread in number of samples (for stereo)

---

routes.lib

A library of basic elements to handle signal routing in Faust. Its official prefix is `ro`.

Functions Reference

`cross`

Cross n signals: `(x1,x2,..,xn) -> (xn,..,x2,x1)`. `cross` is a standard Faust function.

Usage

```
cross(n)
_,_,_ : cross(3) : _,_,_
```

Where:

* `n`: number of signals (int, must be known at compile time)

Note Special case: `cross2`:

```
cross2 = _,cross(2),_;
```

`crossnn`

Cross two `bus(n)`s.

Usage

```
_,_,... : crossmm(n) : _,_,...
```

Where:

- `n`: the number of signals in the `bus`

`crossn1`

Cross bus(n) and bus(1).

Usage

```
_,_,... : crossn1(n) : _,_,...
```

Where:

- `n`: the number of signals in the first `bus`

`interleave`

Interleave row*col cables from column order to row order. input : x(0), x(1), x(2) . . . , x(row*col-1) output: x(0+0*row), x(0+1*row), x(0+2*row), . . . , x(1+0*row), x(1+1*row), x(1+2*row), . . .

Usage

```
_,_,_,_,_,_ : interleave(row,column) : _,_,_,_,_,_
```

Where:

- `row`: the number of row (int, known at compile time)
- `column`: the number of column (int, known at compile time)

`butterfly`

Addition (first half) then substraction (second half) of interleaved signals.

Usage

```
_,_,_,_ : butterfly(n) : _,_,_,_
```

Where:

- `n`: size of the butterfly (n is int, even and known at compile time)

`hadamard`

Hadamard matrix function of size `n = 2^k`.

Usage

```
_,_,_,_ : hadamard(n) : _,_,_,_
```

Where:

- `n`: `2^k`, size of the matrix (int, must be known at compile time)

Note: Implementation contributed by Remy Muller.

`recursivize`

Create a recursion from two arbitrary processors p and q.

Usage

```
_,_ : recursivize(p,q) : _,_
```

Where:

- `p`: the forward arbitrary processor
- `q`: the feedback arbitrary processor

---

signals.lib

A library of basic elements to handle signals in Faust. Its official prefix is `si`.

Functions Reference

`bus`

n parallel cables. `bus` is a standard Faust function.

Usage

```
bus(n)
bus(4) : _,_,_,_
```

Where:

- `n`: is an integer known at compile time that indicates the number of parallel cables.

`block`

Block - terminate n signals. `block` is a standard Faust function.

Usage

```
_,_,... : block(n) : _,...
```

Where:

- `n`: the number of signals to be blocked

`interpolate`

Linear interpolation between two signals.

Usage

```
_,_ : interpolate(i) : _
```

Where:

- `i`: interpolation control between 0 and 1 (0: first input; 1: second input)

`smoo`

Smoothing function based on `smooth` ideal to smooth UI signals (sliders, etc.) down. `smoo` is a standard Faust function.

Usage

```
hslider(...) : smoo;
```

`polySmooth`

A smoothing function based on `smooth` that doesn't smooth when a trigger signal is given. This is very useful when making polyphonic synthesizer to make sure that the value of the parameter is the right one when the note is started.

Usage

```
hslider(...) : polysmooth(g,s,d) : _
```

Where:

- `g`: the gate/trigger signal used when making polyphonic synths
- `s`: the smoothness (see `smooth`)
- `d`: the number of samples to wait before the signal start being smoothed after `g` switched to 1

---

smoothAndH

A smoothing function based on `smooth` that holds its output signal when a trigger is sent to it. This feature is convenient when implementing polyphonic instruments to prevent some smoothed parameter to change when a note-off event is sent.

Usage

```
hslider(...) : smoothAndH(g,s) : _
```

Where:

- `g`: the hold signal (0 for hold, 1 for bypass)
- `s`: the smoothness (see `smooth`)

---

bsmooth

Block smooth linear interpolation during a block of samples.

Usage

```
hslider(...) : bsmooth : _
```

---

dot

Dot product for two vectors of size n.

Usage

```
_,_,_,_,_,_ : dot(n) : _
```

Where:

- `n`: size of the vectors (int, must be known at compile time)

---

smooth

Exponential smoothing by a unity-dc-gain one-pole lowpass. `smooth` is a standard Faust function.

Usage:

```
_ : smooth(tau2pole(tau)) : _
```

Where:

- `tau`: desired smoothing time constant in seconds, or

```
hslider(...) : smooth(s) : _
```

Where:

- `s`: smoothness between 0 and 1. s=0 for no smoothing, s=0.999 is "very smooth", s>1 is unstable, and s=1 yields the zero signal for all inputs. The exponential time-constant is approximately 1/(1-s) samples, when s is close to (but less than) 1.

Reference: https://ccrma.stanford.edu/~jos/mdft/Convolution_Example_2_ADSR.html

---

lag_ud

Lag filter with separate times for up and down.

Usage

```
_ : lag_ud(up, dn, signal) : _;
```

---

spats.lib

This library contains a collection of tools for sound spatialization. Its official prefix is `sp`.

`panner`

A simple linear stereo panner. `panner` is a standard Faust function.

Usage

```
_ : panner(g) : _,_
```

Where:

- `g`: the panning (0-1)

`spat`

GMEM SPAT: n-outputs spatializer. `spat` is a standard Faust function.

Usage

```
_ : spat(n,r,d) : _,_,...
```

Where:

- `n`: number of outputs
- `r`: rotation (between 0 et 1)
- `d`: distance of the source (between 0 et 1)

`stereoize`

Transform an arbitrary processor `p` into a stereo processor with 2 inputs and 2 outputs.

Usage

```
_,_ : stereoize(p) : _,_
```

Where:

- `p`: the arbitrary processor

---

synths.lib

This library contains a collection of envelope generators. Its official prefix is `sy`.

popFilterPerc

A simple percussion instrument based on a "popped" resonant bandpass filter. `popFilterPerc` is a standard Faust function.

Usage

```
popFilterDrum(freq,q,gate) : _;
```

Where:

- `freq`: the resonance frequency of the instrument
- `q`: the q of the res filter (typically, 5 is a good value)
- `gate`: the trigger signal (0 or 1)

---

dubDub

A simple synth based on a sawtooth wave filtered by a resonant lowpass. `dubDub` is a standard Faust function.

Usage

```
dubDub(freq,ctFreq,q,gate) : _;
```

Where:

- `freq`: frequency of the sawtooth
- `ctFreq`: cutoff frequency of the filter
- `q`: Q of the filter
- `gate`: the trigger signal (0 or 1)

`sawTrombone`

A simple trombone based on a lowpassed sawtooth wave. `sawTrombone` is a standard Faust function.

Usage

```
sawTrombone(att,freq,gain,gate) : _
```

Where:

- `att`: exponential attack duration in s (typically 0.01)
- `freq`: the frequency
- `gain`: the gain (0-1)
- `gate`: the gate (0 or 1)

`combString`

Simplest string physical model ever based on a comb filter. `combString` is a standard Faust function.

Usage

```
combString(freq,res,gate) : _;
```

Where:

- `freq`: the frequency of the string
- `res`: string T60 (resonance time) in second
- `gate`: trigger signal (0 or 1)

`additiveDrum`

A simple drum using additive synthesis. `additiveDrum` is a standard Faust function.

Usage

```
additiveDrum(freq,freqRatio,gain,harmDec,att,rel,gate) : _
```

Where:

- `freq`: the resonance frequency of the drum
- `freqRatio`: a list of ratio to choose the frequency of the mode in function of `freq` e.g.(1 1.2 1.5 …). The first element should always be one (fundamental).
- `gain`: the gain of each mode as a list (1 0.9 0.8 …). The first element is the gain of the fundamental.
- `harmDec`: harmonic decay ratio (0-1): configure the speed at which higher modes decay compare to lower modes.
- `att`: attack duration in second
- `rel`: release duration in second
- `gate`: trigger signal (0 or 1)

`fm`

An FM synthesizer with an arbitrary number of modulators connected as a sequence. `fm` is a standard Faust function.

Usage

```
freqs = (300,400,...);
indices = (20,...);
fm(freqs,indices) : _
```

Where:

- `freqs`: a list of frequencies where the first one is the frequency of the carrier and the others, the frequency of the modulator(s)
- `indices`: the indices of modulation (Nfreqs-1)

---

vaeffects.lib

A library of virtual analog filter effects. Its official prefix is `ve`.

Functions Reference

`moog_vcf`

Moog "Voltage Controlled Filter" (VCF) in "analog" form. Moog VCF implemented using the same logical block diagram as the classic analog circuit. As such, it neglects the one-sample delay associated with the feedback path around the four one-poles. This extra delay alters the response, especially at high frequencies (see reference [1] for details). See `moog_vcf_2b` below for a more accurate implementation.

Usage

`moog_vcf(res,fr)`

Where:

- `fr`: corner-resonance frequency in Hz (less than SR/6.3 or so)
- `res`: Normalized amount of corner-resonance between 0 and 1 (0 is no resonance, 1 is maximum)

References

- https://ccrma.stanford.edu/~stilti/papers/moogvcf.pdf
- https://ccrma.stanford.edu/~jos/pasp/vegf.html

`moog_vcf_2b[n]`

Moog "Voltage Controlled Filter" (VCF) as two biquads. Implementation of the ideal Moog VCF transfer function factored into second-order sections. As a result, it is more accurate than `moog_vcf` above, but its coefficient formulas are more complex when one or both parameters are varied. Here, res is the fourth root of that in `moog_vcf`, so, as the sampling rate approaches infinity, `moog_vcf(res,fr)` becomes equivalent to `moog_vcf_2b[n](res^4,fr)` (when res and fr are constant). `moog_vcf_2b` uses two direct-form biquads (`tf2`). `moog_vcf_2bn` uses two protected normalized-ladder biquads (`tf2np`).

Usage

```
moog_vcf_2b(res,fr)
moog_vcf_2bn(res,fr)
```

Where:

- `fr`: corner-resonance frequency in Hz
- `res`: Normalized amount of corner-resonance between 0 and 1 (0 is min resonance, 1 is maximum)

`wah4`

Wah effect, 4th order. `wah4` is a standard Faust function.

Usage

```
_ : wah4(fr) : _
```

Where:

- `fr`: resonance frequency in Hz

Reference https://ccrma.stanford.edu/~jos/pasp/vegf.html

`autowah`

Auto-wah effect. `autowah` is a standard Faust function.

Usage

```
_ : autowah(level) : _;
```

Where:

- `level`: amount of effect desired (0 to 1).

`crybaby`

Digitized CryBaby wah pedal. `crybaby` is a standard Faust function.

Usage

```
_ : crybaby(wah) : _
```

Where:

- `wah`: "pedal angle" from 0 to 1

Reference https://ccrma.stanford.edu/~jos/pasp/vegf.html

`vocoder`

A very simple vocoder where the spectrum of the modulation signal is analyzed using a filter bank. `vocoder` is a standard Faust function.

Usage

```
_ : vocoder(nBands,att,rel,BWRatio,source,excitation) : _;
```

Where:

- `nBands`: Number of vocoder bands
- `att`: Attack time in seconds
- `rel`: Release time in seconds
- `BWRatio`: Coefficient to adjust the bandwidth of each band (0.1 - 2)
- `source`: Modulation signal
- `excitation`: Excitation/Carrier signal

Licenses

STK 4.3 License

LGPL License