Faust Standard Libraries

Contents

Faust Libraries

NOTE: this documentation was automatically generated.

This page provides information on how to use the Faust libraries.

The `/libraries` folder contains the different Faust libraries. If you wish to add your own functions to this library collection, you can refer to the "Contributing" section providing a set of coding conventions.

WARNING: These libraries replace the "old" Faust libraries. They are still being beta tested so you might encounter bugs while using them. If your codes still use the "old" Faust libraries, you might want to try to use Bart Brouns' script that automatically makes an old Faust code compatible with the new libraries: https://github.com/magnetophon/faustCompressors/blob/master/newlib.sh. If you find a bug, please report it at rmichon_at_ccrma_dot_stanford_dot_edu. Thanks ;)!

Using the Faust Libraries

The easiest and most standard way to use the Faust libraries is to import `stdfaust.lib` in your Faust code:

```
import("stdfaust.lib");
```

This will give you access to all the Faust libraries through a series of environments:

- `sf: all.lib`
- `an: analyzers.lib`
- `ba: basics.lib`
- `co: compressors.lib`
- `de: delays.lib`
- `dm: demos.lib`
- `en: envelopes.lib`
- `fi: filters.lib`
- `ho: hoa.lib`
- `ma: maths.lib`
- `ef: misceffects.lib`
- `os: oscillators.lib`
- `no: noises.lib`
- `pf: phaflangers.lib`
- `pm: physmodels.lib`
- `re: reverbs.lib`
- `ro: routes.lib`
- `si: signals.lib`
- `sp: spats.lib`
- `sy: synths.lib`

- ve: `vaeffects.lib`

Environments can then be used as follows in your Faust code:

```
import("stdfaust.lib");
process = os.osc(440);
```

In this case, we're calling the `osc` function from `oscillators.lib`.

You can also access all the functions of all the libraries directly using the `sf` environment:

```
import("stdfaust.lib");
process = sf.osc(440);
```

Alternatively, environments can be created by hand:

```
os = library("oscillators.lib");
process = os.osc(440);
```

Finally, libraries can be simply imported in the Faust code (not recommended):

```
import("oscillators.lib");
process = osc(440);
```

Contributing

If you wish to add a function to any of these libraries or if you plan to add a new library, make sure that you follow the following conventions:

New Functions

- All functions must be preceded by a markdown documentation header respecting the following format (open the source code of any of the libraries for an example):

```
//----------------functionName-------------------
// Description
//
// #### Usage
//
// ```
// Usage Example
// ```
//
// Where:
//
// * argument1: argument 1 description
//-----------------------------------------------
```

- Every time a new function is added, the documentation should be updated simply by running `make doclib`.
- The environment system (e.g. `os.osc`) should be used when calling a function declared in another library (see the section on *Using the Faust Libraries*).
- Try to reuse exisiting functions as much as possible.
- If you have any question, send an e-mail to rmichon_at_ccrma_dot_stanford_dot_edu.

New Libraries

- Any new "standard" library should be declared in `stdfaust.lib` with its own environment (2 letters - see `stdfaust.lib`).
- Any new "standard" library must be added to `generateDoc`.
- Functions must be organized by sections.
- Any new library should at least `declare` a `name` and a `version`.
- The comment based markdown documentation of each library must respect the following format (open the source code of any of the libraries for an example):

```
//############### libraryName #################
// Description
//
// * Section Name 1
// * Section Name 2
// * ...
//
// It should be used using the `[...]` environment:
//
// ```
// [...] = library("libraryName");
// process = [...].functionCall;
// ```
//
// Another option is to import `stdfaust.lib` which already contains the `[...]`
// environment:
//
// ```
// import("stdfaust.lib");
// process = [...].functionCall;
// ```
//#############################################

//================ Section Name ==============
// Description
//============================================
```

- If you have any question, send an e-mail to rmichon_at_ccrma_dot_stanford_dot_edu.

General Organization

Only the libraries that are considered to be "standard" are documented:

- `analyzers.lib`
- `basics.lib`
- `compressors.lib`
- `delays.lib`
- `demos.lib`
- `envelopes.lib`
- `filters.lib`
- `hoa.lib`
- `maths.lib`
- `misceffects.lib`
- `oscillators.lib`
- `noises.lib`
- `phaflangers.lib`
- `physmodels.lib`
- `reverbs.lib`
- `routes.lib`
- `signals.lib`
- `spats.lib`
- `synths.lib`
- `tonestacks.lib` (not documented but example in `/examples/misc`)
- `tubes.lib` (not documented but example in `/examples/misc`)
- `vaeffects.lib`

Other deprecated libraries such as `music.lib`, etc. are present but are not documented to not confuse new users.

The doumentation of each library can be found in `/documentation/library.html` or in `/documentation/library.pdf`.

The `/examples` directory contains all the examples from the `/examples` folder of the Faust distribution as well as new ones. Most of them were updated to reflect the coding conventions described in the next section. Examples are organized by types in different folders. The `/old` folder contains examples that are fully deprecated, probably because they were integrated to the libraries and fully rewritten (see `freeverb.dsp` for example). Examples using deprecated libraries were integrated to the general tree but a warning comment was added at their beginning to point readers to the right library and function.

Coding Conventions

In order to have a uniformized library system, we established the following conventions (that hopefully will be followed by others when making modifications to them :-)).

Documentation

- All the functions that we want to be "public" are documented.
- We used the `faust2md` "standards" for each library: `//###` for main title (library name - equivalent to `#` in markdown), `//===` for section declarations (equivalent to `##` in markdown) and `//---` for function declarations (equivalent to `####` in markdown - see `basics.lib` for an example).
- Sections in function documentation should be declared as `####` markdown title.
- Each function documentation provides a "Usage" section (see `basics.lib`).

Library Import

To prevent cross-references between libraries we generalized the use of the `library("")` system for function calls in all the libraries. This means that everytime a function declared in another library is called, the environment corresponding to this library needs to be called too. To make things easier, a `stdfaust.lib` library was created and is imported by all the libraries:

```
an = library("analyzers.lib");
ba = library("basics.lib");
co = library("compressors.lib");
de = library("delays.lib");
dm = library("demos.lib");
en = library("envelopes.lib");
fi = library("filters.lib");
ho = library("hoa.lib");
ma = library("maths.lib");
ef = library("misceffects.lib");
os = library("oscillators.lib");
no = library("noises.lib");
pf = library("phaflangers.lib");
pm = library("physmodels.lib");
re = library("reverbs.lib");
ro = library("routes.lib");
sp = library("spats.lib");
si = library("signals.lib");
sy = library("synths.lib");
ve = library("vaeffects.lib");
```

For example, if we wanted to use the `smooth` function which is now declared in `signals.lib`, we would do the following:

```
import("stdfaust.lib");
```

```
process = si.smooth(0.999);
```

This standard is only used within the libraries: nothing prevents coders to still import `signals.lib` directly and call `smooth` without `ro.`, etc.

"Demo" Functions

"Demo" functions are placed in `demos.lib` and have a built-in user interface (UI). Their name ends with the `_demo` suffix. Each of these function have a `.dsp` file associated to them in the `/examples` folder.

Any function containing UI elements should be placed in this library and respect these standards.

"Standard" Functions

"Standard" functions are here to simplify the life of new (or not so new) Faust coders. They are declared in `/libraries/doc/standardFunctions.md` and allow to point programmers to preferred functions to carry out a specific task. For example, there are many different types of lowpass filters declared in `filters.lib` and only one of them is considered to be standard, etc.

Copyright / License

Now that Faust libraries are less author specific, each function will normally have its own copyright-and-license line. If not, then the global copyright/license may be assumed, when present. If there is no local or global notice, try git blame!

Standard Functions

Dozens of functions are implemented in the Faust libraries and many of them are very specialized and not useful to beginners or to people who only need to use Faust for basic applications. This section offers an index organized by categories of the "standard Faust functions" (basic filters, effects, synthesizers, etc.). This index only contains functions without a user interface (UI). Faust functions with a built-in UI can be found in `demos.lib`.

Analysis Tools

Function Type	Function Name	Description
Amplitude Follower	`an.amp_follower`	Classic analog audio envelope follower
Octave Analyzers	`an.mth_octave_analyzer[N]`	Octave analyzers

Basic Elements

Function Type	Function Name	Description
Beats	`ba.beat`	Pulses at a specific tempo
Block	`si.block`	Terminate n signals
Break Point Function	`ba.bpf`	Beak Point Function (BPF)
Bus	`si.bus`	Bus of n signals
Bypass (Mono)	`ba.bypass1`	Mono bypass
Bypass (Stereo)	`ba.bypass2`	Stereo bypass
Count Elements	`ba.count`	Count elements in a list
Count Down	`ba.countdown`	Samples count down
Count Up	`ba.countup`	Samples count up
Delay (Integer)	`de.delay`	Integer delay
Delay (Float)	`de.fdelay`	Fractional delay
Impulsify	`ba.impulsify`	Turns a signal into an impulse
Sample and Hold	`ba.sAndH`	Sample and hold
Signal Crossing	`ro.cross`	Cross n signals
Smoother (Default)	`si.smoo`	Exponential smoothing
Smoother	`si.smooth`	Exponential smoothing with controllable pole
Take Element	`ba.take`	Take en element from a list
Time	`ba.time`	A simple timer

Conversion

Function Type	Function Name	Description
dB to Linear	`ba.db2linear`	Converts dB to linear values
Linear to dB	`ba.linear2db`	Converts linear values to dB
MIDI Key to Hz	`ba.midikey2hz`	Converts a MIDI key number into a frequency
Pole to T60	`ba.pole2tau`	Converts a pole into a time constant (t60)
Samples to Seconds	`ba.samp2sec`	Converts samples to seconds
Seconds to Samples	`ba.sec2samp`	Converts seconds to samples
T60 to Pole	`ba.tau2pole`	Converts a time constant (t60) into a pole

Effects

Function Type	Function Name	Description
Auto Wah	`ve.autowah`	Auto-Wah effect
Compressor	`co.compressor_mono`	Dynamic range compressor
Distortion	`ef.cubicnl`	Cubic nonlinearity distortion
Crybaby	`ve.crybaby`	Crybaby wah pedal
Echo	`ef.echo`	Simple echo
Flanger	`pf.flanger_stereo`	Flanging effect
Gate	`ef.gate_mono`	Mono signal gate
Limiter	`co.limiter_1176_R4_mono`	Limiter
Phaser	`pf.phaser2_stereo`	Phaser effect
Reverb (FDN)	`re.fdnrev0`	Feedback delay network reverberator
Reverb (Freeverb)	`re.mono_freeverb`	Most "famous" Schroeder reverberator
Reverb (Simple)	`re.jcrev`	Simple Schroeder reverberator
Reverb (Zita)	`re.zita_rev1_stereo`	High quality FDN reverberator
Panner	`sp.panner`	Linear stereo panner
Pitch Shift	`ef.transpose`	Simple pitch shifter
Panner	`sp.spat`	N outputs spatializer
Speaker Simulator	`ef.speakerbp`	Simple speaker simulator
Stereo Width	`ef.stereo_width`	Stereo width effect
Vocoder	`ve.vocoder`	Simple vocoder
Wah	`ve.wah4`	Wah effect

Envelope Generators

Function Type	Function Name	Description
ADSR	`en.adsr`	Attack/Decay/Sustain/Release envelope generator
AR	`en.ar`	Attack/Release envelope generator
ASR	`en.asr`	Attack/Sustain/Release envelope generator
Exponential	`en.smoothEnvelope`	Exponential envelope generator

Filters

Function Type	Function Name	Description
Bandpass (Butterworth)	`fi.bandpass`	Generic butterworth bandpass
Bandpass (Resonant)	`fi.resonbp`	Virtual analog resonant bandpass
Bandstop (Butterworth)	`fi.bandstop`	Generic butterworth bandstop
Biquad	`fi.tf2`	"Standard" biquad filter
Comb (Allpass)	`fi.allpass_fcomb`	Schroeder allpass comb filter
Comb (Feedback)	`fi.fb_fcomb`	Feedback comb filter

Function Type	Function Name	Description
Comb (Feedforward)	`fi.ff_fcomb`	Feed-forward comb filter.
DC Blocker	`fi.dcblocker`	Default dc blocker
Filterbank	`fi.filterbank`	Generic filter bank
FIR (Arbitrary Order)	`fi.fir`	Nth-order FIR filter
High Shelf	`fi.high_shelf`	High shelf
Highpass (Butterworth)	`fi.highpass`	Nth-order Butterworth highpass
Highpass (Resonant)	`fi.resonhp`	Virtual analog resonant highpass
IIR (Arbitrary Order)	`fi.iir`	Nth-order IIR filter
Level Filter	`fi.levelfilter`	Dynamic level lowpass
Low Shelf	`fi.low_shelf`	Low shelf
Lowpass (Butterworth)	`fi.lowpass`	Nth-order Butterworth lowpass
Lowpass (Resonant)	`fi.resonlp`	Virtual analog resonant lowpass
Notch Filter	`fi.notchw`	Simple notch filter
Peak Equalizer	`fi.peak_eq`	Peaking equalizer section

Oscillators/Sound Generators

Function Type	Function Name	Description
Impulse	`os.impulse`	Generate an impulse on start-up
Impulse Train	`os.imptrain`	Band-limited impulse train
Phasor	`os.phasor`	Simple phasor
Pink Noise	`no.pink_noise`	Pink noise generator
Pulse Train	`os.pulsetrain`	Band-limited pulse train
Pulse Train (Low Frequency)	`os.lf_imptrain`	Low-frequency pulse train
Sawtooth	`os.sawtooth`	Band-limited sawtooth wave
Sawtooth (Low Frequency)	`os.lf_saw`	Low-frequency sawtooth wave
Sine (Filter-Based)	`os.osc`	Sine oscillator (filter-based)
Sine (Table-Based)	`os.oscsin`	Sine oscillator (table-based)
Square	`os.square`	Band-limited square wave
Square (Low Frequency)	`os.lf_squarewave`	Low-frequency square wave
Triangle	`os.triangle`	Band-limited triangle wave
Triangle (Low Frequency)	`os.lf_triangle`	Low-frequency triangle wave
White Noise	`no.noise`	White noise generator

Synths

Function Type	Function Name	Description
Additive Drum	`sy.additiveDrum`	Additive synthesis drum
Bandpassed Sawtooth	`sy.dubDub`	Sawtooth through resonant bandpass
Comb String	`sy.combString`	String model based on a comb filter

Function Type	Function Name	Description
FM	`sy.fm`	Frequency modulation synthesizer
Lowpassed Sawtooth	`sy.sawTrombone`	"Trombone" based on a filtered sawtooth
Popping Filter	`sy.popFilterPerc`	Popping filter percussion instrument

analyzers.lib

Faust Analyzers library. Its official prefix is `an`.

Amplitude Tracking

amp_follower

Classic analog audio envelope follower with infinitely fast rise and exponential decay. The amplitude envelope instantaneously follows the absolute value going up, but then floats down exponentially. `amp_follower` is a standard Faust function.

Usage

```
_ : amp_follower(rel) : _
```

Where:

- `rel`: release time = amplitude-envelope time-constant (sec) going down

Reference

- Musical Engineer's Handbook, Bernie Hutchins, Ithaca NY, 1975 Electronotes Newsletter, Bernie Hutchins

----

amp_follower_ud

Envelope follower with different up and down time-constants (also called a "peak detector").

Usage

```
_ : amp_follower_ud(att,rel) : _
```

Where:

- `att`: attack time = amplitude-envelope time constant (sec) going up
- `rel`: release time = amplitude-envelope time constant (sec) going down

Note

We assume rel >> att. Otherwise, consider rel ~ max(rel,att). For audio, att is normally faster (smaller) than rel (e.g., 0.001 and 0.01). Use `amp_follower_ar` below to remove this restriction.

Reference

- "Digital Dynamic Range Compressor Design — A Tutorial and Analysis", by Dimitrios Giannoulis, Michael Massberg, and Joshua D. Reiss http://www.eecs.qmul.ac.uk/~josh/documents/GiannoulisMassbergReiss-dynamicrangecompression-JAES2012.pdf

---

Spectrum-Analyzers

Spectrum-analyzers split the input signal into a bank of parallel signals, one for each spectral band. They are related to the Mth-Octave Filter-Banks in `filters.lib`. The documentation of this library contains more details about the implementation. The parameters are:

- `M`: number of band-slices per octave (>1)
- `N`: total number of bands (>2)
- `ftop` = upper bandlimit of the Mth-octave bands ($<SR/2$)

In addition to the Mth-octave output signals, there is a highpass signal containing frequencies from ftop to SR/2, and a "dc band" lowpass signal containing frequencies from 0 (dc) up to the start of the Mth-octave bands. Thus, the N output signals are

`highpass(ftop), MthOctaveBands(M,N-2,ftop), dcBand(ftop*2^(-M*(N-1)))`

A Spectrum-Analyzer is defined here as any band-split whose bands span the relevant spectrum, but whose band-signals do not necessarily sum to the original signal, either exactly or to within an allpass filtering. Spectrum analyzer outputs are normally at least nearly "power complementary", i.e., the power spectra of the individual bands sum to the original power spectrum (to within some negligible tolerance).

Increasing Channel Isolation

Go to higher filter orders - see Regalia et al. or Vaidyanathan (cited below) regarding the construction of more aggressive recursive filter-banks using elliptic or Chebyshev prototype filters.

References

- "Tree-structured complementary filter banks using all-pass sections", Regalia et al., IEEE Trans. Circuits & Systems, CAS-34:1470-1484, Dec. 1987
- "Multirate Systems and Filter Banks", P. Vaidyanathan, Prentice-Hall, 1993
- Elementary filter theory: https://ccrma.stanford.edu/~jos/filters/

`mth_octave_analyzer`

Octave analyzer. `mth_octave_analyzer[N]` are standard Faust functions.

Usage

```
_ : mth_octave_analyzer(O,M,ftop,N) : par(i,N,_); // 0th-order Butterworth
_ : mth_octave_analyzer6e(M,ftop,N) : par(i,N,_); // 6th-order elliptic
```

Also for convenience:

```
_ : mth_octave_analyzer3(M,ftop,N) : par(i,N,_); // 3d-order Butterworth
_ : mth_octave_analyzer5(M,ftop,N) : par(i,N,_); // 5th-roder Butterworth
mth_octave_analyzer_default = mth_octave_analyzer6e;
```

Where:

- `O`: order of filter used to split each frequency band into two
- `M`: number of band-slices per octave
- `ftop`: highest band-split crossover frequency (e.g., 20 kHz)
- `N`: total number of bands (including dc and Nyquist)

Mth-Octave Spectral Level

Spectral Level: Display (in bar graphs) the average signal level in each spectral band.

`mth_octave_spectral_level6e`

Spectral level display.

Usage:

```
_ : mth_octave_spectral_level6e(M,ftop,NBands,tau,dB_offset) : _;
```

Where:

- `M`: bands per octave
- `ftop`: lower edge frequency of top band
- `NBands`: number of passbands (including highpass and dc bands),
- `tau`: spectral display averaging-time (time constant) in seconds,
- `dB_offset`: constant dB offset in all band level meters.

Also for convenience:

```
mth_octave_spectral_level_default = mth_octave_spectral_level6e;
spectral_level = mth_octave_spectral_level(2,10000,20);
```

———————————————————

[third|half]_octave_[analyzer|filterbank]

A bunch of special cases based on the different analyzer functions described above:

```
third_octave_analyzer(N) = mth_octave_analyzer_default(3,10000,N);
third_octave_filterbank(N) = mth_octave_filterbank_default(3,10000,N);
half_octave_analyzer(N) = mth_octave_analyzer_default(2,10000,N);
half_octave_filterbank(N) = mth_octave_filterbank_default(2,10000,N);
octave_filterbank(N) = mth_octave_filterbank_default(1,10000,N);
octave_analyzer(N) = mth_octave_analyzer_default(1,10000,N);
```

Usage

See `mth_octave_spectral_level_demo`.

———————————————————

Arbritary-Crossover Filter-Banks and Spectrum Analyzers

These are similar to the Mth-octave analyzers above, except that the band-split frequencies are passed explicitly as arguments.

analyzer

Analyzer.

Usage

```
_ : analyzer(O,freqs) : par(i,N,_); // No delay equalizer
```

Where:

- `O`: band-split filter order (ODD integer required for filterbank[i])
- `freqs`: (fc1,fc2,...,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : analyzer(3,(fc1,fc2)) : _,_,_
```

---

amp_follower_ar

Envelope follower with independent attack and release times. The release can be shorter than the attack (unlike in `amp_follower_ud` above).

Usage

```
_ : amp_follower_ar(att,rel) : _;
```

- Author Jonatan Liljedahl, revised by RM

---

basics.lib

A library of basic elements for Faust organized in 5 sections:

- Conversion Tools
- Counters and Time/Tempo Tools
- Array Processing/Pattern Matching
- Selectors (Conditions)
- Other Tools (Misc)

The official prefix of this library is `ba`.

Conversion Tools

samp2sec

Converts a number of samples to a duration in seconds. `samp2sec` is a standard Faust function.

Usage

```
samp2sec(n) : _
```

Where:

- `n`: number of samples

---

sec2samp

Converts a duration in seconds to a number of samples. `samp2sec` is a standard Faust function.

Usage

```
sec2samp(d) : _
```

Where:

- `d`: duration in seconds

---

db2linear

Converts a loudness in dB to a linear gain (0-1). `db2linear` is a standard Faust function.

Usage

```
db2linear(l) : _
```

Where:

- `l`: loudness in dB

---

linear2db

Converts a linear gain (0-1) to a loudness in dB. `linear2db` is a standard Faust function.

Usage

```
linear2db(g) : _
```

Where:

- g: a linear gain

---

lin2LogGain

Converts a linear gain (0-1) to a log gain (0-1).

Usage

```
_ : lin2LogGain : _
```

---

log2LinGain

Converts a log gain (0-1) to a linear gain (0-1).

Usage

```
_ : log2LinGain : _
```

---

tau2pole

Returns a real pole giving exponential decay. Note that t60 (time to decay 60 dB) is ~6.91 time constants. `tau2pole` is a standard Faust function.

Usage

```
_ : smooth(tau2pole(tau)) : _
```

Where:

- `tau`: time-constant in seconds

---

pole2tau

Returns the time-constant, in seconds, corresponding to the given real, positive pole in (0,1). `pole2tau` is a standard Faust function.

Usage

```
pole2tau(pole) : _
```

Where:

- `pole`: the pole

---

midikey2hz

Converts a MIDI key number to a frequency in Hz (MIDI key 69 = A440). `midikey2hz` is a standard Faust function.

Usage

```
midikey2hz(mk) : _
```

Where:

- `mk`: the MIDI key number

---

pianokey2hz

Converts a piano key number to a frequency in Hz (piano key 49 = A440).

Usage

```
pianokey2hz(pk) : _
```

Where:

- `pk`: the piano key number

---

hz2pianokey

Converts a frequency in Hz to a piano key number (piano key 49 = A440).

Usage

```
hz2pianokey(f) : _
```

Where:

- `f`: frequency in Hz

Counters and Time/Tempo Tools

`countdown`

Starts counting down from n included to 0. While trig is 1 the output is n. The countdown starts with the transition of trig from 1 to 0. At the end of the countdown the output value will remain at 0 until the next trig. `countdown` is a standard Faust function.

Usage

```
countdown(n,trig) : _
```

Where:

- `count`: the starting point of the countdown
- `trig`: the trigger signal (1: start at `n`; 0: decrease until 0)

`countup`

Starts counting up from 0 to n included. While trig is 1 the output is 0. The countup starts with the transition of trig from 1 to 0. At the end of the countup the output value will remain at n until the next trig. `countup` is a standard Faust function.

Usage

```
countup(n,trig) : _
```

Where:

- `count`: the starting point of the countup
- `trig`: the trigger signal (1: start at 0; 0: increase until `n`)

---

sweep

Counts from 0 to `period` samples repeatedly, while `run` is 1. Outsputs zero while `run` is 0.

Usage

```
sweep(period,run) : _
```

-----

time

A simple timer that counts every samples from the beginning of the process. `time` is a standard Faust function.

Usage

```
time : _
```

-----

tempo

Converts a tempo in BPM into a number of samples.

Usage

```
tempo(t) : _
```

Where:

- `t`: tempo in BPM

-----

period

Basic sawtooth wave of period `p`.

Usage

```
period(p) : _
```

Where:

- **p**: period as a number of samples

---

pulse

Pulses (10000) generated at period **p**.

Usage

```
pulse(p) : _
```

Where:

- **p**: period as a number of samples

---

pulsen

Pulses (11110000) of length **n** generated at period **p**.

Usage

```
pulsen(n,p) : _
```

Where:

- **n**: the length of the pulse as a number of samples
- **p**: period as a number of samples

---

beat

Pulses at tempo **t**. **beat** is a standard Faust function.

Usage

```
beat(t) : _
```

Where:

- `t`: tempo in BPM

---

pulse_countup

Starts counting up pulses. While trig is 1 the output is counting up, while trig is 0 the counter is reset to 0.

Usage

```
_ : pulse_countup(trig) : _
```

Where:

- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

---

pulse_countdown

Starts counting down pulses. While trig is 1 the output is counting down, while trig is 0 the counter is reset to 0.

Usage

```
_ : pulse_countdown(trig) : _
```

Where:

- `trig`: the trigger signal (1: start at next pulse; 0: reset to 0)

---

pulse_countup_loop

Starts counting up pulses from 0 to n included. While trig is 1 the output is counting up, while trig is 0 the counter is reset to 0. At the end of the countup (n) the output value will be reset to 0.

Usage

```
_ : pulse_countup_loop(n,trig) : _
```

Where:

- **n**: the highest number of the countup (included) before reset to 0.
- **trig**: the trigger signal (1: start at next pulse; 0: reset to 0)

---

pulse_countdown_loop

Starts counting down pulses from 0 to n included. While trig is 1 the output is counting down, while trig is 0 the counter is reset to 0. At the end of the countdown (n) the output value will be reset to 0.

Usage

```
_ : pulse_coundown_loop(n,trig) : _
```

Where:

- **n**: the highest number of the countup (included) before reset to 0.
- **trig**: the trigger signal (1: start at next pulse; 0: reset to 0)

Array Processing/Pattern Matching

count

Count the number of elements of list l. **count** is a standard Faust function.

Usage

```
count(l)
count ((10,20,30,40)) -> 4
```

Where:

- **l**: list of elements

---

take

Take an element from a list. **take** is a standard Faust function.

Usage

```
take(e,l)
take(3,(10,20,30,40)) -> 30
```

Where:

- `p`: position (starting at 1)
- `l`: list of elements

---

subseq

Extract a part of a list.

Usage

```
subseq(l, p, n)
subseq((10,20,30,40,50,60), 1, 3) -> (20,30,40)
subseq((10,20,30,40,50,60), 4, 1) -> 50
```

Where:

- `l`: list
- `p`: start point (0: begin of list)
- `n`: number of elements

Note:

Faust doesn't have proper lists. Lists are simulated with parallel compositions and there is no empty list

---

Selectors (Conditions)

if

if-then-else implemented with a select2.

Usage

- `if(c, t, e) : _`

Where:

- `c`: condition

- `t`: signal selected while c is true
- `e`: signal selected while c is false

---

selector

Selects the ith input among n at compile time.

Usage

```
selector(i,n)
_,_,_,_ : selector(2,4) : _  // selects the 3rd input among 4
```

Where:

- `i`: input to select (`int`, numbered from 0, known at compile time)
- `n`: number of inputs (`int`, known at compile time, `n > i`)

---

selectn

Selects the ith input among N at run time.

Usage

```
selectn(N,i)
_,_,_,_ : selectn(4,2) : _  // selects the 3rd input among 4
```

Where:

- `N`: number of inputs (int, known at compile time, N > 0)
- `i`: input to select (int, numbered from 0)

Example test program

```
N=64;
process = par(n,N, (par(i,N,i) : selectn(N,n)));
```

---

select2stereo

Select between 2 stereo signals.

Usage

`_,_,_,_ : select2stereo(bpc) : _,_,_,_`

Where:

- `bpc`: the selector switch (0/1)

Other

`latch`

Latch input on positive-going transition of "clock" ("sample-and-hold").

Usage

`_ : latch(clocksig) : _`

Where:

- `clocksig`: hold trigger (0 for hold, 1 for bypass)

`sAndH`

Sample And Hold. `sAndH` is a standard Faust function.

Usage

`_ : sAndH(t) : _`

Where:

- `t`: hold trigger (0 for hold, 1 for bypass)

`peakhold`

Outputs current max value above zero.

Usage

```
_ : peakhold(mode) : _;
```

Where:

`mode` means: 0 - Pass through. A single sample 0 trigger will work as a reset. 1 - Track and hold max value.

---

peakholder

Tracks abs peak and holds peak for 'holdtime' samples.

Usage

```
_ : peakholder(holdtime) : _;
```

---

impulsify

Turns the signal from a button into an impulse (1,0,0,... when button turns on). `impulsify` is a standard Faust function.

Usage

```
button("gate") : impulsify ;
```

---

automat

Record and replay to the values the input signal in a loop.

Usage

```
hslider(...) : automat(bps, size, init) : _
```

`bpf`

bpf is an environment (a group of related definitions) that can be used to create break-point functions. It contains three functions :

- `start(x,y)` to start a break-point function
- `end(x,y)` to end a break-point function
- `point(x,y)` to add intermediate points to a break-point function

A minimal break-point function must contain at least a start and an end point :

```
f = bpf.start(x0,y0) : bpf.end(x1,y1);
```

A more involved break-point function can contains any number of intermediate points:

```
f = bpf.start(x0,y0) : bpf.point(x1,y1) : bpf.point(x2,y2) : bpf.end(x3,y3);
```

In any case the `x_{i}` must be in increasing order (for all `i`, `x_{i} < x_{i+1}`). For example the following definition :

```
f = bpf.start(x0,y0) : ... : bpf.point(xi,yi) : ... : bpf.end(xn,yn);
```

implements a break-point function f such that :

- `f(x) = y_{0}` when `x < x_{0}`
- `f(x) = y_{n}` when `x > x_{n}`
- `f(x) = y_{i} + (y_{i+1}-y_{i})*(x-x_{i})/(x_{i+1}-x_{i})` when `x_{i} <= x` and `x < x_{i+1}`

`bpf` is a standard Faust function.

`bypass1`

Takes a mono input signal, route it to `e` and bypass it if `bpc = 1`. `bypass1` is a standard Faust function.

Usage

```
_ : bypass1(bpc,e) : _
```

Where:

- `bpc`: bypass switch (0/1)
- `e`: a mono effect

---

bypass2

Takes a stereo input signal, route it to `e` and bypass it if `bpc = 1`. `bypass2` is a standard Faust function.

Usage

```
_,_ : bypass2(bpc,e) : _,_
```

Where:

- `bpc`: bypass switch (0/1)
- `e`: a stereo effect

---

toggle

Triggered by the change of 0 to 1, it toggles the output value between 0 and 1.

Usage

```
_ : toggle : _
```

Examples

```
button("toggle") : toggle : vbargraph("output", 0, 1)
(an.amp_follower(0.1) > 0.01) : toggle : vbargraph("output", 0, 1) // takes audio input
```

---

on_and_off

The first channel set the output to 1, the second channel to 0.

Usage

```
_ , _ : on_and_off : _
```

Example

```
button("on"), button("off") : on_and_off : vbargraph("output", 0, 1)
```

```
selectoutn
```

Route input to the output among N at run time.

Usage

```
_ : selectoutn(n, s) : _,_,...n
```

Where:

- **n**: number of outputs (int, known at compile time, N > 0)
- **s**: output number to route to (int, numbered from 0) (i.e. slider)

Example

```
process = 1 : selectoutn(3, sel) : par(i,3,bar) ;
sel = hslider("volume",0,0,2,1) : int;
bar = vbargraph("v.bargraph", 0, 1);
```

---

compressors.lib

A library of compressor effects. Its official prefix is `co`.

Functions Reference

```
compressor_mono
```

Mono dynamic range compressors. `compressor_mono` is a standard Faust function

Usage

```
_ : compressor_mono(ratio,thresh,att,rel) : _
```

Where:

- **ratio**: compression ratio (1 = no compression, >1 means compression)
- **thresh**: dB level threshold above which compression kicks in (0 dB = max level)
- **att**: attack time = time constant (sec) when level & compression going up
- **rel**: release time = time constant (sec) coming out of compression

References

- http://en.wikipedia.org/wiki/Dynamic_range_compression
- https://ccrma.stanford.edu/~jos/filters/Nonlinear_Filter_Example_ Dynamic.html
- Albert Graef's "faust2pd"/examples/synth/compressor_.dsp
- More features: https://github.com/magnetophon/faustCompressors

----

`compressor_stereo`

Stereo dynamic range compressors.

Usage

```
_,_ : compressor_stereo(ratio,thresh,att,rel) : _,_
```

Where:

- `ratio`: compression ratio (1 = no compression, >1 means compression)
- `thresh`: dB level threshold above which compression kicks in (0 dB = max level)
- `att`: attack time = time constant (sec) when level & compression going up
- `rel`: release time = time constant (sec) coming out of compression

References

- http://en.wikipedia.org/wiki/Dynamic_range_compression
- https://ccrma.stanford.edu/~jos/filters/Nonlinear_Filter_Example_ Dynamic.html
- Albert Graef's "faust2pd"/examples/synth/compressor_.dsp
- More features: https://github.com/magnetophon/faustCompressors

----

`limiter_1176_R4_mono`

A limiter guards against hard-clipping. It can be can be implemented as a compressor having a high threshold (near the clipping level), fast attack and release, and high ratio. Since the ratio is so high, some knee smoothing is desirable ("soft limiting"). This example is intended to get you started using compressor_* as a limiter, so all parameters are hardwired to nominal values here. Ratios: 4 (moderate compression), 8 (severe compression), 12 (mild limiting), or 20 to 1 (hard limiting) Att: 20-800 MICROseconds (Note: scaled by ratio in the 1176) Rel: 50-1100 ms (Note: scaled by ratio in the 1176) Mike Shipley likes 4:1

(Grammy-winning mixer for Queen, Tom Petty, etc.) Faster attack gives "more bite" (e.g. on vocals) He hears a bright, clear eq effect as well (not implemented here) `limiter_1176_R4_mono` is a standard Faust function.

Usage

```
_ : limiter_1176_R4_mono : _;
```

Reference:

http://en.wikipedia.org/wiki/1176_Peak_Limiter

`limiter_1176_R4_stereo`

A limiter guards against hard-clipping. It can be can be implemented as a compressor having a high threshold (near the clipping level), fast attack and release, and high ratio. Since the ratio is so high, some knee smoothing is desirable ("soft limiting"). This example is intended to get you started using compressor_* as a limiter, so all parameters are hardwired to nominal values here. Ratios: 4 (moderate compression), 8 (severe compression), 12 (mild limiting), or 20 to 1 (hard limiting) Att: 20-800 MICROseconds (Note: scaled by ratio in the 1176) Rel: 50-1100 ms (Note: scaled by ratio in the 1176) Mike Shipley likes 4:1 (Grammy-winning mixer for Queen, Tom Petty, etc.) Faster attack gives "more bite" (e.g. on vocals) He hears a bright, clear eq effect as well (not implemented here)

Usage

```
_,_ : limiter_1176_R4_stereo : _,_;
```

Reference:

http://en.wikipedia.org/wiki/1176_Peak_Limiter

----

delays.lib

This library contains a collection of delay functions. Its official prefix is `de`.

Basic Delay Functions

`delay`

Simple `d` samples delay where `n` is the maximum delay length as a number of samples (it needs to be a power of 2). Unlike the `@` delay operator, this function allows to preallocate memory which means that `d` can be changed dynamically at run time as long as it remains smaller than `n`. `delay` is a standard Faust function.

Usage

```
_ : delay(n,d) : _
```

Where:

- `n`: the max delay length as a power of 2
- `d`: the delay length as a number of samples (integer)

`fdelay`

Simple `d` samples fractional delay based on 2 interpolated delay lines where `n` is the maximum delay length as a number of samples (it needs to be a power of 2 - see `delay()`). `fdelay` is a standard Faust function.

Usage

```
_ : fdelay(n,d) : _
```

Where:

- `n`: the max delay length as a power of 2
- `d`: the delay length as a number of samples (float)

`sdelay`

s(mooth)delay: a mono delay that doesn't click and doesn't transpose when the delay time is changed.

Usage

```
_ : sdelay(N,it,dt) : _
```

Where :

- `N`: maximal delay in samples (must be a constant power of 2, for example 65536)
- `it`: interpolation time (in samples) for example 1024
- `dt`: delay time (in samples)

Lagrange Interpolation

fdelaylti and fdelayltv

Fractional delay line using Lagrange interpolation.

Usage

```
_ : fdelaylt[i|v](order, maxdelay, delay, inputsignal) : _
```

Where `order=1,2,3,...` is the order of the Lagrange interpolation polynomial.

`fdelaylti` is most efficient, but designed for constant/slowly-varying delay. `fdelayltv` is more expensive and more robust when the delay varies rapidly.

NOTE: The requested delay should not be less than `(N-1)/2`.

References

- https://ccrma.stanford.edu/~jos/pasp/Lagrange_Interpolation.html
- Timo I. Laakso et al., "Splitting the Unit Delay - Tools for Fractional Delay Filter Design", IEEE Signal Processing Magazine, vol. 13, no. 1, pp. 30-60, Jan 1996.
- Philippe Depalle and Stephan Tassart, "Fractional Delay Lines using Lagrange Interpolators", ICMC Proceedings, pp. 341-343, 1996.

---

fdelay[n]

For convenience, `fdelay1`, `fdelay2`, `fdelay3`, `fdelay4`, `fdelay5` are also available where n is the order of the interpolation.

Thiran Allpass Interpolation

Thiran Allpass Interpolation

Reference

https://ccrma.stanford.edu/~jos/pasp/Thiran_Allpass_Interpolators.html

`fdelay[n]a`

Delay lines interpolated using Thiran allpass interpolation.

Usage

`_ : fdelay[N]a(maxdelay, delay, inputsignal) : _`

(exactly like `fdelay`)

Where:

- `N`=1,2,3, or 4 is the order of the Thiran interpolation filter, and the delay argument is at least N - 1/2.

Note

The interpolated delay should not be less than `N - 1/2`. (The allpass delay ranges from `N - 1/2` to `N + 1/2`.) This constraint can be alleviated by altering the code, but be aware that allpass filters approach zero delay by means of pole-zero cancellations. The delay range `[N-1/2,N+1/2]` is not optimal. What is?

Delay arguments too small will produce an UNSTABLE allpass!

Because allpass interpolation is recursive, it is not as robust as Lagrange interpolation under time-varying conditions. (You may hear clicks when changing the delay rapidly.)

First-order allpass interpolation, delay d in [0.5,1.5]

----

demos.lib

This library contains a set of demo functions based on examples located in the `/examples` folder. Its official prefix is `dm`.

Analyzers

`mth_octave_spectral_level_demo`

Demonstrate mth_octave_spectral_level in a standalone GUI.

Usage

```
_ : mth_octave_spectral_level_demo(BandsPerOctave);
_ : spectral_level_demo : _; // 2/3 octave
```

Filters

`parametric_eq_demo`

A parametric equalizer application.

Usage:

```
_ : parametric_eq_demo : _ ;
```

`spectral_tilt_demo`

A spectral tilt application.

Usage

```
_ : spectral_tilt_demo(N) : _ ;
```
Where:

- N: filter order (integer)

All other parameters interactive

`mth_octave_filterbank_demo` and `filterbank_demo`

Graphic Equalizer: Each filter-bank output signal routes through a fader.

Usage

```
_ : mth_octave_filterbank_demo(M) : _
_ : filterbank_demo : _
```

Where:

- N: number of bands per octave

Effects

cubicnl_demo

Distortion demo application.

Usage:

```
_ : cubicnl_demo : _;
```

---

gate_demo

Gate demo application.

Usage

```
_,_ : gate_demo : _,_;
```

---

compressor_demo

Compressor demo application.

Usage

```
_,_ : compressor_demo : _,_;
```

---

exciter

Psychoacoustic harmonic exciter, with GUI.

Usage

```
_ : exciter : _
```

References

- https://secure.aes.org/forum/pubs/ebriefs/?elib=16939
- https://www.researchgate.net/publication/258333577_Modeling_the_Harmonic_Exciter

––––––––––––––––––––––

moog_vcf_demo

Illustrate and compare all three Moog VCF implementations above.

Usage

```
_ : moog_vcf_demo : _;
```

––––––––––––––––––––––

wah4_demo

Wah pedal application.

Usage

```
_ : wah4_demo : _;
```

––––––––––––––––––––––

crybaby_demo

Crybaby effect application.

Usage

```
_ : crybaby_demo : _ ;
```

––––––––––––––––––––––

vocoder_demo

Use example of the vocoder function where an impulse train is used as excitation.

Usage

```
_ : vocoder_demo : _;
```

---

flanger_demo

Flanger effect application.

Usage

```
_,_ : flanger_demo : _,_;
```

---

phaser2_demo

Phaser effect demo application.

Usage

```
_,_ : phaser2_demo : _,_;
```

---

freeverb_demo

Freeverb demo application.

Usage

```
_,_ : freeverb_demo : _,_;
```

---

stereo_reverb_tester

Handy test inputs for reverberator demos below.

Usage

```
_ : stereo_reverb_tester : _
```

---

fdnrev0_demo

A reverb application using `fdnrev0`.

Usage

```
_,_ : fdnrev0_demo(N,NB,BBSO) : _,_
```

Where:

- `n`: Feedback Delay Network (FDN) order / number of delay lines used = order of feedback matrix / 2, 4, 8, or 16 [extend primes array below for 32, 64, . . .]
- `nb`: Number of frequency bands / Number of (nearly) independent T60 controls / Integer 3 or greater
- `bbso` = Butterworth band-split order / order of lowpass/highpass bandsplit used at each crossover freq / odd positive integer

---

zita_rev_fdn_demo

Reverb demo application based on `zita_rev_fdn`.

Usage

```
si.bus(8) : zita_rev_fdn_demo : si.bus(8)
```

---

zita_rev1

Example GUI for `zita_rev1_stereo` (mostly following the Linux `zita-rev1` GUI).

Only the dry/wet and output level parameters are "dezippered" here. If parameters are to be varied in real time, use `smooth(0.999)` or the like in the same way.

Usage

```
_,_ : zita_rev1 : _,_
```

49

Reference

http://www.kokkinizita.net/linuxaudio/zita-rev1-doc/quickguide.html

---

Generators

sawtooth_demo

An application demonstrating the different sawtooth oscillators of Faust.

Usage

```
sawtooth_demo : _
```

---

virtual_analog_oscillator_demo

Virtual analog oscillator demo application.

Usage

```
virtual_analog_oscillator_demo : _
```

---

oscrs_demo

Simple application demoing filter based oscillators.

Usage

```
oscrs_demo : _
```

---

velvet_noise_demo

Listen to velvet_noise!

Usage

```
velvet_noise_demo : _
```

---

latch_demo

Illustrate latch operation

Usage

```
echo "dm = library("demos.lib");" > latch_demo.dsp
echo "process = dm.latch_demo;" >> latch_demo.dsp
faust2octave latch_demo.dsp
Octave:1> plot(faustout);
```

---

envelopes.lib

This library contains a collection of envelope generators. Its official prefix is `en`.

Functions Reference

smoothEnvelope

An envelope with an exponential attack and release. `smoothEnvelope` is a standard Faust function.

Usage

```
smoothEnvelope(ar,t) : _
```

- `ar`: attack and release duration (s)
- `t`: trigger signal (0-1)

---

ar

AR (Attack, Release) envelope generator (useful to create percussion envelopes). `ar` is a standard Faust function.

Usage

```
ar(a,r,t) : _
```

Where:

- `a`: attack (sec)
- `r`: release (sec)
- `t`: trigger signal (0 or 1)

`asr`

ASR (Attack, Sustain, Release) envelope generator. `asr` is a standard Faust function.

Usage

```
asr(a,s,r,t) : _
```

Where:

- `a`, `s`, `r`: attack (sec), sustain (percentage of t), release (sec)
- `t`: trigger signal (>0 for attack, then release is when t back to 0)

`adsr`

ADSR (Attack, Decay, Sustain, Release) envelope generator. `adsr` is a standard Faust function.

Usage

```
adsr(a,d,s,r,t) : _
```

Where:

- `a`, `d`, `s`, `r`: attack (sec), decay (sec), sustain (percentage of t), release (sec)
- `t`: trigger signal (>0 for attack, then release is when t back to 0)

---

filters.lib

Faust Filters library; Its official prefix is `fi`.

The Filters library is organized into 18 sections:

- Basic Filters
- Comb Filters
- Direct-Form Digital Filter Sections
- Direct-Form Second-Order Biquad Sections
- Ladder/Lattice Digital Filters
- Useful Special Cases
- Ladder/Lattice Allpass Filters
- Digital Filter Sections Specified as Analog Filter Sections
- Simple Resonator Filters
- Butterworth Lowpass/Highpass Filters
- Special Filter-Bank Delay-Equalizing Allpass Filters
- Elliptic (Cauer) Lowpass Filters
- Elliptic Highpass Filters
- Butterworth Bandpass/Bandstop Filters
- Elliptic Bandpass Filters
- Parametric Equalizers (Shelf, Peaking)
- Mth-Octave Filter-Banks
- Arbritary-Crossover Filter-Banks and Spectrum Analyzers

For more information, see ../documentation/library.pdf

Basic Filters

`zero`

One zero filter. Difference equation: $y(n) = x(n) - z * x(n-1)$.

Usage

```
_ : zero(z) : _
```

Where:

- `z`: location of zero along real axis in z-plane

Reference

https://ccrma.stanford.edu/~jos/filters/One_Zero.html

----

pole

One pole filter. Could also be called a "leaky integrator". Difference equation: y(n) = x(n) + p * y(n-1).

Usage

```
_ : pole(z) : _
```

Where:

- **p**: pole location = feedback coefficient

Reference

https://ccrma.stanford.edu/~jos/filters/One_Pole.html

---

integrator

Same as `pole(1)` [implemented separately for block-diagram clarity].

---

dcblockerat

DC blocker with configurable break frequency. The amplitude response is substantially flat above fb, and sloped at about +6 dB/octave below fb. Derived from the analog transfer function $H(s) = s / (s + 2PIfb)$ by the low-frequency-matching bilinear transform method (i.e., the standard frequency-scaling constant 2*SR).

Usage

```
_ : dcblockerat(fb) : _
```

Where:

- **fb**: "break frequency" in Hz, i.e., -3 dB gain frequency.

Reference

https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

---

```
dcblocker
```

DC blocker. Default dc blocker has -3dB point near 35 Hz (at 44.1 kHz) and high-frequency gain near 1.0025 (due to no scaling). `dcblocker` is as standard Faust function.

Usage

```
_ : dcblocker : _
```

Comb Filters

```
ff_comb
```

Feed-Forward Comb Filter. Note that `ff_comb` requires integer delays (uses `delay` internally). `ff_comb` is a standard Faust function.

Usage

```
_ : ff_comb(maxdel,intdel,b0,bM) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input
- `bM`: gain applied to delay-line output and then summed with input

Reference

https://ccrma.stanford.edu/~jos/pasp/Feedforward_Comb_Filters.html

---

```
ff_fcomb
```

Feed-Forward Comb Filter. Note that `ff_fcomb` takes floating-point delays (uses `fdelay` internally). `ff_fcomb` is a standard Faust function.

Usage

```
_ : ff_fcomb(maxdel,del,b0,bM) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input
- `bM`: gain applied to delay-line output and then summed with input

Reference

https://ccrma.stanford.edu/~jos/pasp/Feedforward__Comb__Filters.html

---

ffcombfilter

Typical special case of `ff_comb()` where: `b0 = 1`.

---

fb_comb

Feed-Back Comb Filter (integer delay).

Usage

```
_ : fb_comb(maxdel,intdel,b0,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input and forwarded to output
- `aN`: minus the gain applied to delay-line output before summing with the input and feeding to the delay line

Reference

https://ccrma.stanford.edu/~jos/pasp/Feedback__Comb__Filters.html

---

`fb_fcomb`

Feed-Back Comb Filter (floating point delay).

Usage

```
_ : fb_fcomb(maxdel,del,b0,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `b0`: gain applied to delay-line input and forwarded to output
- `aN`: minus the gain applied to delay-line output before summing with the input and feeding to the delay line

Reference

https://ccrma.stanford.edu/~jos/pasp/Feedback_Comb_Filters.html

---

`rev1`

Special case of `fb_comb` (`rev1(maxdel,N,g)`). The "rev1 section" dates back to the 1960s in computer-music reverberation. See the `jcrev` and `brassrev` in `reverbs.lib` for usage examples.

`fbcombfilter` and `ffbcombfilter`

Other special cases of Feed-Back Comb Filter.

Usage

```
_ : fbcombfilter(maxdel,intdel,g) : _
_ : ffbcombfilter(maxdel,del,g) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `g`: feedback gain

Reference

https://ccrma.stanford.edu/~jos/pasp/Feedback_Comb_Filters.html

---

`allpass_comb`

Schroeder Allpass Comb Filter. Note that

`allpass_comb(maxlen,len,aN) = ff_comb(maxlen,len,aN,1) : fb_comb(maxlen,len-1,1,aN);`

which is a direct-form-1 implementation, requiring two delay lines. The implementation here is direct-form-2 requiring only one delay line.

Usage

`_ : allpass_comb (maxdel,intdel,aN) : _`

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (integer) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `aN`: minus the feedback gain

References

- https://ccrma.stanford.edu/~jos/pasp/Allpass_Two_Combs.html
- https://ccrma.stanford.edu/~jos/pasp/Schroeder_Allpass_Sections.html
- https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

---

`allpass_fcomb`

Schroeder Allpass Comb Filter. Note that

`allpass_comb(maxlen,len,aN) = ff_comb(maxlen,len,aN,1) : fb_comb(maxlen,len-1,1,aN);`

which is a direct-form-1 implementation, requiring two delay lines. The implementation here is direct-form-2 requiring only one delay line.

`allpass_fcomb` is a standard Faust library.

Usage

```
_ : allpass_comb (maxdel,intdel,aN) : _
_ : allpass_fcomb(maxdel,del,aN) : _
```

Where:

- `maxdel`: maximum delay (a power of 2)
- `intdel`: current (float) comb-filter delay between 0 and maxdel
- `del`: current (float) comb-filter delay between 0 and maxdel
- `aN`: minus the feedback gain

References

- https://ccrma.stanford.edu/~jos/pasp/Allpass_Two_Combs.html
- https://ccrma.stanford.edu/~jos/pasp/Schroeder_Allpass_Sections.html
- https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

----

`rev2`

Special case of `allpass_comb` (`rev2(maxlen,len,g)`). The "rev2 section" dates back to the 1960s in computer-music reverberation. See the `jcrev` and `brassrev` in `reverbs.lib` for usage examples.

`allpass_fcomb5` and `allpass_fcomb1a`

Same as `allpass_fcomb` but use `fdelay5` and `fdelay1a` internally (Interpolation helps - look at an fft of faust2octave on

```
`1-1' <: allpass_fcomb(1024,10.5,0.95), allpass_fcomb5(1024,10.5,0.95);`).
```

Direct-Form Digital Filter Sections

`iir`

Nth-order Infinite-Impulse-Response (IIR) digital filter, implemented in terms of the Transfer-Function (TF) coefficients. Such filter structures are termed "direct form".

`iir` is a standard Faust function.

Usage

```
_ : iir(bcoeffs,acoeffs) : _
```

Where:

- `order`: filter order (int) = max(#poles,#zeros)
- `bcoeffs`: (b0,b1,...,b_order) = TF numerator coefficients
- `acoeffs`: (a1,...,a_order) = TF denominator coeffs (a0=1)

Reference

https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

---

`fir`

FIR filter (convolution of FIR filter coefficients with a signal)

Usage

```
_ : fir(bv) : _
```

`fir` is standard Faust function.

Where:

- `bv` = b0,b1,...,bn is a parallel bank of coefficient signals.

Note

`bv` is processed using pattern-matching at compile time, so it must have this normal form (parallel signals).

Example

Smoothing white noise with a five-point moving average:

```
bv = .2,.2,.2,.2,.2;
process = noise : fir(bv);
```

Equivalent (note double parens):

```
process = noise : fir((.2,.2,.2,.2,.2));
```

---

conv and convN

Convolution of input signal with given coefficients.

Usage

```
_ : conv((k1,k2,k3,...,kN)) : _; // Argument = one signal bank
_ : convN(N,(k1,k2,k3,...)) : _; // Useful when N < count((k1,...))
```

---

tf1, tf2 and tf3

tfN = N'th-order direct-form digital filter.

Usage

```
_ : tf1(b0,b1,a1) : _
_ : tf2(b0,b1,b2,a1,a2) : _
_ : tf3(b0,b1,b2,b3,a1,a2,a3) : _
```

Where:

- `a`: the poles
- `b`: the zeros

Reference

https://ccrma.stanford.edu/~jos/fp/Direct_Form_I.html

---

notchw

Simple notch filter based on a biquad (`tf2`). `notchw` is a standard Faust function.

Usage:

```
_ : notchw(width,freq) : _
```

Where:

- `width`: "notch width" in Hz (approximate)
- `freq`: "notch frequency" in Hz

Reference

https://ccrma.stanford.edu/~jos/pasp/Phasing_2nd_Order_Allpass_Filters.html

---

Direct-Form Second-Order Biquad Sections

Direct-Form Second-Order Biquad Sections

Reference

https://ccrma.stanford.edu/~jos/filters/Four_Direct_Forms.html

tf21, tf22, tf22t and tf21t

tfN = N'th-order direct-form digital filter where:

- `tf21` is tf2, direct-form 1
- `tf22` is tf2, direct-form 2
- `tf22t` is tf2, direct-form 2 transposed
- `tf21t` is tf2, direct-form 1 transposed

Usage

```
_ : tf21(b0,b1,b2,a1,a2) : _
_ : tf22(b0,b1,b2,a1,a2) : _
_ : tf22t(b0,b1,b2,a1,a2) : _
_ : tf21t(b0,b1,b2,a1,a2) : _
```

Where:

- `a`: the poles
- `b`: the zeros

Reference

https://ccrma.stanford.edu/~jos/fp/Direct_Form_I.html

Ladder/Lattice Digital Filters

Ladder and lattice digital filters generally have superior numerical properties relative to direct-form digital filters. They can be derived from digital waveguide filters, which gives them a physical interpretation.

av2sv

Compute reflection coefficients sv from transfer-function denominator av.

Usage

`sv = av2sv(av)`

Where:

- `av`: parallel signal bank `a1,...,aN`
- `sv`: parallel signal bank `s1,...,sN`

where `ro = ith` reflection coefficient, and `ai` = coefficient of `z^(-i)` in the filter transfer-function denominator `A(z)`.

Reference

https://ccrma.stanford.edu/~jos/filters/Step_Down_Procedure.html (where reflection coefficients are denoted by k rather than s).

---

bvav2nuv

Compute lattice tap coefficients from transfer-function coefficients.

Usage

`nuv = bvav2nuv(bv,av)`

Where:

- `av`: parallel signal bank `a1,...,aN`
- `bv`: parallel signal bank `b0,b1,...,aN`
- `nuv`: parallel signal bank `nu1,...,nuN`

where `nui` is the i'th tap coefficient, `bi` is the coefficient of `z^(-i)` in the filter numerator, `ai` is the coefficient of `z^(-i)` in the filter denominator

---

iir_lat2

Two-multiply latice IIR filter or arbitrary order.

Usage

```
_ : iir_lat2(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

---

allpassnt

Two-multiply lattice allpass (nested order-1 direct-form-ii allpasses).

Usage

```
_ : allpassnt(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

---

iir_kl

Kelly-Lochbaum ladder IIR filter or arbitrary order.

Usage

```
_ : iir_kl(bv,av) : _
```

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

---

allpassnklt

Kelly-Lochbaum ladder allpass.

Usage:

`_ : allpassklt(n,sv) : _`

Where:

- **n**: the order of the filter
- **sv**: the reflexion coefficients (-1 1)

`iir_lat1`

One-multiply latice IIR filter or arbitrary order.

Usage

`_ : iir_lat1(bv,av) : _`

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

`allpassn1mt`

One-multiply lattice allpass with tap lines.

Usage

`_ : allpassn1mt(n,sv) : _`

Where:

- **n**: the order of the filter
- **sv**: the reflexion coefficients (-1 1)

`iir_nl`

Normalized ladder filter of arbitrary order.

Usage

`_ : iir_nl(bv,av) : _`

Where:

- bv: zeros as a bank of parallel signals
- av: poles as a bank of parallel signals

References

- J. D. Markel and A. H. Gray, Linear Prediction of Speech, New York: Springer Verlag, 1976.
- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

`allpassnnlt`

Normalized ladder allpass filter of arbitrary order.

Usage:

`_ : allpassnnlt(n,sv) : _`

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1,1)

References

- J. D. Markel and A. H. Gray, Linear Prediction of Speech, New York: Springer Verlag, 1976.
- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

Useful Special Cases

`tf2np`

Biquad based on a stable second-order Normalized Ladder Filter (more robust to modulation than `tf2` and protected against instability).

Usage

```
_ : tf2np(b0,b1,b2,a1,a2) : _
```

Where:

- `a`: the poles
- `b`: the zeros

---

wgr

Second-order transformer-normalized digital waveguide resonator.

Usage

```
_ : wgr(f,r) : _
```

Where:

- `f`: resonance frequency (Hz)
- `r`: loss factor for exponential decay (set to 1 to make a numerically stable oscillator)

References

- https://ccrma.stanford.edu/~jos/pasp/Power_Normalized_Waveguide_Filters.html
- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

nlf2

Second order normalized digital waveguide resonator.

Usage

```
_ : nlf2(f,r) : _
```

Where:

- `f`: resonance frequency (Hz)
- `r`: loss factor for exponential decay (set to 1 to make a sinusoidal oscillator)

Reference

https://ccrma.stanford.edu/~jos/pasp/Power_Normalized_Waveguide_
Filters.html

`apnl`

Passive Nonlinear Allpass based on Pierce switching springs idea. Switch between allpass coefficient `a1` and `a2` at signal zero crossings.

Usage

```
_ : apnl(a1,a2) : _
```

Where:

- `a1` and `a2`: allpass coefficients

Reference

- "A Passive Nonlinear Digital Filter Design . . . " by John R. Pierce and Scott A. Van Duyne, JASA, vol. 101, no. 2, pp. 1120-1126, 1997

Ladder/Lattice Allpass Filters

An allpass filter has gain 1 at every frequency, but variable phase. Ladder/lattice allpass filters are specified by reflection coefficients. They are defined here as nested allpass filters, hence the names allpassn*.

References

- https://ccrma.stanford.edu/~jos/pasp/Conventional_Ladder_Filters.
  html
- https://ccrma.stanford.edu/~jos/pasp/Nested_Allpass_Filters.html
- Linear Prediction of Speech, Markel and Gray, Springer Verlag, 1976

`allpassn`

Two-multiply lattice - each section is two multiply-adds.

Usage:

```
_ : allpassn(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

References

- J. O. Smith and R. Michon, "Nonlinear Allpass Ladder Filters in FAUST", in Proceedings of the 14th International Conference on Digital Audio Effects (DAFx-11), Paris, France, September 19-23, 2011.

---

allpassnn

Normalized form - four multiplies and two adds per section, but coefficients can be time varying and nonlinear without "parametric amplification" (modulation of signal energy).

Usage:

```
_ : allpassnn(n,tv) : _
```

Where:

- `n`: the order of the filter
- `tv`: the reflexion coefficients (-PI PI)

---

allpasskl

Kelly-Lochbaum form - four multiplies and two adds per section, but all signals have an immediate physical interpretation as traveling pressure waves, etc.

Usage:

```
_ : allpassnkl(n,sv) : _
```

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

`allpass1m`

One-multiply form - one multiply and three adds per section. Normally the most efficient in special-purpose hardware.

Usage:

`_ : allpassn1m(n,sv) : _`

Where:

- `n`: the order of the filter
- `sv`: the reflexion coefficients (-1 1)

Digital Filter Sections Specified as Analog Filter Sections

`tf2s` and `tf2snp`

Second-order direct-form digital filter, specified by ANALOG transfer-function polynomials B(s)/A(s), and a frequency-scaling parameter. Digitization via the bilinear transform is built in.

Usage

`_ : tf2s(b2,b1,b0,a1,a0,w1) : _`

Where:

```
        b2 s^2 + b1 s + b0
H(s) = --------------------
            s^2 + a1 s + a0
```

and `w1` is the desired digital frequency (in radians/second) corresponding to analog frequency 1 rad/sec (i.e., `s = j`).

Example

A second-order ANALOG Butterworth lowpass filter, normalized to have cutoff frequency at 1 rad/sec, has transfer function

```
            1
H(s) = -----------------
         s^2 + a1 s + 1
```

where `a1 = sqrt(2)`. Therefore, a DIGITAL Butterworth lowpass cutting off at SR/4 is specified as `tf2s(0,0,1,sqrt(2),1,PI*SR/2);`

Method

Bilinear transform scaled for exact mapping of w1.

Reference

https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

----

`tf3slf`

Analogous to tf2s above, but third order, and using the typical low-frequency-matching bilinear-transform constant 2/T ("lf" series) instead of the specific-frequency-matching value used in tf2s and tf1s. Note the lack of a "w1" argument.

Usage

`_ : tf3slf(b3,b2,b1,b0,a3,a2,a1,a0) : _`

`tf1s`

First-order direct-form digital filter, specified by ANALOG transfer-function polynomials B(s)/A(s), and a frequency-scaling parameter.

Usage

`tf1s(b1,b0,a0,w1)`

Where:

```
    b1 s + b0
```

H(s) = ———- s + a0

and `w1` is the desired digital frequency (in radians/second) corresponding to analog frequency 1 rad/sec (i.e., `s = j`).

Example

A first-order ANALOG Butterworth lowpass filter, normalized to have cutoff frequency at 1 rad/sec, has transfer function

$$H(s) = \frac{1}{s + 1}$$

so `b0 = a0 = 1` and `b1 = 0`. Therefore, a DIGITAL first-order Butterworth lowpass with gain -3dB at `SR/4` is specified as

```
tf1s(0,1,1,PI*SR/2); // digital half-band order 1 Butterworth
```

Method

Bilinear transform scaled for exact mapping of w1.

Reference

https://ccrma.stanford.edu/~jos/pasp/Bilinear_Transformation.html

---

`tf2sb`

Bandpass mapping of `tf2s`: In addition to a frequency-scaling parameter `w1` (set to HALF the desired passband width in rad/sec), there is a desired center-frequency parameter wc (also in rad/s). Thus, `tf2sb` implements a fourth-order digital bandpass filter section specified by the coefficients of a second-order analog lowpass prototpe section. Such sections can be combined in series for higher orders. The order of mappings is (1) frequency scaling (to set lowpass cutoff w1), (2) bandpass mapping to wc, then (3) the bilinear transform, with the usual scale parameter `2*SR`. Algebra carried out in maxima and pasted here.

Usage

```
_ : tf2sb(b2,b1,b0,a1,a0,w1,wc) : _
```

`tf1sb`

First-to-second-order lowpass-to-bandpass section mapping, analogous to tf2sb above.

Usage

```
_ : tf1sb(b1,b0,a0,w1,wc) : _
```

Simple Resonator Filters

`resonlp`

Simple resonant lowpass filter based on `tf2s` (virtual analog). `resonlp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

`resonhp`

Simple resonant highpass filters based on `tf2s` (virtual analog). `resonhp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

---

resonbp

Simple resonant bandpass filters based on `tf2s` (virtual analog). `resonbp` is a standard Faust function.

Usage

```
_ : resonlp(fc,Q,gain) : _
_ : resonhp(fc,Q,gain) : _
_ : resonbp(fc,Q,gain) : _
```

Where:

- `fc`: center frequency (Hz)
- `Q`: q
- `gain`: gain (0-1)

Butterworth Lowpass/Highpass Filters

lowpass

Nth-order Butterworth lowpass filter. `lowpass` is a standard Faust function.

Usage

```
_ : lowpass(N,fc) : _
```

Where:

- `N`: filter order (number of poles) [nonnegative constant integer]
- `fc`: desired cut-off frequency (-3dB frequency) in Hz

References

- https://ccrma.stanford.edu/~jos/filters/Butterworth_Lowpass_Design. html
- `butter` function in Octave ("`[z,p,g] = butter(N,1,'s');`")

---

highpass

Nth-order Butterworth highpass filters. `highpass` is a standard Faust function.

Usage

```
_ : highpass(N,fc) : _
```

Where:

- `N`: filter order (number of poles) [nonnegative constant integer]
- `fc`: desired cut-off frequency (-3dB frequency) in Hz

References

- https://ccrma.stanford.edu/~jos/filters/Butterworth_Lowpass_Design.html
- `butter` function in Octave (`"[z,p,g] = butter(N,1,'s');"`)

`lowpass0_highpass1`

Special Filter-Bank Delay-Equalizing Allpass Filters

These special allpass filters are needed by filterbank et al. below. They are equivalent to (`lowpass(N,fc)` +|- `highpass(N,fc))/2`, but with canceling pole-zero pairs removed (which occurs for odd N).

`lowpass_plus|minus_highpass`

Elliptic (Cauer) Lowpass Filters

Elliptic (Cauer) Lowpass Filters

References

- <http://en.wikipedia.org/wiki/Elliptic_filter
- functions `ncauer` and `ellip` in Octave

`lowpass3e`

Third-order Elliptic (Cauer) lowpass filter.

Usage

`_ : lowpass3e(fc) : _`

Where:

- `fc`: -3dB frequency in Hz

Design

For spectral band-slice level display (see `octave_analyzer3e`):

```
[z,p,g] = ncauer(Rp,Rs,3);  % analog zeros, poles, and gain, where
Rp = 60  % dB ripple in stopband
Rs = 0.2 % dB ripple in passband
```

`lowpass6e`

Sixth-order Elliptic/Cauer lowpass filter.

Usage

`_ : lowpass6e(fc) : _`

Where:

- `fc`: -3dB frequency in Hz

Design

For spectral band-slice level display (see octave_analyzer6e):

```
[z,p,g] = ncauer(Rp,Rs,6);  % analog zeros, poles, and gain, where
 Rp = 80  % dB ripple in stopband
 Rs = 0.2 % dB ripple in passband
```

Elliptic Highpass Filters

`highpass3e`

Third-order Elliptic (Cauer) highpass filter. Inversion of `lowpass3e` wrt unit circle in s plane (s <- 1/s)

Usage

```
_ : highpass3e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

---

highpass6e

Sixth-order Elliptic/Cauer highpass filter. Inversion of lowpass3e wrt unit circle in s plane (s <- 1/s)

Usage

```
_ : highpass6e(fc) : _
```

Where:

- `fc`: -3dB frequency in Hz

Butterworth Bandpass/Bandstop Filters

bandpass

Order 2*Nh Butterworth bandpass filter made using the transformation `s <- s + wc^2/s` on `lowpass(Nh)`, where `wc` is the desired bandpass center frequency. The `lowpass(Nh)` cutoff `w1` is half the desired bandpass width. `bandpass` is a standard Faust function.

Usage

```
_ : bandpass(Nh,fl,fu) : _
```

Where:

- `Nh`: HALF the desired bandpass order (which is therefore even)
- `fl`: lower -3dB frequency in Hz
- `fu`: upper -3dB frequency in Hz Thus, the passband width is `fu-fl`, and its center frequency is `(fl+fu)/2`.

Reference

http://cnx.org/content/m16913/latest/

---

bandstop

Order 2*Nh Butterworth bandstop filter made using the transformation `s <- s + wc^2/s` on `highpass(Nh)`, where `wc` is the desired bandpass center frequency. The `highpass(Nh)` cutoff `w1` is half the desired bandpass width. `bandstop` is a standard Faust function.

Usage

`_ : bandstop(Nh,fl,fu) : _`

Where:

- `Nh`: HALF the desired bandstop order (which is therefore even)
- `fl`: lower -3dB frequency in Hz
- `fu`: upper -3dB frequency in Hz Thus, the passband (stopband) width is `fu-fl`, and its center frequency is `(fl+fu)/2`.

Reference

http://cnx.org/content/m16913/latest/

Elliptic Bandpass Filters

bandpass6e

Order 12 elliptic bandpass filter analogous to `bandpass(6)`.

---

bandpass12e

Order 24 elliptic bandpass filter analogous to `bandpass(6)`.

Parametric Equalizers (Shelf, Peaking)

Parametric Equalizers (Shelf, Peaking)

References

- http://en.wikipedia.org/wiki/Equalization
- http://www.musicdsp.org/files/Audio-EQ-Cookbook.txt
- Digital Audio Signal Processing, Udo Zolzer, Wiley, 1999, p. 124
- https://ccrma.stanford.edu/~jos/filters/Low_High_Shelving_Filters.html>
- https://ccrma.stanford.edu/~jos/filters/Peaking_Equalizers.html>
- maxmsp.lib in the Faust distribution
- bandfilter.dsp in the faust2pd distribution

`low_shelf`

First-order "low shelf" filter (gain boost|cut between dc and some frequency) `low_shelf` is a standard Faust function.

Usage

```
_ : lowshelf(N,L0,fx) : _
_ : low_shelf(L0,fx) : _ // default case (order 3)
_ : lowshelf_other_freq(N,L0,fx) : _
```

Where: * `N`: filter order 1, 3, 5, . . . (odd only). (default should be 3) * `L0`: desired level (dB) between dc and fx (boost `L0>0` or cut `L0<0`) * `fx`: -3dB frequency of lowpass band (`L0>0`) or upper band (`L0<0`) (see "SHELF SHAPE" below).

The gain at SR/2 is constrained to be 1. The generalization to arbitrary odd orders is based on the well known fact that odd-order Butterworth band-splits are allpass-complementary (see filterbank documentation below for references).

Shelf Shape

The magnitude frequency response is approximately piecewise-linear on a log-log plot ("BODE PLOT"). The Bode "stick diagram" approximation L(lf) is easy to state in dB versus dB-frequency lf = dB(f):

- L0 > 0:
- L(lf) = L0, f between 0 and fx = 1st corner frequency;
- L(lf) = L0 - N * (lf - lfx), f between fx and f2 = 2nd corner frequency;
- L(lf) = 0, lf > lf2.
- lf2 = lfx + L0/N = dB-frequency at which level gets back to 0 dB.
- L0 < 0:
- L(lf) = L0, f between 0 and f1 = 1st corner frequency;

- L(lf) = - N * (lfx - lf), f between f1 and lfx = 2nd corner frequency;
- L(lf) = 0, lf > lfx.
- lf1 = lfx + L0/N = dB-frequency at which level goes up from L0.

See `lowshelf_other_freq`.

---

high_shelf

First-order "high shelf" filter (gain boost|cut above some frequency). `high_shelf` is a standard Faust function.

Usage

```
_ : highshelf(N,Lpi,fx) : _
_ : high_shelf(L0,fx) : _ // default case (order 3)
_ : highshelf_other_freq(N,Lpi,fx) : _
```

Where:

- `N`: filter order 1, 3, 5, . . . (odd only).
- `Lpi`: desired level (dB) between fx and SR/2 (boost Lpi>0 or cut Lpi<0)
- `fx`: -3dB frequency of highpass band (L0>0) or lower band (L0<0) (Use highshelf_other_freq() below to find the other one.)

The gain at dc is constrained to be 1. See `lowshelf` documentation above for more details on shelf shape.

---

peak_eq

Second order "peaking equalizer" section (gain boost or cut near some frequency) Also called a "parametric equalizer" section. `peak_eq` is a standard Faust function.

Usage

```
_ : peak_eq(Lfx,fx,B) : _;
```

Where:

- `Lfx`: level (dB) at fx (boost Lfx>0 or cut Lfx<0)
- `fx`: peak frequency (Hz)
- `B`: bandwidth (B) of peak in Hz

`peak_eq_cq`

Constant-Q second order peaking equalizer section.

Usage

`_ : peak_eq_cq(Lfx,fx,Q) : _;`

Where:

- `Lfx`: level (dB) at fx
- `fx`: boost or cut frequency (Hz)
- `Q`: "Quality factor" = fx/B where B = bandwidth of peak in Hz

---

`peak_eq_rm`

Regalia-Mitra second order peaking equalizer section

Usage

`_ : peak_eq_rm(Lfx,fx,tanPiBT) : _;`

Where:

- `Lfx`: level (dB) at fx
- `fx`: boost or cut frequency (Hz)
- `tanPiBT: tan(PI*B/SR)`, where B = -3dB bandwidth (Hz) when
  10^(Lfx/20) = 0 ~ PI*B/SR for narrow bandwidths B

Reference

P.A. Regalia, S.K. Mitra, and P.P. Vaidyanathan, "The Digital All-Pass Filter: A Versatile Signal Processing Building Block" Proceedings of the IEEE, 76(1):19-37, Jan. 1988. (See pp. 29-30.)

`spectral_tilt`

Spectral tilt filter, providing an arbitrary spectral rolloff factor alpha in (-1,1), where -1 corresponds to one pole (-6 dB per octave), and +1 corresponds to one zero (+6 dB per octave). In other words, alpha is the slope of the ln magnitude versus ln frequency. For a "pinking filter" (e.g., to generate 1/f noise from white noise), set alpha to -1/2.

Usage

```
_ : spectral_tilt(N,f0,bw,alpha) : _
```

Where:

- `N`: desired integer filter order (fixed at compile time)
- `f0`: lower frequency limit for desired roll-off band
- `bw`: bandwidth of desired roll-off band
- `alpha`: slope of roll-off desired in nepers per neper (ln mag / ln radian freq)

Examples

See `spectral_tilt_demo`.

Reference

Link to appear here when write up is done

---

levelfilter

Dynamic level lowpass filter. `levelfilter` is a standard Faust function.

Usage

```
_ : levelfilter(L,freq) : _
```

Where:

- `L`: desired level (in dB) at Nyquist limit (SR/2), e.g., -60
- `freq`: corner frequency (-3dB point) usually set to fundamental freq
- `N`: Number of filters in series where L = L/N

Reference

https://ccrma.stanford.edu/realsimple/faust_strings/Dynamic_Level_Lowpass_Filter.html

---

levelfilterN

Dynamic level lowpass filter.

Usage

```
_ : levelfilterN(N,freq,L) : _
```

Where:

- `L`: desired level (in dB) at Nyquist limit (SR/2), e.g., -60
- `freq`: corner frequency (-3dB point) usually set to fundamental freq
- `N`: Number of filters in series where L = L/N

Reference

https://ccrma.stanford.edu/realsimple/faust_strings/Dynamic_Level_Lowpass_Filter.html

---

Mth-Octave Filter-Banks

Mth-octave filter-banks split the input signal into a bank of parallel signals, one for each spectral band. They are related to the Mth-Octave Spectrum-Analyzers in `analysis.lib`. The documentation of this library contains more details about the implementation. The parameters are:

- `M`: number of band-slices per octave (>1)
- `N`: total number of bands (>2)
- `ftop`: upper bandlimit of the Mth-octave bands ($<SR/2$)

In addition to the Mth-octave output signals, there is a highpass signal containing frequencies from ftop to SR/2, and a "dc band" lowpass signal containing frequencies from 0 (dc) up to the start of the Mth-octave bands. Thus, the N output signals are

```
highpass(ftop), MthOctaveBands(M,N-2,ftop), dcBand(ftop*2^(-M*(N-1)))
```

A Filter-Bank is defined here as a signal bandsplitter having the property that summing its output signals gives an allpass-filtered version of the filter-bank input signal. A more conventional term for this is an "allpass-complementary filter bank". If the allpass filter is a pure delay (and possible scaling), the filter bank is said to be a "perfect-reconstruction filter bank" (see Vaidyanathan-1993 cited below for details). A "graphic equalizer", in which band signals are scaled by gains and summed, should be based on a filter bank.

The filter-banks below are implemented as Butterworth or Elliptic spectrum-analyzers followed by delay equalizers that make them allpass-complementary.

Increasing Channel Isolation

Go to higher filter orders - see Regalia et al. or Vaidyanathan (cited below) regarding the construction of more aggressive recursive filter-banks using elliptic or Chebyshev prototype filters.

References

- "Tree-structured complementary filter banks using all-pass sections", Regalia et al., IEEE Trans. Circuits & Systems, CAS-34:1470-1484, Dec. 1987
- "Multirate Systems and Filter Banks", P. Vaidyanathan, Prentice-Hall, 1993
- Elementary filter theory: https://ccrma.stanford.edu/~jos/filters/

`mth_octave_filterbank[n]`

Allpass-complementary filter banks based on Butterworth band-splitting. For Butterworth band-splits, the needed delay equalizer is easily found.

Usage

```
_ : mth_octave_filterbank(O,M,ftop,N) : par(i,N,_); // Oth-order
_ : mth_octave_filterbank_alt(O,M,ftop,N) : par(i,N,_); // dc-inverted version
```

Also for convenience:

```
_ : mth_octave_filterbank3(M,ftop,N) : par(i,N,_); // 3d-order Butterworth
_ : mth_octave_filterbank5(M,ftop,N) : par(i,N,_); // 5th-roder Butterworth
mth_octave_filterbank_default = mth_octave_analyzer6e;
```

Where:

- `O`: order of filter used to split each frequency band into two
- `M`: number of band-slices per octave
- `ftop`: highest band-split crossover frequency (e.g., 20 kHz)
- `N`: total number of bands (including dc and Nyquist)

Arbritary-Crossover Filter-Banks and Spectrum Analyzers

These are similar to the Mth-octave analyzers above, except that the band-split frequencies are passed explicitly as arguments.

`filterbank`

Filter bank. `filterbank` is a standard Faust function.

Usage

```
_ : filterbank (O,freqs) : par(i,N,_); // Butterworth band-splits
```

Where:

- `O`: band-split filter order (ODD integer required for filterbank[i])
- `freqs`: (fc1,fc2,...,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : filterbank(3,(fc1,fc2)) : _,_,_
```

---

filterbanki

Inverted-dc filter bank.

Usage

```
_ : filterbanki(O,freqs) : par(i,N,_); // Inverted-dc version
```

Where:

- `O`: band-split filter order (ODD integer required for `filterbank[i]`)
- `freqs`: (fc1,fc2,...,fcNs) [in numerically ascending order], where Ns=N-1 is the number of octave band-splits (total number of bands N=Ns+1).

If frequencies are listed explicitly as arguments, enclose them in parens:

```
_ : filterbanki(3,(fc1,fc2)) : _,_,_
```

---

hoa.lib

Faust library for high order ambisonic. Its official prefix is `ho`.

encoder

Ambisonic encoder. Encodes a signal in the circular harmonics domain depending on an order of decomposition and an angle.

Usage

```
encoder(n, x, a) : _
```

Where:

- **n**: the order
- **x**: the signal
- **a**: the angle

---

decoder

Decodes an ambisonics sound field for a circular array of loudspeakers.

Usage

```
_ : decoder(n, p) : _
```

Where:

- **n**: the order
- **p**: the number of speakers

Note

Number of loudspeakers must be greater or equal to 2n+1. It's preferable to use 2n+2 loudspeakers.

---

decoderStereo

Decodes an ambisonic sound field for stereophonic configuration. An "home made" ambisonic decoder for stereophonic restitution (30° - 330°) : Sound field lose energy around 180°. You should use `inPhase` optimization with ponctual sources. #### Usage

```
_ : decoderStereo(n) : _
```

Where:

- **n**: the order

Optimization Functions

Functions to weight the circular harmonics signals depending to the ambisonics optimization. It can be `basic` for no optimization, `maxRe` or `inPhase`.

optimBasic

The basic optimization has no effect and should be used for a perfect circle of loudspeakers with one listener at the perfect center loudspeakers array.

Usage

`_ : optimBasic(n) : _`

Where:

- **n**: the order

---

optimMaxRe

The maxRe optimization optimize energy vector. It should be used for an auditory confined in the center of the loudspeakers array.

Usage

`_ : optimMaxRe(n) : _`

Where:

- **n**: the order

---

optimInPhase

The inPhase Optimization optimize energy vector and put all loudspeakers signals n phase. It should be used for an auditory.

Usage

" optimInPhase(n) : _ "

here:

n: the order

`wider`

Can be used to wide the diffusion of a localized sound. The order depending signals are weighted and appear in a logarithmic way to have linear changes.

Usage

`_ : wider(n,w) : _`

Where:

- **`n`**: the order
- **`w`**: the width value between 0 - 1

`map`

It simulate the distance of the source by applying a gain on the signal and a wider processing on the soundfield.

Usage

`map(n, x, r, a)`

Where:

- **`n`**: the order
- **`x`**: the signal
- **`r`**: the radius
- **`a`**: the angle in radian

`rotate`

Rotates the sound field.

Usage

`_ : rotate(n, a) : _`

Where:

- **`n`**: the order

- `a`: the angle in radian

----

maths.lib

Mathematic library for Faust. Some functions are implemenented as Faust foreign functions of `math.h` functions that are not part of Faust's primitives. Defines also various constants and several utilities.

The official prefix of this library is `ma`.

Functions Reference

SR

Current sampling rate (between 1Hz and 192000Hz). Constant during program execution.

Usage

```
SR : _
```

BS

Current block-size. Can change during the execution.

Usage

```
BS : _
```

PI

Constant PI in double precisio.n

Usage

```
PI : _
```

FTZ

Flush to zero: force samples under the "maximum subnormal number" to be zero. Usually not needed in C++ because the architecture file take care of this, but can be useful in javascript for instance.

Usage

`_ : ftz : _`

See : http://docs.oracle.com/cd/E19957-01/806-3568/ncg_math.html

---

neg

Invert the sign (-x) of a signal.

Usage

`_ : neg : _`

---

sub(x,y)

Subtract `x` and `y`.

---

inv

Compute the inverse (1/x) of the input signal.

Usage

`_ : inv : _`

---

cbrt

Computes the cube root of of the input signal.

Usage

```
_ : cbrt : _
```

---

hypot

Computes the euclidian distance of the two input signals sqrt($xx+yy$) without undue overflow or underflow.

Usage

```
_,_ : hypot : _
```

---

ldexp

Takes two input signals: x and n, and multiplies x by 2 to the power n.

Usage

```
_,_ : ldexp : _
```

---

scalb

Takes two input signals: x and n, and multiplies x by 2 to the power n.

Usage

```
_,_ : scalb : _
```

---

log1p

Computes $\log(1 + x)$ without undue loss of accuracy when x is nearly zero.

Usage

```
_ : log1p : _
```

---

logb

Return exponent of the input signal as a floating-point number.

Usage

`_ : logb : _`

---

ilogb

Return exponent of the input signal as an integer number.

Usage

`_ : ilogb : _`

---

log2

Returns the base 2 logarithm of x.

Usage

`_ : log2 : _`

---

expm1

Return exponent of the input signal minus 1 with better precision.

Usage

`_ : expm1 : _`

---

acosh

Computes the principle value of the inverse hyperbolic cosine of the input signal.

```
_ : acosh : _
```

---

asinh

Computes the inverse hyperbolic sine of the input signal.

Usage

```
_ : asinh : _
```

---

atanh

Computes the inverse hyperbolic tangent of the input signal.

Usage

```
_ : atanh : _
```

---

sinh

Computes the hyperbolic sine of the input signal.

Usage

```
_ : sinh : _
```

---

cosh

Computes the hyperbolic cosine of the input signal.

Usage

```
_ : cosh : _
```

---

tanh

Computes the hyperbolic tangent of the input signal.

Usage

```
_ : tanh : _
```

---

erf

Computes the error function of the input signal.

Usage

```
_ : erf : _
```

---

erfc

Computes the complementary error function of the input signal.

Usage

```
_ : erfc : _
```

---

gamma

Computes the gamma function of the input signal.

Usage

```
_ : gamma : _
```

---

lgamma

Calculates the natural logorithm of the absolute value of the gamma function of the input signal.

Usage

`_ : lgamma : _`

`J0`

Computes the Bessel function of the first kind of order 0 of the input signal.

Usage

`_ : J0 : _`

`J1`

Computes the Bessel function of the first kind of order 1 of the input signal.

Usage

`_ : J1 : _`

`Jn`

Computes the Bessel function of the first kind of order n (first input signal) of the second input signal.

Usage

`_,_ : Jn : _`

`Y0`

Computes the linearly independent Bessel function of the second kind of order 0 of the input signal.

Usage

```
_ : Y0 : _
```

Y1

Computes the linearly independent Bessel function of the second kind of order 1 of the input signal.

Usage

```
_ : Y0 : _
```

Yn

Computes the linearly independent Bessel function of the second kind of order n (first input signal) of the second input signal.

Usage

```
_,_ : Yn : _
```

---

fabs, fmax, fmin

Just for compatibility...

```
fabs = abs
fmax = max
fmin = min
```

---

np2

Gives the next power of 2 of x.

Usage

```
np2(n) : _
```

Where:

- **n**: an integer

---

frac

Gives the fractional part of n.

Usage

```
frac(n) : _
```

Where:

- **n**: a decimal number

---

isnan

Return non-zero if and only if x is a NaN.

Usage

```
isnan(x)
_ : isnan : _
```

Where:

- **x**: signal to analyse

---

chebychev

Chebychev transformation of order n.

Usage

```
_ : chebychev(n) : _
```

Where:

- **n**: the order of the polynomial

Semantics

```
T[0](x) = 1,
T[1](x) = x,
T[n](x) = 2x*T[n-1](x) - T[n-2](x)
```

Reference

http://en.wikipedia.org/wiki/Chebyshev_polynomial

---

chebychevpoly

Linear combination of the first Chebyshev polynomials.

Usage

```
_ : chebychevpoly((c0,c1,...,cn)) : _
```

Where:

- **cn**: the different Chebychevs polynomials such that: chebychevpoly((c0,c1,…,cn)) = Sum of chebychev(i)*ci

Reference

http://www.csounds.com/manual/html/chebyshevpoly.html

---

diffn

Negated first-roder difference.

Usage

```
_ : diffn : _
```

---

misceffects.lib

This library contains a collection of audio effects. Its official prefix is `ef`.

Dynamic

cubicnl

Cubic nonlinearity distortion. `cubicnl` is a standard Faust library.

Usage:

```
_ : cubicnl(drive,offset) : _
_ : cubicnl_nodc(drive,offset) : _
```

Where:

- `drive`: distortion amount, between 0 and 1
- `offset`: constant added before nonlinearity to give even harmonics. Note: offset can introduce a nonzero mean - feed cubicnl output to dcblocker to remove this.

References:

- https://ccrma.stanford.edu/~jos/pasp/Cubic_Soft_Clipper.html
- https://ccrma.stanford.edu/~jos/pasp/Nonlinear_Distortion.html

---

gate_mono

Mono signal gate. `gate_mono` is a standard Faust function.

Usage

```
_ : gate_mono(thresh,att,hold,rel) : _
```

Where:

- `thresh`: dB level threshold above which gate opens (e.g., -60 dB)
- `att`: attack time = time constant (sec) for gate to open (e.g., 0.0001 s = 0.1 ms)
- `hold`: hold time = time (sec) gate stays open after signal level < thresh (e.g., 0.1 s)
- `rel`: release time = time constant (sec) for gate to close (e.g., 0.020 s = 20 ms)

References

- http://en.wikipedia.org/wiki/Noise_gate
- http://www.soundonsound.com/sos/apr01/articles/advanced.asp
- http://en.wikipedia.org/wiki/Gating_(sound_engineering)

———————————————————

`gate_stereo`

Stereo signal gates. `gate_stereo` is a standard Faust function.

Usage

```
_,_ : gate_stereo(thresh,att,hold,rel) : _,_
```

Where:

- `thresh`: dB level threshold above which gate opens (e.g., -60 dB)
- `att`: attack time = time constant (sec) for gate to open (e.g., 0.0001 s = 0.1 ms)
- `hold`: hold time = time (sec) gate stays open after signal level < thresh (e.g., 0.1 s)
- `rel`: release time = time constant (sec) for gate to close (e.g., 0.020 s = 20 ms)

References

- http://en.wikipedia.org/wiki/Noise_gate
- http://www.soundonsound.com/sos/apr01/articles/advanced.asp
- http://en.wikipedia.org/wiki/Gating_(sound_engineering)

———————————————————

Filtering

`speakerbp`

Dirt-simple speaker simulator (overall bandpass eq with observed roll-offs above and below the passband).

Low-frequency speaker model = +12 dB/octave slope breaking to flat near f1. Implemented using two dc blockers in series.

High-frequency model = -24 dB/octave slope implemented using a fourth-order Butterworth lowpass.

Example based on measured Celestion G12 (12" speaker):

`speakerbp` is a standard Faust function

Usage

```
speakerbp(f1,f2)
_ : speakerbp(130,5000) : _
```

––––––––––––––––––––––––––––––––

`piano_dispersion_filter`

Piano dispersion allpass filter in closed form.

Usage

```
piano_dispersion_filter(M,B,f0)
_ : piano_dispersion_filter(1,B,f0) : +(totalDelay),_ : fdelay(maxDelay) : _
```

Where:

- `M`: number of first-order allpass sections (compile-time only) Keep below 20. 8 is typical for medium-sized piano strings.
- `B`: string inharmonicity coefficient (0.0001 is typical)
- `f0`: fundamental frequency in Hz

Outputs

- MINUS the estimated delay at `f0` of allpass chain in samples, provided in negative form to facilitate subtraction from delay-line length.
- Output signal from allpass chain

`stereo_width`

Stereo Width effect using the Blumlein Shuffler technique. `stereo_width` is a standard Faust function.

Usage

```
_,_ : stereo_width(w) : _,_
```

Where:

- `w`: stereo width between 0 and 1

At `w=0`, the output signal is mono ((left+right)/2 in both channels). At `w=1`, there is no effect (original stereo image). Thus, w between 0 and 1 varies stereo width from 0 to "original".

Reference

- "Applications of Blumlein Shuffling to Stereo Microphone Techniques" Michael A. Gerzon, JAES vol. 42, no. 6, June 1994

Time Based

`echo`

A simple echo effect.

`echo` is a standard Faust function

Usage

```
_ : echo(maxDuration,duration,feedback) : _
```

Where:

- `maxDuration`: the max echo duration in seconds
- `duration`: the echo duration in seconds
- `feedback`: the feedback coefficient

Pitch Shifting

`transpose`

A simple pitch shifter based on 2 delay lines. `transpose` is a standard Faust function.

Usage

```
_ : transpose(w, x, s) : _
```

Where:

- `w`: the window length (samples)
- `x`: crossfade duration duration (samples)
- `s`: shift (semitones)

Meshes

`mesh_square`

Square Rectangular Digital Waveguide Mesh.

Usage

`bus(4*N) : mesh_square(N) : bus(4*N);`

Where:

- `N`: number of nodes along each edge - a power of two (1,2,4,8,...)

Reference

https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Mesh.html

Signal Order In and Out

The mesh is constructed recursively using 2x2 embeddings. Thus, the top level of `mesh_square(M)` is a block 2x2 mesh, where each block is a `mesh(M/2)`. Let these blocks be numbered 1,2,3,4 in the geometry NW,NE,SW,SE, i.e., as 1 2 3 4 Each block has four vector inputs and four vector outputs, where the length of each vector is `M/2`. Label the input vectors as Ni,Ei,Wi,Si, i.e., as the inputs from the North, East South, and West, and similarly for the outputs. Then, for example, the upper left input block of M/2 signals is labeled 1Ni. Most of the connections are internal, such as 1Eo -> 2Wi. The `8*(M/2)` input signals are grouped in the order 1Ni 2Ni 3Si 4Si 1Wi 3Wi 2Ei 4Ei and the output signals are 1No 1Wo 2No 2Eo 3So 3Wo 4So 4Eo or

In: 1No 1Wo 2No 2Eo 3So 3Wo 4So 4Eo

Out: 1Ni 2Ni 3Si 4Si 1Wi 3Wi 2Ei 4Ei

Thus, the inputs are grouped by direction N,S,W,E, while the outputs are grouped by block number 1,2,3,4, which can also be interpreted as directions NW, NE, SW, SE. A simple program illustrating these orderings is `process = mesh_square(2);`.

Example

Reflectively terminated mesh impulsed at one corner:

```
mesh_square_test(N,x) = mesh_square(N)~(busi(4*N,x)) // input to corner
with { busi(N,x) = bus(N) : par(i,N,*(-1)) : par(i,N-1,_), +(x); };
process = 1-1' : mesh_square_test(4); // all modes excited forever
```

In this simple example, the mesh edges are connected as follows:

1No -> 1Ni, 1Wo -> 2Ni, 2No -> 3Si, 2Eo -> 4Si,

3So -> 1Wi, 3Wo -> 3Wi, 4So -> 2Ei, 4Eo -> 4Ei

A routing matrix can be used to obtain other connection geometries.

---

noises.lib

Faust Noise Generator Library. Its official prefix is `no`.

Functions Reference

`noise`

White noise generator (outputs random number between -1 and 1). `Noise` is a standard Faust function.

Usage

```
noise : _
```

`multirandom`

Generates multiple decorrelated random numbers in parallel.

Usage

```
multirandom(n) : _
```

Where:

- `n`: the number of decorrelated random numbers in parallel

`multinoise`

Generates multiple decorrelated noises in parallel.

Usage

```
multinoise(n) : _
```

Where:

- `n`: the number of decorrelated random numbers in parallel

`noises`

TODO.

`pink_noise`

Pink noise (1/f noise) generator (third-order approximation) `pink_noise` is a standard Faust function.

Usage

```
pink_noise : _;
```

Reference:

https://ccrma.stanford.edu/~jos/sasp/Example_Synthesis_1_F_Noise.html

---

`pink_noise_vm`

Multi pink noise generator.

Usage

```
pink_noise_vm(N) : _;
```

Where:

- `N`: number of latched white-noise processes to sum, not to exceed sizeof(int) in C++ (typically 32).

References

- http://www.dsprelated.com/showarticle/908.php
- http://www.firstpr.com.au/dsp/pink-noise/#Voss-McCartney

`lfnoise, lfnoise0 and lfnoiseN`

Low-frequency noise generators (Butterworth-filtered downsampled white noise)

Usage

```
lfnoise0(rate) : _;    // new random number every int(SR/rate) samples or so
lfnoiseN(N,rate) : _; // same as "lfnoise0(rate) : lowpass(N,rate)" [see filters.lib]
lfnoise(rate) : _;     // same as "lfnoise0(rate) : seq(i,5,lowpass(N,rate))" (no overshoot)
```

Example

(view waveforms in faust2octave):

```
rate = SR/100.0; // new random value every 100 samples (SR from music.lib)
process = lfnoise0(rate),   // sampled/held noise (piecewise constant)
          lfnoiseN(3,rate), // lfnoise0 smoothed by 3rd order Butterworth LPF
          lfnoise(rate);    // lfnoise0 smoothed with no overshoot
```

`velvet_noise_vm`

velvet noise generator.

Usage

```
velvet_noise(amp,f0) : _;
```

Where:

- `amp`: amplitude of noise impulses (positive and negative)
- `f0`: average frequency of noise impulses per second

Reference

- Matti Karjalainen and Hanna Jarvelainen, "Reverberation Modeling Using Velvet Noise", in Proc. 30th Int. Conf. Intelligent Audio Environments (AES07), March 2007.

oscillators.lib

This library contains a collection of sound generators. Its official prefix is `os`.

Wave-Table-Based Oscillators

sinwaveform

Sine waveform ready to use with a `rdtable`.

Usage

```
sinwaveform(tablesize) : _
```

Where:

- `tablesize`: the table size

---

coswaveform

Cosine waveform ready to use with a `rdtable`.

Usage

```
coswaveform(tablesize) : _
```

Where:

- `tablesize`: the table size

---

phasor

A simple phasor to be used with a `rdtable`. `phasor` is a standard Faust function.

Usage

```
phasor(tablesize,freq) : _
```

Where:

- `tablesize`: the table size
- `freq`: the frequency of the wave (Hz)

---

oscsin

Sine wave oscillator. `oscsin` is a standard Faust function.

Usage

```
oscsin(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

---

osccos

Cosine wave oscillator.

Usage

```
osccos(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

---

oscp

A sine wave generator with controllable phase.

Usage

```
oscp(freq,p) : _
```

Where:

- `freq`: the frequency of the wave (Hz)
- `p`: the phase in radian

---

osci

Interpolated phase sine wave oscillator.

Usage

```
osci(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

LFOs

Low-frequency oscillators have prefix `lf_` (no aliasing suppression, signal-means not necessarily zero).

lf_imptrain

Unit-amplitude low-frequency impulse train. `lf_imptrain` is a standard Faust function.

Usage

```
lf_imptrain(freq) : _
```

Where:

- `freq`: frequency in Hz

---

lf_pulsetrainpos

Unit-amplitude nonnegative LF pulse train, duty cycle between 0 and 1

Usage

```
lf_pulsetrainpos(freq,duty) : _
```

Where:

- `freq`: frequency in Hz
- `duty`: duty cycle between 0 and 1

---

lf_squarewavepos

Positive LF square wave in [0,1]

Usage

```
lf_squarewavepos(freq) : _
```

Where:

- `freq`: frequency in Hz

---

lf_squarewave

Zero-mean unit-amplitude LF square wave. `lf_squarewave` is a standard Faust function.

Usage

```
lf_squarewave(freq) : _
```

Where:

- `freq`: frequency in Hz

---

lf_trianglepos

Positive unit-amplitude LF positive triangle wave

Usage

```
lf_trianglepos(freq) : _
```

Where:

- `freq`: frequency in Hz

Low Frequency Sawtooths

Sawtooth waveform oscillators for virtual analog synthesis et al. The 'simple' versions (`lf_rawsaw`, `lf_sawpos` and `saw1`), are mere samplings of the ideal continuous-time ("analog") waveforms. While simple, the aliasing due to sampling is quite audible. The differentiated polynomial waveform family (`saw2`, `sawN`, and derived functions) do some extra processing to suppress aliasing (not audible for very low fundamental frequencies). According to Lehtonen et al. (JASA 2012), the aliasing of `saw2` should be inaudible at fundamental frequencies below 2 kHz or so, for a 44.1 kHz sampling rate and 60 dB SPL presentation level; fundamentals 415 and below required no aliasing suppression (i.e., `saw1` is ok).

lf_rawsaw

Simple sawtooth waveform oscillator between 0 and period in samples.

Usage

```
lf_rawsaw(periodsamps)
```

Where:

- `periodsamps`: number of periods per samples

---

lf_sawpos_phase

Simple sawtooth waveform oscillator between 0 and 1 with phase control.

Usage

```
lf_sawpos_phase(freq,phase)
```

Where:

- `freq`: frequency
- `phase`: phase

Bandlimited Sawtooth

Bandlimited Sawtooth

`sawN(N,freq)`, `sawNp`, `saw2dpw(freq)`, `saw2(freq)`, `saw3(freq)`, `saw4(freq)`, `saw5(freq)`, `saw6(freq)`, `sawtooth(freq)`, `saw2f2(freq)` `saw2f4(freq)`

Method 1 (`saw2`)

Polynomial Transition Regions (PTR) (for aliasing suppression)

Reference

- Kleimola, J.; Valimaki, V., "Reducing Aliasing from Synthetic Audio Signals Using Polynomial Transition Regions," in Signal Processing Letters, IEEE , vol.19, no.2, pp.67-70, Feb. 2012
- https://aaltodoc.aalto.fi/bitstream/handle/123456789/7747/publication6.pdf?sequence=9
- http://research.spa.aalto.fi/publications/papers/spl-ptr/

Method 2 (`sawN`)

Differentiated Polynomial Waves (DPW) (for aliasing suppression)

Reference

"Alias-Suppressed Oscillators based on Differentiated Polynomial Waveforms", Vesa Valimaki, Juhan Nam, Julius Smith, and Jonathan Abel, IEEE Tr. Acoustics, Speech, and Language Processing (IEEE-ASLP), Vol. 18, no. 5, May 2010.

Other Cases

Correction-filtered versions of `saw2`: `saw2f2`, `saw2f4` The correction filter compensates "droop" near half the sampling rate. See reference for sawN.

Usage

```
sawN(N,freq) : _
sawNp(N,freq,phase) : _
saw2dpw(freq) : _
saw2(freq) : _
saw3(freq) : _ // based on sawN
saw4(freq) : _ // based on sawN
saw5(freq) : _ // based on sawN
saw6(freq) : _ // based on sawN
sawtooth(freq) : _ // = saw2
saw2f2(freq) : _
saw2f4(freq) : _
```

Where:

- `N`: polynomial order
- `freq`: frequency in Hz
- `phase`: phase

sawN

TODO: implemented but not documented. For now, you can look at the source code.

---

sawNp

TODO: implemented but not documented. For now, you can look at the source code.

---

saw2dpw

TODO: implemented but not documented. For now, you can look at the source code.

---

saw3

TODO: implemented but not documented. For now, you can look at the source code.

`sawtooth`

Alias-free sawtooth wave. 2nd order interpolation (based on `saw2`). `sawtooth` is a standard Faust function.

Usage

`sawtooth(freq) : _`

Where:

- `freq`: frequency

`saw2f2`

TODO: implemented but not documented. For now, you can look at the source code.

`saw2f4`

TODO: implemented but not documented. For now, you can look at the source code.

Bandlimited Pulse, Square, and Impulse Trains

Bandlimited Pulse, Square, and Impulse Trains

`pulsetrainN`, `pulsetrain`, `squareN`, `square`, `imptrain`, `imptrainN`, `triangle`, `triangleN`

All are zero-mean and meant to oscillate in the audio frequency range. Use simpler sample-rounded lf_* versions above for LFOs.

Usage

```
pulsetrainN(N,freq,duty) : _
pulsetrain(freq, duty) : _ // = pulsetrainN(2)
squareN(N, freq) : _
square : _ // = squareN(2)
imptrainN(N,freq) : _
imptrain : _ // = imptrainN(2)
triangleN(N,freq) : _
triangle : _ // = triangleN(2)
```

Where:

- `N`: polynomial order
- `freq`: frequency in Hz

pulsetrainN

TODO: implemented but not documented. For now, you can look at the source code.

---

pulsetrain

Bandlimited pulse train oscillator. Based on `pulsetrainN(2)`. `pulsetrain` is a standard Faust function.

Usage

```
pulsetrain(freq, duty) : _
```

Where:

- `freq`: frequency
- `duty`: duty cycle between 0 and 1

---

squareN

TODO: implemented but not documented. For now, you can look at the source code.

---

square

Bandlimited square wave oscillator. Based on `squareN(2)`. `square` is a standard Faust function.

Usage

`square(freq) : _`

Where:

- `freq`: frequency

---

impulse

One-time impulse generated when the Faust process is started. `impulse` is a standard Faust function.

Usage

`impulse : _`

---

imptrainN

TODO: implemented but not documented. For now, you can look at the source code.

---

imptrain

Bandlimited impulse train generator. Based on `imptrainN(2)`. `imptrain` is a standard Faust function.

Usage

`imptrain(freq) : _`

Where:

- `freq`: frequency

---

triangleN

TODO: implemented but not documented. For now, you can look at the source code.

---

triangle

Bandlimited triangle wave oscillator. Based on `triangleN(2)`. `triangle` is a standard Faust function.

Usage

`triangle(freq) : _`

Where:

- `freq`: frequency

Filter-Based Oscillators

Filter-Based Oscillators

Usage

`osc[b|r|rs|rc|s|w](f), where f = frequency in Hz.`

References

- http://lac.linuxaudio.org/2012/download/lac12-slides-jos.pdf
- https://ccrma.stanford.edu/~jos/pdf/lac12-paper-jos.pdf

oscb

Sinusoidal oscillator based on the biquad.

Usage

`oscb(freq) : _`

Where:

- `freq`: frequency

---

oscrq

Sinusoidal (sine and cosine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

`oscrq(freq) : _,_`

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

oscrs

Sinusoidal (sine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

`oscrs(freq) : _`

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_Junctions.html

---

oscrc

Sinusoidal (cosine) oscillator based on 2D vector rotation, = undamped "coupled-form" resonator = lossless 2nd-order normalized ladder filter.

Usage

```
oscrc(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Normalized_Scattering_
  Junctions.html

---

osc

Default sine wave oscillator (same as oscrs). `osc` is a standard Faust function.

Usage

```
osc(freq) : _
```

Where:

- `freq`: the frequency of the wave (Hz)

---

oscs

Sinusoidal oscillator based on the state variable filter = undamped "modified-coupled-form" resonator = "magic circle" algorithm used in graphics

---

Waveguide-Resonator-Based Osccilators

Sinusoidal oscillator based on the waveguide resonator `wgr`.

oscw

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine oscillator.

Usage

```
oscwc(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator. html

---

oscws

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude sine oscillator

Usage

```
oscws(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator. html

---

oscwq

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine and sine (quadrature) oscillator.

Usage

```
oscwq(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

oscw

Sinusoidal oscillator based on the waveguide resonator `wgr`. Unit-amplitude cosine oscillator (default)

Usage

```
oscw(freq) : _
```

Where:

- `freq`: frequency

Reference

- https://ccrma.stanford.edu/~jos/pasp/Digital_Waveguide_Oscillator.html

---

lf_sawpos

Simple sawtooth waveform oscillator between 0 and 1.

Usage

```
lf_sawpos(freq)
```

Where:

- `freq`: frequency

Author: Bart Brouns (MarkDown by RM)

---

lf_saw

Simple sawtooth waveform. `lf_saw` is a standard Faust function.

Usage

```
lf_saw(freq)
```

Where:

- `freq`: frequency

---

lf_triangle

Positive unit-amplitude LF triangle wave `lf_triangle` is a standard Faust function.

Usage

```
lf_triangle(freq) : _
```

Where:

- `freq`: frequency in Hz

---

phaflangers.lib

A library of phasor and flanger effects. Its official prefix is `pf`.

Functions Reference

flanger_mono

Mono flanging effect.

Usage:

```
_ : flanger_mono(dmax,curdel,depth,fb,invert) : _;
```

Where:

- `dmax`: maximum delay-line length (power of 2) - 10 ms typical
- `curdel`: current dynamic delay (not to exceed dmax)
- `depth`: effect strength between 0 and 1 (1 typical)
- `fb`: feedback gain between 0 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference

https://ccrma.stanford.edu/~jos/pasp/Flanging.html

---

flanger_stereo

Stereo flanging effect. `flanger_stereo` is a standard Faust function.

Usage:

`_,_ : flanger_stereo(dmax,curdel1,curdel2,depth,fb,invert) : _,_;`

Where:

- `dmax`: maximum delay-line length (power of 2) - 10 ms typical
- `curdel`: current dynamic delay (not to exceed dmax)
- `depth`: effect strength between 0 and 1 (1 typical)
- `fb`: feedback gain between 0 and 1 (0 typical)
- `invert`: 0 for normal, 1 to invert sign of flanging sum

Reference

https://ccrma.stanford.edu/~jos/pasp/Flanging.html

---

phaser2_mono

Mono phasing effect.

Phaser

`_ : phaser2_mono(Notches,phase,width,frqmin,fratio,frqmax,speed,depth,fb,invert) : _;`

Where:

- `Notches`: number of spectral notches (MACRO ARGUMENT - not a signal)
- `phase`: phase of the oscillator (0-1)
- `width`: approximate width of spectral notches in Hz
- `frqmin`: approximate minimum frequency of first spectral notch in Hz
- `fratio`: ratio of adjacent notch frequencies
- `frqmax`: approximate maximum frequency of first spectral notch in Hz
- `speed`: LFO frequency in Hz (rate of periodic notch sweep cycles)

- **depth**: effect strength between 0 and 1 (1 typical) (aka "intensity") when depth=2, "vibrato mode" is obtained (pure allpass chain)
- **fb**: feedback gain between -1 and 1 (0 typical)
- **invert**: 0 for normal, 1 to invert sign of flanging sum

Reference:

- https://ccrma.stanford.edu/~jos/pasp/Phasing.html
- http://www.geofex.com/Article_Folders/phasers/phase.html
- 'An Allpass Approach to Digital Phasing and Flanging', Julius O. Smith III, Proc. Int. Computer Music Conf. (ICMC-84), pp. 103-109, Paris, 1984.
- CCRMA Tech. Report STAN-M-21: https://ccrma.stanford.edu/STANM/stanms/stanm21/

---

phaser2_stereo

Stereo phasing effect. `phaser2_stereo` is a standard Faust function.

Phaser

`_ : phaser2_stereo(Notches,phase,width,frqmin,fratio,frqmax,speed,depth,fb,invert) : _;`

Where:

- **Notches**: number of spectral notches (MACRO ARGUMENT - not a signal)
- **phase**: phase of the oscillator (0-1)
- **width**: approximate width of spectral notches in Hz
- **frqmin**: approximate minimum frequency of first spectral notch in Hz
- **fratio**: ratio of adjacent notch frequencies
- **frqmax**: approximate maximum frequency of first spectral notch in Hz
- **speed**: LFO frequency in Hz (rate of periodic notch sweep cycles)
- **depth**: effect strength between 0 and 1 (1 typical) (aka "intensity") when depth=2, "vibrato mode" is obtained (pure allpass chain)
- **fb**: feedback gain between -1 and 1 (0 typical)
- **invert**: 0 for normal, 1 to invert sign of flanging sum

Reference:

- https://ccrma.stanford.edu/~jos/pasp/Phasing.html
- http://www.geofex.com/Article_Folders/phasers/phase.html
- 'An Allpass Approach to Digital Phasing and Flanging', Julius O. Smith III, Proc. Int. Computer Music Conf. (ICMC-84), pp. 103-109, Paris, 1984.

- CCRMA Tech. Report STAN-M-21: https://ccrma.stanford.edu/STANM/stanms/stanm21/

---

physmodels.lib

Faust physical modeling library. Its official prefix is `pm`.

chain(A:B:...)

Creates a chain of bidirectional blocks. Blocks must have 3 inputs and out-
puts. The first input/output correspond to the left going signal, the second
input/output correspond to the right going signal and the third input/output
is the mix of the main signal output. The implied one sample delay created by
the ~ operator is generalized to the left and right going waves. Thus, n blocks
in `chain()` will add an n samples delay to both the left and right going waves.
Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : chain(A:B) : rightGoingWaves,leftGoingWaves,mix
with{
    A = _,_,_;
    B = _,_,_;
};
```

Requires

`routes.lib` (`crossnn`)

---

input(x)

Adds a waveguide input anywhere between 2 blocks in a chain of blocks (see
`chain()`). ### Usage

```
string(x) = chain(A:input(x):B)
```

Where `x` is the input signal to be added to the chain.

---

output()

Adds a waveguide output anywhere between 2 blocks in a chain of blocks and sends it to the mix output channel (see `chain()`). ### Usage

```
chain(A:output:B)
```

---

terminations(a,b,c)

Creates terminations on both sides of a `chain()` without closing the inputs and outputs of the bidirectional signals chain. As for `chain()`, this function adds a 1 sample delay to the bidirectional signal both ways. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(a,b,c) : rightGoingWaves,leftGoing
with{
    a = *(-1); // left termination
    b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
    c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

fullTerminations(a,b,c)

Same as `terminations()` but closes the inputs and outputs of the bidirectional chain (only the mixed output remains). ### Usage

```
terminations(a,b,c) : _
with{
    a = *(-1); // left termination
    b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
    c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

leftTermination(a,b)

Creates a termination on the left side of a `chain()` without closing the inputs
and outputs of the bidirectional signals chain. This function adds a 1 sample
delay near the termination. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(a,b) : rightGoingWa
with{
    a = *(-1); // left termination
    b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
};
```

Requires

`routes.lib` (`crossnn`)

---

rightTermination(b,c)

Creates a termination on the right side of a `chain()` without closing the inputs
and outputs of the bidirectional signals chain. This function adds a 1 sample
delay near the termination. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : terminations(b,c) : rightGoingWa
with{
    b = chain(D:E:F); // bidirectional chain of blocks (D, E, F, etc.)
    c = *(-1); // right termination
};
```

Requires

`routes.lib` (`crossnn`)

---

waveguide(nMax,n)

A simple waveguide block based on a 4th order fractional delay. ### Usage

```
rightGoingWaves,leftGoingWaves,mixedOutput : waveguide(nMax,n) : rightGoingWa
```

With: * `nMax`: the maximum length of the waveguide in samples * `n` the length
of the waveguide in samples. ### Requires `delays.lib` (`fdelay4`)

---

idealString(length,reflexion,xPosition,x)

An ideal string with rigid terminations and where the plucking position and the pick-up position are the same. ### Usage

```
1-1' : idealString(length,reflexion,xPosition,x)
```

With: * `length`: the length of the string in meters * `reflexion`: the coefficient of reflexion (0-0.99999999) * `pluckPosition`: the plucking position (0.001-0.999) * `x`: the input signal for the excitation ### Requires `routes.lib` (`crossnn`) `delays.lib` (`fdelay4`)

---

reverbs.lib

A library of reverb effects. Its official prefix is `re`.

Functions Reference

jcrev

This artificial reverberator take a mono signal and output stereo (`satrev`) and quad (`jcrev`). They were implemented by John Chowning in the MUS10 computer-music language (descended from Music V by Max Mathews). They are Schroeder Reverberators, well tuned for their size. Nowadays, the more expensive freeverb is more commonly used (see the Faust examples directory).

`jcrev` reverb below was made from a listing of "RV", dated April 14, 1972, which was recovered from an old SAIL DART backup tape. John Chowning thinks this might be the one that became the well known and often copied JCREV.

`jcrev` is a standard Faust function

Usage

```
_ : jcrev : _,_,_,_
```

---

satrev

This artificial reverberator take a mono signal and output stereo (`satrev`) and quad (`jcrev`). They were implemented by John Chowning in the MUS10 computer-music language (descended from Music V by Max Mathews). They

are Schroeder Reverberators, well tuned for their size. Nowadays, the more expensive freeverb is more commonly used (see the Faust examples directory).

`satrev` was made from a listing of "SATREV", dated May 15, 1971, which was recovered from an old SAIL DART backup tape. John Chowning thinks this might be the one used on his often-heard brass canon sound examples, one of which can be found at https://ccrma.stanford.edu/~jos/wav/FM_BrassCanon2.wav

Usage

```
_ : satrev : _,_
```

---

mono_freeverb

A simple Schroeder reverberator primarily developed by "Jezar at Dreampoint" that is extensively used in the free-software world. It uses four Schroeder allpasses in series and eight parallel Schroeder-Moorer filtered-feedback comb-filters for each audio channel, and is said to be especially well tuned.

`mono_freeverb` is a standard Faust function.

Usage

```
_ : mono_freeverb(fb1, fb2, damp, spread) : _;
```

Where:

- `fb1`: coefficient of the lowpass comb filters (0-1)
- `fb2`: coefficient of the allpass comb filters (0-1)
- `damp`: damping of the lowpass comb filter (0-1)
- `spread`: spatial spread in number of samples (for stereo)

---

stereo_freeverb

A simple Schroeder reverberator primarily developed by "Jezar at Dreampoint" that is extensively used in the free-software world. It uses four Schroeder allpasses in series and eight parallel Schroeder-Moorer filtered-feedback comb-filters for each audio channel, and is said to be especially well tuned.

Usage

```
_,_ : stereo_freeverb(fb1, fb2, damp, spread) : _,_;
```

Where:

- **fb1**: coefficient of the lowpass comb filters (0-1)
- **fb2**: coefficient of the allpass comb filters (0-1)
- **damp**: damping of the lowpass comb filter (0-1)
- **spread**: spatial spread in number of samples (for stereo)

---

fdnrev0

Pure Feedback Delay Network Reverberator (generalized for easy scaling). **fdnrev0** is a standard Faust function.

Usage

```
<1,2,4,...,N signals> <:
fdnrev0(MAXDELAY,delays,BBSO,freqs,durs,loopgainmax,nonl) :>
<1,2,4,...,N signals>
```

Where:

- **N**: 2, 4, 8, ... (power of 2)
- **MAXDELAY**: power of 2 at least as large as longest delay-line length
- **delays**: N delay lines, N a power of 2, lengths perferably coprime
- **BBSO**: odd positive integer = order of bandsplit desired at freqs
- **freqs**: NB-1 crossover frequencies separating desired frequency bands
- **durs**: NB decay times (t60) desired for the various bands
- **loopgainmax**: scalar gain between 0 and 1 used to "squelch" the reverb
- **nonl**: nonlinearity (0 to 0.999..., 0 being linear)

Reference

https://ccrma.stanford.edu/~jos/pasp/FDN__Reverberation.html

---

zita_rev_fdn

Internal 8x8 late-reverberation FDN used in the FOSS Linux reverb zita-rev1 by Fons Adriaensen fons@linuxaudio.org. This is an FDN reverb with allpass comb filters in each feedback delay in addition to the damping filters.

Usage

```
bus(8) : zita_rev_fdn(f1,f2,t60dc,t60m,fsmax) : bus(8)
```

Where:

- `f1`: crossover frequency (Hz) separating dc and midrange frequencies
- `f2`: frequency (Hz) above f1 where T60 = t60m/2 (see below)
- `t60dc`: desired decay time (t60) at frequency 0 (sec)
- `t60m`: desired decay time (t60) at midrange frequencies (sec)
- `fsmax`: maximum sampling rate to be used (Hz)

Reference

- http://www.kokkinizita.net/linuxaudio/zita-rev1-doc/quickguide.html
- https://ccrma.stanford.edu/~jos/pasp/Zita_Rev1.html

———————————————

`zita_rev1_stereo`

Extend `zita_rev_fdn` to include `zita_rev1` input/output mapping in stereo mode. `zita_rev1_stereo` is a standard Faust function.

Usage

```
_,_ : zita_rev1_stereo(rdel,f1,f2,t60dc,t60m,fsmax) : _,_
```

Where:

`rdel` = delay (in ms) before reverberation begins (e.g., 0 to ~100 ms) (remaining args and refs as for `zita_rev_fdn` above)

———————————————

`zita_rev1_ambi`

Extend zita_rev_fdn to include zita_rev1 input/output mapping in "ambisonics mode", as provided in the Linux C++ version.

Usage

```
_,_ : zita_rev1_ambi(rgxyz,rdel,f1,f2,t60dc,t60m,fsmax) : _,_,_,_
```

Where:

`rgxyz` = relative gain of lanes 1,4,2 to lane 0 in output (e.g., -9 to 9) (remaining args and references as for zita_rev1_stereo above)

131

---

routes.lib

A library of basic elements to handle signal routing in Faust. Its official prefix is `ro`.

Functions Reference

cross

Cross n signals: `(x1,x2,..,xn) -> (xn,..,x2,x1)`. `cross` is a standard Faust function.

Usage

```
cross(n)
_,_,_ : cross(3) : _,_,_
```

Where:

- **n**: number of signals (int, must be known at compile time)

Note

Special case: `cross2`:

```
cross2 = _,cross(2),_;
```

---

crossnn

Cross two `bus(n)`s.

Usage

```
_,_,... : crossmm(n) : _,_,...
```

Where:

- **n**: the number of signals in the `bus`

---

crossn1

Cross bus(n) and bus(1).

Usage

```
_,_,... : crossn1(n) : _,_,...
```

Where:

- `n`: the number of signals in the first `bus`

---

interleave

Interleave row*col cables from column order to row order. input : x(0), x(1), x(2) ..., x(row*col-1) output: x(0+0*row), x(0+1*row), x(0+2*row), ..., x(1+0*row), x(1+1*row), x(1+2*row), ...

Usage

```
_,_,_,_,_,_ : interleave(row,column) : _,_,_,_,_,_
```

Where:

- `row`: the number of row (int, known at compile time)
- `column`: the number of column (int, known at compile time)

---

butterfly

Addition (first half) then substraction (second half) of interleaved signals.

Usage

```
_,_,_,_ : butterfly(n) : _,_,_,_
```

Where:

- `n`: size of the butterfly (n is int, even and known at compile time)

---

hadamard

Hadamard matrix function of size `n = 2^k`.

Usage

```
_,_,_,_ : hadamard(n) : _,_,_,_
```

Where:

- n: 2^k, size of the matrix (int, must be known at compile time)

Note:

Implementation contributed by Remy Muller.

---

recursivize

Create a recursion from two arbitrary processors p and q.

Usage

```
_,_ : recursivize(p,q) : _,_
```

Where:

- p: the forward arbitrary processor
- q: the feedback arbitrary processor

---

signals.lib

A library of basic elements to handle signals in Faust. Its official prefix is `si`.

Functions Reference

bus

n parallel cables. `bus` is a standard Faust function.

Usage

```
bus(n)
bus(4) : _,_,_,_
```

Where:

- **n**: is an integer known at compile time that indicates the number of parallel cables.

---

block

Block - terminate n signals. `block` is a standard Faust function.

Usage

`_,_,... : block(n) : _,...`

Where:

- **n**: the number of signals to be blocked

---

interpolate

Linear interpolation between two signals.

Usage

`_,_ : interpolate(i) : _`

Where:

- **i**: interpolation control between 0 and 1 (0: first input; 1: second input)

---

smooth

Exponential smoothing by a unity-dc-gain one-pole lowpass. `smooth` is a standard Faust function.

Usage:

`_ : smooth(tau2pole(tau)) : _`

Where:

- **tau**: desired smoothing time constant in seconds, or

`hslider(...) : smooth(s) : _`

Where:

- **s**: smoothness between 0 and 1. s=0 for no smoothing, s=0.999 is "very smooth", s>1 is unstable, and s=1 yields the zero signal for all inputs. The exponential time-constant is approximately $1/(1-s)$ samples, when s is close to (but less than) 1.

Reference:

https://ccrma.stanford.edu/~jos/mdft/Convolution_Example_2_ADSR.html

---

smoo

Smoothing function based on `smooth` ideal to smooth UI signals (sliders, etc.) down. `smoo` is a standard Faust function.

Usage

```
hslider(...) : smoo;
```

---

polySmooth

A smoothing function based on `smooth` that doesn't smooth when a trigger signal is given. This is very useful when making polyphonic synthesizer to make sure that the value of the parameter is the right one when the note is started.

Usage

```
hslider(...) : polysmooth(g,s,d) : _
```

Where:

- **g**: the gate/trigger signal used when making polyphonic synths
- **s**: the smoothness (see `smooth`)
- **d**: the number of samples to wait before the signal start being smoothed after **g** switched to 1

---

bsmooth

Block smooth linear interpolation during a block of samples.

Usage

```
hslider(...) : bsmooth : _
```

---

lag_ud

Lag filter with separate times for up and down.

Usage

```
_ : lag_ud(up, dn, signal) : _;
```

---

dot

Dot product for two vectors of size n.

Usage

```
_,_,_,_,_,_ : dot(n) : _
```

Where:

- **n**: size of the vectors (int, must be known at compile time)

---

spats.lib

This library contains a collection of tools for sound spatialization. Its official prefix is `sp`.

panner

A simple linear stereo panner. `panner` is a standard Faust function.

Usage

```
_ : panner(g) : _,_
```

Where:

- g: the panning (0-1)

---

spat

GMEM SPAT: n-outputs spatializer. `spat` is a standard Faust function.

Usage

```
_ : spat(n,r,d) : _,_,...
```

Where:

- **n**: number of outputs
- **r**: rotation (between 0 et 1)
- **d**: distance of the source (between 0 et 1)

---

stereoize

Transform an arbitrary processor `p` into a stereo processor with 2 inputs and 2 outputs.

Usage

```
_,_ : stereoize(p) : _,_
```

Where:

- **p**: the arbitrary processor

---

synths.lib

This library contains a collection of envelope generators. Its official prefix is `sy`.

popFilterPerc

A simple percussion instrument based on a "popped" resonant bandpass filter. `popFilterPerc` is a standard Faust function.

Usage

```
popFilterDrum(freq,q,gate) : _;
```

Where:

- `freq`: the resonance frequency of the instrument
- `q`: the q of the res filter (typically, 5 is a good value)
- `gate`: the trigger signal (0 or 1)

---

dubDub

A simple synth based on a sawtooth wave filtered by a resonant lowpass. `dubDub` is a standard Faust function.

Usage

```
dubDub(freq,ctFreq,q,gate) : _;
```

Where:

- `freq`: frequency of the sawtooth
- `ctFreq`: cutoff frequency of the filter
- `q`: Q of the filter
- `gate`: the trigger signal (0 or 1)

---

sawTrombone

A simple trombone based on a lowpassed sawtooth wave. `sawTrombone` is a standard Faust function.

Usage

```
sawTrombone(att,freq,gain,gate) : _
```

Where:

- `att`: exponential attack duration in s (typically 0.01)
- `freq`: the frequency

- `gain`: the gain (0-1)
- `gate`: the gate (0 or 1)

---

combString

Simplest string physical model ever based on a comb filter. `combString` is a standard Faust function.

Usage

```
combString(freq,res,gate) : _;
```

Where:

- `freq`: the frequency of the string
- `res`: string T60 (resonance time) in second
- `gate`: trigger signal (0 or 1)

---

additiveDrum

A simple drum using additive synthesis. `additiveDrum` is a standard Faust function.

Usage

```
additiveDrum(freq,freqRatio,gain,harmDec,att,rel,gate) : _
```

Where:

- `freq`: the resonance frequency of the drum
- `freqRatio`: a list of ratio to choose the frequency of the mode in function of `freq` e.g.(1 1.2 1.5 . . .). The first element should always be one (fundamental).
- `gain`: the gain of each mode as a list (1 0.9 0.8 . . .). The first element is the gain of the fundamental.
- `harmDec`: harmonic decay ratio (0-1): configure the speed at which higher modes decay compare to lower modes.
- `att`: attack duration in second
- `rel`: release duration in second
- `gate`: trigger signal (0 or 1)

---

fm

An FM synthesizer with an arbitrary number of modulators connected as a sequence. `fm` is a standard Faust function.

Usage

```
freqs = (300,400,...);
indices = (20,...);
fm(freqs,indices) : _
```

Where:

- `freqs`: a list of frequencies where the first one is the frequency of the carrier and the others, the frequency of the modulator(s)
- `indices`: the indices of modulation (Nfreqs-1)

---

vaeffects.lib

A library of virtual analog filter effects. Its official prefix is `ve`.

Functions Reference

moog_vcf

Moog "Voltage Controlled Filter" (VCF) in "analog" form. Moog VCF implemented using the same logical block diagram as the classic analog circuit. As such, it neglects the one-sample delay associated with the feedback path around the four one-poles. This extra delay alters the response, especially at high frequencies (see reference [1] for details). See `moog_vcf_2b` below for a more accurate implementation.

Usage

```
moog_vcf(res,fr)
```

Where:

- `fr`: corner-resonance frequency in Hz (less than SR/6.3 or so)
- `res`: Normalized amount of corner-resonance between 0 and 1 (0 is no resonance, 1 is maximum)

References

- https://ccrma.stanford.edu/~stilti/papers/moogvcf.pdf
- https://ccrma.stanford.edu/~jos/pasp/vegf.html

`moog_vcf_2b[n]`

Moog "Voltage Controlled Filter" (VCF) as two biquads. Implementation of the ideal Moog VCF transfer function factored into second-order sections. As a result, it is more accurate than `moog_vcf` above, but its coefficient formulas are more complex when one or both parameters are varied. Here, res is the fourth root of that in `moog_vcf`, so, as the sampling rate approaches infinity, `moog_vcf(res,fr)` becomes equivalent to `moog_vcf_2b[n](res^4,fr)` (when res and fr are constant). `moog_vcf_2b` uses two direct-form biquads (`tf2`). `moog_vcf_2bn` uses two protected normalized-ladder biquads (`tf2np`).

Usage

```
moog_vcf_2b(res,fr)
moog_vcf_2bn(res,fr)
```

Where:

- `fr`: corner-resonance frequency in Hz
- `res`: Normalized amount of corner-resonance between 0 and 1 (0 is min resonance, 1 is maximum)

`wah4`

Wah effect, 4th order. `wah4` is a standard Faust function.

Usage

```
_ : wah4(fr) : _
```

Where:

- `fr`: resonance frequency in Hz

Reference

https://ccrma.stanford.edu/~jos/pasp/vegf.html

---

autowah

Auto-wah effect. `autowah` is a standard Faust function.

Usage

`_ : autowah(level) : _;`

Where:

- `level`: amount of effect desired (0 to 1).

---

crybaby

Digitized CryBaby wah pedal. `crybaby` is a standard Faust function.

Usage

`_ : crybaby(wah) : _`

Where:

- `wah`: "pedal angle" from 0 to 1

Reference

https://ccrma.stanford.edu/~jos/pasp/vegf.html

---

vocoder

A very simple vocoder where the spectrum of the modulation signal is analyzed using a filter bank. `vocoder` is a standard Faust function.

Usage

`_ : vocoder(nBands,att,rel,BWRatio,source,excitation) : _;`

Where:

- `nBands`: Number of vocoder bands
- `att`: Attack time in seconds
- `rel`: Release time in seconds
- `BWRatio`: Coefficient to adjust the bandwidth of each band (0.1 - 2)

- `source`: Modulation signal
- `excitation`: Excitation/Carrier signal

Licenses

STK 4.3 License

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

Any person wishing to distribute modifications to the Software is asked to send the modifications to the original developer so that they can be incorporated into the canonical version. This is, however, not a binding provision of this license.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.