CPSC 440

Chapter 4: The Processor (part 3)*

* This ppt is provided by the publisher of the textbook

MIPS Pipelined Datapath



Pipeline registers

- Need registers between stages
  - To hold information produced in previous cycle



Pipeline Operation

- Cycle-by-cycle flow of instructions through the pipelined datapath
  - “Single-clock-cycle” pipeline diagram
    - Shows pipeline usage in a single cycle
    - Highlight resources used
  - c.f. “multi-clock-cycle” diagram
    - Graph of operation over time
- We’ll look at “single-clock-cycle” diagrams for load & store

IF for Load, Store, …



ID for Load, Store, …



EX for Load


lw
Execution
IF/ID
ID/EX
EX/MEM
MEM/WB
Add
4
M
u
x
0
1
PC
Address
Instruction memory
Instruction
Read register 1
Read register 2
Registers
Write register
Write data
Read data 1
Read data 2
Shift left 2
Add
Add result
ALU
Zero
ALU result
Address
Read data
Data memory
Write data
16
Sign-extend
32

MEM for Load


lw
Memory
IF/ID
ID/EX
EX/MEM
MEM/WB
Add
4
0
M
u
x
1
PC
Address
Instruction memory
Instruction
Read register 1
Read register 2
Registers
Write register
Write data
Read data 1
Read data 2
16
Sign-extend
32
Shift left 2
Add
Add result
ALU
Zero
ALU result
Address
Data memory
Read data
Write data

WB for Load


lw
Write back
IF/ID
ID/EX
EX/MEM
MEM/WB
Add
4
M u x
0
1
PC
Address
Instruction memory
Instruction
Read register 1
Read register 2
Registers
Write register
Write data
Read data 1
Read data 2
Shift left 2
Add
Add result
ALU
Zero
ALU result
Address
Read data
Data memory
Write data
16
Sign-extend
32
Wrong register number

Corrected Datapath for Load



EX for Store


sw
Execution
IF/ID
ID/EX
EX/MEM
MEM/WB
Add
4
M
u
x
0
1
PC
Address
Instruction memory
Instruction
Read register 1
Read register 2
Registers
Write register
Write data
Read data 1
Read data 2
16
Sign-extend
32
Shift left 2
Add
Add result
ALU
Zero
ALU result
Address
Read data
Data memory
Write data

MEM for Store



WB for Store


SW
Write-back
IF/ID
ID/EX
EX/MEM
MEM/WB
Add
4
M
u
x
0
1
PC
Address
Instruction memory
Instruction
Read register 1
Read register 2
Registers
Write register
Write data
Read data 1
Read data 2
16
Sign-extend
32
Shift left 2
Add
Add result
ALU
Zero
ALU result
Address
Read data
Data memory
Write data

Multi-Cycle Pipeline Diagram

- Form showing resource usage



Multi-Cycle Pipeline Diagram

- Traditional form



Single-Cycle Pipeline Diagram

- State of pipeline in a given cycle

add $14, $5, $6	lw $13, 24 ($1)	add $12, $3, $4	sub $11, $2, $3	lw $10, 20($1)
Instruction fetch	Instruction decode	Execution	Memory	Write-back



Pipelined Control (Simplified)



Pipelined Control

- Control signals derived from instruction
  - As in single-cycle implementation



Pipelined Control



Data Hazards in ALU Instructions

- Consider this sequence:

```
sub $2, $1,$3
and $12,$2,$5
or  $13,$6,$2
add $14,$2,$2
sw  $15,100($2)
```

- We can resolve hazards with forwarding
  - How do we detect when to forward?

Dependencies & Forwarding



Detecting the Need to Forward

- Pass register numbers along pipeline
  - e.g., ID/EX.RegisterRs = register number for Rs sitting in ID/EX pipeline register
- ALU operand register numbers in EX stage are given by
  - ID/EX.RegisterRs, ID/EX.RegisterRt
- Data hazards when
  1a. EX/MEM.RegisterRd = ID/EX.RegisterRs
  1b. EX/MEM.RegisterRd = ID/EX.RegisterRt
  2a. MEM/WB.RegisterRd = ID/EX.RegisterRs
  2b. MEM/WB.RegisterRd = ID/EX.RegisterRt

Fwd from EX/MEM pipeline reg

Fwd from MEM/WB pipeline reg

Detecting the Need to Forward

- But only if forwarding instruction will write to a register!
  - EX/MEM.RegWrite, MEM/WB.RegWrite
- And only if Rd for that instruction is not $zero
  - EX/MEM.RegisterRd ≠ 0, MEM/WB.RegisterRd ≠ 0

Forwarding Paths



b. With forwarding

Forwarding Conditions

- EX hazard
  - if (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0)
    and (EX/MEM.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 10
  - if (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0)
    and (EX/MEM.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 10
- MEM hazard
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0)
    and (MEM/WB.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 01
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0)
    and (MEM/WB.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 01

Double Data Hazard

- Consider the sequence:

```
add $1,$1,$2
add $1,$1,$3
add $1,$1,$4
```

- Both hazards occur
  - Want to use the most recent
- Revise MEM hazard condition
  - Only fwd if EX hazard condition isn't true

Revised Forwarding Condition

- MEM hazard
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0)
    and not (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0)
    and (EX/MEM.RegisterRd = ID/EX.RegisterRs))
    and (MEM/WB.RegisterRd = ID/EX.RegisterRs))
    ForwardA = 01
  - if (MEM/WB.RegWrite and (MEM/WB.RegisterRd ≠ 0)
    and not (EX/MEM.RegWrite and (EX/MEM.RegisterRd ≠ 0)
    and (EX/MEM.RegisterRd = ID/EX.RegisterRt))
    and (MEM/WB.RegisterRd = ID/EX.RegisterRt))
    ForwardB = 01

Datapath with Forwarding



Load-Use Data Hazard



Load-Use Hazard Detection

- Check when using instruction is decoded in ID stage
- ALU operand register numbers in ID stage are given by
  - IF/ID.RegisterRs, IF/ID.RegisterRt
- Load-use hazard when
  - ID/EX.MemRead and
    ((ID/EX.RegisterRt = IF/ID.RegisterRs) or
    (ID/EX.RegisterRt = IF/ID.RegisterRt))
- If detected, stall and insert bubble

How to Stall the Pipeline

- Force control values in ID/EX register to 0
  - EX, MEM and WB do nop (no-operation)
- Prevent update of PC and IF/ID register
  - Using instruction is decoded again
  - Following instruction is fetched again
  - 1-cycle stall allows MEM to read data for `lw`
    - Can subsequently forward to EX stage

Stall/Bubble in the Pipeline



Stall/Bubble in the Pipeline



Or, more accurately…

Datapath with Hazard Detection



Stalls and Performance

The BIG Picture

- Stalls reduce performance
  - But are required to get correct results
- Compiler can arrange code to avoid hazards and stalls
  - Requires knowledge of the pipeline structure

Branch Hazards

- If branch outcome determined in MEM



Reducing Branch Delay

- Move hardware to determine outcome to ID stage
  - Target address adder
  - Register comparator
- Example: branch taken

```
36:   sub   $10, $4, $8
40:   beq   $1,  $3, 7
44:   and   $12, $2, $5
48:   or    $13, $2, $6
52:   add   $14, $4, $2
56:   slt   $15, $6, $7
      ...
72:   lw    $4, 50($7)
```

Example: Branch Taken



Example: Branch Taken



Data Hazards for Branches

- If a comparison register is a destination of 2nd or 3rd preceding ALU instruction

```
add $1, $2, $3
add $4, $5, $6
…
beq $1, $4, target
```



- Can resolve using forwarding

Data Hazards for Branches

- If a comparison register is a destination of preceding ALU instruction or 2nd preceding load instruction
  - Need 1 stall cycle

```
lw  $1, addr
add $4, $5, $6
beq stalled
beq $1, $4, target
```



Data Hazards for Branches

- If a comparison register is a destination of immediately preceding load instruction
  - Need 2 stall cycles

```
lw  $1, addr
beq stalled
beq stalled
beq $1, $0, target
```



Dynamic Branch Prediction

- In deeper and superscalar pipelines, branch penalty is more significant
- Use dynamic prediction
  - Branch prediction buffer (aka branch history table)
  - Indexed by recent branch instruction addresses
  - Stores outcome (taken/not taken)
  - To execute a branch
    - Check table, expect the same outcome
    - Start fetching from fall-through or target
    - If wrong, flush pipeline and flip prediction

1-Bit Predictor: Shortcoming

- Inner loop branches mispredicted twice!



  - Mispredict as taken on last iteration of inner loop
  - Then mispredict as not taken on first iteration of inner loop next time around

2-Bit Predictor

- Only change prediction on two successive mispredictions



Calculating the Branch Target

- Even with predictor, still need to calculate the target address
  - 1-cycle penalty for a taken branch
- Branch target buffer
  - Cache of target addresses
  - Indexed by PC when instruction fetched
    - If hit and instruction is branch predicted taken, can fetch target immediately