

Feedback — Lecture 5 Quiz

[Help Center](#)

Thank you. Your submission for this quiz was received.

You submitted this quiz on **Sun 13 Sep 2015 8:11 PM PDT**. You got a score of **10.00** out of **10.00**.

Question 1

A student writes several functions to swap the values of the two variables x and y, i.e. if x=1 and y=2, after calling the swap function x=2 and y=1. The different functions that the student writes are given below:

```
def swap1(x,y) :  
    x=y  
    y=x  
    return(x,y)
```

```
def swap2(x,y) :  
    return(y,x)
```

```
def swap3(x,y) :  
    z=x  
    x=y  
    y=z  
    return(x,y)
```

```
def swap4(x,y) :  
    x,y=y,x  
    return(x,y)
```

Which of the functions swap1, swap2, swap3, and swap4 is correct?

Your Answer	Score	Explanation
-------------	-------	-------------

- ☐ Functions swap1, and swap4 only
- ☐ Functions swap2, and swap3 only
- ☒ Functions swap2, swap3, and swap4 only ✓ 1.00
- ☐ Functions swap1, swap2, and swap3 only

Total 1.00 / 1.00

Question 2

Consider the following two functions:

```
def f1(x):
    if (x > 0):
        x = 3*x
        x = x / 2
    return x
```

```
def f2(x):
    if (x > 0):
        x = 3*x
    x = x / 2
    return x
```

For what values of x will f1 and f2 return the same value?

- | Your Answer | Score | Explanation |
|---|---|-------------|
| <input checked="" type="radio"/> When x is zero or positive | ✓ 1.00 | |
| <input type="radio"/> Any value of x | | |
| <input type="radio"/> For negative values of x only | | |
| <input type="radio"/> For x | | |


Total 1.00 / 1.00

Question 3

A recursive function in programming is a function that calls itself during its execution. The following two functions are examples of recursive functions:

```
def function1(length):  
    if length > 0:  
        print(length)  
        function1(length - 1)  
  
def function2(length):  
    while length > 0:  
        print(length)  
        function2(length - 1)
```

What can you say about the output of function1(3) and function2(3)?

Your Answer	Score	Explanation
<input checked="" type="radio"/> function1 produces the output: 3 2 1 and function2 runs infinitely.	 1.00	
<input type="radio"/> The two functions produce the same output 3 2 1.		
<input type="radio"/> The two functions produce the same output: 3 2 1		
<input type="radio"/> function1 produces the output: 3 2 1 and function2 runs infinitely.		
Total	1.00 / 1.00	

Question 4

The following recursive function takes three positive integer arguments:

```
def compute(n,x,y)
    if n==0 : return x
    return compute(n-1,x+y,y)
```

What is the value returned by the compute function?

Your Answer	Score	Explanation
<input checked="" type="radio"/> $x+n*y$	✓ 1.00	
<input type="radio"/> x		
<input type="radio"/> $n*(x+y)$		
<input type="radio"/> $n*x+y$		
Total	1.00 / 1.00	

Question 5

What will the returned value be for the compute function defined in Question 4 if the argument n is negative?

Your Answer	Score	Explanation
<input checked="" type="radio"/> The function will never return a value.	✓ 1.00	
<input type="radio"/> x		
<input type="radio"/> $x-n*y$		
<input type="radio"/> $x+n*y$		
Total	1.00 / 1.00	

Question 6

The following functions are all intended to check whether a string representing a dna sequence contains any characters that are not 'a','c','g','t', 'A', 'C', 'G', or 'T'. At least some of these functions are wrong. Which ones are correct?

```
def valid_dna1(dna):  
    for c in dna:  
        if c in 'acgtACGT':  
            return True  
        else:  
            return False
```

```
def valid_dna2(dna):  
    for c in dna:  
        if 'c' in 'acgtACGT':  
            return 'True'  
        else:  
            return 'False'
```

```
def valid_dna3(dna):  
    for c in dna:  
        flag = c in 'acgtACGT'  
    return flag
```

```
def valid_dna4(dna):  
    for c in dna:  
        if not c in 'acgtACGT':  
            return False  
    return True
```

Your Answer	Score	Explanation
<input checked="" type="radio"/> valid_dna4 only	✓ 1.00	
<input type="radio"/> valid_dna2, valid_dna3, and valid_dna4 only		
<input type="radio"/> valid_dna1 only		
<input type="radio"/> valid_dna1, valid_dna2, and valid_dna4 only		

Total

1.00 / 1.00

Question 7

What is the type of variable L3 and what is its value if L1 and L2 are lists?

L3 = [i for i in set(L1) if i in L2]

Your Answer	Score	Explanation
<input type="radio"/> L3 is a list with all the elements in L1 and L2		
<input type="radio"/> L3 is a set with elements common between the lists L2 and L3.		
<input type="radio"/> L3 is a tuple with elements that are both in L1 and L2		
<input checked="" type="radio"/> L3 is a list that contains only the elements that are common between the lists (without duplicates).	✓ 1.00	
Total	1.00 / 1.00	

Question 8

What will be printed after executing the following code?

```
>>>def f(mystring):  
    print(message)  
    print(mystring)  
    message="Inside function now!"  
    print(message)  
>>>message="Outside function!"  
>>>f("Test function:")
```

Your Answer	Score	Explanation
<input type="radio"/> Outside function! Test function: Inside function now!		

☐ Test function:
Inside function now!

☒ An error message. ✓ 1.00

☐ Outside function!

Total 1.00 / 1.00

Question 9

Which statement below is true about a function:

Your Answer	Score	Explanation
<input type="radio"/> must have at least one parameter		
<input type="radio"/> its arguments always appear within brackets		
<input type="radio"/> must always have a return statement		
<input checked="" type="radio"/> may have no parameters	✓ 1.00	
Total	1.00 / 1.00	

Question 10

Which of the following function headers is correct?

- A. `def afunction(a1 = 1, a2):`
 B. `def afunction(a1 = 1, a2, a3 = 3):`
 C. `def afunction(a1 = 1, a2 = 2, a3 = 3):`

Your Answer	Score	Explanation
<input checked="" type="radio"/> C	✓ 1.00	
<input type="radio"/> A,C		
<input type="radio"/> A,B,C		

☐ None is correct.

Total

1.00 / 1.00