Signature anchors: my wallet software

The signing-key fingerprints of your own programs, checked once, recorded for good · belongs to chapters 3 and 6

Why fingerprints instead of checksums: A file's SHA-256 is bound to one version and changes with every release. It is fetched fresh at every update and checked against the signature. The fingerprint of the signing key, by contrast, is the durable anchor: it practically never changes, and a change is an event the vendor announces publicly several times over. This sheet is your own record: at the next update you compare against your paper instead of against the internet. **Rule of thumb:** hash differs and the signature holds → a website problem. Hash matches and the signature breaks → alarm. This applies where the signature sits on the file itself. If the vendor signs a list of checksums, as Sparrow does, a mismatch means the wrong or an altered file, so install nothing.

How to fill in this sheet: Check the vendor key's fingerprint across **several independent channels** (vendor website, official documentation, developer profiles). Only when all of them agree do you enter it here, with the date and the channels you checked. One channel alone is not enough, and the short key ID (the last 16 characters) is not a second proof, it is the same value in short form.

MY SIGNATURE ANCHORS

Program / vendor	Fingerprint (40 characters, in groups of four)	Expiry date	Checked at (channels) + date

⚠ **"Good signature" alone is not enough.** That message only means: some key from your keyring signed. What matters is that the fingerprint of the signing key matches your entry on this sheet. ⚠ **If a key carries an expiry date,** the date belongs in your calendar. After expiry the check reports an expired signature, and that is then neither an attack nor a bug but the expected key rollover.

UPDATE LOG

Date	Program	Version	Signature checked, fingerprint matches	Notes

alien-investor.org · v0.1 prototype · as of 2026-10-25 · CC BY-SA 4.0