

---

# OBJECT ORIENTED PROGRAMMING USING JAVA



# OUTLINE

- Method Overriding
- Super Keyword
- Types of Inheritance

---

## METHOD OVERRIDING

- If subclass (child class) has the same method as declared in the parent class, it is known as **method overriding in Java**.
- In **other words**, If a subclass provides the specific implementation of the method that has been **declared** by one of its **parent class**, it is known as method overriding.

### ❑ Usage of Overriding

- Method overriding is used to provide the specific implementation of a method which is **already** provided by its **superclass**.
- Method overriding is used for runtime **polymorphism**.

---

## RULES FOR METHOD OVERRIDING

- The method must have the same name as in the parent class
- The method must have the same parameter as in the parent class.
- There must be an IS-A relationship (inheritance).

## EXAMPLE OF METHOD OVERRIDING

//Creating a parent class.

```
class Vehicle{  
    //defining a method  
    void run(){  
        System.out.println("Vehicle is running");  
    }  
}
```

//Creating a child class


```
class Bike2 extends Vehicle{  
    //defining the same method as in the parent class  
    void run(){  
        System.out.println("Bike is running safely");  
    }  
}
```

```
public static void main(String args[]){  
    Bike2 obj = new Bike2(); //creating object  
    obj.run(); //calling method  
}
```

**Output:**  
**Bike is Running Safely**

## EXAMPLE OF METHOD OVERRIDING

Consider a scenario where Bank is a class that provides functionality to get the rate of interest. However, the rate of interest varies according to banks. For example, SBI, ICICI and AXIS banks could provide 8%, 7%, and 9% rate of interest.



## A REAL EXAMPLE OF METHOD OVERRIDING

//Creating a parent class.

```
class Bank{  
int getRateOfInterest(){return 0;}}
```

//Creating child classes.

```
class SBI extends Bank{  
int getRateOfInterest(){return 8;} }
```

```
class ICICI extends Bank{  
int getRateOfInterest(){return 7;} }
```

```
class AXIS extends Bank{  
int getRateOfInterest(){return 9;} }
```

//Test class to create objects and call the methods

```
class Test2{  
public static void main(String args[]){  
SBI s=new SBI();  
ICICI i=new ICICI();  
AXIS a=new AXIS();  
System.out.println("SBI Rate of Interest: "+s.getRateOfInterest());  
System.out.println("ICICI Rate of Interest: "+i.getRateOfInterest());  
System.out.println("AXIS Rate of Interest: "+a.getRateOfInterest());  
} }
```

Output:

SBI Rate of Interest: 8

ICICI Rate of Interest: 7

AXIS Rate of Interest: 9

## PROBLEM DESCRIPTION: NEED OF SUPER KEYWORD

```
class Main
{
    public static void main (String[] args) {

        child obj;
        obj=new child();
        obj.val_method();
    }
}

class Parent
{
    int a=10,b=100,c;
    Parent()
    {
        System.out.println("parent first"+ a +b);
    }

    void val_method()
    {
        c=a+b;
        System.out.println("sum is: "+c );
    }
}

class child extends Parent
{
    int a=200,b=20;
    child(){
        System.out.println("Child second"+a +b);
    }
    void val_method()
    {
        c=a+b;
        System.out.println("sum is: "+c );
    }
}
```

**Output:**  
**Parent first10100**  
**Child second20020**  
**Sum is 220**



## PROBLEM DESCRIPTION: NEED OF SUPER KEYWORD

```
class Main
{
    public static void main (String[] args) {
        child obj;
        obj=new child();
        obj.val_method();
    }
}
```

Step: 1

null

Step: 2

obj

a=0  
b=0  
c=0

Child object

Step: 3

obj

a=10  
b=100  
c=0

Child object

Step: 4

obj

a=200  
b=20  
c=220

Child object

```
class Parent
{
    int a=10,b=100,c;
    Parent()
    {
        System.out.println("parent first"+ a +b);
    }
    void val_method()
    {
        c=a+b;
        System.out.println("sum is: "+c );
    }
}
class child extends Parent
{
    int a=200,b=20;
    child(){
        System.out.println("Child second"+a +b);
    }
    void val_method()
    {
        c=a+b;
        System.out.println("sum is: "+c );
    }
}
```

## PROBLEM DESCRIPTION: NEED OF SUPER KEYWORD

```
class Main
{
    public static void main (String[] args) {
        child obj;
        obj=new child();
        obj.val_method();
    }
}

class Parent
{
    int a=10,b=100,c;
    Parent()
    {
        System.out.println("parent first"+ a +b);
    }

    void val_method()
    {
        c=a+b;
        System.out.println("sum is: "+c);
    }
}

class child extends Parent
{
    int a=200,b=20;
    child(){
        System.out.println("Child second"+a +b);
    }
    void val_method()
    {
        c=super.a+b;
        System.out.println("sum is: "+c );
    }
}
```

### Output

```
parent first10100
Child second20020
sum is: 30
```

super.a executes parent class variable which is  
a=10;

---

## THE SUPER KEYWORD

- It is used to **differentiate the members** of superclass (**immediate parent**) from the members of subclass, if they have same names.
- **super** can be used to refer **immediate** parent class **instance variable**.
- **super** can be used to invoke **immediate** parent **class method**.
- **super()** can be used to invoke **immediate** **parent class constructor**.

---

## I. SUPER CAN BE USED TO INVOKE PARENT CLASS VARIABLE

- The first form of super acts somewhat like this, except that it always refers to the **immediate** superclass variables of the subclass in which it is used.
- This usage has the following general form:

**super.variable**

---

## I. SUPER CAN BE USED TO INVOKE PARENT CLASS VARIABLE

```
class Animal{
    String color="white";
}
class Dog extends Animal{
    String color="black";
    void printColor(){
        System.out.println(color); //prints color of Dog class
        System.out.println(super.color); //prints color of Animal class
    }
}
class TestSuperI{ //class with a main method
    public static void main(String args[]){
        Dog d=new Dog(); //object of sub class
        d.printColor();
    }
}
```

---

## I. SUPER CAN BE USED TO INVOKE PARENT CLASS VARIABLE

```
class Animal{
    String color="white";
}
class Dog extends Animal{
    String color="black";
    void printColor(){
        System.out.println(color); //prints color of Dog class
        System.out.println(super.color); //prints color of Animal class
    }
}
class TestSuperI{ //class with a main method
    public static void main(String args[]){
        Dog d=new Dog(); //object of sub class
        d.printColor();
    }
}
```

---

## I. SUPER CAN BE USED TO INVOKE PARENT CLASS VARIABLE

```
class Animal{
    String color="white";
}
class Dog extends Animal{
    String color="black";
    void printColor(){
        System.out.println(color); //prints color of Dog class
        System.out.println(super.color); //prints color of Animal class
    }
}
class TestSuperI{ //class with a main method
    public static void main(String args[]){
        Dog d=new Dog(); //object of sub class
        d.printColor();
    }
}
```

**Output:**

black  
white

---

## 2. SUPER CAN BE USED TO INVOKE PARENT CLASS METHOD

- The second form of super acts somewhat like this, except that it always refers to the immediate superclass method of the subclass in which it is used.
- This usage has the following general form:

**super.method()**



---

## 2. SUPER CAN BE USED TO INVOKE PARENT CLASS METHOD

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void eat()
        {System.out.println("eating bread...");}
    void bark()
        {System.out.println("barking...");}
    void work(){
        super.eat();
        bark();
    }
}
class TestSuper2{
    public static void main(String args[]){
        Dog d=new Dog();
        d.work();
    }
}
```

## 2. SUPER CAN BE USED TO INVOKE PARENT CLASS METHOD

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void eat()
        {System.out.println("eating bread...");}
    void bark()
        {System.out.println("barking...");}
    void work(){
        super.eat();
        bark();
    }
}
class TestSuper2{
    public static void main(String args[]){
        Dog d=new Dog();
        d.work();
    }
}
```

**Output**

**eating...**  
**barking...**

---

### 3. USING SUPER TO CALL SUPERCLASS CONSTRUCTORS

- A subclass can call a constructor defined by its superclass by use of the following form of super:  
**super(arg-list);**
- Here , arg-list specifies any arguments needed by the constructor in the **superclass.super( )**
- It always be the first statement executed inside a subclass constructor.
- When a subclass calls **super()**, it is calling the constructor of its immediate superclass. Thus , **super()** always refers to the superclass immediately above the calling class.

---

### 3. USING SUPER TO CALL SUPERCLASS CONSTRUCTORS

```
class Animal{
    Animal(){System.out.println("animal is created");}
}
class Dog extends Animal{
    Dog(){
        super(); //first statement
        System.out.println("dog is created");
    }
}
class TestSuper3{
    public static void main(String args[]){
        Dog d=new Dog();
    }
}
```

### 3. USING SUPER TO CALL SUPERCLASS CONSTRUCTORS

```
class Animal{
    Animal(){System.out.println("animal is created");}
}
class Dog extends Animal{
    Dog(){
        super(); //first statement
    }
    System.out.println("dog is created");
}
class TestSuper3{
    public static void main(String args[]){
        Dog d=new Dog();
    }
}
```

## Output

**animal is created**  
**dog is created**

---

## NOTE:

- Call to `super()` must be first statement in Derived(Student) Class constructor.
- If a constructor does not explicitly invoke a superclass constructor, the Java compiler automatically inserts a call to the no-argument constructor of the superclass. If the superclass does not have a no-argument constructor, you will get a compile-time error. Object does have such a constructor, so if Object is the only superclass, there is no problem.
- If a subclass constructor invokes a constructor of its superclass, either explicitly or implicitly, you might think that a whole chain of constructors called, all the way back to the constructor of Object. This, in fact, is the case. It is called constructor chaining..

---

## TYPES OF INHERITANCE IN JAVA

There are four types of inheritance in java:

- 1) Single
- 2) Multilevel and
- 3) Hierarchical.
- 4) Hybrid

In java programming, **multiple and hybrid inheritance** is supported through **interface** only.

---

## TYPES OF INHERITANCE IN JAVA


There are four types of inheritance in java:

- 1) Single
- 2) Multilevel and
- 3) Hierarchical.
- 4) Hybrid


In java programming, **multiple and hybrid inheritance** is supported through **interface** only.




# TYPES OF INHERITANCE IN JAVA




1) Single




2) Multilevel



3) Hierarchical



4) Multiple



5) Hybrid

---

## SINGLE INHERITANCE

```
class Animal
{
    void eat()
    {System.out.println("eating...");}
}

class Dog extends Animal{
    void bark()
    {System.out.println("barking...");}
}

class TestInheritance{
    public static void main(String args[]){
        Dog d=new Dog();
        d.bark();
        d.eat();
    }}
}
```

**Note: When a class inherits another class, it is known as a *single inheritance*. In the example given below, Dog class inherits the Animal class, so there is the single inheritance.**

---

## MULTILEVEL INHERITANCE

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void bark()
        {System.out.println("barking...");}
}
class BabyDog extends Dog{
    void weep(){System.out.println("weeping...");}
}
class TestInheritance2{
public static void main(String args[]){
    BabyDog d=new BabyDog();
        d.weep();
        d.bark();
        d.eat();
    }
}
```

**When there is a chain of inheritance, it is known as *multilevel inheritance*. As you can see in the example given below, BabyDog class inherits the Dog class which again inherits the Animal class, so there is a multilevel inheritance.**

## MULTILEVEL INHERITANCE

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void bark()
        {System.out.println("barking...");}
}
class BabyDog extends Dog{
    void weep(){System.out.println("weeping...");}
}
class TestInheritance2{
    public static void main(String args[]){
        BabyDog d=new BabyDog();
        d.weep();
        d.bark();
        d.eat();
    }
}
```

When there is a chain of inheritance, it is known as ***multilevel inheritance***. As you can see in the example given below, BabyDog class inherits the Dog class which again inherits the Animal class, so there is a multilevel inheritance.

### OUTPUT:

```
weeping...
barking...
eating...
```

# HIERARCHICAL INHERITANCE

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void bark()
        {System.out.println("barking...");}
}
class Cat extends Animal{
    void meow()
        {System.out.println("meowing...");}
}
class TestInheritance3{
    public static void main(String args[]){
        Cat c=new Cat();
        c.meow();
        c.eat();
        //c.bark();//C.T.Error
    }
}
```

**When two or more classes inherits a single class, it is known as *hierarchical inheritance*. In the example given below, Dog and Cat classes inherits the Animal class, so there is hierarchical inheritance.**

# HIERARCHICAL INHERITANCE

```
class Animal{
    void eat()
        {System.out.println("eating...");}
}
class Dog extends Animal{
    void bark()
        {System.out.println("barking...");}
}
class Cat extends Animal{
    void meow()
        {System.out.println("meowing...");}
}
class TestInheritance3{
    public static void main(String args[]){
        Cat c=new Cat();
        c.meow();
        c.eat();
        //c.bark();//C.T.Error
    }
}
```

**When two or more classes inherits a single class, it is known as *hierarchical inheritance*. In the example given below, Dog and Cat classes inherits the Animal class, so there is hierarchical inheritance.**


## **OUTPUT**

meowing...  
eating...

---

## MULTIPLE INHERITANCE

When a class extends multiple classes i.e., known as multiple inheritance. For Example:



4) Multiple

It is not allowed in Java through extends

A large orange circle with a thin black border. Inside the circle, the text 'It is not allowed in Java through extends' is written in a white, sans-serif font, centered horizontally and vertically.

---

## WHY MULTIPLE INHERITANCE IS NOT SUPPORTED IN JAVA?

- Consider a scenario where A, B and C are three classes. The C class inherits A and B classes. If A and B classes have same method and you call it from child class object.
- There will be ambiguity to call method of A or B class.



# WHY MULTIPLE INHERITANCE IS NOT SUPPORTED IN JAVA?

```
class A{
    void add()
    {a =10;
    b=5;
    c=a+b;}
}

class B{
    void add()
    {a =10;
    b=5;
    c=15;
    d=a+b+c;}
}

class C extends A,B{//suppose if it were
    Public Static void main(String args[]){
        C obj=new C();
        obj.add();//Now which add() method would be invoked?
    }
}
```


---

## WHY MULTIPLE INHERITANCE IS NOT SUPPORTED IN JAVA?

- To reduce the complexity and
- simplify the language,  
**multiple inheritance is not supported in java.**
- Since compile time errors are better than runtime errors,
- java renders compile time error if you inherit 2 classes.
- So whether you have **same method or different**, there will be compile time error now.
- Therefore, Inheritance is called **Compile Time Mechanism**.

```
class A{
    void add()
        {a = 10;
        b=5;
        c=a+b;}
    }
class B{
    void sub()
        {
        a = 10;
        b=5;
        c= a-b;
        }
class C extends A,B{
    Public Static void main(String args[]){
        C obj=new C();
        obj.add();
        }
}
```

**Output:**  
**'{' expected**  
**class C extends A,B**



THANK YOU  
?