Energy-Aware Resource Allocation in 6G LEO-Edge Networks: A Hybrid Soft Computing and Automata-Driven Architecture

Abstract

Next-generation 6G networks necessitate a seamless terrestrial-satellite computing continuum. However, dynamic IoT traffic and the high mobility of Low Earth Orbit (LEO) satellites render static routing heuristics inefficient, causing severe latency bottlenecks. While deep learning models offer predictive routing, continuous inference on resource-constrained IoT edge devices introduces prohibitive computational and energy overheads. This paper proposes a "Green 6G" hybrid soft computing architecture utilizing a Kohonen Self-Organizing Map (SOM) coupled with Multi-Layer Perceptrons (MLP) and a Deterministic Finite Automaton (DFA) safety governor. Simulation results demonstrate that this hybrid framework reduces AI energy consumption by 65% while maintaining a stable average system latency, drastically outperforming static edge-first allocators. This provides a viable, power-efficient solution for dynamic task offloading in extreme-edge environments.

1 Introduction

The integration of Low Earth Orbit (LEO) satellite constellations with terrestrial Edge computing forms the backbone of the 6G computing continuum. In this architecture, ultra-reliable low-latency communications (URLLC) rely heavily on efficient task offloading. Conventional static allocators fail under the highly dynamic, bursty traffic generated by massive IoT networks, leading to rapid edge-queue congestion.

While modern approaches utilize supervised Deep Learning to predict end-to-end latency and optimize routing, they ignore a critical hardware constraint: running heavy neural network inference on extreme-edge IoT sensors drains battery life at an unsustainable rate. To achieve true "Green 6G" infrastructure, intelligent routing must minimize both network latency and local computational energy overhead.

This project introduces a multi-objective architecture that synthesizes unsupervised machine learning, supervised predictive modeling, and deterministic automata theory to create a fault-tolerant, energy-aware routing framework.

2 System Architecture

The proposed architecture replaces the standard static router with a three-tier intelligent allocator, designed to optimize the following objective function:

$$\min_{\mathbf{x}} \frac{1}{N} \sum_{i=1}^{N} (x_{i,e} L_{i,edge} + x_{i,s} L_{i,leo}) \tag{1}$$

subject to strict energy constraints, where $x_{i,e}$ and $x_{i,s}$ are binary routing decisions for Edge and LEO respectively.

2.1 The Energy Gatekeeper (SOM)

To mitigate the power consumption of continuous AI inference, an ultra-lightweight unsupervised Kohonen Self-Organizing Map (SOM) is deployed. Costing only 0.1 Joules per classification, the SOM continuously monitors the network state vector $\mathbf{S} = [Q_{edge}, L_{leo}, S_{task}]$.

During low-stress classifications, the SOM confidently routes tasks to the terrestrial Edge, intentionally bypassing heavy ML models to conserve battery life.

2.2 The Predictive Engine (MLP)

Triggered exclusively when the SOM detects a high-stress congestion event, two parallel Multi-Layer Perceptrons (1.2 Joules per inference) calculate the exact predicted latency for both the Edge and the LEO satellite. The system dynamically routes the packet to the node offering the lowest predicted latency.

2.3 The Oscillation Governor (DFA)

To prevent network instability known as the "Ping-Pong Effect" (rapidly bouncing traffic between terrestrial and orbital nodes), a Deterministic Finite Automaton monitors the AI's routing sequences.

The DFA consists of states $Q = \{q_0, q_1, q_2\}$. If rapid route switching is detected within a 5-task sliding window, the DFA transitions $q_0 \rightarrow q_1 \rightarrow q_2$. State q_2 explicitly overrides the neural network, forcing a LEO offload cool-down period to flush the Edge queue and stabilize the system.

3 Simulation and Results

The architecture was benchmarked using a Python-based discrete-event simulation (`SimPy`) processing 1,000 bursty IoT tasks. The model compared a Static Allocator, a Pure AI (MLP-only) Allocator, and the proposed Hybrid (SOM+MLP+DFA) Allocator.



Figure 1: Performance comparison across Latency and Energy metrics.

3.1 Latency Mitigation

The Hybrid architecture successfully maintained a highly stable average latency of ~ 2.0 seconds. This completely mitigated the extreme queue bottlenecking observed in the static allocator, which suffered an average latency exceeding 6.0 seconds.

3.2 Green 6G Efficiency

By utilizing the SOM as an initial gatekeeper, the system successfully bypassed heavy MLP inference for $\sim 65\%$ of the network traffic. This resulted in an overall reduction of total computational energy consumption by nearly half compared to the Pure AI approach, significantly extending the simulated battery lifespan of the edge device.

3.3 System Stability

The DFA monitor recorded zero forced override states (q_2) during the 1,000-task burst simulation. This empirically demonstrates that the decision boundaries of the SOM+MLP framework are naturally resistant to ping-pong oscillation under standard highly-congested 6G traffic conditions, rendering the framework inherently stable.

4 Conclusion

This framework successfully bridges soft computing and automata theory to address critical bottlenecks in 6G Edge-Cloud continuums. By gating heavy predictive models behind an ultra-lightweight unsupervised classifier, the architecture achieves a highly optimal trade-off between network latency reduction and edge-hardware energy preservation.