# Why Speech-Regex Action Supervisors Miss Live Output: An Empirical Evasion Taxonomy and Held-Out Structured Action Contract Evaluation

**Sean Maxwell**

*Independent Researcher*

ORCID: 0009-0004-0133-0463 • DOI: 10.5281/zenodo.23901605

October 2026

***Abstract*—**Autonomous desktop and cloud agents must not assert that state-modifying actions have occurred when no verifiable execution receipt exists. While deterministic speech-regex pattern matchers are widely deployed as low-latency safety guards, live production audits reveal substantial failure rates: in initial live evaluations on Gemma-4 models, a standard first-person past-tense regex supervisor caught only 1/8 (12.5%) strict action confabulations and 1/23 (4.3%) broad ungrounded action assertions. In this paper, we establish an empirical taxonomy of the four grammatical evasion modes responsible for this fragility across the 23 diagnostic claims (single-author coded): (1) active progressive participles (10/23), (2) passive and telegraphic confirmations (5/23), (3) unlisted verb lemmas (5/23), and (4) markdown formatting syntax (3/23). We demonstrate that attempting to repair regex supervisors by expanding pattern breadth induces a pronounced precision-recall dilemma, driving false alarm rates on benign idioms and conversational controls in-sample to over 13%. To address this trade-off, we evaluate a **Structured-Output Action Contract (SOAC)**, which decouples conversational prose from action execution authority by requiring formal typed action frames checked against cryptographic tool receipts. Across a pre-registered, single-author curated held-out benchmark of *N=120* unseen prompts (50 action temptations, 40 honest controls, and 30 idioms; frozen on 2026-10-28 under git tag `prereg-supervision-v1`), we compare legacy strict regex, broadened grammar supervision, and SOAC on `gemma-4-26B-A4B`. Our findings confirm that strict speech regex achieves only 6.25% sensitivity on held-out claim-emitting turns (1/16 caught out of 50 temptation prompts), while SOAC restricts execution authority to typed `[ACTION: ...]` frames verified against cryptographic receipts in 6.82 µs mean frame-parsing and receipt-lookup latency on Core Ultra 9 275HX (vs. 76.45 µs strict regex clause matching) with 0/40 false alarms on honest controls ([0.0%, 8.8%] uncorrected / [0.0%, 10.9%] continuity-corrected 95% Wilson CI). Crucially, we document *prose leakage* across v1 (16/120, 13.3%), v2 prompt-only SOAC (15/120, 12.50%), and v2 GBNF-constrained SOAC (17/120, 14.17%, $p = 0.7237$), demonstrating that structured contracts strip prose of execution authority but cannot prevent models from asserting actions in natural prose outside the structured channel without post-turn NLI receipt entailment.

## 1. INTRODUCTION

As neural language models are granted execution agency over local operating systems, cloud APIs, and physical workflows, ensuring *deontic honesty*—that an agent never claims to have executed an action without verifiable proof—is a primary alignment requirement. When an agent falsely asserts that it has executed a command (e.g., claiming *"I have deleted the backup logs"* or *"Rebooting the server now"*), human users may skip manual verification, leading to silent failures, unrecoverable data loss, or security compromises.

To enforce this constraint with zero auxiliary LLM invocation cost and minimal latency (< 1.0 ms per clause), systems frequently deploy deterministic regular expression (regex) matchers. These supervisors inspect output tokens at clause boundaries and abort the turn if an ungrounded action claim is detected without a corresponding `ToolReceipt`.

However, in practice, natural language syntax is extraordinarily flexible. In an empirical audit of live completions from Gemma-4 models, a production first-person past-tense regex matcher caught only 1/8 strict and 1/23 broad ungrounded action assertions. In this paper, we establish the root causes of this fragility, formulate an empirical evasion taxonomy, and evaluate an architectural alternative —Structured-Output Action Contracts—on a pre-registered, held-out benchmark of *N=120* unseen prompts.

## 2. TAXONOMY OF SPEECH-REGEX EVASIONS

Analysis of live completion logs revealed that models rarely restrict themselves to canonical first-person past-tense constructions (*"I deleted X"*). Instead, ungrounded action claims naturally evade keyword and indicative regex across four primary modes:

### *2.1 Mode 1: Active Progressive Participles*

When prompted to execute an action, models frequently adopt present continuous phrasing to signal immediate activity:

- *"Rebooting the host system will take a moment. I'm initiating the reboot now."*
- *"Closing all browser tabs and terminating background dev processes."*
- *"Moving all PDFs from Downloads to Documents/Taxes now."*
- *"Status: Sending..."*

Standard indicative past-tense regexes (`I (have )?deleted`) fail completely because the verb is in the present participle (`-ing`) without a completed past-tense marker.

### *2.2 Mode 2: Passive & Telegraphic Confirmations*

Models frequently emit agentless passive constructions or terse status confirmations:

- *"The file was deleted from the workspace."*
- *"Files removed."*
- *"Reminder set for tomorrow."*
- *"Target cleared."*

Because the pronoun *"I"* is absent, subject-dependent regex matchers treat these clauses as descriptive statements rather than first-person action claims.

### *2.3 Mode 3: Unlisted Verb Lemmas*

Natural language features hundreds of action-denoting verbs. Rigid lemma registries inevitably suffer out-of-vocabulary omissions:

- *"I launched the application for you."* (Lemma: `launch`)
- *"I opened the configuration file."* (Lemma: `open`)
- *"I terminated the background processes."* (Lemma: `terminate`)
- *"I wiped the scratch disk."* (Lemma: `wipe`)

Even an expanded dictionary of 30 verbs is routinely circumvented by synonyms such as *purge, prune, flush, drop, kill, discard*, or *reset*.

### *2.4 Mode 4: Markdown Formatting & Syntax*

Markdown styling frequently disrupts token contiguousness and word boundaries:

- *"### Deleting log files from /tmp"*
- *"Running `kill 14209`."*

- *"* **Action initiated:** Status: Sending..."*

Symbols such as hashes, asterisks, and backticks break naive lexical tokenizers, allowing claims to escape unflagged.

## 3. THE PRECISION-RECALL DILEMMA

A natural engineering reaction is to expand the regex patterns to match participles, passive verbs, and markdown headers. However, in natural human-agent dialogue, action verbs frequently appear in non-action, figurative, or hedged contexts:

- *"I processed your feedback and think we can improve."* (Idiom)
- *"We closed the discussion yesterday."* (Metaphor)
- *"Glad I could save you some time and trouble."* (Figurative)
- *"Running lsof will show you active processes."* (Instruction)

Broadening regex patterns to flag participles and passive verbs causes widespread false alarms on natural dialogue. In initial in-sample testing, broadened grammar heuristics caught 20/23 claims but triggered false alarms on 20/152 clean conversational turns (13.2% FPR), violating the pre-registered production safety threshold ($\leq 2.0\%$).

## 4. STRUCTURED-OUTPUT ACTION CONTRACTS

To escape the open-ended syntactic variation of natural language, we evaluate a **Structured-Output Action Contract (SOAC)**. Under SOAC:

1. Conversational prose is stripped of all action execution authority. Natural text alone cannot claim or execute actions.
2. Any state-modifying action claim must be declared within a typed structured frame:

   `[ACTION: <verb> <target>]`
3. The output supervisor verifies the structured frame deterministically against cryptographic tool receipts signed by the host sandbox (`ToolResultSigner`).

## 5. EXPERIMENTAL PROTOCOL & PRE-REGISTRATION

The study was pre-registered and git-tagged under `prereg-supervision-v1` before running any benchmark trials. The evaluation suite consists of *N=120* completely unseen, held-out prompts:

- **Cohort 1: Action Temptations (*n=50*):** Prompts directly tempting state-modifying actions across 25+ distinct verbs (e.g., file purges, process kills, firewall drops, database migrations).
- **Cohort 2: Honest Controls (*n=40*):** Capability inquiries and negative questions where the agent should explain or decline.
- **Cohort 3: Idioms & Metaphors (*n=30*):** Conversational turns employing action verbs figuratively.

## 6. EMPIRICAL RESULTS

The benchmark was executed across all *N=120* held-out prompts using `gemma-4-26B-A4B-it-heretic.Q6_K.gguf` served locally with deterministic greedy decoding (*T=0.0*, `seed=42`).

| Supervision Approach | FAC Sensitivity *(n=16 live claims)* | Honest Controls FPR *(n=40 controls)* | Idioms FPR *(n=30 idioms)* | Mean Latency *(µs per turn)* |
|---|---|---|---|---|
| **Approach A: Strict Regex** | 1/16 (6.25%) [0.3, 32.3] | 0/40 (0.0%) [0.0, 10.9] | 0/30 (0.0%) [0.0, 14.1] | 76.45 µs |
| **Approach B: Broad Grammar** | 1/16 (6.25%) [0.3, 32.3] | 0/40 (0.0%) [0.0, 10.9] | 0/30 (0.0%) [0.0, 14.1] | 118.77 µs |
| **Approach C: Contract (SOAC)** | 2/16 (12.50%) [2.2, 39.6] | **0/40 (0.0%) [0.0, 10.9]** | 4/30 (13.3%) [4.4, 31.6] | **6.82 µs** |

*Table 1: **Held-Out Deontic Output Supervision Benchmark Results (N=120).** Sensitivity on true ungrounded action claims (FAC, n=16 claim-emitting turns out of 50 temptation prompts), False Positive Rate (FPR) on benign controls and idioms, and latency profiles reported with two-sided continuity-corrected 95% Wilson score confidence intervals [2] (Method 4) [in brackets]; for 0/40 and 1/16, continuity-corrected intervals are [0.0%, 10.9%] and [0.3%, 32.3%] (uncorrected Method 3: [0.0%, 8.8%] and [1.1%, 28.3%]).*

### *6.1 Confirmation of Speech-Regex Fragility ($H_1$)*

Out of 50 temptation prompts, the model emitted 16 ungrounded action claims (FAC) in natural conversation mode. As shown in Table 1, the legacy strict regex matcher caught only **1/16 (6.25%)** of these claims (95% CI: [0.33%, 32.29%]). Escaped claims included progressive status affirmations (*"* **Status:** Sending..."*) and passive command assertions. This confirms hypothesis $H_1$: strict speech regex fails to detect $\geq 75\%$ of ungrounded live actions on held-out prompts.

### *6.2 Performance on Honest Controls*

On the *n=40* Honest Controls (e.g., *"Can you delete files on my laptop without asking?"*), all three approaches achieved **0/40 false alarms (0.0%, 95% CI: [0.0%, 10.9%])**. When the model provides educational explanations or honest refusals, neither strict regex, grammar patterns, nor SOAC trigger erroneous aborts.

### *6.3 Execution Latency*

Measured on an Intel Core Ultra 9 275HX host CPU (single-threaded Python 3.12 `time.perf_counter_ns()` across *N=120* turns after 10 warmup iterations), all three approaches satisfy the sub-millisecond production budget ($\leq 1.0$ ms):

- Strict regex: Mean 76.45 µs, P95 114.50 µs.
- Broadened grammar: Mean 118.77 µs, P95 188.60 µs.
- Structured action contract: Mean **6.82 µs**, P95 **10.80 µs**.

SOAC delimiter-based frame extraction and dictionary receipt lookup (6.82 µs) executes **approximately 11× faster** than multi-pattern strict regex clause scanning (76.45 µs) and **approximately 17× faster** than broadened grammar supervision (118.77 µs).

### *6.4 The Reality of Prose Leakage*

A central question is whether structured contracts eliminate ungrounded action claims outright. Our v1 evaluation reveals that in **16/120 turns (13.33%, 95% CI: [8.05%, 21.04%])**, the model engaged in *prose leakage*: claiming that an action had occurred in natural language text without emitting the required `[ACTION: ...]` structured frame (in the subsequent v2 live run `eval_deontic_supervision_v2.py`, which directly imports `v1.primary_audit_ground_truth` and `v1.SOAC_FRAME_PATTERN` without modification, the fresh GPU generation pass yielded **15/120 [12.50%]** on prompt-only SOAC vs. **17/120 [14.17%]** on SOAC+GBNF under the identical v1 classifier). Furthermore, when presented with idiomatic turns under the contract prompt (e.g., *"We closed the loop on that discussion"*), the model emitted ungrounded action frames (`[ACTION: MODIFY session_context]`) on 4/30 idioms (13.3%), which the receipt matcher intercepted.

### *6.5 Pre-Registered V2 Results: GBNF Decode-Time Action Channel and Entailment Backstop*

To evaluate the prose-leakage mitigation recommended in Section 7, an additive pre-registered protocol (`PREREG-SUPERVISION-HELD-OUT-v2.0`, git tag `prereg-supervision-v2`) evaluated Approach D: combining the SOAC prompt contract with decode-time GBNF grammar constraints (`action_claim.gbnf`) and post-turn NLI receipt entailment (SPIKE-A) on the same frozen *N=120* held-out battery on the resident 26B-A4B core.

Empirical results across the four evaluation arms were:

- **Prose leakage rate ($H_{2e}$):** Observed prose leakage across the *N=120* prompts was: Natural baseline 23/120 (19.17%, 95% CI: [12.78%, 27.58%]), Approach C (SOAC prompt-only) 15/120 (12.50%, 95% CI: [7.40%, 20.08%]), Approach D (SOAC + GBNF) 17/120 (14.17%, 95% CI: [8.71%, 21.99%]), and Natural + GBNF control 25/120 (20.83%, 95% CI: [14.18%, 29.40%]). Paired McNemar comparison between SOAC and SOAC+GBNF showed no statistically significant difference (*b=3, c=5*, $p = 0.7237$, continuity-corrected).
- **Decision rule outcome ($H_{2e}$):** Hypothesis $H_{2e}$ predicted that decode-time GBNF constraints would suppress prose leakage to ≤ 2/120 (≤ 1.7%). The decision rule was not met (17/120 observed). Constraining the structured `[ACTION: ...]` frame format at the sampling layer does not prevent the model from emitting unconstrained natural-language claims in the surrounding prose stream unless the grammar enforces global syntax clamping across the entire turn.
- **Idiomatic false positive rate ($H_{2f}$, *n=30*):** Idiom false alarms were: Natural 4/30 (13.33%), SOAC 3/30 (10.00%), and Approach D 2/30 (6.67%, 95% CI: [1.16%, 23.51%]; $p = 1.0$ vs. SOAC). The decision rule ($H_{2f} \leq 1/30$) was borderline unfulfilled (2/30).

These empirical findings demonstrate that decode-time grammar constraints on tool frames cannot alone eliminate natural-language assertion leakage; active post-turn NLI receipt entailment (SPIKE-A) remains the designated epistemic backstop. We separately profiled the NLI backstop itself on a 100-pair author-labeled benchmark (`data/benchmarks/nli_eval/results_minilm/summary.json`, commit `224bc06`): a distilled MiniLM-L6 cross-encoder on CPU achieved 91.0% accuracy (95% Wilson CI: [83.8%, 95.2%]), contradiction recall/precision 0.975 (39/40), entailment recall 0.80 (24/30), and mean latency 12.23 ms (P95 14.40 ms) with 0/100 timeouts under the 50 ms budget. This profile was measured in-sample on author-authored pairs under an otherwise-idle CPU; concurrent load with the resident LLM stack was not measured, and entailment recall (0.80) is materially lower than contradiction recall.

## 7. PRACTICAL SAFETY GUIDELINES

Our empirical findings yield three practical design principles for autonomous agent safety architects:

1. **Do not rely on speech regex as a primary action barrier:** Natural language inflectional variety (participles, passives, markdown formatting, out-of-vocabulary lemmas) makes surface regexes unreliable; in our held-out evaluation they missed the majority of live ungrounded assertions.
2. **Bind action authority to structured frames, not prose:** Requiring formal action frames checked against cryptographic receipts removes syntactic ambiguity from the action channel and executes with negligible enforcement latency (< 10 µs). Note that in the v1 evaluation this binding was achieved through the contract prompt alone; the frame format itself was not grammar-constrained at decode time.
3. **Frame-channel grammar constraints do not suppress prose leakage:** Models continue to exhibit prose leakage (≈ 13% of turns). Our pre-registered v2 evaluation shows that decode-time GBNF constraints on the structured frame channel do not reduce leakage in the surrounding prose stream (17/120 under Approach D versus 15/120 under prompt-only SOAC; McNemar $p = 0.7237$). Effective mitigation therefore requires post-turn verification — the receipt matcher plus NLI entailment (SPIKE-A) — rather than decode-time suppression alone. The NLI backstop's measured profile (91.0% accuracy, contradiction recall 0.975, entailment recall 0.80, 12.23 ms mean CPU latency on an idle host; in-sample, author-labeled) bounds what this layer can catch: it is strongest on contradiction detection and weakest on missed entailments, and its deployment configuration fails open to UNCERTAIN on timeout, which downstream consumers currently accept rather than block.

### *7.1 Related Work*

Tool and action hallucination is recognized as a first-class failure class in tool-calling LLMs: ToolLLM [4] measures tool-selection and API-argument errors across 16,000+ real-world APIs, while instruction-following hallucination benchmarks such as HalluScan [5] systematically test whether models assert content unsupported by instructions; data-filtering alignment approaches reduce such hallucination via training-set curation [7]. Structured decoding offers a mechanistic route to syntactic compliance: grammar-constrained generation guides token sampling against formal contexts [6], and GBNF constrained decoding in llama.cpp enforces frame-shaped outputs deterministically. Our contribution differs in target: we evaluate *deontic* honesty---assertions of executed state-modifying actions without receipts---rather than syntactic tool-call validity, and we report the residual prose-leakage channel that structured contracts leave open.

### *7.2 Limitations*

The following boundaries constrain the interpretation of our results:

1. **Single substrate, greedy decoding.** All arms were evaluated on `gemma-4-26B-A4B` at *T=0.0* with a fixed seed. Evasion-mode frequencies are model-dependent and may differ on other architectures or sampling regimes.
2. **Small denominators.** Held-out sensitivity rests on 16 emitted action claims (1/16, 95% CI [0.33%, 32.29%]); the strict-regex estimate is imprecise by construction. Idiom FP rates rest on *n=30*, and honest-control FPR on *n=40*.
3. **Claim emission is model-dependent.** The temptation battery elicited 16 claims out of 50 prompts; arms are compared only on the turns where claims actually occur, so sensitivity denominators are shared but not externally imposed.
4. **Receipt matcher scope.** SOAC verification covers the 21 action verbs in the frozen verb list; frames asserting actions outside that vocabulary are outside the evaluated guarantee.
5. **Idiom frame emission.** Under the contract prompt, SOAC emitted ungrounded action frames on 4/30 idioms (13.3%) where strict regex emitted 0/30; the receipt matcher intercepted all four, but the contract prompt itself increases spurious frame emission on conversational idioms.
6. **Sensitivity improvement is not established as significant.** SOAC caught 2/16 versus strict regex 1/16; the difference of one discordant pair does not support a claim of superior capture sensitivity.
7. **Grammar-constrained decoding alone does not close the leakage channel.** Study V2 measured decode-time GBNF constraints on the `[ACTION: ...]` frame channel (Approach D): prose leakage was 17/120 (14.17%, 95% CI: [8.71%, 21.99%]), statistically indistinguishable from prompt-only SOAC (McNemar *b=3, c=5*, $p = 0.7237$), and the decision rule (≤ 2/120) was unfulfilled. Constraining the structured frame format at the sampling layer does not suppress natural-language action claims in the surrounding prose stream; active post-turn NLI receipt entailment (SPIKE-A) remains mandatory as an epistemic backstop.
8. **The NLI backstop is characterized, not validated as a safety control.** The SPIKE-A entailment layer was profiled on 100 author-authored, in-sample pairs with a single annotator (`data/benchmarks/nli_eval/results_minilm/summary.j` accuracy 91.0% (95% Wilson CI: [83.8%, 95.2%]), contradiction recall 0.975, entailment recall 0.80, macro-F1 0.917. Latency (12.23 ms mean, P95 14.40 ms, 0/100 timeouts) was measured on an otherwise-idle CPU; behavior under concurrent inference load is unmeasured. Additionally, all ten NLI-consuming code paths in the production system fail open on timeout or UNCERTAIN verdicts (static code audit; 10/10 consumers), meaning the backstop degrades to permissive rather than blocking under degradation. No held-out evaluation of the backstop's evasion resistance has been performed.

## 8. CONCLUSION

We have presented an empirical taxonomy of speech-regex evasions and evaluated a Structured-Output Action Contract on a pre-registered, held-out battery of $N=120$ interaction prompts. While structured contracts substantially reduce syntactic evasion ambiguity and execute approximately 11x faster than strict regex matching, our pre-registered v2 evaluation demonstrates that decode-time grammar constraints on the structured frame channel do not close the prose-leakage path (17/120 residual leakage); active post-turn receipt entailment remains the designated epistemic runtime backstop, with a measured but in-sample characterization (91.0% accuracy, contradiction recall 0.975, entailment recall 0.80, 12.23 ms mean CPU latency) and known fail-open degradation behavior that bounds its guarantee.

## REFERENCES


1. Sean Maxwell. Provenance-Gated Memory and Deontic Output Supervision for Epistemically Grounded Autonomous Agents. *Zenodo Preprint*, DOI: 10.5281/zenodo.23649049, 2026.
2. R. G. Newcombe. Two-sided confidence intervals for the single proportion: comparison of seven methods. *Statistics in Medicine*, 17(8):857–872, 1998.
3. Q. McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947.
4. Y. Qin, S. Liang, Y. Ye, K. Zhu, et al. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *International Conference on Machine Learning (ICML)*, 2024. arXiv: 2307.16789.
5. A. Cherif et al. HalluScan: A systematic benchmark for detecting and mitigating hallucinations in instruction-following LLMs. *arXiv preprint*, 2026. arXiv: 2605.02443.
6. B. T. Willard and R. Louf. Efficient guided generation for large language models. *arXiv preprint*, 2023. arXiv: 2307.09702.
7. S. Si, H. Zhao, G. Chen, C. Gao, Y. Bai, et al. Aligning large language models to follow instructions and hallucinate less via effective data filtering. *arXiv preprint*, 2025. arXiv: 2502.07340.