

Smartrac Web U8 RFID Label

Optimized UHF RFID label with NXP UCODE 8 for apparel hang tags, retail, logistics and supply chain applications.



RFID SPECIFICATION

Chip	NXP UCODE 8
Protocol	ISO 18000-6C, EPC Class 1 Gen 2
Operating Frequency	860–960 MHz
EPC Memory	128-bit
TID Memory	96-bit (48-bit unique serial number)

PHYSICAL SPECIFICATION

Antenna Dimensions	50 × 30 mm
Die-Cut Dimension	54 × 33 mm
Inlay Substrate	PET
Face Sheet	Mid-gloss paper
Standard Pitch	36 mm
Web Width	60 mm
Core Size	76 mm

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40 °C to 85 °C
-----------------------	-----------------

APPLICATIONS

Industries	Apparel, Logistics
Use Cases	Supply chain management, home essentials, brand protection

FEATURE HIGHLIGHTS

- Compact 54 × 33 mm label optimized for apparel hang tags
- ARC and GS1 TIPP certified for global retail deployment
- Compliant with FCC, ETSI and Asia frequency regulations

PRODUCT GROUP

Category	UHF RFID Paper Label
Product Group	RFID Label / Tag