

Xerafy METAL-SKIN-DELTA-U8

Xerafy METAL-SKIN-DELTA-U8 is an industrial RFID tag with read range Up to 29.53 ft (9 m) on metal Up to 19.69 ft (5 m) off metal, IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	NXP UCODE 8
Memory	128 bits EPC; 96 bits TID
Write Cycles	100,000 times
Data Retention	20 years
Read Range (Fixed)	Up to 29.53 ft (9 m) on metal Up to 19.69 ft (5 m) off metal
Read Range (Handheld)	Up to 16.40 ft (5 m) on metal Up to 13.12 ft (3 m) off metal
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer
Dimensions (mm)	80 x 40 x 1
Dimensions (in)	3.15 x 1.57 x 0.04
Weight	1.76 lbs (0.80 kg)
Reel Core	Cardboard
Packing Information	300pcs/roll

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Compression Strength	355 psi (2,450 kPa)
Vibration	MIL-STD-810G
Printer Compatibility	Sato CL4NX; Postek
Warranty	1 year

FEATURE HIGHLIGHTS

- Up to 29.53 ft (9 m) on metal Up to 19.69 ft (5 m) off metal
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag