

Xerafy METAL-SKIN-TITANIUM-25-LASSO

Xerafy METAL-SKIN-TITANIUM-25-LASSO is an industrial RFID tag with read range Up to 26.25 ft (8 m) US on metal Up to 11.84 ft (3.50 m) EU on metal, IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	860-960 MHz (Global)
Chip	NXP UCODE 9
Memory	96 bits EPC; 96 bits TID
Write Cycles	100,000 times
Data Retention	20 years
Read Range (Fixed)	Up to 26.25 ft (8 m) US on metal Up to 11.84 ft (3.50 m) EU on metal
Polarization	Linear

PHYSICAL SPECIFICATION

Material	White thermal transfer face stock
Dimensions (mm)	68 x 13 x 1
Dimensions (in)	2.68 x 0.51 x 0.04
Weight	4.28 lbs (1.94 kg)
Packing Information	2500pcs/roll

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +85°C -40°F to +185°F
IP Rating	IP68
Vibration	MIL-STD-810G
Storage Humidity	50±15%RH
Printer Compatibility	SATO CL4NX,
Warranty	1 year

APPLICATIONS

Applications	Jewelry management, High-value item tracking, Inventory management
--------------	--

FEATURE HIGHLIGHTS

- Up to 26.25 ft (8 m) US on metal Up to 11.84 ft (3.50 m) EU on metal
- IP68
- 40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag