


Xerafy Pico-iN Plus

Xerafy Pico-iN Plus is an industrial RFID tag with read range Up to 9.84 ft (3 m), IP68 protection.



RFID SPECIFICATION

Protocol	EPC global Class 1 Gen 2
Operating Frequency	902-928 MHz (US); 865-868 MHz (EU)
Chip	1 Impinj M830
Memory	128 bits EPC, 96 bits TID
Write Cycles	10,000 times
Data Retention	10 years
Read Range (Fixed)	Up to 9.84 ft (3 m)
Read Range (Handheld)	Up to 4.92 ft (1.50 m)
Polarization	Linear
Radiation Pattern	in metal

PHYSICAL SPECIFICATION

Material	Ceramic
Dimensions (mm)	12.80 x 7.08 x 3.08
Dimensions (in)	ø 0.50 x 0.28 x 0.12
Weight	0.05 oz (1.40 g)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C -40°F to +185°F
Survival Temperature	-40°C to +150°C (168 hours) -40°F to +302°F
Peak Temperature	220°C (428°F)
IP Rating	IP68
Shock	3 ft (1 m) to concrete/granite
Vibration	MIL-STD-810G
Warranty	1 year

APPLICATIONS

Applications	Hand tools and equipments, Oil wells equipments, Injection molding
--------------	--

FEATURE HIGHLIGHTS

- Up to 9.84 ft (3 m)
- IP68
- -40°C to +85°C -40°F to +185°F

PRODUCT GROUP

Category	UHF RFID On-Metal Tag
Product Group	RFID Label / Tag