

SATO CT4-LX RFID Printer

The SATO CT4-LX is a compact 4-inch smart desktop thermal printer that brings industrial-grade features — including auto UHF/HF/NFC RFID encoding, a 4.3-inch full-color touchscreen, user-replaceable print head and platen roller, and SATO AEP on-printer intelligence — into a lightweight chassis. It supports linerless printing, dual-band Wi-Fi, Bluetooth 4.1, and encodes approximately 2,500–7,000 RFID tags/labels per day.



PRINT SPECIFICATIONS

Print Method	Direct Thermal / Thermal Transfer
Resolution	8 dots/mm (203 dpi), 12 dots/mm (305 dpi)
Print Speed	203 dpi: 8 ips (203 mm/sec); 305 dpi: 6 ips (152 mm/sec); Linerless mode: 4 ips
Print Width	104 mm (4.09 in)
Print Mode	Continuous, Tear-off, Cutter, Dispenser, Linerless
Display	4.3-inch full-color touch screen

RFID SPECIFICATIONS

Air Interface Protocol (UHF)	ISO/IEC 18000-6 Type C (EPC Gen2 / ISO/IEC 18000-63)
Air Interface Protocol (HF)	ISO/IEC 15693 (extended-range HF logistics)
Air Interface Protocol (NFC)	ISO/IEC 14443 (NFC short-range)
Operating Frequency (UHF)	860 – 960 MHz
Operating Frequency (HF/NFC)	13.56 MHz
RFID Positioning	Auto RFID positioning — encodes UHF / HF / NFC inlays
SATO RF Analyze (SRA)	Automatic antenna/inlay optimization
Dual Antenna	Supports exact encoding to small-sized inlays

MEDIA SPECIFICATIONS

Media Type	Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket, Linerless
Label Width	Min. 25 mm (0.98 in) – Max. 118 mm (4.65 in)
Media Roll OD	Max. 115 mm (4.53 in)
Media Core ID	76 mm (3.0 in)
Ribbon Width	45 – 111 mm (1.77 – 4.37 in)
Ribbon Length	Max. 100 m (328 ft)
Ribbon Core ID	12.7 mm (0.5 in)

CONNECTIVITY

Data Interface (Standard)	USB 2.0 (Type A & Type B), Ethernet (DHCPv4/DHCPv6), NFC pairing
Data Interface (Optional)	Wi-Fi (dual-band), Bluetooth 4.1, RS-232C

SYSTEM

Memory	4 GB Flash / 1 GB RAM
Emulation	SBPL, SEPL, SZPL, SDPL, SIPL, STCL (auto-detect switching)
Additional	Direct PDF Printing, AEP (Application Enabled Printing)
Fonts	40 Scalable Fonts; 47 print languages, 31 display languages

PHYSICAL SPECIFICATIONS

Dimensions (W x D x H)	178 x 238 x 214 mm (7.0 x 9.4 x 8.4 in)
Weight	DT model: approx. 3.3 kg (7.3 lbs); TT model: approx. 3.4 kg (7.5 lbs)
User-Replaceable Components	Print head, Platen roller

ELECTRICAL SPECIFICATIONS

Power Supply	AC 100–240 V, 50/60 Hz
Power Consumption (Peak)	155 VA / 95 W (AC100V, 30% printing ratio)
Power Consumption (Standby)	18 VA / 8 W (AC100V)

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 – 40 °C (32 – 104 °F); Linerless mode: 5 – 35 °C (41 – 95 °F)
Operating Humidity	30 – 80% RH (non-condensing)
Storage Temperature	-10 – 60 °C (14 – 140 °F)
Storage Humidity	15 – 90% RH (non-condensing)

FEATURE HIGHLIGHTS

- Auto RFID positioning for UHF (860–960 MHz), HF (ISO/IEC 15693), and NFC (ISO/IEC 14443) inlay encoding
- Dual antenna design for precise encoding of small-sized inlays
- SATO RF Analyze (SRA) for automatic RFID optimization
- 4.3-inch full-color touch screen with 31 display languages
- User-replaceable print head and platen roller to minimize downtime
- Patented label waste prevention technology
- Linerless printing mode support
- Compact and lightweight: 178 x 238 x 214 mm, ~3.4 kg
- 4 GB Flash / 1 GB RAM with 40 scalable fonts
- AEP (Application Enabled Printing) for standalone custom applications

PRODUCT GROUP

Category	Desktop RFID Printer
Product Group	Desktop RFID Printer