

SATO CL6NX Plus RFID Printer

The SATO CL6NX Plus is a next-generation 6-inch industrial thermal label printer with best-in-class 10 ips print speed (203 dpi), optional fully integrated UHF RFID (EPC C1G2 / ISO/IEC 18000-6C) encoder, dual CPU/dual OS architecture, and a metal two-layer cover design. It supports an 8.6-inch media roll and 600 m ribbon, and features PureLine™ roller technology with visual wear indication, enhanced print accuracy for small labels, and SATO RF Analyze (SRA) for automatic RFID optimization.



PRINT SPECIFICATIONS

Print Method	Direct Thermal / Thermal Transfer
Resolution	8 dots/mm (203 dpi), 12 dots/mm (305 dpi)
Print Speed	203 dpi: 2–10 ips (default 6 ips); 305 dpi: 2–8 ips (default 6 ips)
Print Width	168 mm (6.59 in)
Print Length	Max. 2500 mm (98.42 in)
Print Mode	Continuous, Tear-off, Cutter, Dispenser, Peel & Present, Linerless
Display	Full-color interactive LCD

RFID SPECIFICATIONS

Air Interface Protocol	EPC C1G2 (ISO/IEC 18000-6C) [UHF]
UHF Frequency	ETSI: 865–868 MHz; FCC: 902–928 MHz
RFID Module	Fully Integrated UHF RFID Reader/Encoder Module
SATO RF Analyze (SRA)	Automatic antenna and inlay optimization
Metal Tag Support	Compatible with flexible metal RFID tags (Confidex, Epozzy)

MEDIA SPECIFICATIONS

Media Type	Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket
Label Width	Min. 22 mm (0.87 in) – Max. 177.8 mm (7.0 in)
Media Roll OD	Max. 220 mm (8.6 in)
Media Core ID	76 mm (3.0 in)
Ribbon Width	39.5 mm (1.55 in) – 177 mm (6.97 in)
Ribbon Length	Max. 600 m (1968.5 ft)
Ribbon Core ID	25.4 mm (1.0 in)

CONNECTIVITY

Data Interface (Standard)	USB 2.0 (Type A & Type B), Ethernet (IPv4/IPv6), RS-232C, Parallel (IEEE 1284), EXT I/O Interface, NFC
Data Interface (Optional)	Wi-Fi & Wi-Fi Direct (IEEE 802.11 a/b/g/n, Dual Band 2.4 GHz / 5 GHz), Bluetooth 3.0

SYSTEM

CPU	Dual CPU / Dual OS; CPU1: 800 MHz (Linux OS); CPU2: 800 MHz (ITRON OS)
Memory	CPU1: 2 GB Flash, 256 MB RAM; CPU2: 4 MB Flash, 64 MB RAM
Emulation (Auto Detect)	SBPL, SEPL, SZPL, SDPL, SIPL, STCL
Additional	XML, Direct PDF Printing, AEP (Application Enabled Printing)
Label Sensor	Adjustable Transmissive Sensor (Gap), Adjustable Reflective Sensor (Black Mark)

PHYSICAL SPECIFICATIONS

Dimensions (W x D x H)	338 x 457 x 321 mm (13.3 x 18.0 x 12.6 in)
Weight	Approx. 20.3 kg (44.75 lbs)
Construction	Metal case with two-layer cover; PureLine™ roller with wear-level visualization

ELECTRICAL SPECIFICATIONS

Power Supply	Universal Auto-ranging; AC 100–240 V ±10%, 50/60 Hz
Power Consumption (Peak)	233 VA / 217 W (at 30% printing ratio)
Power Consumption (Standby)	60 VA / 23 W
Compliance	ENERGY STAR Compliant

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 – 40 °C (32 – 104 °F)
Operating Humidity	30 – 80% RH (non-condensing)
Storage Temperature	-20 – 60 °C (-4 – 140 °F)
Storage Humidity	30 – 90% RH (non-condensing)

FEATURE HIGHLIGHTS

- Best-in-class print speed: up to 10 ips at 203 dpi, 8 ips at 305 dpi
- 6-inch (168 mm) print width
- Optional fully integrated UHF RFID (EPC C1G2 / ISO/IEC 18000-6C) encoder
- Compatible with flexible metal RFID tags (Confidex, Epozzy)
- Metal case with two-layer cover — enhanced industrial durability
- PureLine™ roller with visual wear-level indicator
- Dual CPU / Dual OS architecture (Linux + ITRON OS)
- High-capacity: 220 mm OD media roll, 600 m ribbon
- Supports 47 print languages and 31 display languages
- AEP for on-printer custom applications

PRODUCT GROUP

Category	Industrial RFID Printer
Product Group	Industrial RFID Printer