

Zebra ZT411 On Metal RFID Printer

Zebra's RFID On-metal Tagging Solution is ideal for on-demand RFID asset tagging for all surfaces, including metal. The ZT411 RFID On-metal Solution — developed in partnership with Confidex — uses a specially engineered printhead assembly and adjustable sensor assembly to print and encode Silverline labels up to 1.5 mm thick, with 300 dpi print quality and field-upgradeable technology.



RFID	
Protocol	Supports labels compatible with UHF EPC Gen 2 V2 / ISO 18000-6C
Minimum Pitch	Prints and encodes labels with a minimum pitch of 0.6"/16 mm
Adaptive Encoding	Automatically eliminates complex RFID placement guidelines
Variable Inlay Placement	Supports a range of inlay positions for maximum media flexibility
Monitoring	Track performance with RFID job-monitoring tools
MCS	Supports industry standard multi-vendor chip-based serialization (MCS)
Block Permalocking	Supports block permalocking of user memory compatible with ATA Spec 2000
RFID Module	Integrated ThingMagic RFID reader/encoder

STANDARD FEATURES

Print Methods	Thermal transfer and direct thermal
Construction	Metal frame and bi-fold metal media cover with enlarged clear viewing window
Connectivity	USB 2.0, RS-232 Serial, 10/100 Ethernet, Bluetooth 4.1, Dual USB Host
Display	4.3-inch, full-color touch display
Print Quality	Element Energy Equalizer (E3) for superior print quality
Energy	ENERGY STAR qualified

PRINTER SPECIFICATIONS

Resolution	203 dpi/8 dots per mm; 300 dpi/12 dots per mm (optional)
Memory	256 MB SDRAM; 512 MB on-board linear Flash
Maximum Print Width	4.09 in./104 mm
Maximum Print Speed	14 ips/356 mm per second
Media Sensors	Adjustable dual media sensors: transmissive and reflective

MEDIA CHARACTERISTICS

Maximum Media Roll Size	8.0 in./203 mm O.D. on a 3 in./76 mm I.D. core
Media Thickness	Optimized for Silverline labels up to 1.5 mm thick; also supports all labels appropriate for standard ZT411
Media Types	Continuous, die-cut, notch, black-mark

RIBBON CHARACTERISTICS

Outside Diameter	450 m: 3.2 in./81.3 mm O.D. on a 1.0 in./25.4 mm I.D. core
Standard Length	1476 ft./450 m
Width	2.00 in./51 mm – 4.33 in./110 mm
Recommended Ribbon	5095 Performance Resin Ribbon for use with Silverline labels

CONFIDEX SILVERLINE RFID LABELS

RFID Protocol	EPC Global Class1 Gen2 ISO 18000-6C
Operational Frequency	ETSI: 865–869 MHz; FCC: 902–928 MHz
Classic (100x40x1.1mm)	Read range up to 6 m/20 ft
Micro II (45x13x1.3mm)	Metal up to 3.5 m; Plastic up to 1.5 m; Liquid up to 2 m
Slim II (100x13x1.3mm)	Metal up to 7 m (ETSI) / 7 m (FCC)
Blade II (60x25x1.2mm)	Metal up to 10 m (ETSI) / 10 m (FCC)

FEATURE HIGHLIGHTS

- Prints and encodes RFID labels that work directly on all surfaces, including metal
- Four Silverline label types: Classic, Micro II, Slim II and Blade II
- Read range of up to 10 m (Blade II on metal)
- Printhead assembly engineered for Silverline labels up to 1.5 mm thick
- Integrated ThingMagic RFID reader/encoder
- 300 dpi optional print quality
- 14 ips maximum print speed
- Adaptive Encoding Technology with variable inlay placement
- UHF EPC Gen 2 V2 / ISO 18000-6C protocol
- Metal frame construction with bi-fold metal media cover
- ENERGY STAR qualified

PRODUCT GROUP

Category	Industrial RFID Printer
Product Group	Industrial RFID Printer