

Brady HH85 UHF RFID Handheld Terminal ACD LTE (2D Imager)

The Brady HH85 is a ruggedized handheld RFID terminal designed for industrial data collection with UHF, NFC, HF, and 2D barcode scanning. Its ergonomic pistol-grip design, hot-swappable battery, and extended read range via di-pole antenna make it the premier choice for demanding logistics and asset tracking environments.



UHF RFID

Air Interface Protocol	EPC Class 1 Gen2v2 (ISO 18000-63)
Operating Frequency	ETSI 865.6–867.6 MHz / FCC/IC 902–928 MHz
Max Receive Sensitivity	-80 dBm
Typical Reading Speed	Up to 1000 tags per second
Antenna Type	Software controllable antenna polarisations (vertical, horizontal or vertical/horizontal switching)
Reader Module	Nordic ID NUR2-1W

PLATFORM

CPU	Octa-Core ARM Cortex-A53 1.8 GHz
Operating System	Android 10
RAM	2 GB
Storage	16 GB Flash
Expansion	MicroSD slot with SDXC support

CAMERA & IMAGER

Camera	5 Mpix rear-facing with autofocus and LED flash (torch mode supported)
Barcode Imager	Integrated 2D imager

CONNECTIVITY

WWAN	4G LTE, 3G, GPRS/EDGE
WLAN	IEEE 802.11 a/b/g/n/ac
Bluetooth	Bluetooth 4.2
USB	USB 2.0 via USB Type-C connector

BATTERY

Battery Type	Rechargeable Lithium-ion
Hot-Swap	Supported

MECHANICAL

Dimensions	(W) 87 mm x (H) 214 mm x (D) 135 mm
Weight	642 g
IP Rating	IP65
Drop Resistance	1.6 m
Sensors	Accelerometer, ambient light sensor, Time of Flight sensor, proximity sensor, pedometer, gyroscope

ENVIRONMENT

Operating Temperature	-20 °C to +55 °C
-----------------------	------------------

FEATURE HIGHLIGHTS

- Ruggedized IP65 rated design with 1.6-meter drop resistance
- Extended read range with di-pole antenna
- Hot-swappable battery for continuous field operation
- Integrated 2D barcode imager and NFC support
- Ergonomic pistol-grip suitable for gloved use

PRODUCT GROUP

Category	RFID Reader
Product Group	UHF RFID Handheld Terminal