

altis teknoloji

pursuing perfection with you

Avery Dennison AD-229r6-P UHF RFID Inlay

High-performing 95 × 8.15 mm Gen2 UHF RFID inlay with Impinj Monza R6-P chip. Offers multiple EPC and user memory options, kill and access password protection. Suitable for supply chain, RTUs, apparel and brand protection.



RFID SPECIFICATION

Chip	Impinj Monza R6-P
Standard	ISO/IEC 18000-63 Type C
Frequency Band	UHF 860–960 MHz
EPC Memory Options	128-bit or 96-bit
User Memory Options	32-bit or 64-bit
TID Memory	96-bit / 48-bit unique serial number
Access Password	Supported
Kill Password	Supported
On-Metal	Non metal
Certificate	ARC (RFID Lab, Auburn University)
RoHS	EU Directive 2011/65/EU and 2015/863 Compliant

PHYSICAL SPECIFICATION

Antenna Dimensions	95 × 8.15 mm / 3.74 × 0.32 in
Dry Inlay (RF600776)	Opaque PET — 20,000 pcs/reel — pitch 15.88 mm — core 152 mm / 6 in
Wet Inlay (RF600773)	98.7 × 11.2 mm die-cut — Opaque PET — 20,000 pcs/reel — core 76 mm / 3 in
Web Width (Dry)	98 mm / 3.875 in
Web Width (Wet)	105 mm / 4.125 in
Operating Temperature	-40°C to +85°C

FEATURE HIGHLIGHTS

- Impinj Monza R6-P chip – multiple EPC and user memory options (128/96-bit EPC, 32/64-bit user)
- Kill and access password protection for user privacy
- 96-bit TID with 48-bit unique factory-encoded serial number
- Long 95 × 8.15 mm antenna for high read performance
- Available in dry inlay and wet inlay formats
- ARC accredited quality by RFID Lab at Auburn University
- RoHS compliant – EU Directive 2011/65/EU and 2015/863

PRODUCT GROUP

Category	UHF RFID Inlay
Product Group	RFID Label / Inlay