

Confidex Carrier HF RFID Label

Washable and reusable UHF RFID label for plastic containers and returnable transport items. IP68-rated with industrial washing resistance, designed for long-term reuse in demanding supply chain environments.



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2v2 (ISO 18000-6C)
IC Options	Impinj Monza 4QT / Monza 4E
Operating Frequency	860–960 MHz (Global)
Memory (Monza 4QT)	EPC 128 bit; User 512 bit; TID 96 bit
Memory (Monza 4E)	EPC 496 bit; User 128 bit; TID 96 bit
Read Range (2W ERP)	Up to 10 m on plastic (ETSI)

PHYSICAL SPECIFICATION

Dimensions	73 × 8 × 0.2 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Washing Resistance	Industrial laundry up to 60°C
Chemical Resistance	Salt water, motor oil, sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- EPCglobal Gen2v2 – 860–960 MHz global operation
- Impinj Monza 4QT / 4E IC options
- Read range up to 10 m on plastic (ETSI)
- Withstands industrial washing – reusable lifecycle
- IP68 waterproof, chemical resistant
- Slim 73 × 8 × 0.2 mm printable white PET label

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag