

Confidex Crosswave Neo
4×6" RFID Label

4×6 inch high-performance printable UHF RFID label with Impinj M730 IC. The larger format offers superior read performance for logistics, supply chain and inventory applications requiring a standard shipping label size.



RFID SPECIFICATION

Protocol	EPCglobal UHF Class 1 Gen 2v2 (ISO 18000-6C)
Integrated Circuit	Impinj M730
Operating Frequency	865–928 MHz (Global)
Read Range (2W ERP)	Up to 11 m on plastic

PHYSICAL SPECIFICATION

Dimensions	4×6 inch (approx. 100 × 150 mm)
Material	Printable matt coated paper
Adhesive	Permanent adhesive
Delivery Format	Reel
Applicable Surfaces	Plastic, cardboard, non-metal

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +70°C / -31°F to +158°F
Chemical Resistance	Salt water, motor oil exposure
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Standard 4×6 inch shipping label format
- Impinj M730 IC – 865–928 MHz global operation
- Read range up to 11 m on plastic
- Printable matt-coated paper face
- Applications: logistics, supply chain, inventory management

PRODUCT GROUP

Category	UHF RFID Label
Product Group	RFID Label / Tag