

Confidex Ferrowave Micro RFID Label

Compact UHF RFID on-metal label with Impinj M730 IC in a slim 45 × 8 mm form factor. Ideal for asset tracking in retail, maintenance and sports equipment sectors where minimal labeling space is available.



RFID SPECIFICATION

Protocol	EPCGlobal Class1 Gen2 ISO 18000-6C
Integrated Circuit	Impinj M730
Operating Frequency	865–928 MHz (Global)
Read Range – ETSI on metal	Up to 3 m / 10 ft
Read Range – FCC on metal	Up to 4 m / 13 ft
Off-metal Read Range	Up to 1.5 m / 5 ft

PHYSICAL SPECIFICATION

Dimensions	45 × 8 × 1.5 mm
Material	Printable white PET
Adhesive	Permanent acrylic adhesive
Delivery Format	Reel
Applicable Surfaces	Metal (optimized)

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Chemical Resistance	Salt water, motor oil, sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Optimized for metal surfaces – compact 45 × 8 mm format
- Impinj M730 IC – 865–928 MHz global operation
- Read range up to 3 m (ETSI) / 4 m (FCC) on metal
- IP68 waterproof with chemical resistance
- Printable white PET adhesive label
- Applications: retail asset tracking, maintenance equipment, sports equipment

PRODUCT GROUP

Category	UHF RFID On-Metal Label
Product Group	RFID Label / Tag