

Confidex Ironside Micro NFC Tag

Ruggedized NFC tag in the same compact 27 × 27 mm form factor as the Ironside Micro UHF. IP68-rated and built for harsh environments involving impacts, chemicals and moisture, compatible with any NFC smartphone.



RFID SPECIFICATION

Protocol	NFC Forum Type 2 / ISO 14443A
Integrated Circuit	NXP NTAG213
Operating Frequency	13.56 MHz
User Memory	144 Bytes
Read Range – Mobile phone	Up to 30 mm
Read Range – Fixed reader	Up to 70 mm
Applicable Surfaces	All materials including metal

PHYSICAL SPECIFICATION

Dimensions	27 × 27 × 5.5 mm / 1.06 × 1.06 × 0.22 in
Tag Materials	High quality engineering plastics
Attachment	Adhesive (3M 300LSE), screws (M3), pop rivets, plastic rivets (3mm)
Weight	4.3 g
Amount in Box	500 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Chemical Resistance	168h motor oil, salt water (10%); 5h sulfuric acid (10%); 1h NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- NFC Forum Type 2 / ISO 14443A – 13.56 MHz
- NXP NTAG213 IC – 144 bytes User Memory
- Read range up to 30 mm (mobile) / 70 mm (fixed reader)
- Works on any surface including metal
- IP68 waterproof with chemical resistance
- Same compact 27 × 27 × 5.5 mm footprint as Ironside Micro UHF

PRODUCT GROUP

Category	NFC Hard Tag
Product Group	RFID Label / Tag