

Confidex Ironside Slim RFID Tag

Versatile and durable slim UHF RFID tag for global asset tracking with excellent on-metal performance. IP68-rated with Impinj Monza 4E IC, delivering read ranges up to 10 m on metal in a compact 85 × 21 mm form factor.



RFID SPECIFICATION

Protocol	EPCGlobal Gen2 v1.2 / ISO 18000-63
Integrated Circuit	Impinj Monza 4E
Operating Frequency	865–928 MHz (Global)
EPC Memory	496 bit
User Memory	128 bit
TID Memory	96 bit
EPC Content	Unique number encoded
Read Range – on metal	Up to 10 m / 33 ft
Read Range – off metal	Up to 4 m / 13 ft

PHYSICAL SPECIFICATION

Dimensions	85 × 21 × 10 mm / 3.35 × 0.83 × 0.39 in
Tag Materials	High quality engineering plastics
Attachment	Acrylic adhesive, polyurethane/epoxy adhesives, M4 screws with compression limiters
Weight	15.5 g
Amount in Box	600 pcs
Delivery Format	Single

ENVIRONMENTAL RESISTANCE

Operating Temperature	-35°C to +85°C / -31°F to +185°F
IP Classification	IP68
Chemical Resistance	168h motor oil; 24h salt water (10%), sulfuric acid (10%), NaOH (10%)
Expected Lifetime	Years in normal operating conditions

FEATURE HIGHLIGHTS

- Slim 85 × 21 × 10 mm form factor – versatile global asset tracking
- Impinj Monza 4E IC – EPC 496 bit / User 128 bit
- Read range up to 10 m on metal / 4 m off metal
- IP68 waterproof with chemical resistance
- Multiple attachment: adhesive, structural adhesive, M4 screws
- Available as Personalization Kit with 700 blank PET data labels per box

PRODUCT GROUP

Category	UHF RFID Hard Tag
Product Group	RFID Label / Tag